

Lenovo™ ThinkVision® T2324d Monitor

EXCEPTIONAL PERFORMANCE.
SURPRISINGLY AFFORDABLE.

A Brilliant 23" Monitor That's Built For Business.



Lenovo™

Exceptional display performance is a key to productivity in business environments, and affordability is just as important. The Lenovo™ ThinkVision® T2324d Monitor delivers on both counts. The 23" screen delivers Full HD resolution for exceptional color and clarity. It connects easily to any PC or notebook, and even supports a VESA® mount to integrate with a Lenovo™ ThinkCentre® Tiny PC. Truly a smart choice for value-conscious businesses.

WHY YOU SHOULD BUY THE LENOVO™ THINKVISION® T2324d MONITOR




Business-Grade Performance

The 23" TN panel (170° / 160° viewing angle) delivers Full HD (1920 x 1080) resolution, 250 nits brightness, 1000:1 contrast, 72% color gamut, and fast 5 ms response time.



Total Versatility

Connect a full range of PCs and notebooks using the VGA and DisplayPort™ interfaces, or mount a ThinkCentre® Tiny PC with a convenient VESA® bracket.



Ergonomic Design

The ergonomically-designed tilt stand adapts to any work style. Practical cable management effectively manages desktop clutter.

THE LENOVO™ THINKVISION® T2324d MONITOR IS BEST SUITED FOR

1 Organizations that need dependable yet affordable monitors for mass deployments.

2 Businesses looking for versatile monitors that contribute to worker productivity.

3 Anyone who wants the enhanced productivity of a second display without breaking the bank.



Lenovo™ ThinkVision® T2324d Monitor

SPECIFICATIONS

DISPLAY		MECHANICAL	
Panel Size	23"	Tilt Angle (Front / Back)	-5° / 22°
Panel Type	TN	Swivel Angle (Left / Right)	No
Backlight	WLED	Lift Range	No
Screen Dimensions (W x H) (mm)	509.76 x 286.74	Pivot	No
Resolution	1920 x 1080	VESA® Mount (mm)	100 x 100
Aspect Ratio	16:9 (Wide)	Kensington® Lock Slot	Yes
Viewing Angle (H/V at CR 10:1)	170° / 160°	Cable Management	Yes
Maximum Brightness (Typical)	250 cd/m ²	Ambient Light Sensor	No
Contrast Ratio (Typical)	1000:1	Control Buttons	Yes
Dynamic Contrast Ratio	3000000:1	Bezel Color	Raven Black
Pixel Pitch (mm)	0.2655	Bezel Width	
Dot/Pixel Per Inch (DP/PPI)	95.84	Sides (mm / inches)	17.26 / 0.67"
Color Gamut (CIE 1931) NTSC	72%	Top (mm / inches)	17.26 / 0.67"
Number of Colors	16.7 Million	Bottom (mm / inches)	25.25 / 0.99"
Response Time	5 ms		
Anti-Glare	Yes		
SIGNAL INPUT		POWER CONSUMPTION	
Video Input Signals	VGA + DisplayPort™	Power Supply	Internal
Video Cables Supplied	VGA + DisplayPort™	Power Consumption	
Video Cable Length	1.8 m	Typical / Maximum	20 W / 27 W
USB Hub	No	Sleep-Mode	<0.3 W
USB Cable Supplied	No	Switch-Off Mode	<0.3 W
		Power Voltage	90 VAC — 264 VAC
		Voltage Dynamic Frequency	47 Hz — 63 Hz
SIGNAL INTERFACE / PERFORMANCE		DIMENSIONS (W x D x H)	
Horizontal Frequency	30 kHz - 81 kHz	Size Unpacked with Stand	
Vertical Frequency	50 Hz - 75 Hz	(mm)	545.8 x 204.9 x 400.3
Native Resolution	1920 x 1080	(inches)	21.49" x 8.06" x 15.75"
Maximum Pixel Clock Speed / Bandwidth	205 MHz	Size Unpacked without Stand	
Default Color Temperature	7200K	(Monitor Head Only)	
Plug 'n' Play	Yes	(mm)	545.8 x 171 x 331
Preset Display Modes	26	(inches)	21.49" x 0.67" x 13.03"
User-defined Display Modes	16	Distance from Table to Panel (mm / inches)	
OSD Buttons	5	Lowest Pixel at Bottom of Screen	95.3 / 3.75"
OSD Languages	8	Highest Pixel at Top of Screen	382.1 / 15.04"
Lockable Controls	No	Stand Base Footprint Area	
		(Diameter) (mm / inches)	200 / 7.87"
		Weight	
		Packed	Starting at 10.36 lbs (4.7 kg)
		Unpacked	Starting at 7.05 lbs (3.2 kg)
		Monitor Head Only	Starting at 6.38 lbs (2.9 kg)
ENVIRONMENTAL		COMPLIANCE	
Temperature		EPEAT™	Gold
Operating	5°C - 40°C	ENERGY STAR® Rating	7.0
Non-operating	-20°C - 60°C	TCO	Display 7.0 / Edge 2.0
Humidity		RoHS (EU 2002/95/EC)	WW RoHS Requirement
Operating	10% - 80%	Windows Certification	Windows 7, Windows 10
Non-operating	5% - 90%	Image Quality Capability	ISO 9241-307
Altitude		China Energy Efficiency Standard	Tier 1
Operating	5000 m		
Non-operating	0 ft — 40,000 ft		
Arsenic-free Glass	Yes		
PVC-free	Yes		
Mercury-free	Yes		
PCC % of Plastic Resins	ABS 85% PCR		
		WARRANTY AND AVAILABILITY	
		Warranty	3 Years
		Geography Availability	World Wide
		Global Model	Yes



WWW.LENOVO.COM

Lenovo reserves the right to alter product offerings and specifications at any time, without notice. Lenovo makes every effort to ensure accuracy of all information but is not liable or responsible for any editorial, photographic or typographic errors. All images are for illustration purposes only. For full Lenovo product, service and warranty specifications visit www.lenovo.com. Lenovo makes no representations or warranties regarding third party products or services. **Trademarks:** The following are trademarks or registered trademarks of Lenovo: Lenovo, the Lenovo logo, Rescue and Recovery, ThinkPad, ThinkCentre, ThinkStation, ThinkServer, ThinkVantage and ThinkVision. Microsoft, Windows and Vista are registered trademarks of Microsoft Corporation. Ultrabook, Celeron, Celeron Inside, Core Inside, Intel, Intel Logo, Intel Atom, Intel Atom Inside, Intel Core, Intel Inside, Intel Inside Logo, Intel vPro, Itanium, Itanium Inside, Pentium, Pentium Inside, vPro Inside, Xeon, Xeon Phi, and Xeon Inside are trademarks of Intel Corporation in the U.S. and/or other countries. Other company, product and service names may be trademarks or service marks of others. Battery life (and recharge times) will vary based on many factors including system settings and usage. Visit www.lenovo.com/lenovo/us/en/safecomp/ periodically for the latest information on safe and effective computing. ©2016 Lenovo. All rights reserved.

Lenovo™