

ThinkStation



Lenovo ThinkStation C30



Lenovo ThinkStation C30



Lenovo ThinkStation C30



Lenovo ThinkStation C30



Lenovo ThinkStation C30



Lenovo ThinkStation C30

ThinkStation C30 Platform Specifications - I of IV

Text in **red** shows that these features only apply to MT type 1095 and 1097 models, text in **green** shows that the features are supported on other models except MT type 1095 and 1097 models

Chipset	Intel C602 Chipset										
Intel AMT	MT type 1095 and 1097: Intel Active Management Technology 7 Others MT types: Intel Active Management Technology 8										
Processor	Two LGA2011 sockets, supports up to two processors from Intel Xeon E5-2600 and Intel Xeon E5-2600 v2 family, or up to one processor from Intel Xeon E5-1600 v2 family, integrated 4-channel DDR3 memory controller per processor. Supports the following:										
	Processor Number	# of Cores	# of Threads	Clock Speed	Max Turbo Frequency	Cache	Intel QPI Speed	# of QPI Links	Max TDP	Memory Speed	Intel vPro technology
	Xeon E5-2603	4	4	1.8 GHz		10 MB	6.4 GT/s	2	80 W	1066MHz	vPro
	Xeon E5-2609	4	4	2.4 GHz		10 MB	6.4 GT/s	2	80 W	1066MHz	vPro
	Xeon E5-2620	6	12	2 GHz	2.5 GHz	15 MB	7.2 GT/s	2	95 W	1333MHz	vPro
	Xeon E5-2630	6	12	2.3 GHz	2.8 GHz	15 MB	7.2 GT/s	2	95 W	1333MHz	vPro
	Xeon E5-2630L	6	12	2 GHz	2.5 GHz	15 MB	7.2 GT/s	2	60 W	1333MHz	vPro
	Xeon E5-2637	2	4	3 GHz	3.5 GHz	5 MB	8 GT/s	2	80 W	1600MHz	vPro
	Xeon E5-2640	6	12	2.5 GHz	3 GHz	15 MB	7.2 GT/s	2	95 W	1333MHz	vPro
	Xeon E5-2643	4	8	3.3 GHz	3.5 GHz	10 MB	8 GT/s	2	130 W	1600MHz	vPro
	Xeon E5-2650	8	16	2 GHz	2.8 GHz	20 MB	8 GT/s	2	95 W	1600MHz	vPro
	Xeon E5-2650L	8	16	1.8 GHz	2.3 GHz	20 MB	8 GT/s	2	70 W	1600MHz	vPro
	Xeon E5-2660	8	16	2.2 GHz	3 GHz	20 MB	8 GT/s	2	95 W	1600MHz	vPro
	Xeon E5-2665	8	16	2.4 GHz	3.1 GHz	20 MB	8 GT/s	2	115 W	1600MHz	vPro
	Xeon E5-2667	6	12	2.9 GHz	3.5 GHz	15 MB	8 GT/s	2	130 W	1600MHz	vPro
	Xeon E5-2670	8	16	2.6 GHz	3.3 GHz	20 MB	8 GT/s	2	115 W	1600MHz	vPro
	Xeon E5-2680	8	16	2.7 GHz	3.5 GHz	20 MB	8 GT/s	2	130 W	1600MHz	vPro
	Xeon E5-2690	8	16	2.9 GHz	3.8 GHz	20 MB	8 GT/s	2	135 W	1600MHz	vPro
	Xeon E5-1603	4	4	2.8 GHz		10 MB			130 W	1066MHz	vPro
	Xeon E5-2603 v2	4	4	1.8 GHz	1.8 GHz	10 MB	6.4 GT/s	2	80 W	1333MHz	vPro
	Xeon E5-2609 v2	4	4	2.5 GHz	2.5 GHz	10 MB	6.4 GT/s	2	80 W	1333MHz	vPro
	Xeon E5-2620 v2	6	12	2.1 GHz	2.6 GHz	15 MB	7.2 GT/s	2	80 W	1600MHz	vPro
	Xeon E5-2630L v2	6	12	2.4 GHz	2.8 GHz	15 MB	7.2 GT/s	2	60 W	1600MHz	vPro
	Xeon E5-2630 v2	6	12	2.6 GHz	3.1 GHz	15 MB	7.2 GT/s	2	80 W	1600MHz	vPro
	Xeon E5-2637 v2	4	8	3.5 GHz	3.8 GHz	15 MB	8 GT/s	2	130 W	1866MHz	vPro
	Xeon E5-2640 v2	8	16	2 GHz	2.5 GHz	20 MB	7.2 GT/s	2	95 W	1600MHz	vPro
	Xeon E5-2643 v2	6	12	3.5 GHz	3.8 GHz	25 MB	8 GT/s	2	130 W	1866MHz	vPro
	Xeon E5-2650L v2	10	20	1.7 GHz	2.1 GHz	25 MB	7.2 GT/s	2	70 W	1600MHz	vPro
	Xeon E5-2650 v2	8	16	2.6 GHz	3.4 GHz	20 MB	8 GT/s	2	95 W	1866MHz	vPro
	Xeon E5-2660 v2	10	20	2.2 GHz	3 GHz	25 MB	8 GT/s	2	95 W	1866MHz	vPro
	Xeon E5-2667 v2	8	16	3.3 GHz	4 GHz	25 MB	8 GT/s	2	130 W	1866MHz	vPro
	Xeon E5-2670 v2	10	20	2.5 GHz	3.3 GHz	25 MB	8 GT/s	2	115 W	1866MHz	vPro
	Xeon E5-2680 v2	10	20	2.8 GHz	3.6 GHz	25 MB	8 GT/s	2	115 W	1866MHz	vPro
	Xeon E5-2690 v2	10	20	3 GHz	3.6 GHz	25 MB	8 GT/s	2	130 W	1866MHz	vPro
	Xeon E5-2695 v2	12	24	2.4 GHz	3.2 GHz	30 MB	8 GT/s	2	115 W	1866MHz	vPro
	Xeon E5-2697 v2	12	24	2.7 GHz	3.5 GHz	30 MB	8 GT/s	2	130 W	1866MHz	vPro
	Xeon E5-1607 v2	4	4	3 GHz		10 MB			130 W	1600MHz	vPro
	Xeon E5-1620 v2	4	8	3.7 GHz	3.9 GHz	10 MB			130 W	1866MHz	vPro
	Xeon E5-1650 v2	6	12	3.5 GHz	3.9 GHz	12 MB			130 W	1866MHz	vPro
	Xeon E5-1660 v2	6	12	3.7 GHz	4 GHz	15 MB			130 W	1866MHz	vPro

Notes:

1. ThinkStation C30 support two processors. When ordering two processors, they must be the same
2. When using Intel Xeon E5-1600 and E5-1600 v2 series processors, max CPU configuration is 1
3. Intel Xeon processor numbering system is an alpha numeric representation of product line, product family and version. An 'L' suffix will be used to identify a low power processor.
More details please see http://www.intel.com/products/processor_number
4. All information is provided by Intel and may be changed at any time without notice. The information herein is provided "as-is". Intel may update this information in non-scheduled. For latest information, please see <http://ark.intel.com/products/family/59138/Intel-Xeon-Processor-E5-Family/server>

ThinkStation C30 Platform Specifications - II of IV

Text in red shows that these features only apply to MT type 1095 and 1097 models, text in green shows that the features are supported on other models except MT type 1095 and 1097 models

Memory	UDIMM or RDIMM, ECC, DDR3 , 8-channel capable (4-channel per processor), eight 240-pin DIMM sockets (four DIMM sockets per processor), 64GB max (UDIMM, 8GBx8)/256GB max (RDIMM, 32GBx8)					
Additional memory disclaimers	<ul style="list-style-type: none"> Actual memory operating speed depends on processor memory controller speed, installed memory speed, and quantity of memory DIMMs Over four DIMMs requires dual processors Mixing of RDIMM and UDIMM is not supported Maximum memory capacity is also limited by operating system When using processor from Xeon E5-1600 and E5-1600 v2 series, only four DIMM sockets for CPU1 are available and max memory capacity is 32GB (UDIMM, 8GBx4)/128GB (RDIMM, 32GBx4) 					
Graphics adapters and GPU computing	Two PCI Express 3.0 x16 slots for graphics adapters and GPU computing processors, supports NVIDIA SLI technology, NVIDIA Maximus technology, supports the following NVIDIA Quadro, NVS graphics adapters and Tesla GPU computing processors:					
	Memory Size	CUDA Processor Cores	Display Connectors	Max. Displays	# of slots	Power
NVIDIA Quadro and NVS Graphics						
Quadro K6000	12GB	2880	1 dual-link DVI-I 1 dual-link DVI-D 2 DisplayPort	4	2	225W
Quadro K5000	4GB	1536	1 dual-link DVI-I 1 dual-link DVI-D 2 DisplayPort	4	2	122W
Quadro K4000	3GB	768	1 dual-link DVI-I 2 DisplayPort	4*	1	80W
Quadro K2000	2GB	384	1 dual-link DVI-I 2 DisplayPort	4*	1	51W
Quadro K2000D	2GB	384	1 dual-link DVI-I 1 dual-link DVI-D 1 mini DisplayPort	4*	1	51W
Quadro K600	1GB	192	1 dual-link DVI-I 1 DisplayPort	2	1	41W
Quadro 410	512MB	192	1 dual-link DVI-I 1 DisplayPort	2	1	37W
Quadro 6000	6GB	448	1 dual-link DVI-I 2 DisplayPort 1 Stereo	2	2	204W
Quadro 5000	2.5GB	352	1 dual-link DVI-I 2 DisplayPort, 1 Stereo	2	2	152W
Quadro 4000	2GB	256	1 dual-link DVI-I 2 DisplayPort 1 Stereo	2	1	142W
Quadro 2000	1GB	192	1 dual-link DVI-I 2 DisplayPort	2	1	62W
Quadro 2000D	1GB	192	2 dual-link DVI-I	2	1	62W
Quadro 600	1GB	96	1 dual-link DVI-I 1 DisplayPort	2	1	40W
NVS 510	2048 MB	192	4 mini DisplayPort (with 4 mini DP to DP dongles)	4	1	35W
NVS 315	1024MB	48	DMS59 to dual single-link DVI-I or dual DisplayPort	2	1	19.5W
NVS 310	512 MB	48	2 DisplayPort	2	1	19.5W
NVS 300	512 MB	16	DMS59 to dual single- link DVI-I	2	1	17.5W
NVIDIA Tesla GPU Computing Processors (as part of NVIDIA Maximus Platform)						
Tesla K20	5GB	2496				225W
Tesla C2075	6GB	448				225W

* Quadro K4000, K2000, and K2000D are equipped with 3 onboard display connectors, 4 Displays require a supported DisplayPort 1.2 Multi-Stream capable hub or displays

Notes:

- ThinkStation supports NVIDIA SLI Technology with selected NVIDIA Quadro graphics adapters, additional SLI cable is needed. For the latest Quadro SLI certified list on ThinkStation, please see www.nvidia.com/object/quadro_sli_compatible_systems.html
- ThinkStation C30 support NVIDIA Maximus technology. Maximus technology combines the visualization and interactive design capability of NVIDIA Quadro graphics and the high performance computing power of NVIDIA Tesla GPU computing processors in a single workstation. For more information on the latest Maximus certifications for ThinkStation and how to build Maximus system, please see www.nvidia.com/object/maximus.html
- CUDA Processor Cores cannot be compared between GPU generations due to several important architectural differences that exist between streaming multiprocessor designs.

ThinkStation C30 Platform Specifications - III of IV

Onboard drive controllers	<ul style="list-style-type: none"> Four SATA connectors via integrated Advanced Host Controller Interface (AHCI) in chipset, two SATA 6.0Gb/s (red), two SATA 3.0Gb/s (orange), RAID 0, 1, 5 support Three SATA connectors via integrated Storage Controller Unit (SCU) in chipset, SATA 3.0Gb/s, RAID 0, 1, 5 support
Upgrade ROM for onboard drive controllers (opt)	Optional SAS HDD Enablement Module upgrades the 3 SATA connectors on SCU to 3 SATA/SAS connectors, SATA 3.0Gb/s, SAS 3.0Gb/s, RAID 0, 1 support
Discrete drive controller (opt)	<p><i>One the following, depending on model:</i></p> <p>LSI SAS 9240-8i: SATA 6.0Gb/s, SAS 6.0Gb/s, RAID 0, 1 support optional upgrade key for RAID 5 support</p> <p>LSI SAS 9260-8i: SATA 6.0Gb/s, SAS 6.0Gb/s, RAID 0, 1, 5 support</p>
Hard drive(s)	<p><i>Supports the following:</i></p> <p>3.5" SATA: SATA 6.0Gb/s, 7200 rpm, up to 4TB 3.5" Hybrid: SATA 6.0Gb/s, 7200 rpm, integrated 8GB NAND flash 2.5" SATA: SATA 6.0Gb/s, 10000 rpm, up to 1TB 3.5" SAS: SAS 6.0Gb/s, 15000 rpm, up to 600GB 2.5" SAS: SAS 6.0Gb/s, 15000 rpm, up to 300GB 2.5" SSD: Solid State Drive (SSD), SATA 6.0Gb/s, OPAL-capable on selected models, up to 300GB mSATA: mSATA Solid State Drive (SSD), SATA 6.0Gb/s, up to 128GB</p>
Optical	Supports DVD-ROM, DVD±RW, or Blu-ray Burner, SATA interface
Drive Bays	One external 5.25" bays for opticals, three internal 3.5" bays for hard drives
Media reader (opt)	None (use USB port)
Front ports	<p><i>MT type 1095 and 1097:</i> Two USB 2.0, microphone (3.5mm), headphone (3.5mm)</p> <p><i>Others MT types:</i> Two USB 3.0, microphone (3.5mm), headphone (3.5mm)</p>
Rear ports	Eight USB 2.0, two USB 3.0 (blue), one serial (9-pin), one ethernet (RJ-45), three analog audio ports (line-in, line-out, mic-in)
IEEE 1394 adptr (optional)	None. Optional FireWire PCIe adapter on selected models, 1394a-2000, 400Mbps, two 6-pin ports on rear
Audio	High Definition (HD) Audio, Realtek® ALC662 codec
Speaker	Internal speaker for business audio
Onboard Ethernet	One onboard gigabit ethernet, Intel 82579
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black
Mouse	Optical Wheel Mouse (USB connector), black
Power supply	800 watts with 80mm side-mounted variable speed fan, universal, Climate Savers® Computing Gold, 80 PLUS® Gold qualified
Security	<ul style="list-style-type: none"> Security chip: <ul style="list-style-type: none"> <i>MT type 1095 and 1097:</i> Nuvoton NPCT421L for TPM function, TCG 1.2-compliant <i>Others MT types:</i> STMicroelectronics ST33TPM12LPC for TPM function, TCG 1.2-compliant Side cover lock (ships with two identical keys) Padlock loop (in rear for opt padlock; padlock prohibits side cover removal) Security slot (in rear for optional Kensington® Microsaver® cable; prohibits side cover removal) Power-on password Administrator password Boot sequence control Boot without keyboard, mouse, diskette Serial port I/O enable/disable USB 2.0 ports enable/disable individually USB 3.0 ports enable/disable concurrently Chassis intrusion switch (optional)
Mechanical	<ul style="list-style-type: none"> Rack-mountable to 3U Raven black color; metal case 5.1"W x 17.5"D x 16.8"H 130mm W x 444mm D x 427mm H (without rubber feet) 40.7 lb (18.5kg) max configuration 24-liter
Expansion slots	<p>Slot 1: half-length, full-height, PCIe 3.0 x16 (near CPU, x4 elec)</p> <p>Slot 2: full-length, full-height, PCIe 3.0 x16*</p> <p>Slot 3: full-length, full-height, 32-bit PCI 2.3</p> <p>Slot 4: full-length, full-height, PCIe 3.0 x16*</p> <p>Slot 5: full-length, full-height, PCIe 2.0 x4</p> <p>Slot 6: half-length, full-height, 32-bit PCI 2.3</p> <p>* Adapters >75W use auxiliary power connector(s) from PSU</p>
Serviceability	<ul style="list-style-type: none"> Toolless side cover removal Toolless disk and optical drive removal Toolless adapter retention Illuminated front icons Rack shelf support or optional rail kit

ThinkStation C30 Platform Specifications - IV of IV

ISV certifications	Please visit www.lenovo.com/support/ISV
Environmental certifications	GREENGUARD® certified RoHS-compliant EPEAT™ Gold rating
Warranty	1 or 3-year limited warranty, parts and labor
ThinkVantage®	Supports ThinkVantage® technologies
Preloaded operating systems	<p><i>One the following, depending on model:</i></p> <ul style="list-style-type: none"> • Windows® 7 Professional 64 • Windows 7 Professional 64 preinstalled through downgrade rights in Windows 8 Pro 64-bit • Windows 8 Pro 64-bit
Preloaded applications (only some listed)	<p><i>For Windows 7 models:</i></p> <ul style="list-style-type: none"> • Rescue and Recovery® • Norton® Internet Security (30 days of virus definitions) • Adobe® Reader® • Adobe Flash® Player • Microsoft® Office preloaded; purchase product key to activate • Corel® WinDVD® (DVD±RW model(s)) • Ulead® DVD MovieFactory® (DVD±RW model(s)) <p><i>For Windows 8 models:</i></p> <ul style="list-style-type: none"> • Evernote® • Norton Internet Security (30 days of virus definitions) • Norton Studio • Skype™ • Microsoft Office 2013 preloaded; purchase product key to activate • Cyberlink Power2Go (DVD±RW model(s)) • Cyberlink PowerProducer (DVD±RW model(s))

ThinkStation C30 (1137) - TopSeller (June 2013)







Product Specifications Reference (PSREF)

Type-model ¹	Processor(s)	Memory (MHz/type)	Memory DIMMs	Upgrade ROM for onboard drive controller	Discrete drive controller	Pre-conf RAID	Hard drive(s) ²	Optical	Media reader	Graphics adapter(s) and GPU computing	1394 adptr	Chassis intrusion switch	Preloaded OS
1137-15G	1xE5-2609 (4C/2.4GHz/10MB/1066)	1600MHz UDIMM	4GBx3	No	No	No	1x2TB 3.5" SATA	DVD±RW	No	No	No	Switch	Win7 Pro64 (Downgrade from Win8)
1137-16G	1xE5-2620 (6C/2.5GHz/15MB/1333)	1600MHz UDIMM	4GBx3	No	No	No	1x256GB 2.5" SSD - OPAL	DVD±RW	No	No	No	Switch	Win7 Pro64 (Downgrade from Win8)
1137-17G	1xE5-2630 (6C/2.3GHz/15MB/1333)	1600MHz UDIMM	4GBx2	No	No	No	1x2TB 3.5" SATA	DVD±RW	No	No	No	Switch	Win7 Pro64 (Downgrade from Win8)
1137-18G	1xE5-2640 (6C/2.5GHz/15MB/1333)	1600MHz UDIMM	4GBx3	No	No	No	1x250GB 3.5" SATA	DVD±RW	No	No	No	Switch	Win7 Pro64 (Downgrade from Win8)
1137-19G	1xE5-2640 (6C/2.5GHz/15MB/1333)	1600MHz UDIMM	4GBx3	No	No	No	1x500GB 3.5" SATA	DVD±RW	No	No	No	Switch	Win7 Pro64 (Downgrade from Win8)

¹ Model in *italics* shows that this is a Global Model

² The SSD drives in *italics* must be plugged into SATA AHCI connectors (red/orange)

- **3-year limited warranty**
- **With new MT type 1136/1137 and beyond, ThinkStation C30 introduces new updates to improve the functionality and usability:** (These new features are not supported on 1095 and 1097MT models)
 - Intel AMT: upgrades to Intel AMT 8 from Intel AMT 7
 - New TPM chip: STMicroelectronics ST33TPM12LPC
 - Two front USB 2.0 ports upgrade to USB3.0
- For ThinkStation C30 platform specifications, please see [ThinkStation C30 Platform Specifications sheet](#)

Chipset	Intel C602 Chipset	Power	<ul style="list-style-type: none"> • Rack-mountable to 3U • Raven black color; metal case • 5.1"W x 17.5"D x 16.8"H • 130mm W x 444mm D x 427mm H (without rubber feet) • 40.7 lb (18.5kg) max configuration • 24-liter • Toolless side cover removal • Toolless disk and optical drive removal • Toolless adapter retention • Illuminated front icons • Rack shelf support or optional rail kit 	
Processor	Two LGA2011 sockets, supports up to two processors from Intel Xeon E5-2600 family, 4-channel DDR3 memory controller per processor			
Memory	UDIMM or RDIMM, ECC, DDR3 , 8-channel capable (4-channel per processor), eight 240-pin DIMM sockets 64GB max (UDIMM, 8GBx8)/256GB max (RDIMM, 32GBx8)	Security	<ul style="list-style-type: none"> • Security chip (see information on left) • Side cover lock (ships with two identical keys) • Padlock loop (in rear for opt padlock; padlock prohibits side cover removal) • Security slot (in rear for optional Kensington® Microsaver® cable; prohibits side cover removal) • Power-on password • Administrator password • Boot sequence control • Boot without keyboard, mouse, diskette • Serial port I/O enable/disable • USB 2.0 ports enable/disable individually • USB 3.0 ports enable/disable concurrently • Chassis intrusion switch on selected model(s) 	
Additional memory disclaimers	<ul style="list-style-type: none"> • Actual memory operating speed depends on processor memory controller speed, installed memory speed, and quantity of memory DIMMs • Over four DIMMs requires dual processors • Mixing of RDIMM and UDIMM is not supported 			
Graphics	Two PCI Express 3.0 x16 slots for graphics adapters and GPU computing processors, supports NVIDIA SLI technology, NVIDIA Maximus technology	Intel AMT	Intel Active Management Technology 8 supported	
Onboard drive controllers	<ul style="list-style-type: none"> • Four SATA connectors via integrated Advanced Host Controller Interface (AHCI) in chipset, two SATA 6.0Gb/s (red), two SATA 3.0Gb/s (orange), RAID 0, 1, 5 support • Three SATA connectors via integrated Storage Controller Unit (SCU) in chipset, SATA 3.0Gb/s, RAID 0, 1, 5 support 			
Upgrade ROM for onboard drive controllers (opt)	Optional SAS HDD Enablement Module upgrades the 3 SATA connectors on SCU to 3 SATA/SAS connectors, SATA 3.0Gb/s, SAS 3.0Gb/s, RAID 0, 1 support	ISV certifications	Please visit www.lenovo.com/support/ISV	
Discrete drive controller (opt)	<i>One the following, depending on model:</i> LSI SAS 9240-8i: SATA 6.0Gb/s, SAS 6.0Gb/s, RAID 0, 1 support optional upgrade key for RAID 5 support LSI SAS 9260-8i: SATA 6.0Gb/s, SAS 6.0Gb/s, RAID 0, 1, 5 support			
Hard drives	3.5" SATA: SATA 6.0Gb/s, 7200 rpm 2.5" SATA: SATA 6.0Gb/s, 10000 rpm 3.5" SAS/2.5" SAS: SAS 6.0Gb/s, 15000 rpm 2.5" SSD: Solid State Drive (SSD), SATA 6.0Gb/s, OPAL-capable on selected models mSATA: mSATA SSD, SATA 6.0Gb/s	Environmental certifications	GREENGUARD® certified RoHS-compliant EPEAT™ Gold rating	
Optical	Supports DVD-ROM, DVD±RW, or Blu-ray Burner, SATA interface			
Media reader	None (use USB port)	Supports ThinkVantage® technologies		
Front ports	Two USB 3.0, microphone (3.5mm), headphone (3.5mm)			
Rear ports	Eight USB 2.0, two USB 3.0 (blue), one serial (9-pin), one ethernet (RJ-45), three analog audio ports (line-in, line-out, mic-in)			
IEEE 1394 adptr (optional)	None. Optional FireWire PCIe adapter on selected models, 1394a-2000, 400Mbps, two 6-pin ports on rear			
Audio	High Definition (HD) Audio, Realtek® ALC662 codec			
Speaker	Internal speaker for business audio			
Onboard Ethernet	One onboard gigabit ethernet, Intel 82579			
Security chip	STMicroelectronics ST33TPM12LPC, TCG 1.2-compliant			
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black			
Mouse	Optical Wheel Mouse (USB connector), black			
Power supply	800 watts with 80mm side-mounted variable speed fan, universal, Climate Savers® Computing Gold, 80 PLUS® Gold qualified			
Preloaded operating systems (OS)	<i>One the following, depending on model:</i> <ul style="list-style-type: none"> • Windows 7 Professional 64 • Windows 7 Professional 64 preinstalled through downgrade rights in Windows 8 Pro 64-bit • Windows 8 Pro 64-bit 			

See footnotes for important warranty information
Model(s) announced June 18, 2013

© Lenovo
(G-ALI1-3) June 2013

ThinkStation C30 (1137) - TopSeller (June 2013) - II


Product Specifications Reference (PSREF)

Type-model ¹	Processor(s)	Memory (MHz/type)	Memory DIMMs	Upgrade ROM for onboard drive controller	Discrete drive controller	Pre-conf RAID	Hard drive(s) ²	Optical	Media reader	Graphics adapter(s) and GPU computing	1394 adptr	Chassis intrusion switch	Preloaded OS
1137-21G	1xE5-2640 (6C/2.5GHz/15MB/1333)	1600MHz UDIMM	4GBx3	No	No	No	1x1TB 2.5" SATA	DVD±RW	No	No	No	Switch	Win7 Pro64 (Downgrade from Win8)
1137-22G	1xE5-2640 (6C/2.5GHz/15MB/1333)	1600MHz UDIMM	4GBx4	No	No	No	1x128GB 2.5" SSD	DVD±RW	No	1xNVS 310 (512MB, DMS59 to dual DP, 19.5W)	No	Switch	Win7 Pro64 (Downgrade from Win8)
1137-23G	1xE5-2640 (6C/2.5GHz/15MB/1333)	1600MHz UDIMM	4GBx3	No	No	No	1x256GB 2.5" SSD	DVD±RW	No	No	No	Switch	Win7 Pro64 (Downgrade from Win8)
1137-24G	1xE5-2640 (6C/2.5GHz/15MB/1333)	1600MHz UDIMM	4GBx3	SAS	No	No	1x600GB 3.5" SAS	DVD±RW	No	No	No	Switch	Win7 Pro64 (Downgrade from Win8)
1137-25G	1xE5-2640 (6C/2.5GHz/15MB/1333)	1600MHz UDIMM	4GBx3	No	No	No	1x3TB 3.5" SATA	DVD±RW	No	No	No	Switch	Win7 Pro64 (Downgrade from Win8)

¹ Model in italics shows that this is a Global Model

² The SSD drives in italics must be plugged into SATA AHCI connectors (red/orange)

- **3-year limited warranty**
- **With new MT type 1136/1137 and beyond, ThinkStation C30 introduces new updates to improve the functionality and usability:**
 - (These new features are not supported on 1095 and 1097MT models)
 - Intel AMT: upgrades to Intel AMT 8 from Intel AMT 7
 - New TPM chip: STMicroelectronics ST33TPM12LPC
 - Two front USB 2.0 ports upgrade to USB3.0
- For ThinkStation C30 platform specifications, please see [ThinkStation C30 Platform Specifications sheet](#)

Chipset	Intel C602 Chipset	Tower	
Processor	Two LGA2011 sockets, supports up to two processors from Intel Xeon E5-2600 family, 4-channel DDR3 memory controller per processor		
Memory	UDIMM or RDIMM, ECC, DDR3 , 8-channel capable (4-channel per processor), eight 240-pin DIMM sockets 64GB max (UDIMM, 8GBx8)/256GB max (RDIMM, 32GBx8)	<ul style="list-style-type: none"> • Rack-mountable to 3U • Raven black color; metal case • 5.1"W x 17.5"D x 16.8"H • 130mm W x 444mm D x 427mm H (without rubber feet) • 40.7 lb (18.5kg) max configuration • 24-liter • Toolless side cover removal • Toolless disk and optical drive removal • Toolless adapter retention • Illuminated front icons • Rack shelf support or optional rail kit 	
Additional memory disclaimers	<ul style="list-style-type: none"> • Actual memory operating speed depends on processor memory controller speed, installed memory speed, and quantity of memory DIMMs • Over four DIMMs requires dual processors • Mixing of RDIMM and UDIMM is not supported 	Bay 1 5.25", 1.6" high, external, for optical Bay 2-4 3.5", 1" high, internal, for hard drive Slot 1: half-length, full-height, PCIe 3.0 x16 (near CPU, x4 elec) Slot 2: full-length, full-height, PCIe 3.0 x16* Slot 3: full-length, full-height, 32-bit PCI 2.3 Slot 4: full-length, full-height, PCIe 3.0 x16* Slot 5: full-length, full-height, PCIe 2.0 x4 Slot 6: half-length, full-height, 32-bit PCI 2.3	
Graphics	Two PCI Express 3.0 x16 slots for graphics adapters and GPU computing processors, supports NVIDIA SLI technology, NVIDIA Maximus technology	* Adapters >75W use auxiliary power connector(s) from PSU	
Onboard drive controllers	<ul style="list-style-type: none"> • Four SATA connectors via integrated Advanced Host Controller Interface (AHCI) in chipset, two SATA 6.0Gb/s (red), two SATA 3.0Gb/s (orange), RAID 0, 1, 5 support • Three SATA connectors via integrated Storage Controller Unit (SCU) in chipset, SATA 3.0Gb/s, RAID 0, 1, 5 support 	SECURITY <ul style="list-style-type: none"> • Security chip (see information on left) • Side cover lock (ships with two identical keys) • Padlock loop (in rear for opt padlock; padlock prohibits side cover removal) • Security slot (in rear for optional Kensington® Microsaver® cable; prohibits side cover removal) • Power-on password • Administrator password • Boot sequence control • Boot without keyboard, mouse, diskette • Serial port I/O enable/disable • USB 2.0 ports enable/disable individually • USB 3.0 ports enable/disable concurrently • Chassis intrusion switch on selected model(s) 	
Upgrade ROM for onboard drive controllers (opt)	Optional SAS HDD Enablement Module upgrades the 3 SATA connectors on SCU to 3 SATA/SAS connectors, SATA 3.0Gb/s, SAS 3.0Gb/s, RAID 0, 1 support		
Discrete drive controller (opt)	<i>One the following, depending on model:</i> LSI SAS 9240-8i: SATA 6.0Gb/s, SAS 6.0Gb/s, RAID 0, 1 support optional upgrade key for RAID 5 support LSI SAS 9260-8i: SATA 6.0Gb/s, SAS 6.0Gb/s, RAID 0, 1, 5 support		
Hard drives	3.5" SATA: SATA 6.0Gb/s, 7200 rpm 2.5" SATA: SATA 6.0Gb/s, 10000 rpm 3.5" SAS/2.5" SAS: SAS 6.0Gb/s, 15000 rpm 2.5" SSD: Solid State Drive (SSD), SATA 6.0Gb/s, OPAL-capable on selected models mSATA: mSATA SSD, SATA 6.0Gb/s		
Optical	Supports DVD-ROM, DVD±RW, or Blu-ray Burner, SATA interface		
Media reader	None (use USB port)		
Front ports	Two USB 3.0, microphone (3.5mm), headphone (3.5mm)		
Rear ports	Eight USB 2.0, two USB 3.0 (blue), one serial (9-pin), one ethernet (RJ-45), three analog audio ports (line-in, line-out, mic-in)		
IEEE 1394 adptr (optional)	None. Optional FireWire PCIe adapter on selected models, 1394a-2000, 400Mbps, two 6-pin ports on rear		
Audio	High Definition (HD) Audio, Realtek® ALC662 codec		
Speaker	Internal speaker for business audio		
Onboard Ethernet	One onboard gigabit ethernet, Intel 82579		
Security chip	STMicroelectronics ST33TPM12LPC, TCG 1.2-compliant		
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black		
Mouse	Optical Wheel Mouse (USB connector), black		
Power supply	800 watts with 80mm side-mounted variable speed fan, universal, Climate Savers® Computing Gold, 80 PLUS® Gold qualified		
Preloaded operating systems (OS)	<i>One the following, depending on model:</i> <ul style="list-style-type: none"> • Windows 7 Professional 64 • Windows 7 Professional 64 preinstalled through downgrade rights in Windows 8 Pro 64-bit • Windows 8 Pro 64-bit 	Intel AMT Intel Active Management Technology 8 supported ISV certifications Please visit www.lenovo.com/support/ISV Environmental certifications GREENGUARD® certified RoHS-compliant EPEAT™ Gold rating Supports ThinkVantage® technologies	

See footnotes for important warranty information
 Model(s) announced June 18, 2013

© Lenovo
 (G-ALI2-3) June 2013

ThinkStation C30 (1137) - TopSeller (June 2013) - III

Product Specifications Reference (PSREF)

Type-model ¹	Processor(s)	Memory (MHz/type)	Memory DIMMs	Upgrade ROM for onboard drive controller	Discrete drive controller	Pre-conf RAID	Hard drive(s) ²	Optical	Media reader	Graphics adapter(s) and GPU computing	1394 adptr	Chassis intrusion switch	Preloaded OS
1137-26G	1xE5-2640 (6C/2.5GHz/15MB/1333)	1600MHz RDIMM	4GBx4	No	No	No	1x128GB mSATA	DVD±RW	No	1xQuadro K600 (1GB, 1xDVI-I DL*, 1xDP, 41W)	No	Switch	Win7 Pro64 (Downgrade from Win8)
1137-27G	1xE5-2640 (6C/2.5GHz/15MB/1333)	1600MHz RDIMM	4GBx3	SAS	No	No	1x300GB 3.5 SAS	DVD±RW	No	No	No	Switch	Win7 Pro64 (Downgrade from Win8)
1137-28G	1xE5-2640 (6C/2.5GHz/15MB/1333)	1600MHz RDIMM	4GBx2	No	No	No	1x240GB 2.5 SSD	DVD±RW	No	1xNVS 310 (512MB, DMS59 to dual DP, 19.5W)	No	Switch	Win7 Pro64 (Downgrade from Win8)
1137-29G	1xE5-2667 (8C/2.9GHz/15MB/1600)	1600MHz RDIMM	4GBx2	No	No	No	1x180GB 2.5 SSD	DVD±RW	No	No	No	Switch	Win7 Pro64 (Downgrade from Win8)
1137-31G	1xE5-2650 (8C/2GHz/20MB/1600)	1600MHz RDIMM	4GBx3	SAS	No	No	2x300GB 3.5 SAS	DVD±RW	No	1xQuadro K2000 (2GB, 1xDVI-I DL, 2xDP, 51W)	No	No	Win7 Pro64 (Downgrade from Win8)

¹ Model in italics shows that this is a Global Model

² The SSD drives in italics must be plugged into SATA AHCI connectors (red/orange)

* DL = Dual Link, SL = Single Link

- **3-year limited warranty**
- **With new MT type 1136/1137 and beyond, ThinkStation C30 introduces new updates to improve the functionality and usability:**
 - (These new features are not supported on 1095 and 1097MT models)
 - Intel AMT: upgrades to Intel AMT 8 from Intel AMT 7
 - New TPM chip: STMicroelectronics ST33TPM12LPC
 - Two front USB 2.0 ports upgrade to USB3.0
- For ThinkStation C30 platform specifications, please see [ThinkStation C30 Platform Specifications sheet](#)

Chipset	Intel C602 Chipset	<p>Tower</p> <ul style="list-style-type: none"> • Rack-mountable to 3U • Raven black color; metal case • 5.1"W x 17.5"D x 16.8"H • 130mm W x 444mm D x 427mm H (without rubber feet) • 40.7 lb (18.5kg) max configuration • 24-liter • Toolless side cover removal • Toolless disk and optical drive removal • Toolless adapter retention • Illuminated front icons • Rack shelf support or optional rail kit <p>Bay 1 5.25", 1.6" high, external, for optical Bay 2-4 3.5", 1" high, internal, for hard drive</p> <p>Slot 1: half-length, full-height, PCIe 3.0 x16 (near CPU, x4 elec) Slot 2: full-length, full-height, PCIe 3.0 x16* Slot 3: full-length, full-height, 32-bit PCI 2.3 Slot 4: full-length, full-height, PCIe 3.0 x16* Slot 5: full-length, full-height, PCIe 2.0 x4 Slot 6: half-length, full-height, 32-bit PCI 2.3</p> <p>* Adapters >75W use auxiliary power connector(s) from PSU</p> <p>SECURITY</p> <ul style="list-style-type: none"> • Security chip (see information on left) • Side cover lock (ships with two identical keys) • Padlock loop (in rear for opt padlock; padlock prohibits side cover removal) • Security slot (in rear for optional Kensington® Microsaver® cable; prohibits side cover removal) • Power-on password • Administrator password • Boot sequence control • Boot without keyboard, mouse, diskette • Serial port I/O enable/disable • USB 2.0 ports enable/disable individually • USB 3.0 ports enable/disable concurrently • Chassis intrusion switch on selected model(s) <p>Intel AMT</p> <p>Intel Active Management Technology 8 supported</p> <p>ISV certifications</p> <p>Please visit www.lenovo.com/support/ISV</p> <p>Environmental certifications</p> <p>GREENGUARD® certified RoHS-compliant EPEAT™ Gold rating</p> <p>Supports ThinkVantage® technologies</p>
Processor	Two LGA2011 sockets, supports up to two processors from Intel Xeon E5-2600 family, 4-channel DDR3 memory controller per processor	
Memory	UDIMM or RDIMM, ECC, DDR3 , 8-channel capable (4-channel per processor), eight 240-pin DIMM sockets 64GB max (UDIMM, 8GBx8)/256GB max (RDIMM, 32GBx8)	
Additional memory disclaimers	<ul style="list-style-type: none"> • Actual memory operating speed depends on processor memory controller speed, installed memory speed, and quantity of memory DIMMs • Over four DIMMs requires dual processors • Mixing of RDIMM and UDIMM is not supported 	
Graphics	Two PCI Express 3.0 x16 slots for graphics adapters and GPU computing processors, supports NVIDIA SLI technology, NVIDIA Maximus technology	
Onboard drive controllers	<ul style="list-style-type: none"> • Four SATA connectors via integrated Advanced Host Controller Interface (AHCI) in chipset, two SATA 6.0Gb/s (red), two SATA 3.0Gb/s (orange), RAID 0, 1, 5 support • Three SATA connectors via integrated Storage Controller Unit (SCU) in chipset, SATA 3.0Gb/s, RAID 0, 1, 5 support 	
Upgrade ROM for onboard drive controllers (opt)	Optional SAS HDD Enablement Module upgrades the 3 SATA connectors on SCU to 3 SATA/SAS connectors, SATA 3.0Gb/s, SAS 3.0Gb/s, RAID 0, 1 support	
Discrete drive controller (opt)	<p>One the following, depending on model:</p> <p>LSI SAS 9240-8i: SATA 6.0Gb/s, SAS 6.0Gb/s, RAID 0, 1 support optional upgrade key for RAID 5 support</p> <p>LSI SAS 9260-8i: SATA 6.0Gb/s, SAS 6.0Gb/s, RAID 0, 1, 5 support</p>	
Hard drives	<p>3.5" SATA: SATA 6.0Gb/s, 7200 rpm</p> <p>2.5" SATA: SATA 6.0Gb/s, 10000 rpm</p> <p>3.5" SAS/2.5" SAS: SAS 6.0Gb/s, 15000 rpm</p> <p>2.5" SSD: Solid State Drive (SSD), SATA 6.0Gb/s, OPAL-capable on selected models</p> <p>mSATA: mSATA SSD, SATA 6.0Gb/s</p>	
Optical	Supports DVD-ROM, DVD±RW, or Blu-ray Burner, SATA interface	
Media reader	None (use USB port)	
Front ports	Two USB 3.0, microphone (3.5mm), headphone (3.5mm)	
Rear ports	Eight USB 2.0, two USB 3.0 (blue), one serial (9-pin), one ethernet (RJ-45), three analog audio ports (line-in, line-out, mic-in)	
IEEE 1394 adptr (optional)	None. Optional FireWire PCIe adapter on selected models, 1394a-2000, 400Mbps, two 6-pin ports on rear	
Audio	High Definition (HD) Audio, Realtek® ALC662 codec	
Speaker	Internal speaker for business audio	
Onboard Ethernet	One onboard gigabit ethernet, Intel 82579	
Security chip	STMicroelectronics ST33TPM12LPC, TCG 1.2-compliant	
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black	
Mouse	Optical Wheel Mouse (USB connector), black	
Power supply	800 watts with 80mm side-mounted variable speed fan, universal, Climate Savers® Computing Gold, 80 PLUS® Gold qualified	
Preloaded operating systems (OS)	<p>One the following, depending on model:</p> <ul style="list-style-type: none"> • Windows 7 Professional 64 • Windows 7 Professional 64 preinstalled through downgrade rights in Windows 8 Pro 64-bit • Windows 8 Pro 64-bit 	

See footnotes for important warranty information
 Model(s) announced June 18, 2013

© Lenovo
 (G-ALI3-3) June 2013

ThinkStation C30 (1137) - TopSeller (June 2013) - IV

Product Specifications Reference (PSREF)

Type-model ¹	Processor(s)	Memory (MHz/type)	Memory DIMMs	Upgrade ROM for onboard drive controller	Discrete drive controller	Pre-conf RAID	Hard drive(s) ²	Optical	Media reader	Graphics adapter(s) and GPU computing	1394 adptr	Chassis intrusion switch	Preloaded OS
1137-32G	1xE5-2660 (8C/2.2GHz/20MB/1600)	1600MHz RDIMM	4GBx3	No	No	No	1x3TB 3.5" SATA	DVD±RW	No	1xQuadro K2000 (2GB, 1xDVI-I DL*, 2xDP, 51W)	No	Switch	Win7 Pro64 (Downgrade from Win8)
1137-33G	1xE5-2660 (8C/2.2GHz/20MB/1600)	1600MHz RDIMM	4GBx3	No	No	No	1x2TB 3.5" SATA	DVD±RW	No	1xQuadro K5000 (4GB, 1xDVI-I DL, 1xDVI-D DL, 2xDP, 122W)	No	Switch	Win7 Pro64 (Downgrade from Win8)
1137-34G	1xE5-2665 (8C/2.4GHz/20MB/1600)	1600MHz RDIMM	4GBx4	No	No	No	1x1TB 2.5" SATA	DVD±RW	No	2xQuadro K5000 SLI (Quadro K5000: 4GB, 1xDVI-I DL, 1xDVI-D DL, 2xDP, 122W)	No	Switch	Win7 Pro64 (Downgrade from Win8)
1137-35G	1xE5-2665 (8C/2.4GHz/20MB/1600)	1600MHz RDIMM	4GBx4	No	No	No	1x1TB 2.5" SATA	DVD±RW	No	1xQuadro K4000 (3GB, 1xDVI-I DL, 2xDP, 80W)	No	Switch	Win7 Pro64 (Downgrade from Win8)
1137-36G	1xE5-2670 (8C/2.6GHz/20MB/1600)	1600MHz RDIMM	4GBx3	No	No	No	1x2TB 3.5" SATA	DVD±RW	No	1xQuadro K2000D (2GB, 1xDVI-I DL, 1xDVI-D DL, 1xmini-DP, 51W)	No	Switch	Win7 Pro64 (Downgrade from Win8)

¹ Model in italics shows that this is a Global Model

² The SSD drives in italics must be plugged into SATA AHCI connectors (red/orange)

* DL = Dual Link, SL = Single Link

- **3-year limited warranty**
- **With new MT type 1136/1137 and beyond, ThinkStation C30 introduces new updates to improve the functionality and usability:**
(These new features are not supported on 1095 and 1097MT models)
 - Intel AMT: upgrades to Intel AMT 8 from Intel AMT 7
 - New TPM chip: STMicroelectronics ST33TPM12LPC
 - Two front USB 2.0 ports upgrade to USB3.0
- **For ThinkStation C30 platform specifications, please see [ThinkStation C30 Platform Specifications sheet](#)**

Chipset	Intel C602 Chipset	<p>Tower</p> <ul style="list-style-type: none"> • Rack-mountable to 3U • Raven black color; metal case • 5.1"W x 17.5"D x 16.8"H • 130mm W x 444mm D x 427mm H (without rubber feet) • 40.7 lb (18.5kg) max configuration • 24-liter • Toolless side cover removal • Toolless disk and optical drive removal • Toolless adapter retention • Illuminated front icons • Rack shelf support or optional rail kit <p>Bay 1 5.25", 1.6" high, external, for optical Bay 2-4 3.5", 1" high, internal, for hard drive</p> <p>Slot 1: half-length, full-height, PCIe 3.0 x16 (near CPU, x4 elec) Slot 2: full-length, full-height, PCIe 3.0 x16* Slot 3: full-length, full-height, 32-bit PCI 2.3 Slot 4: full-length, full-height, PCIe 3.0 x16* Slot 5: full-length, full-height, PCIe 2.0 x4 Slot 6: half-length, full-height, 32-bit PCI 2.3</p> <p>* Adapters >75W use auxiliary power connector(s) from PSU</p> <p>SECURITY</p> <ul style="list-style-type: none"> • Security chip (see information on left) • Side cover lock (ships with two identical keys) • Padlock loop (in rear for opt padlock; padlock prohibits side cover removal) • Security slot (in rear for optional Kensington® Microsaver® cable; prohibits side cover removal) • Power-on password • Administrator password • Boot sequence control • Boot without keyboard, mouse, diskette • Serial port I/O enable/disable • USB 2.0 ports enable/disable individually • USB 3.0 ports enable/disable concurrently • Chassis intrusion switch on selected model(s) <p>Intel AMT</p> <p>Intel Active Management Technology 8 supported</p> <p>ISV certifications</p> <p>Please visit www.lenovo.com/support/ISV</p> <p>Environmental certifications</p> <p>GREENGUARD® certified RoHS-compliant EPEAT™ Gold rating</p> <p>Supports ThinkVantage® technologies</p>
Processor	Two LGA2011 sockets, supports up to two processors from Intel Xeon E5-2600 family, 4-channel DDR3 memory controller per processor	
Memory	UDIMM or RDIMM, ECC, DDR3 , 8-channel capable (4-channel per processor), eight 240-pin DIMM sockets 64GB max (UDIMM, 8GBx8)/256GB max (RDIMM, 32GBx8)	
Additional memory disclaimers	<ul style="list-style-type: none"> • Actual memory operating speed depends on processor memory controller speed, installed memory speed, and quantity of memory DIMMs • Over four DIMMs requires dual processors • Mixing of RDIMM and UDIMM is not supported 	
Graphics	Two PCI Express 3.0 x16 slots for graphics adapters and GPU computing processors, supports NVIDIA SLI technology, NVIDIA Maximus technology	
Onboard drive controllers	<ul style="list-style-type: none"> • Four SATA connectors via integrated Advanced Host Controller Interface (AHCI) in chipset, two SATA 6.0Gb/s (red), two SATA 3.0Gb/s (orange), RAID 0, 1, 5 support • Three SATA connectors via integrated Storage Controller Unit (SCU) in chipset, SATA 3.0Gb/s, RAID 0, 1, 5 support 	
Upgrade ROM for onboard drive controllers (opt)	Optional SAS HDD Enablement Module upgrades the 3 SATA connectors on SCU to 3 SATA/SAS connectors, SATA 3.0Gb/s, SAS 3.0Gb/s, RAID 0, 1 support	
Discrete drive controller (opt)	<p>One the following, depending on model:</p> <p>LSI SAS 9240-8i: SATA 6.0Gb/s, SAS 6.0Gb/s, RAID 0, 1 support optional upgrade key for RAID 5 support</p> <p>LSI SAS 9260-8i: SATA 6.0Gb/s, SAS 6.0Gb/s, RAID 0, 1, 5 support</p>	
Hard drives	<p>3.5" SATA: SATA 6.0Gb/s, 7200 rpm</p> <p>2.5" SATA: SATA 6.0Gb/s, 10000 rpm</p> <p>3.5" SAS/2.5" SAS: SAS 6.0Gb/s, 15000 rpm</p> <p>2.5" SSD: Solid State Drive (SSD), SATA 6.0Gb/s, OPAL-capable on selected models</p> <p>mSATA: mSATA SSD, SATA 6.0Gb/s</p>	
Optical	Supports DVD-ROM, DVD±RW, or Blu-ray Burner, SATA interface	
Media reader	None (use USB port)	
Front ports	Two USB 3.0, microphone (3.5mm), headphone (3.5mm)	
Rear ports	Eight USB 2.0, two USB 3.0 (blue), one serial (9-pin), one ethernet (RJ-45), three analog audio ports (line-in, line-out, mic-in)	
IEEE 1394 adptr (optional)	None. Optional FireWire PCIe adapter on selected models, 1394a-2000, 400Mbps, two 6-pin ports on rear	
Audio	High Definition (HD) Audio, Realtek® ALC662 codec	
Speaker	Internal speaker for business audio	
Onboard Ethernet	One onboard gigabit ethernet, Intel 82579	
Security chip	STMicroelectronics ST33TPM12LPC, TCG 1.2-compliant	
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black	
Mouse	Optical Wheel Mouse (USB connector), black	
Power supply	800 watts with 80mm side-mounted variable speed fan, universal, Climate Savers® Computing Gold, 80 PLUS® Gold qualified	
Preloaded operating systems (OS)	<p>One the following, depending on model:</p> <ul style="list-style-type: none"> • Windows 7 Professional 64 • Windows 7 Professional 64 preinstalled through downgrade rights in Windows 8 Pro 64-bit • Windows 8 Pro 64-bit 	

See footnotes for important warranty information
Model(s) announced June 18, 2013

© Lenovo
(G-ALI4-3) June 2013

ThinkStation C30 (1137) - TopSeller (June 2013) - V

Product Specifications Reference (PSREF)

Type-model ¹	Processor(s)	Memory (MHz/type)	Memory DIMMs	Upgrade ROM for onboard drive controller	Discrete drive controller	Pre-conf RAID	Hard drive(s) ²	Optical	Media reader	Graphics adapter(s) and GPU computing	1394 adptr	Chassis intrusion switch	Preloaded OS
1137-37G	1xE5-2680 (8C/2.7GHz/20MB/1600)	1600MHz RDIMM	4GBx3	No	No	No	2x256GB 2.5" SSD - OPAL	DVD±RW	No	1xQuadro K2000 (2GB, 1xDVI-I DL*, 2xDP, 51W)	No	Switch	Win7 Pro64 (Downgrade from Win8)
1137-38G	1xE5-2690 (8C/2.9GHz/20MB/1600)	1600MHz RDIMM	4GBx3	No	No	No	1x3TB 3.5" SATA	DVD±RW	No	1xQuadro K5000 (4GB, 1xDVI-I DL, 1xDVI-D DL, 2xDP, 122W)	No	Switch	Win7 Pro64 (Downgrade from Win8)
1137-39G	2xE5-2630 (6C/2.3GHz/15MB/1333)	1600MHz RDIMM	4GBx4	No	No	No	1x3TB 3.5" SATA	DVD±RW	No	1xQuadro K5000 (4GB, 1xDVI-I DL, 1xDVI-D DL, 2xDP, 122W)	No	Switch	Win7 Pro64 (Downgrade from Win8)
1137-41G	2xE5-2630 (6C/2.3GHz/15MB/1333)	1600MHz RDIMM	4GBx3	No	No	No	1x2TB 3.5" SATA	DVD±RW	No	1xQuadro K4000 (3GB, 1xDVI-I DL, 2xDP, 80W)	No	Switch	Win7 Pro64 (Downgrade from Win8)
1137-66G	2xE5-2640 (6C/2.5GHz/15MB/1333)	1600MHz UDIMM	2GBx8	No	No	No	1x1TB 3.5" SATA	DVD±RW	No	1xQuadro K4000 (3GB, 1xDVI-I DL, 2xDP, 80W)	No	Switch	Win7 Pro64 (Downgrade from Win8)

1 Model in italics shows that this is a Global Model

2 The SSD drives in italics must be plugged into SATA AHCI connectors (red/orange)

* DL = Dual Link, SL = Single Link

- **3-year limited warranty**
- **With new MT type 1136/1137 and beyond, ThinkStation C30 introduces new updates to improve the functionality and usability:**
 - (These new features are not supported on 1095 and 1097MT models)
 - Intel AMT: upgrades to Intel AMT 8 from Intel AMT 7
 - New TPM chip: STMicroelectronics ST33TPM12LPC
 - Two front USB 2.0 ports upgrade to USB3.0
- **For ThinkStation C30 platform specifications, please see [ThinkStation C30 Platform Specifications sheet](#)**

Chipset	Intel C602 Chipset	Tower <ul style="list-style-type: none"> • Rack-mountable to 3U • Raven black color; metal case • 5.1"W x 17.5"D x 16.8"H • 130mm W x 444mm D x 427mm H (without rubber feet) • 40.7 lb (18.5kg) max configuration • 24-liter • Toolless side cover removal • Toolless disk and optical drive removal • Toolless adapter retention • Illuminated front icons • Rack shelf support or optional rail kit 	
Processor	Two LGA2011 sockets, supports up to two processors from Intel Xeon E5-2600 family, 4-channel DDR3 memory controller per processor		
Memory	UDIMM or RDIMM, ECC, DDR3 , 8-channel capable (4-channel per processor), eight 240-pin DIMM sockets 64GB max (UDIMM, 8GBx8)/256GB max (RDIMM, 32GBx8)	<ul style="list-style-type: none"> Bay 1 5.25", 1.6" high, external, for optical Bay 2-4 3.5", 1" high, internal, for hard drive Slot 1: half-length, full-height, PCIe 3.0 x16 (near CPU, x4 elec) Slot 2: full-length, full-height, PCIe 3.0 x16* Slot 3: full-length, full-height, 32-bit PCI 2.3 Slot 4: full-length, full-height, PCIe 3.0 x16* Slot 5: full-length, full-height, PCIe 2.0 x4 Slot 6: half-length, full-height, 32-bit PCI 2.3 	<ul style="list-style-type: none"> • Security chip (see information on left) • Side cover lock (ships with two identical keys) • Padlock loop (in rear for opt padlock; padlock prohibits side cover removal) • Security slot (in rear for optional Kensington® Microsaver® cable; prohibits side cover removal) • Power-on password • Administrator password • Boot sequence control • Boot without keyboard, mouse, diskette • Serial port I/O enable/disable • USB 2.0 ports enable/disable individually • USB 3.0 ports enable/disable concurrently • <i>Chassis intrusion switch on selected model(s)</i>
Additional memory disclaimers	<ul style="list-style-type: none"> • Actual memory operating speed depends on processor memory controller speed, installed memory speed, and quantity of memory DIMMs • Over four DIMMs requires dual processors • Mixing of RDIMM and UDIMM is not supported 		
Graphics	Two PCI Express 3.0 x16 slots for graphics adapters and GPU computing processors, supports NVIDIA SLI technology, NVIDIA Maximus technology	<p>SECURITY</p>	<p>Intel AMT</p> <p>Intel Active Management Technology 8 supported</p>
Onboard drive controllers	<ul style="list-style-type: none"> • Four SATA connectors via integrated Advanced Host Controller Interface (AHCI) in chipset, two SATA 6.0Gb/s (red), two SATA 3.0Gb/s (orange), RAID 0, 1, 5 support • Three SATA connectors via integrated Storage Controller Unit (SCU) in chipset, SATA 3.0Gb/s, RAID 0, 1, 5 support 		
Upgrade ROM for onboard drive controllers (opt)	Optional SAS HDD Enablement Module upgrades the 3 SATA connectors on SCU to 3 SATA/SAS connectors, SATA 3.0Gb/s, SAS 3.0Gb/s, RAID 0, 1 support	<p>ISV certifications</p> <p>Please visit www.lenovo.com/support/ISV</p>	<p>Environmental certifications</p> <p>GREENGUARD® certified RoHS-compliant EPEAT™ Gold rating</p>
Discrete drive controller (opt)	<i>One the following, depending on model:</i> LSI SAS 9240-8i: SATA 6.0Gb/s, SAS 6.0Gb/s, RAID 0, 1 support optional upgrade key for RAID 5 support LSI SAS 9260-8i: SATA 6.0Gb/s, SAS 6.0Gb/s, RAID 0, 1, 5 support		
Hard drives	3.5" SATA: SATA 6.0Gb/s, 7200 rpm 2.5" SATA: SATA 6.0Gb/s, 10000 rpm 3.5" SAS/2.5" SAS: SAS 6.0Gb/s, 15000 rpm 2.5" SSD: Solid State Drive (SSD), SATA 6.0Gb/s, OPAL-capable on selected models mSATA: mSATA SSD, SATA 6.0Gb/s	<p>Supports ThinkVantage® technologies</p>	
Optical	Supports DVD-ROM, DVD±RW, or Blu-ray Burner, SATA interface		
Media reader	None (use USB port)		
Front ports	Two USB 3.0, microphone (3.5mm), headphone (3.5mm)		
Rear ports	Eight USB 2.0, two USB 3.0 (blue), one serial (9-pin), one ethernet (RJ-45), three analog audio ports (line-in, line-out, mic-in)		
IEEE 1394 adptr (optional)	None. Optional FireWire PCIe adapter on selected models, 1394a-2000, 400Mbps, two 6-pin ports on rear		
Audio	High Definition (HD) Audio, Realtek® ALC662 codec		
Speaker	Internal speaker for business audio		
Onboard Ethernet	One onboard gigabit ethernet, Intel 82579		
Security chip	STMicroelectronics ST33TPM12LPC, TCG 1.2-compliant		
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black		
Mouse	Optical Wheel Mouse (USB connector), black		
Power supply	800 watts with 80mm side-mounted variable speed fan, universal, Climate Savers® Computing Gold, 80 PLUS® Gold qualified		
Preloaded operating systems (OS)	<i>One the following, depending on model:</i> <ul style="list-style-type: none"> • Windows 7 Professional 64 • Windows 7 Professional 64 preinstalled through downgrade rights in Windows 8 Pro 64-bit • Windows 8 Pro 64-bit 		

See footnotes for important warranty information
Model(s) announced June 18, 2013

© Lenovo
(G-ALI5-3) June 2013

ThinkStation C30 (1137) - TopSeller (June 2013) - VI

Product Specifications Reference (PSREF)

Type-model ¹	Processor(s)	Memory (MHz/type)	Memory DIMMs	Upgrade ROM for onboard drive controller	Discrete drive controller	Pre-conf RAID	Hard drive(s) ²	Optical	Media reader	Graphics adapter(s) and GPU computing	1394 adptr	Chassis intrusion switch	Preloaded OS
1137-67G	2xE5-2640 (6C/2.5GHz/15MB/1333)	1600MHz UDIMM	2GBx8	No	No	No	1x1TB 3.5" SATA	DVD±RW	No	1xQuadro K4000 (3GB, 1xDVI-I DL*, 2xDP, 80W)	No	Switch	Win7 Pro64
1137-68G	2xE5-2640 (6C/2.5GHz/15MB/1333)	1600MHz UDIMM	2GBx8	No	No	No	1x1TB 3.5" SATA	DVD±RW	No	1xQuadro K4000 (3GB, 1xDVI-I DL*, 2xDP, 80W)	No	Switch	Win7 Pro64
1137-69G	2xE5-2660 (8C/2.2GHz/20MB/1600)	1600MHz UDIMM	2GBx8	No	No	No	1x1TB 3.5" SATA	DVD±RW	No	1xQuadro K4000 (3GB, 1xDVI-I DL*, 2xDP, 80W)	No	Switch	Win7 Pro64
1137-71G	2xE5-2660 (8C/2.2GHz/20MB/1600)	1600MHz UDIMM	2GBx8	No	No	No	1x1TB 3.5" SATA	DVD±RW	No	1xQuadro K4000 (3GB, 1xDVI-I DL*, 2xDP, 80W)	No	Switch	Win7 Pro64
1137-72G	2xE5-2660 (8C/2.2GHz/20MB/1600)	1600MHz UDIMM	2GBx8	No	No	No	1x1TB 3.5" SATA	DVD±RW	No	1xQuadro K4000 (3GB, 1xDVI-I DL*, 2xDP, 80W)	No	Switch	Win7 Pro64 (Downgrade from Win8)

¹ Model in italics shows that this is a Global Model

² The SSD drives in italics must be plugged into SATA AHCI connectors (red/orange)

* DL = Dual Link, SL = Single Link

- **3-year limited warranty**
- **With new MT type 1136/1137 and beyond, ThinkStation C30 introduces new updates to improve the functionality and usability:**
(These new features are not supported on 1095 and 1097MT models)
 - Intel AMT: upgrades to Intel AMT 8 from Intel AMT 7
 - New TPM chip: STMicroelectronics ST33TPM12LPC
 - Two front USB 2.0 ports upgrade to USB3.0
- For ThinkStation C30 platform specifications, please see [ThinkStation C30 Platform Specifications sheet](#)

Chipset	Intel C602 Chipset	Processor Two LGA2011 sockets, supports up to two processors from Intel Xeon E5-2600 family, 4-channel DDR3 memory controller per processor	Memory UDIMM or RDIMM, ECC, DDR3 , 8-channel capable (4-channel per processor), eight 240-pin DIMM sockets 64GB max (UDIMM, 8GBx8)/256GB max (RDIMM, 32GBx8)	Additional memory disclaimers <ul style="list-style-type: none"> • Actual memory operating speed depends on processor memory controller speed, installed memory speed, and quantity of memory DIMMs • Over four DIMMs requires dual processors • Mixing of RDIMM and UDIMM is not supported 	Graphics Two PCI Express 3.0 x16 slots for graphics adapters and GPU computing processors, supports NVIDIA SLI technology, NVIDIA Maximus technology	Onboard drive controllers <ul style="list-style-type: none"> • Four SATA connectors via integrated Advanced Host Controller Interface (AHCI) in chipset, two SATA 6.0Gb/s (red), two SATA 3.0Gb/s (orange), RAID 0, 1, 5 support • Three SATA connectors via integrated Storage Controller Unit (SCU) in chipset, SATA 3.0Gb/s, RAID 0, 1, 5 support 	Upgrade ROM for onboard drive controllers (opt) Optional SAS HDD Enablement Module upgrades the 3 SATA connectors on SCU to 3 SATA/SAS connectors, SATA 3.0Gb/s, SAS 3.0Gb/s, RAID 0, 1 support	Discrete drive controller (opt) <i>One the following, depending on model:</i> LSI SAS 9240-8i: SATA 6.0Gb/s, SAS 6.0Gb/s, RAID 0, 1 support optional upgrade key for RAID 5 support LSI SAS 9260-8i: SATA 6.0Gb/s, SAS 6.0Gb/s, RAID 0, 1, 5 support	Hard drives 3.5" SATA: SATA 6.0Gb/s, 7200 rpm 2.5" SATA: SATA 6.0Gb/s, 10000 rpm 3.5" SAS/2.5" SAS: SAS 6.0Gb/s, 15000 rpm 2.5" SSD: Solid State Drive (SSD), SATA 6.0Gb/s, OPAL-capable on selected models mSATA: mSATA SSD, SATA 6.0Gb/s	Optical Supports DVD-ROM, DVD±RW, or Blu-ray Burner, SATA interface	Media reader None (use USB port)	Front ports Two USB 3.0, microphone (3.5mm), headphone (3.5mm)	Rear ports Eight USB 2.0, two USB 3.0 (blue), one serial (9-pin), one ethernet (RJ-45), three analog audio ports (line-in, line-out, mic-in)	IEEE 1394 adptr (optional) None. Optional FireWire PCIe adapter on selected models, 1394a-2000, 400Mbps, two 6-pin ports on rear	Audio High Definition (HD) Audio, Realtek® ALC662 codec	Speaker Internal speaker for business audio	Onboard Ethernet One onboard gigabit ethernet, Intel 82579	Security chip STMicroelectronics ST33TPM12LPC, TCG 1.2-compliant	Keyboard Preferred Pro USB Keyboard (USB connector), 104-key, black	Mouse Optical Wheel Mouse (USB connector), black	Power supply 800 watts with 80mm side-mounted variable speed fan, universal, Climate Savers® Computing Gold, 80 PLUS® Gold qualified	Preloaded operating systems (OS) <i>One the following, depending on model:</i> <ul style="list-style-type: none"> • Windows 7 Professional 64 • Windows 7 Professional 64 preinstalled through downgrade rights in Windows 8 Pro 64-bit • Windows 8 Pro 64-bit 	Tower <ul style="list-style-type: none"> • Rack-mountable to 3U • Raven black color; metal case • 5.1"W x 17.5"D x 16.8"H • 130mm W x 444mm D x 427mm H (without rubber feet) • 40.7 lb (18.5kg) max configuration • 24-liter • Toolless side cover removal • Toolless disk and optical drive removal • Toolless adapter retention • Illuminated front icons • Rack shelf support or optional rail kit 		Bay 1 5.25", 1.6" high, external, for optical Bay 2-4 3.5", 1" high, internal, for hard drive Slot 1: half-length, full-height, PCIe 3.0 x16 (near CPU, x4 elec) Slot 2: full-length, full-height, PCIe 3.0 x16* Slot 3: full-length, full-height, 32-bit PCI 2.3 Slot 4: full-length, full-height, PCIe 3.0 x16* Slot 5: full-length, full-height, PCIe 2.0 x4 Slot 6: half-length, full-height, 32-bit PCI 2.3	* Adapters >75W use auxiliary power connector(s) from PSU
SECURITY <ul style="list-style-type: none"> • Security chip (see information on left) • Side cover lock (ships with two identical keys) • Padlock loop (in rear for opt padlock; padlock prohibits side cover removal) • Security slot (in rear for optional Kensington® Microsaver® cable; prohibits side cover removal) • Power-on password • Administrator password • Boot sequence control • Boot without keyboard, mouse, diskette • Serial port I/O enable/disable • USB 2.0 ports enable/disable individually • USB 3.0 ports enable/disable concurrently • Chassis intrusion switch on selected model(s) 	Intel AMT Intel Active Management Technology 8 supported																						ISV certifications Please visit www.lenovo.com/support/ISV		Environmental certifications GREENGUARD® certified RoHS-compliant EPEAT™ Gold rating	Supports ThinkVantage® technologies

See footnotes for important warranty information
Model(s) announced June 18, 2013

© Lenovo
(G-ALI6-3) June 2013

ThinkStation C30 (1137) - TopSeller (September 2013)

Product Specifications Reference (PSREF)

Type-model ¹	Processor(s) - Xeon E5 Family	Memory (MHz/type)	Memory DIMMs	Upgrade ROM for onboard drive controller	Pre-conf RAID	Hard drive(s) ²	Optical	Media reader	Graphics adapter(s) and GPU computing ³	1394 adptr	Chassis intrusion switch	Preloaded OS
1137-86G	1xE5-2609 v2 (4C/2.5GHz/10MB/1333)	1600MHz RDIMM	4GBx2	No	No	1x1TB 3.5" SATA	DVD±RW	No	No	No	Switch	Win7 Pro64 (Downgrade from Win8)
1137-87G	1xE5-2620 v2 (6C/2.1GHz/15MB/1600)	1600MHz RDIMM	4GBx2	No	No	1x256GB 2.5" SSD - OPAL	DVD±RW	No	No	No	Switch	Win7 Pro64 (Downgrade from Win8)
1137-88G	1xE5-2630 v2 (6C/2.6GHz/15MB/1600)	1600MHz RDIMM	4GBx2	No	No	1x2TB 3.5" SATA	DVD±RW	No	No	No	Switch	Win7 Pro64 (Downgrade from Win8)
1137-89G	1xE5-2603 v2 (4C/1.8GHz/10MB/1333)	1600MHz RDIMM	4GBx1	No	No	1x1TB 3.5" SATA	DVD±RW	No	No	No	Switch	Win7 Pro64 (Downgrade from Win8)
1137-91G	1xE5-2630 v2 (6C/2.6GHz/15MB/1600)	1600MHz RDIMM	4GBx2	SAS	No	2x300GB 2.5" SAS	DVD±RW	No	1xQuadro K4000 (3GB, 1xDVI-I DL, 2xDP, 80W)	No	Switch	Win7 Pro64 (Downgrade from Win8)
1137-92G	1xE5-2640 v2 (8C/2GHz/20MB/1600)	1600MHz RDIMM	4GBx4	No	No	1x3TB 3.5" SATA	DVD±RW	No	1xQuadro K5000 (4GB, 1xDVI-I DL, 1xDVI-D DL, 2xDP, 122W)	No	Switch	Win7 Pro64 (Downgrade from Win8)
1137-93G	1xE5-2650 v2 (8C/2.6GHz/20MB/1866)	1600MHz RDIMM	4GBx2	No	No	2x3TB 3.5" SATA	DVD±RW	No	1xQuadro K5000 (4GB, 1xDVI-I DL, 1xDVI-D DL, 2xDP, 122W)	No	Switch	Win7 Pro64 (Downgrade from Win8)

¹ Model in italics shows that this is a Global Model ² The SSD drives in italics must be plugged into red or orange SATA connectors ³ DL = Dual Link, SL = Single Link

- 3-year limited warranty
- For ThinkStation C30 platform specifications, please see [ThinkStation C30 Platform Specifications sheet](#)

Chipset	Intel C602 Chipset		
Intel AMT	Intel Active Management Technology 8 supported		
Processor	Two LGA2011 sockets, integrated 4-channel DDR3 memory controller per processor, only one E5-1600 or E5-1600 v2 processor are supported		
Memory	UDIMM or RDIMM, ECC, DDR3 , 8-channel capable (4-channel per processor), eight 240-pin DIMM sockets 64GB max (UDIMM, 8GBx8)/256GB max (RDIMM, 32GBx8)		
Additional memory disclaimers	<ul style="list-style-type: none"> • Actual memory operating speed depends on processor memory controller speed, installed memory speed, and quantity of memory DIMMs • Over four DIMMs requires dual processors • Mixing of RDIMM and UDIMM is not supported • When using processor from Xeon E5-1600 and E5-1600 v2 series, only four DIMM sockets for CPU1 are available and max memory capacity is 32GB (UDIMM, 8GBx4)/128GB (RDIMM, 32GBx4) 		
Graphics	Two PCI Express 3.0 x16 slots for graphics adapters and GPU computing processors, supports NVIDIA SLI technology, NVIDIA Maximus technology		
Onboard drive controllers	<ul style="list-style-type: none"> • Four SATA connectors via integrated Advanced Host Controller Interface (AHCI) in chipset, two SATA 6.0Gb/s (red), two SATA 3.0Gb/s (orange), RAID 0, 1, 5 support • Three SATA connectors via integrated Storage Controller Unit (SCU) in chipset, SATA 3.0Gb/s, RAID 0, 1, 5 support 		
Upgrade ROM for onboard drive controllers (opt)	Optional SAS HDD Enablement Module upgrades the 3 SATA connectors on SCU to 3 SATA/SAS connectors, SATA 3.0Gb/s, SAS 3.0Gb/s, RAID 0, 1 support		
Discrete drive controller (opt)	None		
Hard drive(s)	3.5" SATA: SATA 6.0Gb/s, 7200 rpm 3.5" Hybrid: SATA 6.0Gb/s, 7200 rpm, integrated 8GB NAND flash 2.5" SATA: SATA 6.0Gb/s, 10000 rpm 3.5" SAS/2.5" SAS: SAS 6.0Gb/s, 15000 rpm 2.5" SSD: Solid State Drive (SSD), SATA 6.0Gb/s OPAL-capable on some models mSATA: mSATA SSD, SATA 6.0Gb/s		
Optical	Supports DVD-ROM, DVD±RW, or Blu-ray Burner, SATA interface		
Media reader	None (use USB port)		
Front ports	Two USB 3.0, microphone (3.5mm), headphone (3.5mm)		
Rear ports	Eight USB 2.0, two USB 3.0 (blue), one serial (9-pin), one ethernet (RJ-45), three analog audio ports (line-in, line-out, mic-in)		
IEEE 1394 adptr (optional)	None. Optional FireWire PCIe adapter on selected models, 1394a-2000, 400Mbps, two 6-pin ports on rear		
Audio	High Definition (HD) Audio, Realtek® ALC662 codec		
Speaker	Internal speaker for business audio		
Onboard Ethernet	One onboard gigabit ethernet, Intel 82579		
Security chip	STMicroelectronics ST33TPM12LPC, TCG 1.2-compliant		
Keyboard/Mouse	104-key keyboard (USB)/Optical Wheel Mouse (USB)		
Power supply	800 watts with 80mm side-mounted variable speed fan, universal, Climate Savers® Computing Gold, 80 PLUS® Gold qualified		
	Tower <ul style="list-style-type: none"> • Rack-mountable to 3U • Raven black color; metal case • 5.1"W x 17.5"D x 16.8"H • 130mm W x 444mm D x 427mm H (without rubber feet) • 40.7 lb (18.5kg) max configuration • 24-liter • Toolless side cover removal • Toolless disk and optical drive removal • Toolless adapter retention • Illuminated front icons • Rack shelf support or optional rail kit Bay 1 5.25", 1.6" high, external, for optical Bay 2-4 3.5", 1" high, internal, for hard drive Slot 1: half-length, full-height, PCIe 3.0 x16 (near CPU, x4 elec) Slot 2: full-length, full-height, PCIe 3.0 x16* Slot 3: full-length, full-height, 32-bit PCI 2.3 Slot 4: full-length, full-height, PCIe 3.0 x16* Slot 5: full-length, full-height, PCIe 2.0 x4 Slot 6: half-length, full-height, 32-bit PCI 2.3 * Adapters >75W use auxiliary power connector(s) from PSU		
	SECURITY <ul style="list-style-type: none"> • Security chip (see information on left) • Side cover lock (ships with two identical keys) • Padlock loop (in rear for opt padlock; padlock prohibits side cover removal) • Security slot (in rear for optional Kensington® Microsaver® cable; prohibits side cover removal) • Power-on password • Administrator password • Boot sequence control • Boot without keyboard, mouse, diskette • Serial port I/O enable/disable • USB 2.0 ports enable/disable individually • USB 3.0 ports enable/disable concurrently • Chassis intrusion switch on selected model(s) 		
	ISV certifications Please visit www.lenovo.com/support/ISV		
	Environmental certifications GREENGUARD® certified RoHS-compliant EPEAT™ Gold rating Supports ThinkVantage® technologies		

See footnotes for important warranty information
 Model(s) announced September 10, 2013

© Lenovo
 (1137-7E) September 2013

ThinkStation C30 (1137) - TopSeller (September 2013) - II

Product Specifications Reference (PSREF)

Type-model	Processor(s) - Xeon E5 Family	Memory (MHz/type)	Memory DIMMs	Upgrade ROM for onboard drive controller	Pre-conf RAID	Hard drive(s)**	Optical	Media reader	Graphics adapter(s) and GPU computing***	1394 adptr	Chassis intrusion switch	Preloaded OS
1137-94G	2xE5-2650 v2 (8C/2.6GHz/20MB/1866)	1600MHz RDIMM	4GBx4	SAS	No	2x300GB 3.5" SAS	DVD±RW	No	1xQuadro K5000 (4GB, 1xDVI-I DL, 1xDVI-D DL, 2xDP, 122W)	No	Switch	Win7 Pro64 (Downgrade from Win8)
1137-95G	2xE5-2643 v2 (6C/3.5GHz/25MB/1866)	1600MHz RDIMM	4GBx4	No	No	1x128GB mSATA 3.5	DVD±RW	No	1xQuadro K5000 (4GB, 1xDVI-I DL, 1xDVI-D DL, 2xDP, 122W)	No	Switch	Win7 Pro64 (Downgrade from Win8)
1137-96G	1xE5-1660 v2 (6C/3.7GHz/15MB/1866)	1600MHz RDIMM	4GBx1	No	No	1x180GB 2.5" SSD	DVD±RW	No	1xQuadro K2000 (2GB, 1xDVI-I DL, 2xDP, 51W)	No	Switch	Win7 Pro64 (Downgrade from Win8)
1137-97G	1xE5-2609 v2 (4C/2.5GHz/10MB/1333)	1600MHz RDIMM	4GBx2	No	No	1x256GB 2.5" SSD - OPAL	DVD±RW	No	No	No	Switch	Win7 Pro64 (Downgrade from Win8)
1137-D3G	1xE5-2620 v2 (6C/2.1GHz/15MB/1600)	1600MHz UDIMM	4GBx2	No	No	1x256GB 2.5" SSD - OPAL	DVD±RW	No	No	No	Switch	Win7 Pro64 (Downgrade from Win8)
1137-D4G	1xE5-2630 v2 (6C/2.6GHz/15MB/1600)	1600MHz UDIMM	4GBx2	No	No	1x1TB 3.5" SATA	DVD±RW	No	No	No	Switch	Win7 Pro64 (Downgrade from Win8)

* Model in italics shows that this is a Global Model ** The SSD drives in italics must be plugged into red or orange SATA connectors *** DL = Dual Link, SL = Single Link

- 3-year limited warranty
- For ThinkStation C30 platform specifications, please see [ThinkStation C30 Platform Specifications sheet](#)

Chipset	Intel C602 Chipset		<div style="border: 1px solid black; padding: 5px;"> <div style="display: flex; align-items: center;"> <div style="writing-mode: vertical-rl; transform: rotate(180deg); font-size: 8px; margin-right: 5px;">1 optical</div> <div style="border-left: 1px solid black; border-right: 1px solid black; border-bottom: 1px solid black; width: 20px; height: 20px; margin-right: 5px;"></div> <div style="font-size: 8px; margin-right: 5px;">0</div> </div> <div style="display: flex; align-items: center; margin-top: 5px;"> <div style="border-left: 1px solid black; border-right: 1px solid black; border-bottom: 1px solid black; width: 20px; height: 10px; margin-right: 5px;"></div> <div style="font-size: 8px; margin-right: 5px;">2 disk</div> </div> <div style="display: flex; align-items: center; margin-top: 5px;"> <div style="border-left: 1px solid black; border-right: 1px solid black; border-bottom: 1px solid black; width: 20px; height: 10px; margin-right: 5px;"></div> <div style="font-size: 8px; margin-right: 5px;">3 disk</div> </div> <div style="display: flex; align-items: center; margin-top: 5px;"> <div style="border-left: 1px solid black; border-right: 1px solid black; border-bottom: 1px solid black; width: 20px; height: 10px; margin-right: 5px;"></div> <div style="font-size: 8px; margin-right: 5px;">4 disk</div> </div> </div>
Intel AMT	Intel Active Management Technology 8 supported		
Processor	Two LGA2011 sockets, integrated 4-channel DDR3 memory controller per processor, only one E5-1600 or E5-1600 v2 processor are supported		
Memory	UDIMM or RDIMM, ECC, DDR3 , 8-channel capable (4-channel per processor), eight 240-pin DIMM sockets 64GB max (UDIMM, 8GBx8)/256GB max (RDIMM, 32GBx8)		
Additional memory disclaimers	<ul style="list-style-type: none"> • Actual memory operating speed depends on processor memory controller speed, installed memory speed, and quantity of memory DIMMs • Over four DIMMs requires dual processors • Mixing of RDIMM and UDIMM is not supported • When using processor from Xeon E5-1600 and E5-1600 v2 series, only four DIMM sockets for CPU1 are available and max memory capacity is 32GB (UDIMM, 8GBx4)/128GB (RDIMM, 32GBx4) 		
Graphics	Two PCI Express 3.0 x16 slots for graphics adapters and GPU computing processors, supports NVIDIA SLI technology, NVIDIA Maximus technology		
Onboard drive controllers	<ul style="list-style-type: none"> • Four SATA connectors via integrated Advanced Host Controller Interface (AHCI) in chipset, two SATA 6.0Gb/s (red), two SATA 3.0Gb/s (orange), RAID 0, 1, 5 support • Three SATA connectors via integrated Storage Controller Unit (SCU) in chipset, SATA 3.0Gb/s, RAID 0, 1, 5 support 		
Upgrade ROM for onboard drive controllers (opt)	Optional SAS HDD Enablement Module upgrades the 3 SATA connectors on SCU to 3 SATA/SAS connectors, SATA 3.0Gb/s, SAS 3.0Gb/s, RAID 0, 1 support		
Discrete drive controller (opt)	None		
Hard drive(s)	3.5" SATA: SATA 6.0Gb/s, 7200 rpm 3.5" Hybrid: SATA 6.0Gb/s, 7200 rpm, integrated 8GB NAND flash 2.5" SATA: SATA 6.0Gb/s, 10000 rpm 3.5" SAS/2.5" SAS: SAS 6.0Gb/s, 15000 rpm 2.5" SSD: Solid State Drive (SSD), SATA 6.0Gb/s OPAL-capable on some models mSATA: mSATA SSD, SATA 6.0Gb/s		
Optical	Supports DVD-ROM, DVD±RW, or Blu-ray Burner, SATA interface		
Media reader	None (use USB port)		
Front ports	Two USB 3.0, microphone (3.5mm), headphone (3.5mm)		
Rear ports	Eight USB 2.0, two USB 3.0 (blue), one serial (9-pin), one ethernet (RJ-45), three analog audio ports (line-in, line-out, mic-in)		
IEEE 1394 adptr (optional)	None. Optional FireWire PCIe adapter on selected models, 1394a-2000, 400Mbps, two 6-pin ports on rear		
Audio	High Definition (HD) Audio, Realtek® ALC662 codec		
Speaker	Internal speaker for business audio		
Onboard Ethernet	One onboard gigabit ethernet, Intel 82579		
Security chip	STMicroelectronics ST33TPM12LPC, TCG 1.2-compliant		
Keyboard/Mouse	104-key keyboard (USB)/Optical Wheel Mouse (USB)		
Power supply	800 watts with 80mm side-mounted variable speed fan, universal, Climate Savers® Computing Gold, 80 PLUS® Gold qualified		
Tower <ul style="list-style-type: none"> • Rack-mountable to 3U • Raven black color; metal case • 5.1"W x 17.5"D x 16.8"H • 130mm W x 444mm D x 427mm H (without rubber feet) • 40.7 lb (18.5kg) max configuration • 24-liter • Toolless side cover removal • Toolless disk and optical drive removal • Toolless adapter retention • Illuminated front icons • Rack shelf support or optional rail kit 			
Bay 1 5.25", 1.6" high, external, for optical Bay 2-4 3.5", 1" high, internal, for hard drive Slot 1: half-length, full-height, PCIe 3.0 x16 (near CPU, x4 elec) Slot 2: full-length, full-height, PCIe 3.0 x16* Slot 3: full-length, full-height, 32-bit PCI 2.3 Slot 4: full-length, full-height, PCIe 3.0 x16* Slot 5: full-length, full-height, PCIe 2.0 x4 Slot 6: half-length, full-height, 32-bit PCI 2.3 * Adapters >75W use auxiliary power connector(s) from PSU			
SECURITY <ul style="list-style-type: none"> • Security chip (see information on left) • Side cover lock (ships with two identical keys) • Padlock loop (in rear for opt padlock; padlock prohibits side cover removal) • Security slot (in rear for optional Kensington® Microsaver® cable; prohibits side cover removal) • Power-on password • Administrator password • Boot sequence control • Boot without keyboard, mouse, diskette • Serial port I/O enable/disable • USB 2.0 ports enable/disable individually • USB 3.0 ports enable/disable concurrently • Chassis intrusion switch on selected model(s) 			
ISV certifications Please visit www.lenovo.com/support/ISV			
Environmental certifications GREENGUARD® certified RoHS-compliant EPEAT™ Gold rating Supports ThinkVantage® technologies			

See footnotes for important warranty information
 Model(s) announced September 10, 2013

© Lenovo
 (1137-8E) September 2013

ThinkStation C30 (1137) - TopSeller (March 2014)

Product Specifications Reference (PSREF)

Type-model ¹	Processor(s) - Xeon E5 Family	Memory (MHz/type)	Memory DIMMs	Upgrade ROM for onboard drive controller	Pre-conf RAID	Hard drive(s)**	Optical	Media reader	Graphics adapter(s) and GPU computing***	1394 adptr	Chassis intrusion switch	Preloaded OS
1137-J3G	1xE5-2603 v2 4C/1.8GHz/10MB/1333MHz	1600MHz UDIMM	2GBx2	No	No	1x1TB 3.5" SATA	DVD±RW	N/A	Open	No	Switch	Win7 Pro64 (Downgrade from Win8)

* Model in *italics* shows that this is a Global Model ** The SSD drives in *italics* must be plugged into red or orange SATA connectors *** DL = Dual Link, SL = Single Link

- 3-year limited warranty
- For ThinkStation C30 platform specifications, please see [ThinkStation C30 Platform Specifications sheet](#)

Chipset	Intel C602 Chipset		<div style="border: 1px solid black; padding: 5px; width: fit-content;"> <div style="border: 1px solid black; padding: 2px; margin-bottom: 2px;">1 optical</div> <div style="border: 1px solid black; padding: 2px; margin-bottom: 2px;">2 disk</div> <div style="border: 1px solid black; padding: 2px; margin-bottom: 2px;">3 disk</div> <div style="border: 1px solid black; padding: 2px;">4 disk</div> </div>
Intel AMT	Intel Active Management Technology 8 supported		
Processor	Two LGA2011 sockets, integrated 4-channel DDR3 memory controller per processor, only one E5-1600 or E5-1600 v2 processor are supported		
Memory	UDIMM or RDIMM, ECC, DDR3 , 8-channel capable (4-channel per processor), eight 240-pin DIMM sockets 64GB max (UDIMM, 8GBx8)/256GB max (RDIMM, 32GBx8)		
Additional memory disclaimers	<ul style="list-style-type: none"> • Actual memory operating speed depends on processor memory controller speed, installed memory speed, and quantity of memory DIMMs • Over four DIMMs requires dual processors • Mixing of RDIMM and UDIMM is not supported • When using processor from Xeon E5-1600 and E5-1600 v2 series, only four DIMM sockets for CPU1 are available and max memory capacity is 32GB (UDIMM, 8GBx4)/128GB (RDIMM, 32GBx4) 		
Graphics	Two PCI Express 3.0 x16 slots for graphics adapters and GPU computing processors, supports NVIDIA SLI technology, NVIDIA Maximus technology		
Onboard drive controllers	<ul style="list-style-type: none"> • Four SATA connectors via integrated Advanced Host Controller Interface (AHCI) in chipset, two SATA 6.0Gb/s (red), two SATA 3.0Gb/s (orange), RAID 0, 1, 5 support • Three SATA connectors via integrated Storage Controller Unit (SCU) in chipset, SATA 3.0Gb/s, RAID 0, 1, 5 support 		
Upgrade ROM for onboard drive controllers (opt)	Optional SAS HDD Enablement Module upgrades the 3 SATA connectors on SCU to 3 SATA/SAS connectors, SATA 3.0Gb/s, SAS 3.0Gb/s, RAID 0, 1 support		
Discrete drive controller (opt)	None		
Hard drive(s)	3.5" SATA: SATA 6.0Gb/s, 7200 rpm 3.5" Hybrid: SATA 6.0Gb/s, 7200 rpm, integrated 8GB NAND flash 2.5" SATA: SATA 6.0Gb/s, 10000 rpm 3.5" SAS/2.5" SAS: SAS 6.0Gb/s, 15000 rpm 2.5" SSD: Solid State Drive (SSD), SATA 6.0Gb/s OPAL-capable on some models mSATA: mSATA SSD, SATA 6.0Gb/s		
Optical	Supports DVD-ROM, DVD±RW, or Blu-ray Burner, SATA interface		
Media reader	None (use USB port)		
Front ports	Two USB 3.0, microphone (3.5mm), headphone (3.5mm)		
Rear ports	Eight USB 2.0, two USB 3.0 (blue), one serial (9-pin), one ethernet (RJ-45), three analog audio ports (line-in, line-out, mic-in)		
IEEE 1394 adptr (optional)	None. Optional FireWire PCIe adapter on selected models, 1394a-2000, 400Mbps, two 6-pin ports on rear		
Audio	High Definition (HD) Audio, Realtek® ALC662 codec		
Speaker	Internal speaker for business audio		
Onboard Ethernet	One onboard gigabit ethernet, Intel 82579		
Security chip	STMicroelectronics ST33TPM12LPC, TCG 1.2-compliant		
Keyboard/Mouse	104-key keyboard (USB)/Optical Wheel Mouse (USB)		
Power supply	800 watts with 80mm side-mounted variable speed fan, universal, Climate Savers® Computing Gold, 80 PLUS® Gold qualified		
	Tower <ul style="list-style-type: none"> • Rack-mountable to 3U • Raven black color; metal case • 5.1"W x 17.5"D x 16.8"H • 130mm W x 444mm D x 427mm H (without rubber feet) • 40.7 lb (18.5kg) max configuration • 24-liter • Toolless side cover removal • Toolless disk and optical drive removal • Toolless adapter retention • Illuminated front icons • Rack shelf support or optional rail kit Bay 1 5.25", 1.6" high, external, for optical Bay 2-4 3.5", 1" high, internal, for hard drive Slot 1: half-length, full-height, PCIe 3.0 x16 (near CPU, x4 elec) Slot 2: full-length, full-height, PCIe 3.0 x16* Slot 3: full-length, full-height, 32-bit PCI 2.3 Slot 4: full-length, full-height, PCIe 3.0 x16* Slot 5: full-length, full-height, PCIe 2.0 x4 Slot 6: half-length, full-height, 32-bit PCI 2.3 * Adapters >75W use auxiliary power connector(s) from PSU		
	SECURITY <ul style="list-style-type: none"> • Security chip (see information on left) • Side cover lock (ships with two identical keys) • Padlock loop (in rear for opt padlock; padlock prohibits side cover removal) • Security slot (in rear for optional Kensington® Microsaver® cable; prohibits side cover removal) • Power-on password • Administrator password • Boot sequence control • Boot without keyboard, mouse, diskette • Serial port I/O enable/disable • USB 2.0 ports enable/disable individually • USB 3.0 ports enable/disable concurrently • Chassis intrusion switch on selected model(s) 		
	ISV certifications Please visit www.lenovo.com/support/ISV		
	Environmental certifications GREENGUARD® certified RoHS-compliant EPEAT™ Gold rating Supports ThinkVantage® technologies		

See footnotes for important warranty information
 Model(s) announced March 25, 2014

© Lenovo
 (1137-9E) March 2014

ThinkStation C30 (1137) - TopSeller (April 2014)

Product Specifications Reference (PSREF)

Type-model	Processor(s) - Xeon E5 Family	Memory (MHz/type)	Memory DIMMs	Upgrade ROM for onboard drive controller	Pre-conf RAID	Hard drive(s)**	Optical	Media reader	Graphics adapter(s) and GPU computing***	1394 adptr	Chassis intrusion switch	Preloaded OS
1137-G9G	1xXeonE5-2630 v2 6C/2.6GHz/15MB/1600MHz	1600MHz UDIMM	4GBx2	No	No	1x2TB 3.5" SATA	DVD±RW	No	Open	No	Switch	Win7 Pro64 (Downgrade from Win8.1)
1137-H1G	1xXeonE5-2609 v2 4C/2.5GHz/10MB/1333MHz	1600MHz UDIMM	4GBx2	No	No	1x256GB 2.5" SSD(OPAL)	DVD±RW	No	Open	No	Switch	Win7 Pro64 (Downgrade from Win8.1)
1137-J3G	1xXeonE5-2603 v2 4C/1.8GHz/10MB/1333MHz	1600MHz UDIMM	2GBx2	No	No	1x1TB 3.5" SATA	DVD±RW	No	Open	No	Switch	Win7 Pro64 (Downgrade from Win8)

* Model in italics shows that this is a Global Model ** The SSD drives in italics must be plugged into red or orange SATA connectors *** DL = Dual Link, SL = Single Link

- 3-year limited warranty
- For ThinkStation C30 platform specifications, please see [ThinkStation C30 Platform Specifications sheet](#)

Chipset	Intel C602 Chipset		<div style="border: 1px solid black; padding: 5px;"> <div style="display: flex; align-items: center;"> <div style="writing-mode: vertical-rl; transform: rotate(180deg); border: 1px solid black; padding: 2px;">1 optical</div> <div style="margin-left: 10px;"> <div style="border: 1px solid black; padding: 2px; margin-bottom: 2px;">2 disk</div> <div style="border: 1px solid black; padding: 2px; margin-bottom: 2px;">3 disk</div> <div style="border: 1px solid black; padding: 2px;">4 disk</div> </div> </div> </div>
Intel AMT	Intel Active Management Technology 8 supported		
Processor	Two LGA2011 sockets, integrated 4-channel DDR3 memory controller per processor, only one E5-1600 or E5-1600 v2 processor are supported		
Memory	UDIMM or RDIMM, ECC, DDR3 , 8-channel capable (4-channel per processor), eight 240-pin DIMM sockets 64GB max (UDIMM, 8GBx8)/256GB max (RDIMM, 32GBx8)		
Additional memory disclaimers	<ul style="list-style-type: none"> • Actual memory operating speed depends on processor memory controller speed, installed memory speed, and quantity of memory DIMMs • Over four DIMMs requires dual processors • Mixing of RDIMM and UDIMM is not supported • When using processor from Xeon E5-1600 and E5-1600 v2 series, only four DIMM sockets for CPU1 are available and max memory capacity is 32GB (UDIMM, 8GBx4)/128GB (RDIMM, 32GBx4) 		
Graphics	Two PCI Express 3.0 x16 slots for graphics adapters and GPU computing processors, supports NVIDIA SLI technology, NVIDIA Maximus technology		
Onboard drive controllers	<ul style="list-style-type: none"> • Four SATA connectors via integrated Advanced Host Controller Interface (AHCI) in chipset, two SATA 6.0Gb/s (red), two SATA 3.0Gb/s (orange), RAID 0, 1, 5 support • Three SATA connectors via integrated Storage Controller Unit (SCU) in chipset, SATA 3.0Gb/s, RAID 0, 1, 5 support 		
Upgrade ROM for onboard drive controllers (opt)	Optional SAS HDD Enablement Module upgrades the 3 SATA connectors on SCU to 3 SATA/SAS connectors, SATA 3.0Gb/s, SAS 3.0Gb/s, RAID 0, 1 support		
Discrete drive controller (opt)	None		
Hard drive(s)	3.5" SATA: SATA 6.0Gb/s, 7200 rpm 3.5" Hybrid: SATA 6.0Gb/s, 7200 rpm, integrated 8GB NAND flash 2.5" SATA: SATA 6.0Gb/s, 10000 rpm 3.5" SAS/2.5" SAS: SAS 6.0Gb/s, 15000 rpm 2.5" SSD: Solid State Drive (SSD), SATA 6.0Gb/s OPAL-capable on some models mSATA: mSATA SSD, SATA 6.0Gb/s		
Optical	Supports DVD-ROM, DVD±RW, or Blu-ray Burner, SATA interface		
Media reader	None (use USB port)		
Front ports	Two USB 3.0, microphone (3.5mm), headphone (3.5mm)		
Rear ports	Eight USB 2.0, two USB 3.0 (blue), one serial (9-pin), one ethernet (RJ-45), three analog audio ports (line-in, line-out, mic-in)		
IEEE 1394 adptr (optional)	None. Optional FireWire PCIe adapter on selected models, 1394a-2000, 400Mbps, two 6-pin ports on rear		
Audio	High Definition (HD) Audio, Realtek® ALC662 codec		
Speaker	Internal speaker for business audio		
Onboard Ethernet	One onboard gigabit ethernet, Intel 82579		
Security chip	STMicroelectronics ST33TPM12LPC, TCG 1.2-compliant		
Keyboard/Mouse	104-key keyboard (USB)/Optical Wheel Mouse (USB)		
Power supply	800 watts with 80mm side-mounted variable speed fan, universal, Climate Savers® Computing Gold, 80 PLUS® Gold qualified		
	Tower <ul style="list-style-type: none"> • Rack-mountable to 3U • Raven black color; metal case • 5.1"W x 17.5"D x 16.8"H • 130mm W x 444mm D x 427mm H (without rubber feet) • 40.7 lb (18.5kg) max configuration • 24-liter • Toolless side cover removal • Toolless disk and optical drive removal • Toolless adapter retention • Illuminated front icons • Rack shelf support or optional rail kit Bay 1 5.25", 1.6" high, external, for optical Bay 2-4 3.5", 1" high, internal, for hard drive Slot 1: half-length, full-height, PCIe 3.0 x16 (near CPU, x4 elec) Slot 2: full-length, full-height, PCIe 3.0 x16* Slot 3: full-length, full-height, 32-bit PCI 2.3 Slot 4: full-length, full-height, PCIe 3.0 x16* Slot 5: full-length, full-height, PCIe 2.0 x4 Slot 6: half-length, full-height, 32-bit PCI 2.3 * Adapters >75W use auxiliary power connector(s) from PSU		
	SECURITY <ul style="list-style-type: none"> • Security chip (see information on left) • Side cover lock (ships with two identical keys) • Padlock loop (in rear for opt padlock; padlock prohibits side cover removal) • Security slot (in rear for optional Kensington® Microsaver® cable; prohibits side cover removal) • Power-on password • Administrator password • Boot sequence control • Boot without keyboard, mouse, diskette • Serial port I/O enable/disable • USB 2.0 ports enable/disable individually • USB 3.0 ports enable/disable concurrently • Chassis intrusion switch on selected model(s) 		
	ISV certifications Please visit www.lenovo.com/support/ISV		
	Environmental certifications GREENGUARD® certified RoHS-compliant EPEAT™ Gold rating Supports ThinkVantage® technologies		

See footnotes for important warranty information
 Model(s) announced April 1, 2014

© Lenovo
 (1137-10E) April 2014

Type-model ¹	Processor(s)	Memory (MHz/type)	Memory DIMMs	Upgrade ROM for onboard drive controller	Discrete drive controller	Pre-conf RAID	Hard drive(s) ²	Optical	Media reader	Graphics adapter(s) and GPU computing	1394 adptr	Chassis intrusion switch	Preloaded OS
<i>1136-21G</i>	1xE5-2620 (6C/2GHz/15MB/1333)	1600MHz UDIMM	4GBx1	No	No	No	1x1TB 3.5" SATA	DVD±RW	No	1xQuadro K2000 (2GB, 1xDVI-I DL*, 2xDP, 51W)	No	Switch	Win7 Pro64 (Downgrade from Win8)
<i>1136-23G</i>	1xE5-2620 (6C/2GHz/15MB/1333)	1600MHz UDIMM	4GBx1	SAS	No	No	1x300GB 3.5" SAS	DVD±RW	No	1xQuadro K2000 (2GB, 1xDVI-I DL, 2xDP, 51W)	No	Switch	Win7 Pro64 (Downgrade from Win8)
<i>1136-25G</i>	1xE5-2620 (6C/2GHz/15MB/1333)	1600MHz UDIMM	4GBx1	No	No	No	1x1TB 3.5" SATA	DVD±RW	No	1xQuadro K2000 (2GB, 1xDVI-I DL, 2xDP, 51W)	No	Switch	Win8 Pro64
<i>1136-27G</i>	1xE5-2620 (6C/2GHz/15MB/1333)	1600MHz UDIMM	4GBx1	SAS	No	No	1x300GB 3.5" SAS	DVD±RW	No	1xQuadro K2000 (2GB, 1xDVI-I DL, 2xDP, 51W)	No	Switch	Win8 Pro64


¹ Model in italics shows that this is a Global Model

² The SSD drives in italics must be plugged into SATA AHCI connectors (red/orange)

* DL = Dual Link, SL = Single Link

- **3-year limited warranty**
- **With new MT type 1136/1137 and beyond, ThinkStation C30 introduces new updates to improve the functionality and usability:** (These new features are not supported on 1095 and 1097MT models)
 - Intel AMT: upgrades to Intel AMT 8 from Intel AMT 7
 - New TPM chip: STMicroelectronics ST33TPM12LPC
 - Two front USB 2.0 ports upgrade to USB3.0
- **For ThinkStation C30 platform specifications, please see [ThinkStation C30 Platform Specifications sheet](#)**


Chipset	Intel C602 Chipset	<p>Tower</p> <ul style="list-style-type: none"> • Rack-mountable to 3U • Raven black color; metal case • 5.1"W x 17.5"D x 16.8"H • 130mm W x 444mm D x 427mm H (without rubber feet) • 40.7 lb (18.5kg) max configuration • 24-liter • Toolless side cover removal • Toolless disk and optical drive removal • Toolless adapter retention • Illuminated front icons • Rack shelf support or optional rail kit <p>Bay 1 5.25", 1.6" high, external, for optical Bay 2-4 3.5", 1" high, internal, for hard drive</p> <p>Slot 1: half-length, full-height, PCIe 3.0 x16 (near CPU, x4 elec) Slot 2: full-length, full-height, PCIe 3.0 x16* Slot 3: full-length, full-height, 32-bit PCI 2.3 Slot 4: full-length, full-height, PCIe 3.0 x16* Slot 5: full-length, full-height, PCIe 2.0 x4 Slot 6: half-length, full-height, 32-bit PCI 2.3</p> <p>* Adapters >75W use auxiliary power connector(s) from PSU</p> <p>SECURITY</p> <ul style="list-style-type: none"> • Security chip (see information on left) • Side cover lock (ships with two identical keys) • Padlock loop (in rear for opt padlock; padlock prohibits side cover removal) • Security slot (in rear for optional Kensington® Microsaver® cable; prohibits side cover removal) • Power-on password • Administrator password • Boot sequence control • Boot without keyboard, mouse, diskette • Serial port I/O enable/disable • USB 2.0 ports enable/disable individually • USB 3.0 ports enable/disable concurrently • Chassis intrusion switch on selected model(s) <p>Intel AMT</p> <p>Intel Active Management Technology 8 supported</p> <p>ISV certifications</p> <p>Please visit www.lenovo.com/support/ISV</p> <p>Environmental certifications</p> <p>GREENGUARD® certified RoHS-compliant EPEAT™ Gold rating</p> <p>Supports ThinkVantage® technologies</p>
Processor	Two LGA2011 sockets, supports up to two processors from Intel Xeon E5-2600 family, 4-channel DDR3 memory controller per processor	
Memory	UDIMM or RDIMM, ECC, DDR3 , 8-channel capable (4-channel per processor), eight 240-pin DIMM sockets 64GB max (UDIMM, 8GBx8)/256GB max (RDIMM, 32GBx8)	
Additional memory disclaimers	<ul style="list-style-type: none"> • Actual memory operating speed depends on processor memory controller speed, installed memory speed, and quantity of memory DIMMs • Over four DIMMs requires dual processors • Mixing of RDIMM and UDIMM is not supported 	
Graphics	Two PCI Express 3.0 x16 slots for graphics adapters and GPU computing processors, supports NVIDIA SLI technology, NVIDIA Maximus technology	
Onboard drive controllers	<ul style="list-style-type: none"> • Four SATA connectors via integrated Advanced Host Controller Interface (AHCI) in chipset, two SATA 6.0Gb/s (red), two SATA 3.0Gb/s (orange), RAID 0, 1, 5 support • Three SATA connectors via integrated Storage Controller Unit (SCU) in chipset, SATA 3.0Gb/s, RAID 0, 1, 5 support 	
Upgrade ROM for onboard drive controllers (opt)	Optional SAS HDD Enablement Module upgrades the 3 SATA connectors on SCU to 3 SATA/SAS connectors, SATA 3.0Gb/s, SAS 3.0Gb/s, RAID 0, 1 support	
Discrete drive controller (opt)	<p>One the following, depending on model:</p> <p>LSI SAS 9240-8i: SATA 6.0Gb/s, SAS 6.0Gb/s, RAID 0, 1 support optional upgrade key for RAID 5 support</p> <p>LSI SAS 9260-8i: SATA 6.0Gb/s, SAS 6.0Gb/s, RAID 0, 1, 5 support</p>	
Hard drives	<p>3.5" SATA: SATA 6.0Gb/s, 7200 rpm</p> <p>2.5" SATA: SATA 6.0Gb/s, 10000 rpm</p> <p>3.5" SAS/2.5" SAS: SAS 6.0Gb/s, 15000 rpm</p> <p>2.5" SSD: Solid State Drive (SSD), SATA 6.0Gb/s, OPAL-capable on selected models</p> <p>mSATA: mSATA SSD, SATA 6.0Gb/s</p>	
Optical	Supports DVD-ROM, DVD±RW, or Blu-ray Burner, SATA interface	
Media reader	None (use USB port)	
Front ports	Two USB 3.0, microphone (3.5mm), headphone (3.5mm)	
Rear ports	Eight USB 2.0, two USB 3.0 (blue), one serial (9-pin), one ethernet (RJ-45), three analog audio ports (line-in, line-out, mic-in)	
IEEE 1394 adptr (optional)	None. Optional FireWire PCIe adapter on selected models, 1394a-2000, 400Mbps, two 6-pin ports on rear	
Audio	High Definition (HD) Audio, Realtek® ALC662 codec	
Speaker	Internal speaker for business audio	
Onboard Ethernet	One onboard gigabit ethernet, Intel 82579	
Security chip	STMicroelectronics ST33TPM12LPC, TCG 1.2-compliant	
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black	
Mouse	Optical Wheel Mouse (USB connector), black	
Power supply	800 watts with 80mm side-mounted variable speed fan, universal, Climate Savers® Computing Gold, 80 PLUS® Gold qualified	
Preloaded operating systems (OS)	<p>One the following, depending on model:</p> <ul style="list-style-type: none"> • Windows 7 Professional 64 • Windows 7 Professional 64 preinstalled through downgrade rights in Windows 8 Pro 64-bit • Windows 8 Pro 64-bit 	



Type-model ¹	Processor(s) - Xeon E5 Family	Memory (MHz/type)	Memory DIMMs	Upgrade ROM for onboard drive controller	Pre-conf RAID	Hard drive(s)**	Optical	Media reader	Graphics adapter(s) and GPU computing***	1394 adptr	Chassis intrusion switch	Preloaded OS
1136-78G	1xE5-2667 v2 (8C/3.3GHz/25MB/1866)	1600MHz RDIMM	4GBx2	No	No	1x240GB 2.5" SSD	DVD±RW	No	1xQuadro K4000 (3GB, 1xDVI-I DL, 2xDP, 80W)	No	Switch	Win7 Pro64 (Downgrade from Win8)
1136-79G	1xE5-2695 v2 (12C/2.4GHz/30MB/1866)	1600MHz RDIMM	8GBx2	No	No	2x4TB 3.5" SATA	DVD±RW	No	1xQuadro K5000 (4GB, 1xDVI-I DL, 1xDVI-D DL, 2xDP, 122W)	No	Switch	Win7 Pro64 (Downgrade from Win8)
1136-81G	1xE5-2680 v2 (10C/2.8GHz/25MB/1866)	1600MHz RDIMM	4GBx4	No	No	2x2TB 3.5" SATA Hybrid	DVD±RW	No	1xQuadro K5000 (4GB, 1xDVI-I DL, 1xDVI-D DL, 2xDP, 122W)	No	Switch	Win7 Pro64 (Downgrade from Win8)

* Model in italics shows that this is a Global Model ** The SSD drives in italics must be plugged into red or orange SATA connectors *** DL = Dual Link, SL = Single Link

- 3-year limited warranty
- For ThinkStation C30 platform specifications, please see [ThinkStation C30 Platform Specifications sheet](#)

Chipset	Intel C602 Chipset		
Intel AMT	Intel Active Management Technology 8 supported		
Processor	Two LGA2011 sockets, integrated 4-channel DDR3 memory controller per processor, only one E5-1600 or E5-1600 v2 processor are supported		
Memory	UDIMM or RDIMM, ECC, DDR3 , 8-channel capable (4-channel per processor), eight 240-pin DIMM sockets 64GB max (UDIMM, 8GBx8)/256GB max (RDIMM, 32GBx8)		
Additional memory disclaimers	<ul style="list-style-type: none"> • Actual memory operating speed depends on processor memory controller speed, installed memory speed, and quantity of memory DIMMs • Over four DIMMs requires dual processors • Mixing of RDIMM and UDIMM is not supported • When using processor from Xeon E5-1600 and E5-1600 v2 series, only four DIMM sockets for CPU1 are available and max memory capacity is 32GB (UDIMM, 8GBx4)/128GB (RDIMM, 32GBx4) 		
Graphics	Two PCI Express 3.0 x16 slots for graphics adapters and GPU computing processors, supports NVIDIA SLI technology, NVIDIA Maximus technology		
Onboard drive controllers	<ul style="list-style-type: none"> • Four SATA connectors via integrated Advanced Host Controller Interface (AHCI) in chipset, two SATA 6.0Gb/s (red), two SATA 3.0Gb/s (orange), RAID 0, 1, 5 support • Three SATA connectors via integrated Storage Controller Unit (SCU) in chipset, SATA 3.0Gb/s, RAID 0, 1, 5 support 		
Upgrade ROM for onboard drive controllers (opt)	Optional SAS HDD Enablement Module upgrades the 3 SATA connectors on SCU to 3 SATA/SAS connectors, SATA 3.0Gb/s, SAS 3.0Gb/s, RAID 0, 1 support		
Discrete drive controller (opt)	None		
Hard drive(s)	3.5" SATA: SATA 6.0Gb/s, 7200 rpm 3.5" Hybrid: SATA 6.0Gb/s, 7200 rpm, integrated 8GB NAND flash 2.5" SATA: SATA 6.0Gb/s, 10000 rpm 3.5" SAS/2.5" SAS: SAS 6.0Gb/s, 15000 rpm 2.5" SSD: Solid State Drive (SSD), SATA 6.0Gb/s OPAL-capable on some models mSATA: mSATA SSD, SATA 6.0Gb/s		
Optical	Supports DVD-ROM, DVD±RW, or Blu-ray Burner, SATA interface		
Media reader	None (use USB port)		
Front ports	Two USB 3.0, microphone (3.5mm), headphone (3.5mm)		
Rear ports	Eight USB 2.0, two USB 3.0 (blue), one serial (9-pin), one ethernet (RJ-45), three analog audio ports (line-in, line-out, mic-in)		
IEEE 1394 adptr (optional)	None. Optional FireWire PCIe adapter on selected models, 1394a-2000, 400Mbps, two 6-pin ports on rear		
Audio	High Definition (HD) Audio, Realtek® ALC662 codec		
Speaker	Internal speaker for business audio		
Onboard Ethernet	One onboard gigabit ethernet, Intel 82579		
Security chip	STMicroelectronics ST33TPM12LPC, TCG 1.2-compliant		
Keyboard/Mouse	104-key keyboard (USB)/Optical Wheel Mouse (USB)		
Power supply	800 watts with 80mm side-mounted variable speed fan, universal, Climate Savers® Computing Gold, 80 PLUS® Gold qualified		
	Tower <ul style="list-style-type: none"> • Rack-mountable to 3U • Raven black color; metal case • 5.1"W x 17.5"D x 16.8"H • 130mm W x 444mm D x 427mm H (without rubber feet) • 40.7 lb (18.5kg) max configuration • 24-liter • Toolless side cover removal • Toolless disk and optical drive removal • Toolless adapter retention • Illuminated front icons • Rack shelf support or optional rail kit Bay 1 5.25", 1.6" high, external, for optical Bay 2-4 3.5", 1" high, internal, for hard drive Slot 1: half-length, full-height, PCIe 3.0 x16 (near CPU, x4 elec) Slot 2: full-length, full-height, PCIe 3.0 x16* Slot 3: full-length, full-height, 32-bit PCI 2.3 Slot 4: full-length, full-height, PCIe 3.0 x16* Slot 5: full-length, full-height, PCIe 2.0 x4 Slot 6: half-length, full-height, 32-bit PCI 2.3 * Adapters >75W use auxiliary power connector(s) from PSU		
	SECURITY <ul style="list-style-type: none"> • Security chip (see information on left) • Side cover lock (ships with two identical keys) • Padlock loop (in rear for opt padlock; padlock prohibits side cover removal) • Security slot (in rear for optional Kensington® Microsaver® cable; prohibits side cover removal) • Power-on password • Administrator password • Boot sequence control • Boot without keyboard, mouse, diskette • Serial port I/O enable/disable • USB 2.0 ports enable/disable individually • USB 3.0 ports enable/disable concurrently • Chassis intrusion switch on selected model(s) 		
	ISV certifications Please visit www.lenovo.com/support/ISV		
	Environmental certifications GREENGUARD® certified RoHS-compliant EPEAT™ Gold rating Supports ThinkVantage® technologies		

See footnotes for important warranty information
 Model(s) announced September 10, 2013


ThinkStation C30 (1136) - October 2013

Product Specifications Reference (PSREF)

Type-model	Processor(s) - Xeon E5 Family	Memory (MHz/type)	Memory DIMMs	Upgrade ROM for onboard drive controller	Pre-conf RAID	Hard drive(s)**	Optical	Media reader	Graphics adapter(s) and GPU computing***	1394 adptr	Chassis intrusion switch	Preloaded OS
<i>1136-A8G</i>	1xE5-2620 v2 6C/2.1GHz/15MB/1600MHz	1600MHz UDIMM	4GBx1	No	No	1x1TB 3.5" SATA Hybrid	DVD±RW	No	1xQuadro K2000 (2GB, 1xDVI-I DL*, 2xDP, 51W)	No	Switch	Win7 Pro64 (Downgrade from Win8)
<i>1136-B2G</i>	1xE5-2650 v2 8C/2.6GHz/20MB/1866MHz	1600MHz UDIMM	8GBx1	No	No	1x256GB 2.5" SSD - OPAL	DVD±RW	No	No	No	Switch	Win7 Pro64 (Downgrade from Win8)
<i>1136-C5G</i>	1xE5-2620 v2 6C/2.1GHz/15MB/1600MHz	1600MHz UDIMM	4GBx1	No	No	1x2TB 3.5" SATA	DVD±RW	No	No	No	Switch	Win7 Pro64 (Downgrade from Win8)

* Model in *italics* shows that this is a Global Model ** The SSD drives in *italics* must be plugged into red or orange SATA connectors *** DL = Dual Link, SL = Single Link

- 3-year limited warranty
- For ThinkStation C30 platform specifications, please see [ThinkStation C30 Platform Specifications sheet](#)

Chipset	Intel C602 Chipset		
Intel AMT	Intel Active Management Technology 8 supported		
Processor	Two LGA2011 sockets, integrated 4-channel DDR3 memory controller per processor, only one E5-1600 or E5-1600 v2 processor are supported		
Memory	UDIMM or RDIMM, ECC, DDR3 , 8-channel capable (4-channel per processor), eight 240-pin DIMM sockets 64GB max (UDIMM, 8GBx8)/256GB max (RDIMM, 32GBx8)		
Additional memory disclaimers	<ul style="list-style-type: none"> • Actual memory operating speed depends on processor memory controller speed, installed memory speed, and quantity of memory DIMMs • Over four DIMMs requires dual processors • Mixing of RDIMM and UDIMM is not supported • When using processor from Xeon E5-1600 and E5-1600 v2 series, only four DIMM sockets for CPU1 are available and max memory capacity is 32GB (UDIMM, 8GBx4)/128GB (RDIMM, 32GBx4) 		
Graphics	Two PCI Express 3.0 x16 slots for graphics adapters and GPU computing processors, supports NVIDIA SLI technology, NVIDIA Maximus technology		
Onboard drive controllers	<ul style="list-style-type: none"> • Four SATA connectors via integrated Advanced Host Controller Interface (AHCI) in chipset, two SATA 6.0Gb/s (red), two SATA 3.0Gb/s (orange), RAID 0, 1, 5 support • Three SATA connectors via integrated Storage Controller Unit (SCU) in chipset, SATA 3.0Gb/s, RAID 0, 1, 5 support 		
Upgrade ROM for onboard drive controllers (opt)	Optional SAS HDD Enablement Module upgrades the 3 SATA connectors on SCU to 3 SATA/SAS connectors, SATA 3.0Gb/s, SAS 3.0Gb/s, RAID 0, 1 support		
Discrete drive controller (opt)	None		
Hard drive(s)	3.5" SATA: SATA 6.0Gb/s, 7200 rpm 3.5" Hybrid: SATA 6.0Gb/s, 7200 rpm, integrated 8GB NAND flash 2.5" SATA: SATA 6.0Gb/s, 10000 rpm 3.5" SAS/2.5" SAS: SAS 6.0Gb/s, 15000 rpm 2.5" SSD: Solid State Drive (SSD), SATA 6.0Gb/s, OPAL-capable on some models mSATA: mSATA SSD, SATA 6.0Gb/s		
Optical	Supports DVD-ROM, DVD±RW, or Blu-ray Burner, SATA interface		
Media reader	None (use USB port)		
Front ports	Two USB 3.0, microphone (3.5mm), headphone (3.5mm)		
Rear ports	Eight USB 2.0, two USB 3.0 (blue), one serial (9-pin), one ethernet (RJ-45), three analog audio ports (line-in, line-out, mic-in)		
IEEE 1394 adptr (optional)	None. Optional FireWire PCIe adapter on selected models, 1394a-2000, 400Mbps, two 6-pin ports on rear		
Audio	High Definition (HD) Audio, Realtek® ALC662 codec		
Speaker	Internal speaker for business audio		
Onboard Ethernet	One onboard gigabit ethernet, Intel 82579		
Security chip	STMicroelectronics ST33TPM12LPC, TCG 1.2-compliant		
Keyboard/Mouse	104-key keyboard (USB)/Optical Wheel Mouse (USB)		
Power supply	800 watts with 80mm side-mounted variable speed fan, universal, Climate Savers® Computing Gold, 80 PLUS® Gold qualified		
	Tower <ul style="list-style-type: none"> • Rack-mountable to 3U • Raven black color; metal case • 5.1"W x 17.5"D x 16.8"H • 130mm W x 444mm D x 427mm H (without rubber feet) • 40.7 lb (18.5kg) max configuration • 24-liter • Toolless side cover removal • Toolless disk and optical drive removal • Toolless adapter retention • Illuminated front icons • Rack shelf support or optional rail kit 		
	Bay 1 5.25", 1.6" high, external, for optical Bay 2-4 3.5", 1" high, internal, for hard drive Slot 1: half-length, full-height, PCIe 3.0 x16 (near CPU, x4 elec) Slot 2: full-length, full-height, PCIe 3.0 x16* Slot 3: full-length, full-height, 32-bit PCI 2.3 Slot 4: full-length, full-height, PCIe 3.0 x16* Slot 5: full-length, full-height, PCIe 2.0 x4 Slot 6: half-length, full-height, 32-bit PCI 2.3		
	* Adapters >75W use auxiliary power connector(s) from PSU		
	SECURITY <ul style="list-style-type: none"> • Security chip (see information on left) • Side cover lock (ships with two identical keys) • Padlock loop (in rear for opt padlock; padlock prohibits side cover removal) • Security slot (in rear for optional Kensington® Microsaver® cable; prohibits side cover removal) • Power-on password • Administrator password • Boot sequence control • Boot without keyboard, mouse, diskette • Serial port I/O enable/disable • USB 2.0 ports enable/disable individually • USB 3.0 ports enable/disable concurrently • Chassis intrusion switch on selected model(s) 		
	ISV certifications Please visit www.lenovo.com/support/ISV		
	Environmental certifications GREENGUARD® certified RoHS-compliant EPEAT™ Gold rating Supports ThinkVantage® technologies		


See footnotes for important warranty information
 Model(s) announced October 8 (C5G) or 15 (A8G/B2G), 2013

© Lenovo
 (1136-3E) September 2013

Type-model	Processor(s) - Xeon E5 Family	Memory (MHz/type)	Memory DIMMs	Upgrade ROM for onboard drive controller	Pre-conf RAID	Hard drive(s)**	Optical	Media reader	Graphics adapter(s) and GPU computing***	1394 adptr	Chassis intrusion switch	Preloaded OS
<i>1136-D4G</i>	2xXeonE5-2667 v2 8C/3.3GHz/25MB/1866MHz	1866MHz UDIMM	4GBx4	No	No	1x500GB 3.5" SATA	DVD	No	1xNVS 510 2GB/4xminiDP/35W	No	Switch	Win7 Pro64
<i>1136-D5G</i>	2xXeonE5-2620 v2 6C/2.1GHz/15MB/1600MHz	1600MHz UDIMM	4GBx4	No	No	1x2TB 3.5" SATA	DVD±RW	No	1xNVS 310 512MB/2xDP/19.5W	No	Switch	Win7 Pro64

* Model in italics shows that this is a Global Model ** The SSD drives in italics must be plugged into red or orange SATA connectors *** DL = Dual Link, SL = Single Link

- 3-year limited warranty
- For ThinkStation C30 platform specifications, please see [ThinkStation C30 Platform Specifications sheet](#)

Chipset	Intel C602 Chipset		
Intel AMT	Intel Active Management Technology 8 supported		
Processor	Two LGA2011 sockets, integrated 4-channel DDR3 memory controller per processor, only one E5-1600 or E5-1600 v2 processor are supported		
Memory	UDIMM or RDIMM, ECC, DDR3 , 8-channel capable (4-channel per processor), eight 240-pin DIMM sockets 64GB max (UDIMM, 8GBx8)/256GB max (RDIMM, 32GBx8)		
Additional memory disclaimers	<ul style="list-style-type: none"> • Actual memory operating speed depends on processor memory controller speed, installed memory speed, and quantity of memory DIMMs • Over four DIMMs requires dual processors • Mixing of RDIMM and UDIMM is not supported • When using processor from Xeon E5-1600 and E5-1600 v2 series, only four DIMM sockets for CPU1 are available and max memory capacity is 32GB (UDIMM, 8GBx4)/128GB (RDIMM, 32GBx4) 		
Graphics	Two PCI Express 3.0 x16 slots for graphics adapters and GPU computing processors, supports NVIDIA SLI technology, NVIDIA Maximus technology		
Onboard drive controllers	<ul style="list-style-type: none"> • Four SATA connectors via integrated Advanced Host Controller Interface (AHCI) in chipset, two SATA 6.0Gb/s (red), two SATA 3.0Gb/s (orange), RAID 0, 1, 5 support • Three SATA connectors via integrated Storage Controller Unit (SCU) in chipset, SATA 3.0Gb/s, RAID 0, 1, 5 support 		
Upgrade ROM for onboard drive controllers (opt)	Optional SAS HDD Enablement Module upgrades the 3 SATA connectors on SCU to 3 SATA/SAS connectors, SATA 3.0Gb/s, SAS 3.0Gb/s, RAID 0, 1 support		
Discrete drive controller (opt)	None		
Hard drive(s)	3.5" SATA: SATA 6.0Gb/s, 7200 rpm 3.5" Hybrid: SATA 6.0Gb/s, 7200 rpm, integrated 8GB NAND flash 2.5" SATA: SATA 6.0Gb/s, 10000 rpm 3.5" SAS/2.5" SAS: SAS 6.0Gb/s, 15000 rpm 2.5" SSD: Solid State Drive (SSD), SATA 6.0Gb/s OPAL-capable on some models mSATA: mSATA SSD, SATA 6.0Gb/s		
Optical	Supports DVD-ROM, DVD±RW, or Blu-ray Burner, SATA interface		
Media reader	None (use USB port)		
Front ports	Two USB 3.0, microphone (3.5mm), headphone (3.5mm)		
Rear ports	Eight USB 2.0, two USB 3.0 (blue), one serial (9-pin), one ethernet (RJ-45), three analog audio ports (line-in, line-out, mic-in)		
IEEE 1394 adptr (optional)	None. Optional FireWire PCIe adapter on selected models, 1394a-2000, 400Mbps, two 6-pin ports on rear		
Audio	High Definition (HD) Audio, Realtek® ALC662 codec		
Speaker	Internal speaker for business audio		
Onboard Ethernet	One onboard gigabit ethernet, Intel 82579		
Security chip	STMicroelectronics ST33TPM12LPC, TCG 1.2-compliant		
Keyboard/Mouse	104-key keyboard (USB)/Optical Wheel Mouse (USB)		
Power supply	800 watts with 80mm side-mounted variable speed fan, universal, Climate Savers® Computing Gold, 80 PLUS® Gold qualified		
	Tower <ul style="list-style-type: none"> • Rack-mountable to 3U • Raven black color; metal case • 5.1"W x 17.5"D x 16.8"H • 130mm W x 444mm D x 427mm H (without rubber feet) • 40.7 lb (18.5kg) max configuration • 24-liter • Toolless side cover removal • Toolless disk and optical drive removal • Toolless adapter retention • Illuminated front icons • Rack shelf support or optional rail kit 		
	Bay 1 5.25", 1.6" high, external, for optical Bay 2-4 3.5", 1" high, internal, for hard drive Slot 1: half-length, full-height, PCIe 3.0 x16 (near CPU, x4 elec) Slot 2: full-length, full-height, PCIe 3.0 x16* Slot 3: full-length, full-height, 32-bit PCI 2.3 Slot 4: full-length, full-height, PCIe 3.0 x16* Slot 5: full-length, full-height, PCIe 2.0 x4 Slot 6: half-length, full-height, 32-bit PCI 2.3 * Adapters >75W use auxiliary power connector(s) from PSU		
	SECURITY <ul style="list-style-type: none"> • Security chip (see information on left) • Side cover lock (ships with two identical keys) • Padlock loop (in rear for opt padlock; padlock prohibits side cover removal) • Security slot (in rear for optional Kensington® Microsaver® cable; prohibits side cover removal) • Power-on password • Administrator password • Boot sequence control • Boot without keyboard, mouse, diskette • Serial port I/O enable/disable • USB 2.0 ports enable/disable individually • USB 3.0 ports enable/disable concurrently • Chassis intrusion switch on selected model(s) 		
	ISV certifications Please visit www.lenovo.com/support/ISV		
	Environmental certifications GREENGUARD® certified RoHS-compliant EPEAT™ Gold rating Supports ThinkVantage® technologies		

See footnotes for important warranty information
 Model(s) announced April 1, 2014