

OVERVIEW



1. USB-C (USB 10Gbps), with USB PD 3.0 & DP 1.4	5. USB-A (USB 5Gbps)
2. USB-A (USB 5Gbps)	6. HDMI
3. Headphone / microphone combo jack (3.5mm)	7. Kensington Nano Security Slot
4. microSD card reader	



PERFORMANCE

Processor

Processor Family

Intel® N-series Processor

Processor**

Processor Name	Cores	Threads	Base Frequency	Max Frequency	Cache	Processor Graphics	
N100	4	4	0.8GHz	3.4GHz	6MB	Intel® UHD Graphics	
N200	4	4	1.0GHz	3.7GHz	6MB	Intel® UHD Graphics	

Operating System

Operating System

ChromeOS

Graphics

Graphics

Graphics	Туре	Memory	Key Features	
Intel® UHD Graphics	Integrated	Shared	DirectX® 12.1	

Monitor Support

Monitor Support

Supports up to 3 independent displays (native display and 2 external monitors via HDMI® and USB-C®)

- HDMI® supports up to 3840x2160@30Hz
- USB-C® supports up to 3840x2160@60Hz

Chipset

Chipset

Intel® SoC (System on Chip) platform

Memory

Max Memory

- 4GB soldered memory, not upgradable
- 8GB soldered memory, not upgradable

Memory Slots

Memory soldered to systemboard, no slots, single-channel

Memory Type

LPDDR5-4800

Storage

Storage Support[1]

- 64GB eMMC 5.1 on systemboard
- 128GB eMMC 5.1 on systemboard

Storage Slot

eMMC on systemboard, no slots

Storage Type

	Disk Type	Interface	Offering			
ſ	Flash Memory	eMMC 5.1	64GB / 128GB			

Notes:

[1] The storage capacity supported is based on the test results with current Lenovo® storage offerings.

Removable Storage

Card Reader



microSD card reader

Multi-Media

Audio Chip

High Definition (HD) Audio, Realtek® ALC5682I-VD codec

Speakers[1]

Stereo speakers, 2W x2, optimized with Waves MaxxAudio®, MAX98357A Amplifier (AMP)

Microphone

Dual-microphone array, support WoV (Wake-on-Voice), and Google Assistant

Camera**

- FHD 1080p, with privacy shutter, fixed focus
- HD 720p, with privacy shutter, fixed focus

Notes:

[1] Google Approved Vendor List (AVL) Certification.

Sensor

Sensors

- · Accelerometer (G) sensor
- Gyroscope sensor
- Hall sensor

Battery

Battery

Integrated Li-Polymer 47Wh battery

Max Battery Life[1]

Google power load test: 12 hr

Notes:

[1] All battery life claims are approximate maximum and based on results using the MobileMark® 2014, MobileMark® 2018, MobileMark® 25, JEITA 2.0, continuous 1080p video playback (with 150nits brightness and default volume level) or Google Power Load Test (PLT) battery-life benchmark tests. Actual battery life will vary depending on many factors such as product configuration and usage, software use, wireless functionality, power management settings, and screen brightness. The maximum capacity of the battery will decrease with time and use.

Power Adapter

Power Adapter[1]

45W USB-C® (3-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz

Notes

[1] AC adapter offerings depend on the country.

DESIGN

Display

Display[1]

Size	Resolution	Touch	Туре	Brightness	Surface	Aspect Ratio	Contrast Ratio	Color Gamut		Viewing Angle (L/R/U/D)	Key Features
	WUXGA (1920x1200)	Multi- touch	IPS	300nits	Glossy	16:10	800:1	50% NTSC	60Hz	85°/85°/85°/85°	TÜV Low Blue Light (Hardware)

Touchscreen

GF2 or OGM (One Glass Metal mesh) multi-touch, supports 10-point touch

Notes:



[1] IPS (in-plane switching) technology may refer to IPS, PLS, ADS, AHVA, AAS.

Multi-mode

Multi-mode

Laptop, tent, stand, and tablet modes supported by 360° hinge

Input Device

Keyboard

Chrome keyboard, 6-row

Keyboard Backlight

- LED backlight
- · Non-backlight

Touchpad

Buttonless Mylar® surface multi-touch touchpad, 61.5 x 105 mm (2.42 x 4.13 inches)

Mechanical

Dimensions (WxDxH)[1]

284 x 210 x 18.4 mm (11.18 x 8.27 x 0.72 inches)

Weight^[2]

Starting at 1.25 kg (2.76 lbs)

Case Color**

- · Abyss blue, dual-tone design
- · Cloud grey, dual-tone design

Surface Treatment

Texture painting with dual tone

Case Material

PC-ABS (top), PC-ABS (bottom)

Notes:

- [1] The system dimensions may vary depending on configurations.
- [2] The system weight is approximate and based on results in Lenovo® lab, which varies depending on the source of component, variance of the distribution of each component, and manufacturing process. It may not be the exact weight for each specific model.

CONNECTIVITY

Network

Ethernet

No onboard Ethernet

WLAN + Bluetooth®**[1]

- Wi-Fi[®] 6, 802.11ax 2x2 Wi-Fi[®] + Bluetooth[®] 5.3^[2]
- Wi-Fi[®] 6E, 802.11ax 2x2 Wi-Fi[®] + Bluetooth[®] 5.3^[3]

Notes:

- [1] Bluetooth® 5.3 operation requires Windows® 11. For more information please visit <u>General Bluetooth® Support Information on Microsoft®</u>.
- [2] Wi-Fi® 6 full features might be limited by country-level restrictions.
- [3] Wi-Fi® 6E full features might be limited by country-level restrictions.
- 6GHz Wi-Fi® 6E operation is dependent on the support of the operating system, routers/APs/Gateways that support Wi-Fi® 6E, and the regional regulatory certifications & spectrum allocation.

Ports^[1]

Standard Ports

- 2x USB-A (USB 5Gbps / USB 3.2 Gen 1)
- 1x USB-C® (USB 10Gbps / USB 3.2 Gen 2), with USB PD 3.0 and DisplayPort™ 1.4

IP Flex 3 Chrome 12IAN8



- 1x HDMI® 1.4
- 1x Headphone / microphone combo jack (3.5mm)
- 1x microSD card reader

Notes:

[1] The transfer speed of the ports will vary and, depending on many factors, such as the processing speed of the host device, file attributes and other factors related to system configuration and your operating environment, will be slower than theoretical speed.

SECURITY & PRIVACY

Security

Security Chip

Google Security Chip H1

Physical Locks

Kensington® Nano Security Slot™

Fingerprint Reader

No fingerprint reader

BIOS Security

No support

Other Security

Camera privacy shutter

SERVICE

Warranty

Base Warranty**

- 1-year courier or carry-in service
- 2-year (1-yr battery) courier or carry-in service
- 3-year (1-yr battery) courier or carry-in service

ACCESSORIES

Bundled Accessories

Bundled Accessories[1]

None

Notes:

[1] For more compatible accessory solutions, please visit Accessories for IP Flex 3 Chrome 12IAN8.

OPERATING REQUIREMENTS

Operating Environment

Temperature[1]

- At altitudes up to 2438 m (8,000 ft)
 - Operating: 5°C to 35°C (41°F to 95°F)
 - Storage: 5° C to 43° C (41° F to 109° F)
- At altitudes above 2438 m (8,000 ft)
 - Maximum temperature when operating under the unpressurized condition: 31.3°C (88°F)

Relative Humidity

- Operating: 8% to 95% at wet-bulb temperature 23°C (73°F)
- Storage and transportation: 5% to 95% at wet-bulb temperature 27°C (81°F)

Altitude

Maximum altitude (without pressurization): 3048 m (10,000 ft)



Notes:

[1] When you charge the battery, its temperature must be no lower than 10°C (50°F).

CERTIFICATIONS

Green Certifications¹¹

Green Certifications[2]

- ENERGY STAR® 8.0
- EPEAT™ Silver Registered[3]
- ErP Lot 6
- ErP Lot 26
- RoHS compliant

Notes:

[1] The items listed under the "Green Certifications" section may not only refer to certification but also registration or self-declaration. For ESG & regulatory compliance documents, please visit https://compliance.lenovo.com.

[2] EPEAT™ registration and ENERGY STAR® certification are dependent on system OS. Please visit <u>epeat.net</u> and <u>energystar.gov</u> for more information.

[3] EPEAT™ is registered where applicable, please visit epeat.net for registration status by country.

Other Certifications

Other Certifications

TÜV Rheinland® Low Blue Light (Hardware Solution)

- Feature with ** means that only one offering listed under the feature is configured on selected models.
- Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not
 responsible for photographic or typographical errors. LENOVO PROVIDES THIS PUBLICATION "AS IS,"
 WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES
 OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow
 disclaimer of express or implied warranties in certain transactions, therefore this disclaimer may not apply to
 you.
- The specifications on this page may not be available in all regions, and may be changed or updated without notice.













