

OVERVIEW



1. Power button	5. HDMI 1.4b
2. Card reader	6. USB 2.0
3. Headphone / microphone combo jack (3.5mm)	7. 2x USB 3.2 Gen 1
4. Power connector	



PERFORMANCE

Processor

Processor Family

AMD 3000, AMD Athlon™, or AMD Ryzen™ 3 / 5 / 7 Processor

Processor**

Processor Name	Cores	Threads	Base Frequency	Max Frequency	Cache	Memory Support	Processor Graphics	
AMD 3020e	2	2 2 1.2GHz 2.6GHz 1MB L2 / 4MB L3		DDR4-2400	AMD Radeon™ Graphics			
AMD Athlon Gold 3150U	2	4	2.4GHz	3.3GHz	1MB L2 / 4MB L3 DDR4-2400		AMD Radeon Graphics	
AMD Athlon Silver 3050U	2	2	2.3GHz	3.2GHz	1MB L2 / 4MB L3	DDR4-2400	AMD Radeon Graphics	
AMD Ryzen 3 3250U	2	4	2.6GHz	3.5GHz	1MB L2 / 4MB L3	DDR4-2400	AMD Radeon Graphics	
AMD Ryzen 5 3500U	4	8	2.1GHz	3.7GHz	2MB L2 / 4MB L3	DDR4-2400	AMD Radeon Vega 8 Graphics	
AMD Ryzen 7 3700U	4	8	2.3GHz	4.0GHz	2MB L2 / 4MB L3	DDR4-2400	AMD Radeon RX Vega 10 Graphics	

Operating System

Operating System**

- FreeDOS
- Windows® 10 Home 64
- Windows 10 Home 64 Single Language
- Windows 10 Home Single Language in S mode
- Windows 10 Home in S mode
- Windows 10 Pro 64
- Windows 11 Home
- Windows 11 Home Single Language
- Windows 11 Home Single Language in S mode
- Windows 11 Home in S mode
- Windows 11 Pro
- No operating system

Graphics

Graphics**

Graphics	Туре	Memory	Key Features
AMD Radeon Graphics	Integrated	Shared	DirectX® 12
AMD Radeon RX Vega 10 Graphics	Integrated	Shared	DirectX 12
AMD Radeon Vega 8 Graphics	Integrated	Shared	DirectX 12

Monitor Support

Monitor Support

Supports up to 2 independent displays (native display and 1 external monitor via HDMI®)

HDMI supports up to 3840x2160@30Hz

Chipset

Chipset

AMD SoC (System on Chip) platform

Memory

Max Memory**

• Up to 8GB (8GB SO-DIMM) DDR4-2400 offering (AMD 3020e models)



• Up to 12GB (4GB soldered + 8GB SO-DIMM) DDR4-2400 offering (Athlon or Ryzen models)

Memory Slots**

- One DDR4 SO-DIMM slot (AMD 3020e models)
- One memory soldered to systemboard, one DDR4 SO-DIMM slot, dual-channel capable (Athlon or Ryzen models)

Memory Type

DDR4-2400

Storage

Storage Support**[1]

- Models with 45Wh battery: one drive, 1x M.2 SSD
 - M.2 2242 SSD up to 512GB
 - M.2 2280 SSD up to 512GB
- Model with 35Wh battery: up to two drives, 1x 2.5" HDD + 1x M.2 SSD
 - 2.5" HDD up to 1TB
 - M.2 2242 SSD up to 512GB
 - M.2 2280 SSD up to 512GB

Storage Slot**

- Models with 35Wh battery: one 2.5" drive slot + one M.2 slot
 - One 2.5" drive slot, supports 2.5" SATA HDD
 - One M.2 2280 PCle[®] Gen 3x4 slot, supports M.2 2242/2280 SSD
- Models with 45Wh battery: one M.2 slot
 - One M.2 2280 PCIe Gen 3x4 slot, supports M.2 2242/2280 SSD

Storage Type***

Disk Type	Interface	RPM
2.5" SATA HDD	SATA 6Gb/s	5.4K
M.2 2242 SSD	PCIe NVMe®, PCIe 3.0 x2	-
M.2 2280 SSD	PCIe NVMe, PCIe 3.0 x4	-

Notes:

[1] The storage capacity supported is based on the test results with current Lenovo® storage offerings. The system may support larger storage as the technology develops.

Removable Storage

Optical

- USB external DVD burner (DVD±RW), 9.5mm high
- None

Card Reader

4-in-1 card reader (SD, SDHC, SDXC, MMC)

Multi-Media

Audio Chip

High Definition (HD) Audio

Speakers

Stereo speakers, 1.5W x2, Dolby® Audio™

Microphone

Dual-microphone array

Camera**[1]

- HD 720p, with privacy shutter, fixed focus
- 0.3-megapixel, with privacy shutter, fixed focus

Notes:

[1] HD720p camera for AP and NA only.

Battery

Battery



**

- Integrated Li-Polymer 35Wh battery
- Integrated Li-Polymer 45Wh battery, supports Rapid Charge (charge up to 80% in 1hr)

Max Battery Life**[1]

- MobileMark® 2014: 13 hr (45Wh)
- MobileMark 2014: 9.6 hr (35Wh)

Notes:

[1] All battery life claims are approximate maximum and based on results using the MobileMark 2014, MobileMark 2018, MobileMark 25, JEITA 2.0, continuous 1080p video playback (with 150nits brightness and default volume level) or Google Power Load Test (PLT) battery-life benchmark tests. Actual battery life will vary depending on many factors such as product configuration and usage, software use, wireless functionality, power management settings, and screen brightness. The maximum capacity of the battery will decrease with time and use.

Power Adapter

Power Adapter[1]

65W round tip (2-pin, wall-mount) AC adapter, 100-240V, 50-60Hz

Notes:

[1] AC adapter offerings depend on the country.

DESIGN

Display

Display**[1]

Size	Resolution	Touch	Туре	Brightness	Surface	Aspect Ratio	Refresh Rate
15.6"	HD (1366x768)	None	TN	220 nits	Anti-glare	16:9	-
15.6"	FHD (1920x1080)	None	TN	220 nits	Anti-glare	16:9	-
15.6"	HD (1366x768)	Multi-touch	TN	220 nits	Anti-glare	16:9	-
15.6"	FHD (1920x1080)	None	IPS	250 nits	Anti-glare	16:9	-
15.6"	FHD (1920x1080)	Multi-touch	IPS	300 nits	Anti-glare	16:9	-

Touchscreen

- On-cell multi-touch, supports 10-point touch
- Non-touch

Notes:

[1] California Electronic Waste Recycling Fee

In California USA, per state law, Lenovo charges an electronic waste recycling fee on this covered device at the time of sale of the product. For more information, please go to https://www.calrecycle.ca.gov/Electronics/Consumer.

Input Device

Keyboard

6-row, multimedia Fn keys, numeric keypad

Keyboard Backlight

Non-backlight

Touchpad

Buttonless Mylar® surface multi-touch touchpad, supports Precision TouchPad (PTP), 69 x 104 mm (2.72 x 4.09 inches)

Mechanical

Dimensions (WxDxH)[1]

362.2 x 253.4 x 19.9 mm (14.26 x 9.98 x 0.78 inches)

Weight^[2]

Around 1.85 kg (4.08 lbs)



Case Color**

- · Abyss blue
- Almond
- · Business black
- Cherry red
- · Platinum grey

Surface Treatment**

- IMR (in-mold decoration by roller)
- Texture

Case Material

PC-ABS (top), PC-ABS (bottom)

Notes:

[1] The system dimensions may vary depending on configurations.

[2] The system weight is approximate and based on results in Lenovo lab, which varies depending on the source of component, variance of the distribution of each component, and manufacturing process. It may not be the exact weight for each specific model.

CONNECTIVITY

Network

Ethernet

No onboard Ethernet

WLAN + Bluetooth®[1]

802.11ac 2x2 Wi-Fi® + Bluetooth 5.0, M.2 card

Notes:

[1] Bluetooth 5.2 is hardware ready but may run at a lower version due to OS limitations.

Ports^[1]

Standard Ports

- 1x USB 2.0
- 2x USB 3.2 Gen 1
- 1x HDMI 1.4b
- · 1x Card reader
- 1x Headphone / microphone combo jack (3.5mm)
- 1x Power connector

Notes:

[1] The transfer speed of following ports will vary and, depending on many factors, such as the processing speed of the host device, file attributes and other factors related to system configuration and your operating environment, will be slower than theoretical speed.

USB 2.0: 480 Mbit/s;

USB 3.2 Gen 1 (SuperSpeed USB 5Gbps, formerly USB 3.0 / USB 3.1 Gen 1): 5 Gbit/s;

USB 3.2 Gen 2 (SuperSpeed USB 10Gbps, formerly USB 3.1 Gen 2): 10 Gbit/s;

USB4® 20Gbps / USB 3.2 Gen 2x2 (SuperSpeed USB 20Gbps): 20 Gbit/s;

USB4 40Gbps (USB 40Gbps): 40 Gbit/s;

Thunderbolt™ 3/4: 40 Gbit/s.

SECURITY & PRIVACY

Security

Security Chip

Firmware TPM 2.0 integrated in chipset

Fingerprint Reader

• Touch style fingerprint reader on power button



· No fingerprint reader

BIOS Security

- Administrator password
- Power-on password
- Hard disk password

Other Security

Camera privacy shutter

SERVICE

Warranty^[1]

Base Warranty**

- 1-year courier or carry-in service
- 1-year courier or carry-in with 2-year system board service (Korea only)
- · 2-year (1-yr battery) courier or carry-in service
- 3-year (1-yr battery) courier or carry-in service

Notes:

[1] The warranty upgrades may be bundled with some models, please check the "Included upgrade" column in the specific model's configurations. For more service extensions, please go to https://smartfind.lenovo.com/. To learn more details of warranty policy, please access https://pcsupport.lenovo.com/warranty.

ENVIRONMENTAL

Operating Environment

Temperature[1]

- At altitudes up to 2438 m (8,000 ft)
 - Operating: 5°C to 35°C (41°F to 95°F)
 - Storage: 5° C to 43° C (41° F to 109° F)
- At altitudes above 2438 m (8,000 ft)
 - Maximum temperature when operating under the unpressurized condition: 31.3°C (88°F)

Humidity

- Operating: 8% to 95% at wet-bulb temperature 23°C (73°F)
- Storage: 5% to 95% at wet-bulb temperature 27°C (81°F)

Altitude

Maximum altitude (without pressurization): 3048 m (10,000 ft)

Notes:

[1] When you charge the battery, its temperature must be no lower than 10°C (50°F).

CERTIFICATIONS

Green Certifications

- ErP Lot 3
- RoHS compliant

Notes:

[1] The items listed under the "Green Certifications" section may not only refer to certification but also registration or self-declaration.

• Feature with ** means that only one offering listed under the feature is configured on selected models.

IdeaPad 3 15ADAO5



models.

- Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not
 responsible for photographic or typographical errors. LENOVO PROVIDES THIS PUBLICATION "AS IS,"
 WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES
 OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow
 disclaimer of express or implied warranties in certain transactions, therefore this disclaimer may not apply to
 you.
- The specifications on this page may not be available in all regions, and may be changed or updated without notice.







ДОМА





EDMA EDMA



AMD∄



ДОМА