

OVERVIEW



1. Power button	5. USB 3.2 Gen 1
2. MicroSD card reader	6. HDMI 1.4b
3. USB 3.2 Gen 1	7. Headphone / microphone combo jack (3.5mm)
4. Power connector	

PERFORMANCE

Processor

Processor Family

AMD 3000 or AMD Athlon™ Processor

Processor

Processor Name	Cores	Threads	Base Frequency	Max Frequency	Cache	Memory Support	Processor Graphics
AMD 3020e	2	2	1.2GHz	2.6GHz	1MB L2 / 4MB L3	DDR4-2400	AMD Radeon™ Graphics
AMD Athlon Silver 3050e	2	4	1.4GHz	2.8GHz	1MB L2 / 4MB L3	DDR4-2400	AMD Radeon Graphics

Operating System

Operating System

- Windows® 10 Home 64
- Windows 10 Home in S mode
- Windows 11 Home 64
- Windows 11 Home in S mode
- No operating system

Graphics

Graphics

Graphics	Type	Memory	Key Features
AMD Radeon Graphics	Integrated	Shared	DirectX® 12

Monitor Support

Monitor Support

Supports up to 2 independent displays via native display and 1 external monitor; supports external monitor via HDMI® (up to 3840x2160@30Hz)

Chipset

Chipset

AMD SoC (System on Chip) platform

Memory

Max Memory^[1]

4GB soldered memory, not upgradable

Memory Slots

Memory soldered to systemboard, no slots

Memory Type

DDR4-2400

Notes:

1. The max memory is based on the test results with current Lenovo® memory offerings. The system may support more memory as the technology develops.

Storage

Storage Support^[1]

- One drive, up to 256GB M.2 2242 SSD
- 64GB eMMC 5.1 on systemboard

Storage Slot

- eMMC on systemboard, no slots (eMMC model)
- One M.2 2242 PCIe Gen 3x4 slot, supports M.2 2242 SSD (M.2 SSD model)

Storage Type

Disk Type	Interface	RPM	Offering	Security
Flash Memory	eMMC 5.1	-	64GB	-
M.2 2242 SSD	PCIe NVMe, PCIe 3.0 x4	-	128GB / 256GB	-

Notes:

1. System has one eMMC on systemboard or one M.2 2242 SSD exclusively

Removable Storage

Optical

None

Card Reader

MicroSD card reader

Multi-Media

Audio Chip

High Definition (HD) Audio, Realtek® ALC3287 codec

Speakers

Stereo speakers, 1.5W x2, Dolby® Audio™

Microphone

Single microphone

Camera

720p, with privacy shutter, fixed focus

Sensor

Sensors

Accelerometer (G) sensor

Battery

Battery

Integrated Li-Polymer 37.5Wh battery, supports Smart Charge (get 2 hours of runtime with a 15-minute charge)

Max Battery Life^[1]

- MobileMark® 2014: 10.15 hr (FHD model)
- MobileMark 2014: 11.25 hr (HD model)

Notes:

1. All battery life claims are approximate maximum and based on results using the MobileMark 2014, MobileMark 2018, JEITA 2.0, continuous 1080p video playback (with 150nits brightness and default volume level) or Google Power Load Test (PLT) battery-life benchmark tests. Actual battery life will vary and depends on many factors such as product configuration and usage, software use, wireless functionality, power management settings, and screen brightness. The maximum capacity of the battery will decrease with time and use.

Power Adapter

Power Adapter

45W round tip (2-pin, wall-mount) AC adapter

DESIGN

Display

Display^[1]

Size	Resolution	Touch	Type	Brightness	Surface	Aspect Ratio	Contrast Ratio	Color Gamut	Viewing Angle	Key Features
11.6"	HD (1366x768)	Multi-touch	IPS	250 nits	Glossy	16:9	-	50% NTSC	-	-

11.6"	FHD (1920x1080)	Multi-touch	IPS	300 nits	Glossy	16:9	-	50% NTSC	-	-
-------	-----------------	-------------	-----	----------	--------	------	---	----------	---	---

Touchscreen

Capacitive-type multi-touch, supports 10-point touch

Multi-mode

Laptop, tent, stand and tablet modes supported by 360° hinge

Notes:

1. California Electronic Waste Recycling Fee

In California, per state law, Lenovo charges an electronic waste recycling fee on this covered device at the time of sale of the product.

For more information, go to <https://www.calrecycle.ca.gov/Electronics/Consumer>

Input Device**Keyboard**

6-row, multimedia Fn keys

Keyboard Backlight

No support

Touchpad

Buttonless Mylar® surface multi-touch touchpad

Mechanical**Dimensions (WxDxH)**

Models	Dimensions
All models	281.7 x 198 x 17.5 mm (11.09 x 7.79 x 0.68 inches)

Weight⁽¹⁾

Models	Weight
All models	1.2 kg (2.64 lbs)

Case Color

- Abyss blue
- Platinum grey

Surface Treatment

IMR (in-mold decoration by roller)

Case Material

PC + ABS (top), PC + ABS (bottom)

Notes:

1. The system weight varies depending on configurations

CONNECTIVITY**Network****WLAN + Bluetooth®**

802.11ac 2x2 Wi-Fi® + Bluetooth 5.0, M.2 card

Ports⁽¹⁾**Standard Ports**

- 2x USB 3.2 Gen 1
- 1x HDMI 1.4b
- 1x microSD card reader
- 1x Headphone / microphone combo jack (3.5mm)
- 1x Power connector

Notes:

1. The transfer speed of following ports will vary and, depending on many factors, such as the processing speed of the host device, file attributes and other factors related to system configuration and your operating environment, will be slower than theoretical speed.
- USB 2.0: 480 Mbit/s;
 - USB 3.2 Gen 1 (SuperSpeed USB 5Gbps, formerly USB 3.0 / USB 3.1 Gen 1): 5 Gbit/s;
 - USB 3.2 Gen 2 (SuperSpeed USB 10Gbps, formerly USB 3.1 Gen 2): 10 Gbit/s;
 - USB 3.2 Gen 2x2 (SuperSpeed USB 20Gbps): 20 Gbit/s;
 - Thunderbolt™ 3: 40 Gbit/s;
 - FireWire 400: 400 Mbit/s;
 - FireWire 800: 800 Mbit/s

SECURITY & PRIVACY

Security

Security Chip

Firmware TPM 2.0 integrated in chipset

Fingerprint Reader

No fingerprint reader

BIOS Security

- Administrator password
- User password
- Master hard disk password
- User hard disk password

Other Security

Camera privacy shutter

SERVICE

Warranty

Base Warranty

- 1-year depot service
- 2-year (1-yr battery) depot service

ENVIRONMENTAL

Operating Environment

Temperature^[1]

- At altitudes up to 2438 m (8,000 ft)
 - Operating: 5°C to 35°C (41°F to 95°F)
 - Storage: 5°C to 43°C (41°F to 109°F)
- At altitudes above 2438 m (8,000 ft)
 - Maximum temperature when operating under the unpressurized condition: 31.3°C (88°F)

Humidity

- Operating: 8% to 95% at wet-bulb temperature 23°C (73°F)
- Storage: 5% to 95% at wet-bulb temperature 27°C (81°F)

Altitude

Maximum altitude (without pressurization): 3048 m (10,000 ft)

Notes:

1. When you charge the battery, its temperature must be no lower than 10°C (50°F)

CERTIFICATIONS

Green Certifications

Green Certifications

- ENERGY STAR® 8.0
- ErP Lot 3

- RoHS compliant

