

OVERVIEW



1. Kensington Security Slot	4. Headphone / microphone combo jack (3.5mm)
2. USB-C 2.0	5. Card reader
3. USB 2.0	

PERFORMANCE

Processor

Processor Family

MediaTek Processor

Processor

Processor Name	Cores	Threads	Base Frequency	Max Frequency	Cache	Memory Support	Processor Graphics
MediaTek MT8183	Octa-core: 4x A73 + 4x A53	8	-	A73@2.0GHz / A53@2.0GHz	-	LPDDR4x	ARM Mali-G72 MP3 GPU

Operating System

Operating System

Google Chrome OS

Graphics

Graphics

Graphics	Type	Memory
ARM Mali-G72 MP3 GPU	Integrated	Shared

Monitor Support

Monitor Support

Supports up to 2 independent displays via native display and 1 external monitor; supports external monitor via USB-C (up to 1920x1080@60Hz)

Chipset

Chipset

MediaTek SoC (System on Chip) platform

Memory

Max Memory^[1]

4GB soldered memory, not upgradable

Memory Slots

Memory soldered to systemboard, no slots

Memory Type^[2]

LPDDR4x-1866

Notes:

1. The max memory is based on the test results with current Lenovo® memory offerings. The system may support more memory as the technology develops.
2. Installed memory is actually 2400MHz but run at 1866MHz due to processor limitation

Storage

Storage Support

- 32GB eMMC 5.1 on systemboard
- 64GB eMMC 5.1 on systemboard

Storage Type

Disk Type	Interface	RPM	Security
Flash Memory	eMMC 5.1	-	-

Removable Storage

Optical

None

Card Reader

MicroSD card reader

Multi-Media

Audio Chip

High Definition (HD) Audio, Maxim MAX98357A Dialog DA7219 codec

Speakers

Stereo speakers, 2W x2

Microphone

Dual array microphone

Camera

720p, with camera shutter, fixed focus

Sensor

Sensors

Accelerometer (G) sensor

Battery

Battery

Integrated Li-Polymer 42Wh battery, supports Rapid Charge (charge up to 80% in 1hr)

Max Battery Life^[1]

Google power load test: 16 hr

Notes:

- All battery life claims are approximate maximum and based on results using the MobileMark® 2014, MobileMark 2018, and/or JEITA 2.0 battery-life benchmark tests. Actual battery life will vary and depends on many factors such as product configuration and usage, software use, wireless functionality, power management settings, and screen brightness. The maximum capacity of the battery will decrease with time and use.

Power Adapter

Power Adapter

45W USB-C (3-pin) AC adapter

DESIGN

Display

Display^[1]

Size	Resolution	Touch	Type	Brightness	Surface	Aspect Ratio	Contrast Ratio	Color Gamut	Viewing Angle	Key Features
11.6"	HD (1366x768)	Multi-touch	IPS	250 nits	Glossy	16:9	800:1	45% NTSC	170°	-

Touchscreen

GF2 or OGS (One Glass Solution) Direct Bonding, capacitive-type multi-touch, supports 10-point touch

Multi-mode

Laptop, tent, stand and tablet modes supported by 360° hinge

Notes:

- California Electronic Waste Recycling Fee
 In California, per state law, Lenovo charges an electronic waste recycling fee on this covered device at the time of sale of the product. For more information, go to <https://www.calrecycle.ca.gov/Electronics/Consumer>

Input Device

Keyboard

Chrome keyboard, 6-row

Keyboard Backlight

No support

Touchpad

Buttonless Mylar® surface multi-touch touchpad

Mechanical**Dimensions (WxDxH)**

285 x 202 x 18.5 mm (11.22 x 7.95 x 0.73 inches)

Weight^[1]

1.2 kg (2.65 lbs)

Case Color

- Abyss blue, dual-tone design
- Arctic grey, dual-tone design

Surface Treatment

Texture painting

Case Material

PC + ABS (top), PC + ABS (bottom)

Notes:

1. The system weight varies depending on configurations

CONNECTIVITY**Network****Onboard Ethernet**

No Ethernet

WLAN + Bluetooth®

802.11ac 2x2 Wi-Fi® + Bluetooth 4.2

Ports^[1]**Standard Ports^[2]**

- 1x USB 2.0
- 1x USB-C 2.0 (support data transfer, Power Delivery 2.0 and DisplayPort™ 1.1a)
- 1x microSD card reader
- 1x Headphone / microphone combo jack (3.5mm)

Notes:

1. The transfer speed of following ports will vary and, depending on many factors, such as the processing speed of the host device, file attributes and other factors related to system configuration and your operating environment, will be slower than theoretical speed.
USB 2.0: 480 Mbit/s;
USB 3.2 Gen 1 (SuperSpeed USB 5Gbps, formerly USB 3.0 / USB 3.1 Gen 1): 5 Gbit/s;
USB 3.2 Gen 2 (SuperSpeed USB 10Gbps, formerly USB 3.1 Gen 2): 10 Gbit/s;
USB 3.2 Gen 2x2 (SuperSpeed USB 20Gbps): 20 Gbit/s;
Thunderbolt™ 3: 40 Gbit/s;
FireWire 400: 400 Mbit/s;
FireWire 800: 800 Mbit/s
2. Depending on many factors, actual data transfer speed may be lower than theoretical speed

SECURITY & PRIVACY**Security****Security Chip**

Google Security Chip H1

Physical Locks

Kensington® Nano Security Slot

Fingerprint Reader

No fingerprint reader

BIOS Security

No support

Other Security

Camera privacy shutter

SERVICE

Warranty

Base Warranty

- 1-year mail-in service
- 1-year depot service
- 1-year depot with 2-year system board service
- 2-year (1-yr battery) depot service

ENVIRONMENTAL

Operating Environment

Temperature^[1]

- At altitudes up to 2438 m (8,000 ft)
 - Operating: 5°C to 35°C (41°F to 95°F)
 - Storage: 5°C to 43°C (41°F to 109°F)
- At altitudes above 2438 m (8,000 ft)
 - Maximum temperature when operating under the unpressurized condition: 31.3°C (88°F)

Humidity

- Operating: 8% to 95% at wet-bulb temperature 23°C (73°F)
- Storage: 5% to 95% at wet-bulb temperature 27°C (81°F)

Altitude

Maximum altitude (without pressurization): 3048 m (10,000 ft)

Notes:

1. When you charge the battery, its temperature must be no lower than 10°C (50°F)

CERTIFICATIONS

Green Certifications

Green Certifications

- ENERGY STAR® 8.0
- ErP Lot 3
- RoHS compliant

