

# **OVERVIEW**



1. Power connector	5. Headphone / microphone combo jack (3.5mm)
2. USB 3.2 Gen 1	6. Card reader
3. HDMI	7. USB 3.2 Gen 1
4. USB-C 3.2 Gen 1	



## **PERFORMANCE**

### **Processor**

#### **Processor Family**

Intel® U-series or 13th Generation Intel® Core™ i3 / i5 / i7 Processor

#### Processor\*\*

Processor Name	Cores	Threads	Base Frequency	Max Frequency	Cache	Processor Graphics
U300	5 (1 P-core + 4 E-core)	6	P-core 1.2GHz / E-core 0.9GHz	P-core 4.4GHz / E-core 3.3GHz	8MB	Intel® UHD Graphics
Core™ i3- 1305U	5 (1 P-core + 4 E- core)	6	P-core 1.6Ghz / E-core 1.2Ghz	P-core 4.5GHz / E-core 3.3GHz	10MB	Intel® UHD Graphics
Core™ i3- 1315U	6 (2 P-core + 4 E-core)	8	P-core 1.2GHz / E-core 0.9GHz	P-core 4.5GHz / E-core 3.3GHz	10MB	Intel® UHD Graphics
Core™ i5- 1335U	10 (2 P-core + 8 E-core)	12	P-core 1.3GHz / E-core 0.9GHz	P-core 4.6GHz / E-core 3.4GHz	12MB	Intel® Iris® Xe Graphics[1]
Core™ i7- 1355U	10 (2 P-core + 8 E-core)	12	P-core 1.7GHz / E-core 1.2GHz	P-core 5.0GHz / E-core 3.7GHz	12MB	Intel® Iris® Xe Graphics <sup>[2]</sup>

#### Notes:

[1], [2] Intel® Iris® Xe Graphics capability requires system to be configured with dual-channel memory. On the system with single-channel memory, Intel® Iris® Xe Graphics will function as Intel® UHD Graphics.

## **Operating System**

### Operating System\*\*

- Windows® 11 Pro
- Windows® 11 Home
- Windows® 11 Home Single Language
- Windows® 11 Home Single Language in S mode
- Windows® 11 Home in S mode
- No preload operating system

## **Graphics**

### Graphics\*\*

Graphics	Туре	Memory	TGP	Key Features
Intel® UHD Graphics	Integrated	Shared	Share CPU TDP	DirectX® 12.1
Intel® Iris® Xe Graphics[1]	Integrated	Shared	Share CPU TDP	DirectX® 12.1

#### Notes:

[1] Intel® Iris® Xe Graphics capability requires system to be configured with dual-channel memory. On the system with single-channel memory, Intel® Iris® Xe Graphics will function as Intel® UHD Graphics.

## **Monitor Support**

### **Monitor Support**

Supports up to 3 independent displays (native display and 2 external monitors via HDMI® and USB-C®)

- HDMI® supports up to 4K@30Hz
- USB-C® supports up to 4K@60Hz

### Chipset

### Chipset

Intel® SoC (System on Chip) platform

### **Memory**

## **Max Memory**

## IdeaPad Slim 3 14IRU8



- 4GB soldered memory, not upgradable
- 8GB soldered memory, not upgradable
- 16GB soldered memory, not upgradable

#### Memory Slots\*\*

- Memory soldered to systemboard, no slots, single-channel (4GB or 8GB models)
- Memory soldered to systemboard, no slots, dual-channel (16GB models)

#### **Memory Type**

LPDDR5-4800

### **Storage**

### Storage Support[1]

- 128GB UFS 3.1 on systemboard
- One drive, up to 1TB M.2 2242 SSD

#### **Storage Slot**

- UFS on systemboard, no slots (UFS models)
- One M.2 PCle® 4.0 x4 slot (M.2 SSD models)

#### Storage Type\*\*

Disk Type	Interface	Offering		
Flash Memory	UFS 3.1 <sup>[2]</sup>	128GB		
M.2 2242 SSD	PCIe® NVMe®, PCIe® 4.0 x4	256GB / 512GB / 1TB		

#### Notes:

- [1] The storage capacity supported is based on the test results with current Lenovo® storage offerings.
- [2] UFS 3.1 storage is downgraded to closer to UFS 2.1 due to platform limitations.

### **Removable Storage**

#### **Card Reader**

SD card reader

### Multi-Media

#### **Audio Chip**

High Definition (HD) Audio

## Speakers

User-facing stereo speakers, 1.5W x2, optimized with Dolby $^{\circ}$  Audio $^{\mathsf{TM}}$ 

### Microphone

Dual-microphone array

#### Camera\*\*

- FHD 1080p, with privacy shutter, fixed focus
- HD 720p, with privacy shutter, fixed focus

## **Battery**

#### **Battery**

Integrated Li-Polymer 47Wh battery, supports Rapid Charge Boost (get 2 hours of runtime with a 15-minute charge)

#### Max Battery Life[1]

MobileMark® 2018@200nits: 8.1 hr

Local video (1080p) playback@150nits: 12 hr

### Notes:

[1] All battery life claims are approximate maximum and based on results using the MobileMark® 2014, MobileMark® 2018, MobileMark® 25, JEITA 2.0, continuous 1080p video playback (with 150nits brightness and default volume level) or Google Power Load Test (PLT) battery-life benchmark tests. Actual battery life will vary depending on many factors such as product configuration and usage, software use, wireless functionality, power management settings, and screen brightness. The maximum capacity of the battery will decrease with time and use.

### **Power Adapter**



#### **Power Adapter**

65W round tip (3-pin) AC adapter, 100-240V, 50-60Hz

### **DESIGN**

## **Display**

#### Display\*\*

Size	Resolution	Touch	Туре	Brightness	Surface	Aspect Ratio	Contrast Ratio	Color Gamut	Viewing Angle (L/R/U/D)
14"	FHD (1920x1080)	None	TN	250nits	Anti- glare	16:9	400:1	45% NTSC	45°/45°/15°/35°
14"	FHD (1920x1080)	None	IPS <sup>[1]</sup>	300nits	Anti- glare	16:9	700:1	45% NTSC	85°/85°/85°

#### **Touchscreen**

Non-touch

Notes:

[1] IPS (in-plane switching) technology may refer to IPS, PLS, ADS, AHVA, AAS.

## **Input Device**

## Keyboard

6-row, multimedia Fn keys

### **Keyboard Backlight**

- · LED backlight
- · Non-backlight

## Touchpad

Buttonless Mylar® surface multi-touch touchpad, supports Precision TouchPad (PTP), 62 x 104 mm (2.44 x 4.09 inches)

### Mechanical

### Dimensions (WxDxH)[1]

324.3 x 213.8 x 17.9 mm (12.77 x 8.42 x 0.70 inches)

#### Weight<sup>[2]</sup>

Starting at 1.37 kg (3.02 lbs)

#### Case Color\*\*

- · Abyss blue
- · Arctic grey

#### **Surface Treatment**

IMR (in-mold decoration by roller)

#### **Case Material**

PC-ABS (top), PC-ABS (bottom)

#### Notes:

[1] The system dimensions may vary depending on configurations.

[2] The system weight is approximate and based on results in Lenovo® lab, which varies depending on the source of component, variance of the distribution of each component, and manufacturing process. It may not be the exact weight for each specific model.

### CONNECTIVITY

## **Network**

#### Ethernet

No onboard Ethernet



#### WLAN + Bluetooth®\*\*

- 802.11ac 2x2 Wi-Fi® + Bluetooth® 5.1, M.2 card
- Wi-Fi® 6, 802.11ax 2x2 Wi-Fi® + Bluetooth® 5.2, M.2 card[1]

#### Notes:

[1] Wi-Fi® 6 full features might be limited by country-level restrictions.

#### Ports<sup>[1]</sup>

#### **Standard Ports**

- 2x USB 3.2 Gen 1
- 1x USB-C® 3.2 Gen 1 (support data transfer, Power Delivery and DisplayPort™ 1.2)
- 1x HDMI® 1.4
- 1x Headphone / microphone combo jack (3.5mm)
- 1x Card reader
- 1x Power connector

#### Notes:

[1] The transfer speed of following ports will vary and, depending on many factors, such as the processing speed of the host device, file attributes and other factors related to system configuration and your operating environment, will be slower than theoretical speed.

USB 2.0: 480 Mbit/s;

USB 3.2 Gen 1 (SuperSpeed USB 5Gbps, formerly USB 3.0 / USB 3.1 Gen 1): 5 Gbit/s;

USB 3.2 Gen 2 (SuperSpeed USB 10Gbps, formerly USB 3.1 Gen 2): 10 Gbit/s;

USB4® 20Gbps / USB 3.2 Gen 2x2 (SuperSpeed USB 20Gbps): 20 Gbit/s;

USB4® 40Gbps (USB 40Gbps): 40 Gbit/s;

Thunderbolt™ 3/4: 40 Gbit/s.

### **Docking**

#### **Docking**

Various docking solutions supported via USB-C®.

For more compatible docking solutions, please visit Docking for IdeaPad® Slim 3 14IRU8

## **SECURITY & PRIVACY**

## **Security**

#### **Security Chip**

Firmware TPM 2.0 integrated in SoC

### Fingerprint Reader

- Touch style fingerprint reader integrated in power button
- No fingerprint reader

### **BIOS Security**

- · Administrator password
- · Power-on password
- Hard disk password (M.2 SSD models only)
- Self-healing BIOS

#### **Other Security**

Camera privacy shutter

#### **SERVICE**

### Warranty

## Base Warranty\*\*

- 1-year courier or carry-in service
- 1-year courier or carry-in with 2-year system board service (Korea only)
- 2-year (1-yr battery) courier or carry-in service
- 3-year (1-yr battery) courier or carry-in service



## **ENVIRONMENTAL**

## **Operating Environment**

#### Temperature[1]

- At altitudes up to 2438 m (8,000 ft)
  - Operating: 5°C to 35°C (41°F to 95°F)
  - Storage: 5°C to 43°C (41°F to 109°F)
- At altitudes above 2438 m (8,000 ft)
  - Maximum temperature when operating under the unpressurized condition: 31.3°C (88°F)

#### **Relative Humidity**

- Operating: 8% to 95% at wet-bulb temperature 23°C (73°F)
- Storage: 5% to 95% at wet-bulb temperature 27°C (81°F)

#### Altitudo

Maximum altitude (without pressurization): 3048 m (10,000 ft)

Notes:

[1] When you charge the battery, its temperature must be no lower than 10°C (50°F).

### **ACCESSORIES**

## **Bundled Accessories**

#### **Bundled Accessories**

- Lenovo® 15.6" laptop casual toploader, polyester, black
- None

## **CERTIFICATIONS**

### 

#### **Green Certifications**[2]

- ENERGY STAR® 8.0
- EPEAT™ Silver Registered<sup>[3]</sup>
- ErP Lot 6
- ErP Lot 26
- · RoHS compliant

#### Notes:

[1] The items listed under the "Green Certifications" section may not only refer to certification but also registration or self-declaration.

[2] EPEAT™ registration and ENERGY STAR® certification are dependent on system OS. Please visit epeat.net and energystar.gov for more information.

[3] EPEAT™ is registered where applicable, please see epeat.net for registration status by country.

### Other Certifications

#### Mil-Spec Test

MIL-STD-810H military test passed (21 test items)

#### **Other Certifications**

TÜV Rheinland® Low Blue Light (Software Solution)

- Feature with \*\* means that only one offering listed under the feature is configured on selected models.
- Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not
  responsible for photographic or typographical errors. LENOVO PROVIDES THIS PUBLICATION "AS IS,"
  WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES
  OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow

# IdeaPad Slim 3 14IRU8



disclaimer of express or implied warranties in certain transactions, therefore this disclaimer may not apply to you.

• The specifications on this page may not be available in all regions, and may be changed or updated without notice.



