

OVERVIEW



| 1. USB-C 3.2 Gen 1 | 5. microSD card reader |
|--|------------------------------|
| 2. HDMI | 6. USB 3.2 Gen 1 |
| 3. USB-C 3.2 Gen 1 | 7. USB 3.2 Gen 1 (Always On) |
| 4. Headphone / microphone combo jack (3.5mm) | |



PERFORMANCE

Processor

Processor Family

AMD Ryzen™ 3 / 5 / 7 Processor

Processor**

| Processor Name | Cores | Threads | Base Frequency | Max Frequency | Cache | Processor Graphics |
|--------------------|-------|---------|----------------|---------------|------------------|----------------------|
| AMD Ryzen™ 3 7330U | 4 | 8 | 2.3GHz | 4.3GHz | 2MB L2 / 8MB L3 | AMD Radeon™ Graphics |
| AMD Ryzen™ 5 7430U | 6 | 12 | 2.3GHz | 4.3GHz | 3MB L2 / 16MB L3 | AMD Radeon™ Graphics |
| AMD Ryzen™ 5 7530U | 6 | 12 | 2.0GHz | 4.5GHz | 3MB L2 / 16MB L3 | AMD Radeon™ Graphics |
| AMD Ryzen™ 7 7730U | 8 | 16 | 2.0GHz | 4.5GHz | 4MB L2 / 16MB L3 | AMD Radeon™ Graphics |

Operating System

Operating System**

- Windows® 11 Pro
- Windows® 11 Home
- Windows® 11 Home Single Language
- Windows® 11 Home Single Language in S mode
- Windows® 11 Home in S mode
- · No preload operating system

Graphics

Graphics

| | Graphics | Type | Memory | Key Features |
|----------------------|----------|------------|--------|--------------|
| AMD Radeon™ Graphics | | Integrated | Shared | DirectX® 12 |

Monitor Support

Monitor Support

Supports up to 3 independent displays (native display and 2 external monitors via HDMI® and USB-C®)

- HDMI® supports up to 1920x1080@60Hz
- USB-C® supports up to 3840x2160@60Hz

Chipset

Chipset

AMD SoC (System on Chip) platform

Memory

Max Memory

- 8GB soldered memory, not upgradable
- 16GB soldered memory, not upgradable

Memory Slots**

- Memory soldered to systemboard, no slots, single-channel (8GB models)
- Memory soldered to systemboard, no slots, dual-channel (16GB models)

Memory Type

DDR4-3200

Storage

Storage Support[1]

One drive, up to 1TB M.2 2242 SSD or 1TB M.2 2280 SSD

Storage Slot

One M.2 2280 PCIe® 3.0 x4 slot

Storage Type**[2]

| Disk Type | Interface | Offering |
|-----------|-----------|----------|
|-----------|-----------|----------|



| M.2 2242 SSD | PCle® NVMe®, PCle® 4.0 x4 | 256GB / 512GB / 1TB |
|--------------|---------------------------|---------------------|
| M.2 2280 SSD | PCle® NVMe®, PCle® 4.0 x4 | 1TB |

Notes:

- [1] The storage capacity supported is based on the test results with current Lenovo® storage offerings.
- [2] PCle® 4.0x4 is downgraded to be closer to PCle® 3.0x4 due to the system slot limitation.

Removable Storage

Card Reader

microSD card reader

Multi-Media

Audio Chip

High Definition (HD) Audio

Speakers

Stereo speakers, 2W x2, optimized with Dolby Audio™

Microphone

Dual-microphone array

Camera**

- FHD 1080p + IR, with privacy shutter, fixed focus, with ToF sensor
- FHD 1080p, with privacy shutter, fixed focus

Sensor

Sensors

- (Optional) Ambient light sensor (ALS)
- · (Optional) ToF sensor
- · Hall sensor

Battery

Battery**

- Integrated Li-Polymer 47Wh battery, supports Rapid Charge Boost (get 2 hours of runtime with a 15-minute charge)[1]
- Integrated Li-Polymer 56.6Wh battery, supports Rapid Charge Boost (get 2 hours of runtime with a 15-minute charge)[2]
- Integrated Li-Polymer 75.4Wh battery, supports Rapid Charge Boost (get 2 hours of runtime with a 15-minute charge)[3]

Max Battery Life^[4]

• Models with 47Wh battery:

MobileMark® 2018: 10 hr

Local video (1080p) playback@150nits: 13.5 hr

Models with 56.6Wh battery:

MobileMark® 2018: 11.5 hr

Local video (1080p) playback@150nits: 15.5 hr

Models with 75.4Wh battery:

MobileMark® 2018: 15 hr

Local video (1080p) playback@150nits: 19.5 hr

Notes:

[1], [2], [3] Rapid Charge Boost is only effective in hibernates or fully shutting down the computer.

[4] All battery life claims are approximate maximum and based on results using the MobileMark® 2014, MobileMark® 2018, MobileMark® 25, JEITA 2.0, continuous 1080p video playback (with 150nits brightness and default volume level) or Google Power Load Test (PLT) battery-life benchmark tests. Actual battery life will vary depending on many factors such as product configuration and usage, software use, wireless functionality, power management settings, and screen brightness. The maximum capacity of the battery will decrease with time and use.

Power Adapter

Power Adapter**[1]

- 65W USB-C® (3-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz
- 65W USB-C[®] slim (wall-mount) AC adapter, supports PD 3.0, 100-240V, 50-60Hz
- 100W USB-C® slim (3-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz



Notes:

[1] AC adapter offerings depend on the country.

DESIGN

Display

Display**[1]

| Size | Resolution | Touch | Туре | Brightness | Surface | Aspect Ratio | Contrast Ratio | Color Gamut | Refresh Rate | Viewing Angle (L/R/U/D) | Key Features |
|------|----------------------|-----------------|------|------------|----------------|-----------------|-------------------|----------------|-----------------|----------------------------|--|
| 16" | WUXGA (1920x1200) | None | IPS | 300nits | Anti- glare | 16:10 | 1000:1 | 45% NTSC | 60Hz | 85°/85°/85°/85° | TÜV Low Blue Light (Software) |
| 16" | WUXGA (1920x1200) | Multi- touch | IPS | 300nits | Anti- glare | 16:10 | 1000:1 | 45% NTSC | 60Hz | 85°/85°/85°/85° | TÜV Low Blue Light (Software) |
| 16" | 2.5K (2560x1600) | None | IPS | 350nits | Anti- glare | 16:10 | 1200:1 | 100% sRGB | 60Hz | 85°/85°/85°/85° | Dolby Vision®, TÜV Low Blue Light (Hardware) |

Touchscreen

- On-cell multi-touch, supports 10-point touch
- Non-touch

Notes:

[1] IPS (in-plane switching) technology may refer to IPS, PLS, ADS, AHVA, AAS.

Input Device

Keyboard

6-row, multimedia Fn keys, numeric keypad

Keyboard Backlight

- · LED backlight
- · Non-backlight

Touchpad

Buttonless Mylar® surface multi-touch touchpad, supports Precision TouchPad (PTP), 75 x 120 mm (2.95 x 4.72 inches)

Mechanical

Dimensions (WxDxH)[1]

| Models | Dimensions | | | |
|----------------|--|--|--|--|
| Metal models | 356 x 251 x 16.9 mm (14.02 x 9.88 x 0.67 inches) | | | |
| Plastic models | 356 x 251 x 17.9 mm (14.02 x 9.88 x 0.70 inches) | | | |

Weight^[2]

Starting at 1.89 kg (4.17 lbs)

Case Color**

- Abyss blue
- Cloud grey
- Violet

Surface Treatment

Aluminium stamping (anodized with sandblasting)

Case Material**

- Aluminium (top), PC-ABS (bottom)
- Aluminium (top), aluminium (bottom)



Notes:

[1] The system dimensions may vary depending on configurations.

[2] The system weight is approximate and based on results in Lenovo® lab, which varies depending on the source of component, variance of the distribution of each component, and manufacturing process. It may not be the exact weight for each specific model.

CONNECTIVITY

Network

Ethernet

No onboard Ethernet

WLAN + Bluetooth®**

- Wi-Fi® 6, 802.11ax 2x2 Wi-Fi® + Bluetooth® 5.2, M.2 card^[1]
- Wi-Fi® 6E, 802,11ax 2x2 Wi-Fi® + Bluetooth® 5.2, M.2 card[2]

Notes:

[1] Wi-Fi® 6 full features might be limited by country-level restrictions.

[2] Wi-Fi® 6E full features might be limited by country-level restrictions.

6GHz Wi-Fi® 6E operation is dependent on the support of the operating system, routers/APs/Gateways that support Wi-Fi® 6E, and the regional regulatory certifications & spectrum allocation.

Ports^[1]

Standard Ports

- 1x USB 3.2 Gen 1
- 1x USB 3.2 Gen 1 (Always On)
- 2x USB-C® 3.2 Gen 1 (support data transfer, Power Delivery 3.0 and DisplayPort™ 1.4)
- 1x HDMI® 1.4b
- 1x Headphone / microphone combo jack (3.5mm)
- 1x microSD card reader

Notes:

[1] The transfer speed of following ports will vary and, depending on many factors, such as the processing speed of the host device, file attributes and other factors related to system configuration and your operating environment, will be slower than theoretical speed.

USB 2.0: 480 Mbit/s;

USB 3.2 Gen 1 (SuperSpeed USB 5Gbps, formerly USB 3.0 / USB 3.1 Gen 1): 5 Gbit/s;

USB 3.2 Gen 2 (SuperSpeed USB 10Gbps, formerly USB 3.1 Gen 2): 10 Gbit/s;

USB4® 20Gbps / USB 3.2 Gen 2x2 (SuperSpeed USB 20Gbps): 20 Gbit/s;

USB4® 40Gbps (USB 40Gbps): 40 Gbit/s;

Thunderbolt™ 3/4: 40 Gbit/s.

Docking

Docking

Various docking solutions are supported via USB-C®.

For more compatible docking solutions, please visit <u>Docking for IdeaPad® Slim 5 16ABR8</u>

SECURITY & PRIVACY

Security

Security Chip

Firmware TPM 2.0 integrated in SoC

Fingerprint Reader

- · Touch style fingerprint reader on palm rest
- No fingerprint reader

BIOS Security

· Administrator password

IdeaPad Slim 5 16ABR8



- · Master hard disk password
- Self-healing BIOS
- User hard disk password
- User password

Other Security

- (Optional) IR camera for Windows® Hello (facial recognition)
- · Camera privacy shutter

SERVICE

Warranty

Base Warranty**

- 1-year courier or carry-in service
- 1-year courier or carry-in with 2-year system board service (Korea only)
- 2-year (1-yr battery) courier or carry-in service

ACCESSORIES

Bundled Accessories

Bundled Accessories[1]

None

Notes:

[1] For more compatible accessory solutions, please visit Accessories for IdeaPad® Slim 5 16ABR8.

OPERATING REQUIREMENTS

Operating Environment

Temperature[1]

- At altitudes up to 2438 m (8,000 ft)
 - Operating: 5°C to 35°C (41°F to 95°F)
 - Storage: 5°C to 43°C (41°F to 109°F)
- At altitudes above 2438 m (8,000 ft)
 - Maximum temperature when operating under the unpressurized condition: 31.3°C (88°F)

Relative Humidity

- Operating: 8% to 95% at wet-bulb temperature 23°C (73°F)
- Storage and transportation: 5% to 95% at wet-bulb temperature 27°C (81°F)

Altitude

Maximum altitude (without pressurization): 3048 m (10,000 ft)

Notes

[1] When you charge the battery, its temperature must be no lower than 10°C (50°F).

CERTIFICATIONS

Green Certifications¹¹

Green Certifications[2]

- ENERGY STAR® 8.0
- EPEAT™ Gold Registered^[3]
- ErP Lot 6
- ErP Lot 26
- RoHS compliant

Notes:

[1] The items listed under the "Green Certifications" section may not only refer to certification but also registration or self-

IdeaPad Slim 5 16ABR8



declaration. For ESG & regulatory compliance documents, please visit https://compliance.lenovo.com. [2] EPEAT™ registration and ENERGY STAR® certification are dependent on system OS. Please visit epeat.net and energystar.gov for more information.

[3] EPEAT™ is registered where applicable, please visit epeat.net for registration status by country.

Other Certifications

Mil-Spec Test

MIL-STD-810H military test passed (20 test items)

Other Certifications

- (Optional) TÜV Rheinland® Low Blue Light (Hardware Solution)
- (Optional) TÜV Rheinland® Low Blue Light (Software Solution)
- TÜV Rheinland® Flicker Free
- Feature with ** means that only one offering listed under the feature is configured on selected models.
- Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not
 responsible for photographic or typographical errors. LENOVO PROVIDES THIS PUBLICATION "AS IS,"
 WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES
 OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow
 disclaimer of express or implied warranties in certain transactions, therefore this disclaimer may not apply to
 you.
- The specifications on this page may not be available in all regions, and may be changed or updated without notice.













