

OVERVIEW



1. 2x USB 3.2 Gen 1	7. Microphone (3.5mm)
2. Headphone / microphone combo jack (3.5mm)	8. Ethernet (RJ-45)
3. Power button	9. Line-out (3.5mm)
4. USB-C 3.2 Gen 1	10. Line-in (3.5mm)
5. 2x USB 3.2 Gen 1	11. Optional ports on expansion cards
6. 2x USB 2.0	12. Power connector

PERFORMANCE

Processor

Processor Family

10th Generation Intel® Core™ i5 / i7 / i9 Processor

Processor**^[1]

Processor Name	Cores	Threads	Base Frequency	Max Frequency	Cache	Memory Support	Processor Graphics
Core i5-10400	6	12	2.9GHz	4.3GHz	12MB	DDR4-2666	Intel UHD Graphics 630
Core i5-10400F	6	12	2.9GHz	4.3GHz	12MB	DDR4-2666	-
Core i7-10700	8	16	2.9GHz	4.8GHz	16MB	DDR4-2933	Intel UHD Graphics 630
Core i7-10700F	8	16	2.9GHz	4.8GHz	16MB	DDR4-2933	-
Core i7-10700K	8	16	3.8GHz	5.1GHz	16MB	DDR4-2933	Intel UHD Graphics 630
Core i9-10900	10	20	2.8GHz	5.2GHz	20MB	DDR4-2933	Intel UHD Graphics 630
Core i9-10900F	10	20	2.8GHz	5.2GHz	20MB	DDR4-2933	-

Notes:

1. Intel UHD Graphics 630 in processor is disabled

Operating System

Operating System**

- Windows® 10 Home 64
- FreeDOS

Graphics

Graphics**^[1]

Graphics	Type	Memory	Connector	Max Resolution	Key Features
AMD Radeon™ RX 5500	Discrete	4GB GDDR6	1x HDMI® 2.0, 3x DP 1.4	4096x2160@60Hz(HDMI), 7680x4320@60Hz(DP)	DirectX® 12
NVIDIA® GeForce® GTX 1650 SUPER	Discrete	4GB GDDR6	1x HDMI 2.0b, 2x DP 1.4	7680x4320 @60Hz(DP)	DirectX 12
NVIDIA GeForce GTX 1660 SUPER	Discrete	6GB GDDR6	1x DVI, 1x HDMI 2.0b, 1x DP 1.4	7680x4320@60Hz(DP)	DirectX 12
NVIDIA GeForce RTX™ 2060 CD	Discrete	6GB GDDR6	1x HDMI 2.0b, 3x DP 1.4	4096x2160@60Hz(HDMI), 7680x4320@60Hz with DSC(DP)	DirectX 12
NVIDIA GeForce RTX 2070 CD	Discrete	8GB GDDR6	1x HDMI 2.0b, 3x DP 1.4	7680x4320@60Hz(DP)	DirectX 12 VR ready
NVIDIA GeForce RTX 2070 SUPER	Discrete	8GB GDDR6	1x HDMI 2.0b, 1x USB-C Gen 2, 3x DP 1.4	7680x4320@60Hz(DP)	DirectX 12 VR ready
NVIDIA GeForce RTX 3070	Discrete	8G GDDR6	3x DP 1.4a, 1x HDMI 2.1	7680x4320@60Hz(HDMI); 7680x4320@60Hz(DP)	DirectX 12

Notes:

1. The information of integrated graphics are not applicable for the models without integrated graphics (for the details, please refer to processor section)

Monitor Support

Monitor Support^[1]

Supports up to 4 independent displays via discrete graphics

Notes:

1. Ports may vary by the discrete graphics.

Chipset

Chipset

Intel B460 chipset

Memory

Max Memory^[1]

Up to 128GB DDR4-2933

Memory Slots

Four DDR4 UDIMM slots, dual-channel capable

Memory Type^{**[2]}

- DDR4-2933
- DDR4-3200, Armor

Memory Protection

Non-ECC

Notes:

1. The max memory is based on the test results with current Lenovo® memory offerings. The system may support more memory as the technology develops.
2. Installed memory is actually 2933MHz or 3200MHz, but may run at 2666MHz or 2933MHz depending on the memory support capability of processor

Storage

Storage Support^[1]

Up to two drives, 1x 3.5" HDD + 1x M.2 SSD

- 3.5" HDD up to 2TB
- M.2 SSD up to 1TB
- Optional Intel Optane™ Memory Integrated with SSD, M.2

Storage Type^{***}

Disk Type	Interface	RPM	Security
3.5" SATA HDD	SATA 6Gb/s	7.2K	-
M.2 2280 SSD	PCIe® NVMe®	-	-
Intel Optane Memory with Solid State Storage, M.2 2280	PCIe NVMe, PCIe 3.0 x4	-	-

RAID

No support

Notes:

1. The storage capacity supported is based on the test results with current Lenovo storage offerings. The system may support larger storage as the technology develops.

Removable Storage

Optical

- DVD burner (DVD±RW), SATA 1.5Gb/s, slim (9.0mm)
- None

Card Reader

No card reader

Multi-Media

Audio Chip

High Definition (HD) Audio, Realtek® ALC887 codec

Speakers

No speakers

Power Supply

Power Supply^{**}

Power	Type	Efficiency	Key Features
350W	Fixed	-	100-240V, 50-60Hz
400W	Fixed	-	100V - 240V
650W	Fixed	-	100V - 240V

DESIGN

Input Device

Keyboard**

- Lenovo Calliope Keyboard (USB connector), black
- Lenovo Keyboard (USB connector), black
- No keyboard

Mouse

- Lenovo Calliope Mouse (USB connector), black
- No mouse

Mechanical

Form Factor

Tower (28L)

Dimensions (WxDxH)

184.5 x 455.8 x 457 mm (7.26 x 17.94 x 17.99 inches)

Packaging Dimensions (WxDxH)

All models: 330 x 600 x 554 mm (13 x 23.6 x 21.8 inches)

Weight

14 kg (30.86 lbs)

Packaging Weight

All models: 16 kg (35.27 lbs)

Case Color

Phantom black

Chassis

Normal side cover

Bays

2x 3.5" disk bay

Expansion Slots

- One PCIe 3.0 x4
- One PCIe 3.0 x16
- Two PCIe 3.0 x1
- Three M.2 slots (one for WLAN, two for SSD)

Cooling System (Fan & Cooler)***

- (Optional) 1x front system fan, 1x rear system fan for airflow or liquid
- (Optional) 1x front system fan, 1x rear airflow system fan
- (Optional) 2x system fans, 1x airflow rear system fan
- (Optional) 65W Air-Cooler, 95W Air-Cooler, 150W Air-Cooler, or 150W Liquid-Cooler

System Lighting

Legion big-Y iconic LED

Others

(Optional) Carry handle

CONNECTIVITY

Network

Onboard Ethernet

Gigabit Ethernet, 1x RJ-45

WLAN + Bluetooth®^[1]**

- 802.11ac 2x2 Wi-Fi® + Bluetooth 5.0, M.2 card
- Wi-Fi 6, 802.11ax 2x2 Wi-Fi + Bluetooth 5.0, M.2 card
- No WLAN and Bluetooth

Notes:

1. Bluetooth 5.2 is hardware ready but may run at a lower version due to OS limitation

Ports^[1]**Front Ports**

None

Rear Ports^[2]

- 2x USB 2.0
- 2x USB 3.2 Gen 1
- 1x USB-C 3.2 Gen 1 (support data transfer and 5V@3A charging)
- 1x Ethernet (RJ-45)
- 1x line-in (3.5mm)
- 1x line-out (3.5mm)
- 1x microphone (3.5mm)
- 1x power connector

Top Ports

- 2x USB 3.2 Gen 1
- 1x headphone / microphone combo jack (3.5mm)

Notes:

1. The transfer speed of following ports will vary and, depending on many factors, such as the processing speed of the host device, file attributes and other factors related to system configuration and your operating environment, will be slower than theoretical speed.
USB 2.0: 480 Mbit/s;
USB 3.2 Gen 1 (SuperSpeed USB 5Gbps, formerly USB 3.0 / USB 3.1 Gen 1): 5 Gbit/s;
USB 3.2 Gen 2 (SuperSpeed USB 10Gbps, formerly USB 3.1 Gen 2): 10 Gbit/s;
USB 3.2 Gen 2x2 (SuperSpeed USB 20Gbps): 20 Gbit/s;
Thunderbolt™ 3/4: 40 Gbit/s;
FireWire 400: 400 Mbit/s;
FireWire 800: 800 Mbit/s
2. For video ports on discrete graphics, please see graphics section

SECURITY & PRIVACY**Security****Security Chip**

Firmware TPM 2.0 integrated in chipset

BIOS Security

- Administrator password
- Power-on password

SERVICE**Warranty****Base Warranty**^[1]**

- 1-year depot service
- 2-year depot service

Notes:

1. More information of warranty policy, please access <https://pcsupport.lenovo.com/warranty>

ENVIRONMENTAL

Operating Environment

Temperature

Storage: -40°C (-40°F) to 60°C (140°F)

Humidity

- Operating: 20% to 80%
- Storage: 10% to 90%

Altitude

- Operating: 0 m (0 ft) to 3048 m (10,000 ft)
- Storage: 0 m (0 ft) to 12192 m (40,000 ft)

CERTIFICATIONS

Green Certifications

Green Certifications

- ENERGY STAR® 8.0
- ErP Lot 3
- RoHS compliant

- Feature with ** means that only one offering listed under the feature is configured on selected models.
- Feature with *** means that one or more offerings listed under the feature could be configured on selected models.
- Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not responsible for photographic or typographical errors. LENOVO PROVIDES THIS PUBLICATION “AS IS,” WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow disclaimer of express or implied warranties in certain transactions, therefore this disclaimer may not apply to you.
- The specifications on this page may not be available in all regions, and may be changed or updated without notice.

