

OVERVIEW



1. Volume button	6. USB-C 3.1 Gen 1
2. Power button	7. USB 3.1 Gen 1
3. USB 3.1 Gen 1	8. MicroSD card reader *
4. USB-C 3.1 Gen 1	9. Headphone / microphone combo jack (3.5mm)
5. Kensington Security Slot	10. Pen slot

Notes:

- Ports with * are only available on selected models

PERFORMANCE

Processor

Processor Family

Intel® Celeron® Processor

Processor

Processor Name	Cores	Threads	Base Frequency	Max Frequency	Cache	Memory Support	Processor Graphics
Celeron N4100	4	4	1.1GHz	2.4GHz	4MB	LPDDR4-2400	Intel UHD Graphics 600
Celeron N4120	4	4	1.1GHz	2.6GHz	4MB	LPDDR4-2400	Intel UHD Graphics 600

Operating System

Operating System

Google Chrome OS

Graphics

Graphics

Graphics	Type	Memory	Key Features
Intel UHD Graphics 600	Integrated	Shared	DirectX® 12

Monitor Support

Monitor Support

Supports up to 2 independent displays via native display and 1 external monitor; supports external monitor via USB-C

Chipset

Chipset

Intel SoC (System on Chip) platform

Memory

Max Memory^[1]

- 4GB soldered memory, not upgradable
- 8GB soldered memory, not upgradable

Memory Slots

Memory soldered to systemboard, no slots

Memory Type

LPDDR4-2400

Notes:

1. The max memory is based on the test results with current Lenovo® memory offerings. The system may support more memory as the technology develops.

Storage

Storage Support

- 32GB eMMC 5.1 on systemboard
- 64GB eMMC 5.1 on systemboard

Storage Type

Disk Type	Interface	RPM	Security
Flash Memory	eMMC 5.1	-	-

Removable Storage

Optical

None

Card Reader

- MicroSD card reader
- No card reader

Multi-Media

Audio Chip

High Definition (HD) Audio, Maxim MAX98357A Dialog DA7219 codec

Speakers

Stereo speakers, 2W x2

Microphone

Single microphone

Camera

Front 720p, fixed focus; rear 5.0-megapixel, auto focus

Battery

Battery

Integrated Li-Polymer 42Wh battery

Max Battery Life^[1]

Google power load test: 10 hr

Notes:

1. All battery life claims are approximate maximum and based on results using the MobileMark® 2014, MobileMark 2018, and/or JEITA 2.0 battery-life benchmark tests. Actual battery life will vary and depends on many factors such as product configuration and usage, software use, wireless functionality, power management settings, and screen brightness. The maximum capacity of the battery will decrease with time and use.

Power Adapter

Power Adapter

- 45W USB-C (2-pin) AC adapter
- 45W USB-C (3-pin) AC adapter

DESIGN

Display

Display^[1]

Size	Resolution	Touch	Type	Brightness	Surface	Aspect Ratio
11.6"	HD (1366x768)	Multi-touch	IPS	250 nits	Glossy, anti-fingerprint	16:9

Touchscreen

Capacitive-type multi-touch, supports 10-point touch

Multi-mode

Laptop, tent, stand and tablet modes supported by 360° hinge

Notes:

1. California Electronic Waste Recycling Fee
In California, per state law, Lenovo charges an electronic waste recycling fee on this covered device at the time of sale of the product. For more information, go to <https://www.calrecycle.ca.gov/Electronics/Consumer>

Input Device

Pen

Lenovo 500e Chrome Pen, garaged, on-board rechargeable

Keyboard

6-row, spill-resistant, Anti-pry Key Caps

Keyboard Backlight

No support

Touchpad

One-piece multi-touch touchpad

Mechanical

Dimensions (WxDxH)

290 x 204 x 20.35 mm (11.42 x 8.03 x 0.8 inches)

Weight^[1]

1.31 kg (2.89 lbs)

Case Color

Black

Surface Treatment

Texture

Case Material

PC + ABS (top), PC + ABS (bottom)

Notes:

1. The system weight varies depending on configurations

CONNECTIVITY

Network

Onboard Ethernet

No Ethernet

WLAN + Bluetooth®

Intel Wireless-AC 9560, 802.11ac Dual Band 2x2 Wi-Fi® + Bluetooth 4.2, M.2 card

Ports^[1]

Standard Ports^[2]

- 2x USB 3.1 Gen 1
- 2x USB-C 3.1 Gen 1 (support data transfer, Power Delivery and DisplayPort™)
- 1x Headphone / microphone combo jack (3.5mm)

Optional Ports

1x microSD card reader

Notes:

1. The transfer speed of following ports will vary and, depending on many factors, such as the processing speed of the host device, file attributes and other factors related to system configuration and your operating environment, will be slower than theoretical speed.
USB 2.0: 480 Mbit/s;
USB 3.2 Gen 1 (SuperSpeed USB 5Gbps, formerly USB 3.0 / USB 3.1 Gen 1): 5 Gbit/s;
USB 3.2 Gen 2 (SuperSpeed USB 10Gbps, formerly USB 3.1 Gen 2): 10 Gbit/s;
USB 3.2 Gen 2x2 (SuperSpeed USB 20Gbps): 20 Gbit/s;
Thunderbolt™ 3: 40 Gbit/s;
FireWire 400: 400 Mbit/s;
FireWire 800: 800 Mbit/s
2. Depending on many factors, actual data transfer speed may be lower than theoretical speed

SECURITY & PRIVACY

Security

Security Chip

Google Security Chip H1

Physical Locks

Kensington® Security Slot

Fingerprint Reader

No fingerprint reader

BIOS Security

No support

SERVICE

Warranty

Base Warranty

- 1-year mail-in service
- 1-year depot service
- 1-year depot with 2-year system board service
- 2-year (1-yr battery) depot service

ENVIRONMENTAL

Operating Environment

Temperature^[1]

- Operating: 5°C (41°F) to 35°C (95°F)
- Storage: 5°C (41°F) to 43°C (109°F)

Humidity

- Operating: 8% to 95% at wet-bulb temperature 23°C (73°F)
- Storage: 5% to 95% at wet-bulb temperature 27°C (81°F)

Altitude

Maximum altitude (without pressurization): 3048 m (10,000 ft)

Notes:

1. When you charge the battery, its temperature must be no lower than 0°C (32°F)

CERTIFICATIONS

Green Certifications

Green Certifications

- EPEAT™ Silver
- TCO
- RoHS compliant

Other Certifications

Mil-Spec Test

MIL-STD-810G military test passed

