## Lenovo K450e Tower Platform Specifications

Processor	4th Generation I	ntel® Cor	e™ i3, i5, i7 processo	ors or Pe	ntium® processo	rs	Mechanical	<ul> <li>Mini Tower 25L (chassis), Metal Gray (metal brush effect)</li> <li>Dimensions (WxDxH): 9.4" x 23.2" x 21.9"; 240 mm x 590 mm x 555 mm</li> <li>Weights (net weight): from 24.6 lb (11.2 kg), vary by configuration</li> <li>Tool-free for cover, disk, optical drive removal</li> <li>Bay 1: 5.25", 1.6" high, access, optical</li> <li>Bay 2: 3.5", 1" high, no access, standard disk</li> </ul>	
	Processor  Core i5-4460  Core i7-4790	Cores / Threads 4 / 4 4 / 8	Frequency (Base/Max)	z 6 MB	Memory Types DDR3-1600 DDR3-1600	Integrated Graphics HD 4600 HD 4600			
			3.2 GHz / 3.4 GHz						
			3.6 GHz / 4 GHz						
Memory	32GB max, PC3-12800 1600MHz DDR3, four 240-pin DIMM sockets, supports dual channel							Bay 3: 3.5", 1" high, no access, optional disk Slot 1: half-length, full-height, PCle x16 (Version 3.0) Slot 2: half-length, full-height, PCle x1 (Version 2.0)* Slot 3: half-length, full-height, PCle x1 (Version 2.0) Slot 4: half-length, full-height, PCle x1 (Version 2.0) Slot 5: PCle Mini Card x1 (Version 2.0, for optional WLAN) * Some dual slot desgin graphics adapters may occupy adjacent PCle x1 slot	
Disk	Some: Hard Disk Drive, SATA 6.0Gb/s, 3.5" wide, 7200 rpm Some: Solid State Hybrid Drive (SSHD) with 8GB MLC NAND flash memory, SATA 6.0Gb/s, 3.5" wide, 7200 rpm								
Optical	Some: Super Multi-Burner, DVD disk recordable Some: Blu-ray™ burner, Blu-ray and DVD disk recordable SATA 6.0Gb/s controller (in chipset), four SATA connectors (SATA 6.0Gb/s), one eSATA connector (SATA 3.0Gb/s)								
Onboard SATA							Power supply	Some: 280 watts, manual switch, universal Some: 280 watts, EnergyStar 6.0, autosensing, universal Some: 450 watts, autosensing, universal	
Media reader	Optional 7-in-1 media reader (SD, SDHC, SDXC, MMC, MMC plus, MS, MS Pro)					, ,	_	Some: 450 watts, autoserising, universal	
Graphics	Intel HD Graphics or Intel HD Graphics 4400/4600 in processor, uses main memory, DirectX® 11, one VGA, one HDMI, supports two independent displays; Some: NVIDIA® Geforce® GT 720, 2GB DDR3, PCle 3.0 x16 adapter, DirectX 11, one VGA, one HDMI Some: NVIDIA Geforce GTX 750, 2GB GDDR5, PCle 3.0 x16 adapter, occupies two slots, DirectX 11, one DVI-I, one HDMI						Limited warranty	1-year, limited onsite service / service upgrades available	
							Preload	Preloaded operating system Windows® 8.1 64-bit Preloaded applications (only some listed)  • Lenovo® Rescue System  • Driver and Application Installation	
Chipset	Intel B85 Chipset								
Front ports Rear ports	output (3.5mm), rear surround (3.5mm), S/PDIF out					` '		<ul> <li>Lenovo Support</li> <li>Lenovo Solution Center</li> <li>Lenovo Companion</li> <li>McAfee® LiveSafe™ (30 days of virus definitions)</li> <li>Adobe® Reader®</li> <li>Microsoft Office preloaded; purchase a product key to activate</li> </ul>	
·						frequency			
IEEE 1394	None `							Cyberlink PowerDVD (DVD±RW)	
Audio support	High Definition (HD) Audio, Realtek ALC892, supports 7.1 surround sound					und		Cyberlink Power2Go (DVD±RW)     Nitro Pro  RoHS-compliant	
WLAN	Some: 11/b/g/n wireless, PCIe Half Mini Card, 1x1 Some: 11ac wireless, PCIe Half Mini Card, Wi-Fi + Bluetooth 4.0 combo, 1x1 Some: Bluetooth 4.0 wireless, integrated in Wi-Fi + Bluetooth combo adapter One gigabit ethernet port, Realtek RTL8111F-VB None  • Power-on password • Administrator password  Full-size keyboard (USB connector), Fn keys, black Lenovo Optical Mouse (USB connector)					o 1v1	Environment		
Bluetooth™ Ethernet Modem									
Security features									
Keyboard Mouse									

See footnotes for more detailed information

© Lenovo (K450e-Spec) March 2015