

OVERVIEW



1. Kensington Security Slot	8. USB-C 3.2 Gen 1 (15W)
2. Power connector	9. Ethernet (2.5GbE RJ-45)
3. HDMI 2.1 TMDS	10. USB 3.2 Gen 1
4. HDMI 2.1 TMDS	11. USB 3.2 Gen 1
5. DP 1.4	12. Audio-out (3.5mm)
6. USB-C 3.2 Gen 1 (DP 1.4 Alt Mode)	13. USB 3.2 Gen 1
7. USB-B 3.2 Gen 1	14. USB 3.2 Gen 1



PERFORMANCE

Panel

Panel

- · Mini-LED Backlight with 384 zones local dimming
- Vertical Alignment (VA)

Backlight

Mini-LED

Display Size

34 inches

Max View Area

WxH: 792.2 x 333.7 mm

Resolution

3440 x 1440

Aspect Ratio

21:9

Pixel Pitch

0.077 x 0.232 mm

Dot / Pixel Per Inch

110 dpi

Brightness

- Peak: 1200 cd/m²
- Typical: 720 cd/m²

Contrast Ratio

- Contrast Ratio: 3000:1
- Dynamic Contrast Ratio: 3M™:1

View Angle (H / V)

Horizontal: 178°, Vertical: 178°

Response Time

- G to G: 11 ms
- Level 1: 8 ms
- Level 2: 6 ms
- Level 3: 4 ms
- Level 4: 2 ms
- Moving Picture Response Time (MPRT): 1 ms

Refresh Rate

165Hz (Overclock to 180Hz)

Overclocking at 180Hz is based on laboratory test data, and this function may cause irregularities in the display

Color Gamut

- Color Area Ratio: 104% DCI-P3 (CIE 1976)
- Color Area Ratio: 131% sRGB (CIE 1931, CIE 1976)
- Coverage Ratio: 95% DCI-P3 (CIE 1976)
- Coverage Ratio: 99% sRGB (CIE 1931, CIE 1976)

Color Support

1.07 Billion

Color Depth

10-bit (8-bit+FRC)

Screen Surface Treatment

Anti-glare

Curvature

1500R

Operating System



Operating System

- Windows® 11 Support
- Windows® 10 Support

Multi-Media

Camera

Optional Modular Camera Support

Microphone

No microphone

Speakers

Integrated Speakers, 2x 5W

Power Supply

Power Consumption

- Typical / Max: 55W / 330W
- Sleep / Off mode: <0.5W
- Switch-off Mode: <0.3W
- Energy Star Power On: 53W
- · Energy Star TEC: 78kWh
- Internal Power Supply

Voltage Required

AC 100 to 240 V (50-60Hz)

Special Features

Special Features

- · RGB Ambience Light
- Factory Calibration: Avg. Delta E<2
- Brightness Calibration
- ClearMR 7000
- Picture In Picture (PIP) / Picture By Picture (PBP) Support
- DisplayHDR™ 1000
- True Split
- · Gaming Console Support
- KVM Switch
- Natural Low Blue Light
- VESA Adaptive Sync
- AMD FreeSync™ Premium Pro

AMD FreeSync™ technology only can work with AMD Radeon™ series graphics card.

Smart Sense

Auto Ambient Brightness Sensor

Lenovo® Artery (Lenovo® Accessories and Display Manager) Support
 Lenovo® Artery supports Windows® 10 & 11, Mac OS, and Windows® On Arm (functions vary across systems).
 Lenovo® Accessories and Display Manager is formerly Lenovo® Display Control Center.

DESIGN

Mechanical

ThinkCentre® M Series Support

None

Bezel Width

- Side: 2.0mm
- Top / Bottom: 2.0mm / 23.9mm

Cable Management

Support

Case Color

Raven black

Dimensions (WxDxH)[1]



Models	Dimensions
Lowest Position	807.2 x 320.1 x 406.3 mm (31.78 x 12.6 x 16.00 inches)
Highest Position	807.2 x 320.1 x 541.3 mm (31.78 x 12.6 x 21.31 inches)
Head Only	807.2 x 124.6 x 367.8 mm (31.78 x 4.91 x 14.48 inches)

Packaging Dimensions (WxDxH)

1070 x 225 x 525 mm (42.13 x 8.86 x 20.67 inches)

Weight^[2]

Models	Weight
Monitor With Stand	10.5 kg (23.1 lbs)
Monitor Head Only	8.2 kg (18.1 lbs)

Packaging Weight

16.6 kg (36.66 lbs)

Mounting

Supports VESA mount 100mm

Stand

Supports -5° to +22° tilt, left & right 30 swivel, up to 135mm lift

In the Box

- · Monitor with Stand
- 1x DP Cable (1.8m)
- 1x USB-B to USB-A Cable (1.8m)
- 1x USB-C® to USB-C® Cable (1m)
- 1x Power cable (1.8m)
- Factory Calibration Report
- · Quick Setup Guide

Notes:

[1] The system dimensions may vary depending on configurations.

[2] The system weight is approximate and based on results in Lenovo® lab, which varies depending on the source of component, variance of the distribution of each component, and manufacturing process. It may not be the exact weight for each specific model.

CONNECTIVITY

Network

Ethernet

Support 10M / 100M / 1000M / 2500M

Ports^[1]

Rear Ports

- 1x USB-C® 3.2 Gen 1 (15W), USB downstream
- 1x USB-C® 3.2 Gen 1 (DP 1.4 32.4 Gbps for 4 lanes Alt Mode and up to 140W PD), USB upstream
- 1x USB-B 3.2 Gen 1, USB upstream
- 2x USB 3.2 Gen 1, USB downstream
- 2x HDMI® 2.1 TMDS[2]
- 1x DisplayPort™ 1.4
- 1x Ethernet (RJ-45)

Right Ports

- 2x USB 3.2 Gen 1, USB downstream
- 1x audio-out (3.5mm)

Notes:

[1] The transfer speed of following ports will vary and, depending on many factors, such as the processing speed of the host device, file attributes and other factors related to system configuration and your operating environment, will be slower than theoretical speed.



USB 2.0: 480 Mbit/s;

USB 3.2 Gen 1 (SuperSpeed USB 5Gbps, formerly USB 3.0 / USB 3.1 Gen 1): 5 Gbit/s;

USB 3.2 Gen 2 (SuperSpeed USB 10Gbps, formerly USB 3.1 Gen 2): 10 Gbit/s;

USB4® 20Gbps / USB 3.2 Gen 2x2 (SuperSpeed USB 20Gbps): 20 Gbit/s;

USB4® 40Gbps (USB 40Gbps): 40 Gbit/s;

Thunderbolt™ 3/4: 40 Gbit/s.

[2] Supports 3440x1440@165Hz as specified in HDMI® 2.1

SECURITY & PRIVACY

Security

Physical Locks

Kensington® Security Slot™

SERVICE

Warranty

Base Warranty

3-year limited warranty

CERTIFICATIONS

Green Certifications¹¹

Green Certifications

- EU Energy Label (G-class)
- · RoHS compliant

Notes:

[1] The items listed under the "Green Certifications" section may not only refer to certification but also registration or self-declaration. For ESG & regulatory compliance documents, please visit https://compliance.lenovo.com.

Other Certifications

Other Certifications

- Eyesafe® Certified 2.0
- TÜV Rheinland® Eye Comfort Certification
- TÜV Rheinland® Low Blue Light (Hardware Solution)
- Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not
 responsible for photographic or typographical errors. LENOVO PROVIDES THIS PUBLICATION "AS IS,"
 WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES
 OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow
 disclaimer of express or implied warranties in certain transactions, therefore this disclaimer may not apply to
 you.
- The specifications on this page may not be available in all regions, and may be changed or updated without notice.













