ThinkCentre M715 SFF Platform Specifications

						T		
Processor	AMD A6 / A8 / A10 / A1	2 series AP		,	processor	Security features	Security slot (in rear for optional Power-on password	
	APU / processor	Cores / Threads	Frequency (Base/Max)	L2 / L3 Cache	Integrated Graphics		Kensington® MicroSaver® cable) • Padlock loop • Capart LISP protection clleve keyboard.	
	Ryzen 3 PRO 1200	4/4	3.1 / 3.4	2MB / 8MB	None		 Smart USB protection, allows keyboard/ Boot sequence control Boot without keyboard and mouse 	
	Ryzen 3 PRO 1300	4/4	3.5 / 3.7	2MB / 8MB	None		Optional cable lock to physically lock Individual USB port disablement	
	Ryzen 5 PRO 1500	4/8	3.5 / 3.7	2MB / 16MB	None		both keyboard and mouse • Optional chassis intrusion switch	
	Ryzen 7 PRO 1700	8 / 16	3.0 / 3.7	4MB / 16MB	None	Keyboard	Some: Lenovo Calliope Keyboard (USB connector), black	
	PRO A6-8570	2/2	3.5 / 3.8	1MB / -	Radeon R5 Series		Some: Lenovo Traditional Keyboard (USB connector), black	
	PRO A10-8770	4/4	3.5 / 3.8	2MB / -	Radeon R7 Series	Mouse	Some: Lenovo Calliope Wireless Keyboard (2.4GHz via USB receiver), black	
	PRO A12-8870	4/4	3.7 / 4.2	2MB / -	Radeon R7 Series	Mouse	Some: Lenovo Calliope Mouse (USB connector), black Some: Lenovo Calliope Wireless Mouse (2.4GHz via USB receiver), black	
	PRO A6-9500	2/2	3.5 / 3.8	1MB / -	Radeon R5 Series		Some: Lenovo Fingerprint Mouse (USB connector), Windows Hello support, black	
	PRO A8-9600	4 / 4	3.1 / 3.4	2MB / -	Radeon R7 Series	Mechanical	SFF (8.4L), black color; metal case	
	PRO A10-9700	4 / 4	3.5 / 3.8	2MB / -	Radeon R7 Series	IVIECHANICAI	• (WxDxH) 3.6" X 11.4" X 13.5"; 92.5mm X 290.5mm X 343.5mm	
	PRO A12-9800	4 / 4	3.8 / 4.2	2MB / -	Radeon R7 Series		 Approx. 13.2 lb (6.0 kg), weight may vary by configuration 	
Memory	64GB max, UDIMM, DDR4-2400, four 288-pin DIMM sockets, non-ECC, dual-channel capable* * System automatically clocks down for the processors with lower memory controller					Bay 2: 3.5 , hiefflat, hDD/SSD (bay only comes with 2.5" 2nd disk) Bay 3: 2.5", internal, HDD/SSD (bay only comes with 2.5" 2nd disk) Slot 1: low-profile (length < 150mm, height < 68mm), PCle 3.0 x16* Slot 2: low-profile (length < 150mm, height < 68mm), PCle 2.0 x1* Slot 3: low-profile (length < 150mm, height < 68mm), PCle 2.0 x1* Slot 4: no slot, only bracket for optional port extension* M.2 card slots: two (one for WLAN, one for SSD) * Optional front USB3.1 Type-C x2 module occupies PCle x16 slot (x4 card),		
Storage	Some: Hard Drive / SATA 6.0Gb/s, 2.5" or 3.5", 5400 rpm or 7200 rpm Some: Solid State Drive (SSD) / SATA 6.0Gb/s, 2.5" Some: M.2 Solid State Drive (SSD) / PCIe NVMe, PCIe 3.0 x 4, 32Gb/s Some: DVD-ROM SATA 1.5Gb/s Drive, slim (9.0mm) Some: DVD Burner (DVD±RW), SATA 1.5Gb/s Drive, slim (9.0mm) Three onboard SATA 6.0Gb/s connectors Optional 7-in-1 media reader						Bay 3: 2.5", internal, HDD/SSD (bay only comes with 2.5" 2nd disk) Slot 1: low-profile (length < 150mm, height < 68mm), PCle 3.0 x16* Slot 2: low-profile (length < 150mm, height < 68mm), PCle 2.0 x1* Slot 3: low-profile (length < 150mm, height < 68mm), PCle 2.0 x1* Slot 4: no slot, only bracket for optional port extension* M.2 card slots: two (one for WLAN, one for SSD) * Optional front USB3 1 Type-C x2 module occupies PCle x16 slot (x4 card).	
Optical								
Onboard SATA Media reader								
Graphics	AMD Radeon™ Graphics in processor (not for AMD Ryzen processor), uses main memory, DirectX® 12, one VGA, two DisplayPort™ (Onboard VGA and DP ports are invalid on the models with AMD Ryzen processor), supports 3 independent displays, works along with AMD discrete graphics to support more displays; Max resolution: 4096x2160 (DP)@60Hz; 1920x1200 (VGA)@60Hz Some: NVIDIA Geforce® GT 730, DirectX 12, 2GB, PCle 2.0 x8 adapter, two DisplayPort, 35 watts; Max resolution: 3840x2160 (DisplayPort)@60Hz;				ocessor), uses main	Floor Stand	Floor Stand Optional system floor stand for vertical orientation	
					s 3 independent ore displays; OHz	Power supply	Some: 180 watts, autosensing, 85% PSU Some: 210 watts, autosensing, 85% PSU Some: 210 watts, autosensing, 92% PSU (only available via special bid)	
					•	Limited warranty	Some: 1-year or 3-year, depot service / service upgrades available Some: 1-year or 3-year, limited onsite service / service upgrades available	
Monitor cable	Optional DP to VGA, DP to DVI-D (single link), DP to dual DP, or DP to HDMI 1.4						Preloaded operating system	
Chipset	AMD B350 Chipset						Some: Windows® 7 Professional 32/64 preinstalled through downgrade rights in Windows 10 Pro 64-bit (Only available with Pro A6/A10/A12-8xxx APUs) Some: Windows 10 Home 64-bit Preloaded applications (only some listed)	
Front ports*	Two USB 3.1 Gen2, two USB 3.1 Gen1, optional two USB 3.1 Type-C Gen 2 (only available via special bid), microphone (3.5mm), headphone (3.5mm) Two USB 3.1 Gen1, two USB 2.0, optional two USB 2.0, serial (9-pin), optional							
Rear ports*								
	2nd serial (9-pin), optional parallel (25-pin), ethernet (RJ-45), one VGA and two DisplayPort (not available on models with AMD Ryzen processor), two PS/2 ports				ne VGA and two or), two PS/2 ports		Microsoft Office preloaded;	
	(keyboard / mouse);				.,, two ! 6/2 porto		purchase a product key to activate - Only for Window 10	
	àdditional DisplayPort	t on optional graphics on some models					Lenovo Companion	
Rear audio ports	* Line-in (3.5mm), line-out (3.5mm), microphone-in (3.5mm)						- Only for Window 7	
IEEE 1394*	None * Depending on many factor	ors. actual data	a transfer speed	nav be lower th	nan theoretical speed		 Lenovo Solution Center Lenovo ThinkVantage Tools 	
Audio support	High Definition (HD) Audio, Realtek ALC662 / optional internal speaker (1 watt)					1	Create Recovery Media Adobe® Reader® Cyberlink PowerDVD Create (DVD±RW)	
WLAN	Some: 11ac wireless, M.2 Card, Realtek RTL8821AE (dual band),					1		
	Wi-Fi + Bluetooth 4.0 combo adapter, 1x1 Some: 11ac wireless, M.2 Card, Qualcomm Atheros QCA6174A (dual band), Wi-Fi + Bluetooth 4.1 combo adapter, 2x2				A (dual band),	Environment	ENERGY STAR® 6.1, EPEAT™ Gold rating (North America), ErP Lot 3, GREENGUARD®, RoHS-compliant	
	Some: 11ac wireless, M.2 Card, Qualcomm Atheros QCA9377 (dual band), Wi-Fi + Bluetooth 4.1 combo adapter, 1x1				, , ,	Accessories	For compatible accessories, please go to http://www.lenovoquickpick.com	
Bluetooth™ Ethernet Modem	Some: Bluetooth 4.0 or 4.1 wireless, integrated in Wi-Fi + BT combo adapter Gigabit ethernet, Realtek RTL8111EPV, Wake on LAN® None							
Manageability Security chip	DASH TPM (Trusted Platform Module) 2.0, TCG Certified * Downgrade to TPM1.2 for the models with Win10 DG Win7 32 OS							