ThinkCentre M910x Tiny Platform Specifications

Processor	Intel® Celeron®. In	tel Pentiur	n®. or 6/7th Gene	eration In	tel Core™ i3 / i5 /	' i7 Processor	Ethernet	Gigabit	ethernet. Inte	el Ethernet Connection I219-LM(Jac	ksonville). Wake on LAN®	
	Intel® Celeron®, Intel Pentium®, or 6/7th Generation Intel Core™ i3 / i5 / i7 Processor Cores / Frequency Cooks Memory Support Integrated						Manageability		Intel Active Management Technology 11.0 (Intel AMT 11.0);			
	Processor Core i5-6500T		Base/Max(GHz) 2.5G / 3.1G	Cache 6 MB	(Up to) DDR4-2133	Graphics HD 530	Wanageabiiity	Intel vPro technology on some models (require choosing a vPro-support Wi-Fi adapter to enable vPro function through wireless connection) TPM (Trusted Platform Module) 2.0*, TCG Certified * Downgrade to TPM1.2 for the models with Win10 DG Win7 32 OS			support Wi-Fi	
	Core i7-6700T	4/4	2.8G / 3.6G	8 MB	DDR4-2133	HD 530	Security chip					
	Core i5-7500T	4/4	2.7G / 3.3G	6 MB	DDR4-2100	HD 630						
	Core i5-7600T	4/4	2.8G / 3.7G	6 MB	DDR4-2400	HD 630	Security features	• Secu	 Security slot (in rear for optional Kensington® MicroSaver® cable) Smart USB protection, allows keyboard/ Hard disk password Boot sequence control Boot without keyboard and mountered and mountered are sequenced. 			
	Core i7-7700T	4/8	2.9G / 3.8G	8 MB	DDR4-2400	HD 630						
	Core i5-6500	4/4	3.2G / 3.6G	6 MB	DDR4-2133	HD 530		mouse only, blocks all storage devices • Individual USB port disablement				
	Core i7-6700	4/8	3.4G / 4.0G	8 MB	DDR4-2133	HD 530			 Power-on password Chassis intrusion switch 			
	Core i5-7500	4/4	3.4G / 3.8G	6 MB	DDR4-2400	HD 630		Administrator password				
	Core i5-7600	4/4	3.5G / 4.1G	6 MB	DDR4-2400	HD 630	Keyboard	Some:	Some: Lenovo Calliope Keyboard (USB connector), black Some: Lenovo Traditional Keyboard (USB connector), black Some: Lenovo Calliope Wireless Keyboard (2.4GHz via USB receiver), black Some: Lenovo Calliope Mouse (USB connector), black			
	Core i7-7700	4/8	3.6G / 4.2G	8 MB	DDR4-2400	HD 630						
Memory	32GB max DDB4	-2400* tv	n 260-pin SO-DI	MM sock	ets non-FCC		Mouse					
Wichiory	32GB max, DDR4-2400*, two 260-pin SO-DIMM sockets, non-ECC, dual-channel capable							Some: Lenovo Calliope Wireless Mouse (2.4GHz via USB receiver), black				
	* System automatically clocks down for the processors with lower memory controller						Mechanical	Tiny (1L), black color; metal case				
Storage	Some: Hard Drive* / SATA 6.0Gb/s, 2.5", 5400 rpm or 7200 rpm, APS Some: Solid State Drive (SSD)* / SATA 6.0Gb/s, 2.5" (* 2.5" HDD/SSD and RX 460 graphics are mutually exclusive) Some: M.2 SSD (support up to two M.2 SSD) / PCle NVMe, PCle 3.0 x 4, 32Gb/s, RAID 0/1 support (RAID preset only available via special bid model)							 Toolless chassis open Toolless HDD, SSD, memory removal Optional toolless chassis screw Optional dust filter 				
.	Some: Intel Optai	ne™ Mem	ory (models with	7th gen	Core processor),	M.2				Dimensions (WxDxH)	Weight (Approx.)	
Optical	Some: DVD Burn	Some: DVD-ROM, slim (9.0mm), via USB external ODD box Some: DVD Burner (DVD±RW), slim (9.0mm), via USB external ODD box					M910 I	iny only	7.05" X 7.20" X 1.36" 179mm X 182.9mm X 34.5mm	2.91 lb (1.32 kg), vary by config		
Onboard SATA Media reader	One onboard SATA 6.0Gb/s connector None							With VI ODD b	ESA mount & ox	7.42" X 7.30" X 2.48" 188.4mm X 185.38mm X 63mm	3.66 lb (1.66 kg), vary by config	
Graphics	Intel HD Graphics 510/530/610/630 in processor, uses main memory, DirectX [®] 12, two DisplayPort™, one optional video port (HDMI, VGA, 3rd DP, or USB 3.1 Type-C								ESA mount &		3.66 lb (1.66 kg),	
	with DisplayPort A	with DisplayPort Alternate Mode), up to 3 independent displays;						I/O box 188.4mm X 185.38mm X 66.6mm vary by config				
	Max resolution: 4096x2304 (DP)@60Hz; 4096x2304 (Type-C)@60Hz; 4096x2160 (HDMI)@24Hz; 1920x1200 (VGA)@60Hz						VESA mount Floor Stand	Optional VESA mount bracket kit, supports VESA 75mm and 100mm Optional system floor stand for vertical orientation				
	Some: AMD Radeon™ RX 460, DirectX 12, 4GB, PCle 3.0 x8 adapter (low profile), four mini DisplayPort, 35 watts (TDP), up to 4 independent displays, works along with 2 onboard DisplayPort to support up to 6 independent displays;					Power supply	135 watts AC/DC adapter, autosensing, 88% PSU					
						Limited warranty	imited warranty ³ Some: 1-year or 3-year, depot service / service upgrades available					
	Max resolution: 5120x2880 @60Hz (up to 2 mini DisplayPort);							Some: 1-year or 3-year, limited onsite service / service upgrades available				
Monitor cable	Optional DP to VGA, DP to DVI-D, DP to dual DP, mini DP to DP, or DP to HDMI 1.4						Preload	Some: Windows® 7 Professional 32/64 preinstalled through downgrade rights in Windows 10 Pro 64-bit (not available with 7th Gen Intel processor) Some: Windows 10 Pro 64-bit Some: Windows 10 Home 64-bit Preloaded applications (only some listed) Microsoft Office preloaded; purchase a product key to activate - Only for Window 10 Lenovo Companion Intel Unite download link				
Chipset	Intel Q270 Chipset]					
Front ports*	Two USB 3.1 Gen1 (one is Always On and fast charge), one microphone (3.5mm),						1					
	one headphone / microphone combo jack (3.5mm)											
Rear ports*	Four USB 3.1 Gen1 (optional optical box or I/O box occupies one or two specific USB 3.1 Gen1), ethernet (RJ-45), two DisplayPort, two optional ports (not available											
	for the models with	n BX 460	oranhics): Port 1	for IVGA	/ 3rd DP / HDMI	/ serial /				(vPro models	s only)	
	for the models with RX 460 graphics): Port 1 for [VGA / 3rd DP / HDMI / serial / USB 3.1 Type-C Gen 1 (with DisplayPort Alternate Mode)]; Port 2 for [serial]							- Only for Window 7				
I/O box*	Optional external I/O box, extends two USB 2.0, two USB 3.1 Gen1, and one serial on rear, two USB 2.0 on front, via USB cable (occupy 2 specific USB 3.1 G1 of Tiny) * Depending on many factors, actual data transfer speed may be lower than theoretical speed							 Leńovo Solution Center Lenovo ThinkVantage Tools 				
								Create Recovery Media				
Audio cupport		· ·		, ,			-			 Adobe[®] Rea 	der [®]	
Audio support	High Definition (HD) Audio, Realtek ALC294 / optional internal speaker (1w or 2w)						-	 Cyberlink PowerDVD Create (DVD±RW) Intel Unite (vPro models only) 				
WLAN ¹³	Some: 11ac wireless, M.2 Card, Qualcomm Atheros QCA9377A (dual band), Wi-Fi + Bluetooth 4.2 combo adapter, 1x1											
	Some: 11ac wireless, M.2 Card, Qualcomm Atheros QCA6174A (dual band),						ENERGY STAR® 6.1, EPEAT™ Gold rating (North America),					
	Wi-Fi + Bluetooth 4.2 combo adapter, 2x2 Some: 11ac wireless, M.2 Card, Intel Dual Band Wireless-AC 3165,					ErP Lot 3, GREENGUARD®, RoHS-compliant, TUV low noise verified (on some models)						
		Wi-Fi + Bluetooth 4.2 combo adapter, 1x1					MIL-SPEC test	MIL-STD-810G military certification (Low Pressure [Altitude], High Temperature,				
	Some: 11ac wireless, M.2 Card, Intel Dual Band Wireless-AC 8265, Wi-Fi + Bluetooth 4.2 combo adapter, 2x2 Some: 11ac wireless, M.2 Card, Intel Dual Band Wireless-AC 8265,						01 20 1031	Low Temperature, Temperature Shock, Humidity, Sand and Dust, Vibration, Shock,				
								Fungus, Solar Radiation)				
Divista sti Tu	Wi-Fi + Bluetooth 4.2 combo adapter, Intel vPro technology support, 2x2 Some: Bluetooth 4.2 wireless, integrated in Wi-Fi + BT combo adapter						Accessories	For compatible accessories, please go to http://www.lenovoquickpick.com				
Bluetooth™	* Hardware suppo											
	riaiuwaie suppo	113 11 4.2	, but will to moo	unu tall	ici oriiy supports	D1 4.1						