

ThinkCentre M920x Tiny Platform Specifications

Product Specifications Reference (PSREF)

Processor		Intel® Celeron®, Intel Pentium®, or 8th / 9th Gen Intel Core™ i3 / i5 / i7 / i9 Processor					
Processor	Cores / Threads	Frequency Base/Max(GHz)	Cache	Memory Support (Up to)	Integrated Graphics		
Celeron G4900	2 / 2	3.1G	2 MB	DDR4-2400	UHD 610		
Celeron G4920	2 / 2	3.2G	2 MB	DDR4-2400	UHD 610		
Celeron G4930	2 / 2	3.2G	2 MB	DDR4-2400	UHD 610		
Celeron G4950	2 / 2	3.3G	2 MB	DDR4-2400	UHD 610		
Pentium Gold G5400	2 / 4	3.7G	4 MB	DDR4-2400	UHD 610		
Pentium Gold G5500	2 / 4	3.8G	4 MB	DDR4-2400	UHD 630		
Pentium Gold G5600	2 / 4	3.9G	4 MB	DDR4-2400	UHD 630		
Pentium Gold G5420	2 / 4	3.8G	4 MB	DDR4-2400	UHD 610		
Pentium Gold G5620	2 / 4	4.0G	4 MB	DDR4-2400	UHD 630		
Core i3-8100	4 / 4	3.6G	6 MB	DDR4-2400	UHD 630		
Core i3-8300	4 / 4	3.7G	8 MB	DDR4-2400	UHD 630		
Core i5-8400	6 / 6	2.8G / 4.0G	9 MB	DDR4-2666	UHD 630		
Core i5-8500	6 / 6	3.0G / 4.1G	9 MB	DDR4-2666	UHD 630		
Core i5-8600	6 / 6	3.1G / 4.3G	9 MB	DDR4-2666	UHD 630		
Core i7-8700	6 / 12	3.2G / 4.6G	12 MB	DDR4-2666	UHD 630		
Core i3-9100	4 / 4	3.6G / 4.2G	6 MB	DDR4-2400	UHD 630		
Core i3-9300	4 / 4	3.7G / 4.3G	8 MB	DDR4-2400	UHD 630		
Core i3-9320	4 / 4	3.7G / 4.4G	8 MB	DDR4-2400	UHD 630		
Core i5-9400	6 / 6	2.9G / 4.1G	9 MB	DDR4-2666	UHD 630		
Core i5-9500	6 / 6	3.0G / 4.4G	9 MB	DDR4-2666	UHD 630		
Core i5-9600	6 / 6	3.1G / 4.6G	9 MB	DDR4-2666	UHD 630		
Celeron G4900T	2 / 2	2.9G	2 MB	DDR4-2400	UHD 610		
Celeron G4930T	2 / 2	3.0G	2 MB	DDR4-2400	UHD 610		
Pentium Gold G5400T	2 / 4	3.1G	4 MB	DDR4-2400	UHD 610		
Pentium Gold G5500T	2 / 4	3.2G	4 MB	DDR4-2400	UHD 630		
Pentium Gold G5600T	2 / 4	3.3G	4 MB	DDR4-2400	UHD 630		
Pentium Gold G5420T	2 / 4	3.2G	4 MB	DDR4-2400	UHD 610		
Core i3-8100T	4 / 4	3.1G	6 MB	DDR4-2400	UHD 630		
Core i3-8300T	4 / 4	3.2G	8 MB	DDR4-2400	UHD 630		
Core i5-8400T	6 / 6	1.7G / 3.3G	9 MB	DDR4-2666	UHD 630		
Core i5-8500T	6 / 6	2.1G / 3.5G	9 MB	DDR4-2666	UHD 630		
Core i5-8600T	6 / 6	2.3G / 3.7G	9 MB	DDR4-2666	UHD 630		
Core i7-8700T	6 / 12	2.4G / 4.0G	12 MB	DDR4-2666	UHD 630		
Core i3-9100T	4 / 4	3.1G / 3.7G	6 MB	DDR4-2400	UHD 630		
Core i3-9300T	4 / 4	3.2G / 3.8G	8 MB	DDR4-2400	UHD 630		
Core i5-9400T	6 / 6	1.8G / 3.4G	9 MB	DDR4-2666	UHD 630		
Core i5-9500T	6 / 6	2.2G / 3.7G	9 MB	DDR4-2666	UHD 630		
Core i5-9600T	6 / 6	2.3G / 3.9G	9 MB	DDR4-2666	UHD 630		
Core i7-9700T	8 / 8	2.0G / 4.3G	12 MB	DDR4-2666	UHD 630		
Core i9-9900T	8 / 16	2.1G / 4.4G	16 MB	DDR4-2666	UHD 630		

Processor	4x Mini DisplayPort, up to 4 independent displays, works along with onboard DP and HDMI to support up to 6 independent displays; <i>Max resolution:</i> 5120x2880@60Hz ((up to 2 Mini DisplayPort); 4096x2160@60Hz ((up to 4 Mini DisplayPort)									
Monitor cable	Optional DP to VGA dongle, DP to DVI-D dongle, DP to dual DP dongle (for Collage Display with Intel integrated graphics), or DP to HDMI 1.4 dongle, Mini DP to DP									
Chipset	Intel Q370 Chipset									
Front ports (Std.)*	one USB 3.1 Gen1 (Always On and fast charge), one USB 3.1 Type-C Gen 1, one microphone (3.5mm), one headphone / microphone combo jack (3.5mm)									
Rear ports (Std.)*	2x USB 3.1 Gen2, 2x USB 3.1 Gen1, 1x ethernet (RJ-45), 1x DP, 1x HDMI									
Rear ports (Opt.)*	Two optional ports (mutually exclusive with PCIe card): Port 1 for VGA / 2nd DP / 2nd HDMI / serial / USB 3.1 Type-C Gen 1 with DP function); Port 2 for serial; Optional ports via PCIe card: 2x USB 3.1 Gen1 via PCIe x1, 4x serial (9-pin) via PCIe x1, 1x Thunderbolt 3 (combo USB3.1 Type-C Gen 2 / DP) via PCIe x4 * Depending on many factors, actual data transfer speed may be lower than theoretical speed									
Audio support	Realtek ALC233VB2 / optional internal speaker (1.5 watt or 2 watt)									
WLAN	<i>Some:</i> 11ac Wi-Fi + BT 4.2, M.2 Card, Realtek RTL8821CE (dual band), 1x1 <i>Some:</i> 11ac Wi-Fi + BT 4.2, M.2 Card, Realtek RTL8822BE (dual band), 2x2 <i>Some:</i> 11ac Wi-Fi + BT 4.2, M.2 Card, Intel Dual Band Wireless-AC 3165, 1x1 <i>Some:</i> 11ac Wi-Fi + BT 4.2, M.2 Card, Intel Dual Band Wireless-AC 8265, 2x2 <i>Some:</i> 11ac Wi-Fi + BT 5.0, M.2 Card, Intel Wireless-AC 9560 (dual band), Intel vPro technology support, 2x2									
Bluetooth	<i>Some:</i> Bluetooth 4.2/5.0 wireless, integrated in Wi-Fi + BT combo adapter									
Ethernet	Gigabit ethernet, Intel Ethernet Connection I219-LM(Jacksonville), Wake on LAN®									
Ethernet (Opt.)	<i>Some:</i> Intel Ethernet Server Adapter I350-T4, gigabit ethernet, 4x RJ-45, PCIe x4									
Manageability	Intel Active Management Technology 12 (Intel AMT 12); Intel vPro technology on some models (require choosing a vPro-support Wi-Fi adapter to enable vPro function through wireless connection)									
Security chip	Discrete TPM 2.0, TCG Certified									
Security features	<ul style="list-style-type: none"> Security slot (in rear for optional Kensington® MicroSaver® cable) Chassis intrusion switch Power-on password Administrator password Hard disk password <ul style="list-style-type: none"> Boot sequence control Boot without keyboard and mouse Individual USB port disablement Smart USB protection, allows keyboard/mouse only, blocks all storage devices 									
Keyboard	<i>Some:</i> Lenovo Calliope Keyboard (USB connector), black <i>Some:</i> Lenovo Traditional Keyboard (USB connector), black <i>Some:</i> Lenovo Calliope Wireless Keyboard (2.4GHz via USB receiver), black									
Mouse	<i>Some:</i> Lenovo Calliope Mouse (USB connector), black <i>Some:</i> Lenovo Fingerprint Mouse (USB connector), Windows Hello support, black <i>Some:</i> Lenovo Calliope Wireless Mouse (2.4GHz via USB receiver), black									
Mechanical	Tiny (1L), black color; metal case <ul style="list-style-type: none"> Toolless chassis open (need optional toolless chassis screw) Toolless HDD, SSD, memory removal Optional dust filter one 2.5" bay for HDD/SSD, one PCIe 3.0 x8 slot (low-profile), three M.2 slots (one for WLAN, two for M.2 SSD), 2.5" HDD/SSD and PCIe card are mutually exclusive <table border="1" style="margin-left: 20px;"> <thead> <tr> <th></th> <th>Dimensions (WxDxH)</th> <th>Weight (Approx.)</th> </tr> </thead> <tbody> <tr> <td>Tiny only</td> <td>7.0" X 7.2" X 1.5" 179mm X 183mm X 37mm</td> <td>2.91 lb (1.32 kg), vary by config</td> </tr> <tr> <td>With VESA mount & ODD box</td> <td>7.42" X 7.30" X 2.48" 188.4mm X 185.38mm X 63mm</td> <td>3.66 lb (1.66 kg), vary by config</td> </tr> </tbody> </table>		Dimensions (WxDxH)	Weight (Approx.)	Tiny only	7.0" X 7.2" X 1.5" 179mm X 183mm X 37mm	2.91 lb (1.32 kg), vary by config	With VESA mount & ODD box	7.42" X 7.30" X 2.48" 188.4mm X 185.38mm X 63mm	3.66 lb (1.66 kg), vary by config
	Dimensions (WxDxH)	Weight (Approx.)								
Tiny only	7.0" X 7.2" X 1.5" 179mm X 183mm X 37mm	2.91 lb (1.32 kg), vary by config								
With VESA mount & ODD box	7.42" X 7.30" X 2.48" 188.4mm X 185.38mm X 63mm	3.66 lb (1.66 kg), vary by config								
Memory	32GB max, DDR4-2666*, two 260-pin SO-DIMM sockets, dual-channel capable * System automatically clocks down for the processors with lower memory controller									
Storage	<i>Some:</i> Hard Drive / SATA 6.0Gb/s, 2.5", 5400 rpm or 7200 rpm <i>Some:</i> Solid State Drive (SSD) / SATA 6.0Gb/s, 2.5" <i>Some:</i> M.2 SSD (support up to two M.2 SSD) / PCIe NVMe, PCIe 3.0 x 4", 32Gb/s, RAID 0/1 support (RAID preset only available via special bid model) * 128GB SSD M.2 (2242) PCIe NVMe only supports PCIe 3.0 x 2, 16Gb/s <i>Some:</i> Intel Optane™ Memory (not support Celeron / Pentium Processor), M.2									
Optical	<i>Some:</i> DVD-ROM, slim (9.0mm), via USB external ODD box <i>Some:</i> DVD Burner (DVD±RW), slim (9.0mm), via USB external ODD box									
Onboard SATA	One onboard SATA 6.0Gb/s connector									
Graphics	Intel HD Graphics 610/630 in processor, uses main memory, DirectX® 12, one DisplayPort™, one HDMI, one optional video port (2nd HDMI, VGA, 2nd DP, or USB 3.1 Type-C Gen1 with DisplayPort function), up to 3 independent displays; <i>Max resolution:</i> c4096x2304 (DP) @60Hz; 4096x2304 (Type-C) @60Hz; 4096x2160 (onboard HDMI) @24Hz; 2048x1536 (VGA) @50Hz <i>Some:</i> AMD Radeon™ RX 560 , DirectX 12, 4GB GDDR5, PCIe 3.0 x8 adapter,									
VESA mount	Optional VESA mount bracket kit, supports VESA 75mm and 100mm									
Floor Stand	Optional system floor stand for vertical orientation									
Power supply	135 watts AC/DC adapter, autosensing, 88% PSU									
Limited warranty	<i>Some:</i> 1-year or 3-year, depot service / service upgrades available <i>Some:</i> 1-year or 3-year, limited onsite service / service upgrades available									
Preload	<i>Some:</i> Windows® 10 Pro 64-bit <i>Some:</i> Windows 10 Home 64-bit									
Environment	ENERGY STAR® 7.0, EPEAT™ Gold rating (North America), ErP Lot 3, TCO, TUV ultra low noise verified (coming soon, on some models), RoHS-compliant									
MIL-SPEC test	MIL-STD-810G military certification (Low Pressure [Altitude], High Temperature, Low Temperature, Temperature Shock, Humidity, Sand and Dust, Vibration, Shock, Fungus, Solar Radiation)									
Accessories	For compatible accessories, please go to http://smartfind.lenovo.com									

Note: The specifications above may not be available in all regions.

Lenovo, June 2019