OVERVIEW



1. 2x USB 3.1 Gen 1	4. Power connector
2. Headphone / microphone combo jack (3.5mm)	5. DisplayPort
3. HDMI 1.4	6. USB-B 3.1 Gen 1

Notes:

- USB 3.1 Gen 1(only available when a Tiny is installed or a PC is connected)

PERFORMANCE

Panel

Panel

In-Plane Switching (IPS)

Backlight

WLED

Display Size

27 inches

Max View Area

WxH: 596.7 x 335.7 mm

Resolution

2560 x 1440

Aspect Ratio

16:9

Pixel Pitch

0.2331 x 0.2331 mm

Dot / Pixel Per Inch

109 dpi

Brightness

350 cd/m²

Contrast Ratio

- Contrast Ratio: 1000:1
- Dynamic Contrast Ratio (Typical): 3000000:1

View Angle (H / V)

Horizontal: 178°, Vertical: 178°

Response Time

- Extreme Mode: 4 ms
- Normal Mode: 6 ms
- Off Mode: 14 ms

Refresh Rate

60Hz

Color Gamut

99% sRGB

Color Support

16.7 Million

Screen Surface Treatment

Anti-glare

Operating System

Operating System

- Windows® 11 Support
- Windows® 10 Support
- Windows® 7 Support

Multi-Media

Camera

IR + RGB camera, with dual microphone, ThinkShutter, and LED indicator. Supports Windows® Hello and Facial Recognition

Microphone

Dual-microphone array

Speakers

Stereo speakers, 2W x2

Power Supply

Power Consumption

Typical / Max: 37W / 57W

DESIGN

Display

Touchscreen

Non-touch

Mechanical

ThinkCentre® M Series Support

ThinkCentre® Tiny, ThinkCentre® Nano, and ThinkStaion Tiny

Bezel Width

- Top / side: 2.0mm
- Bottom: 23.3mm

Buttons

- Brightness button
- Exit button
- Menu button
- Mode-switching button
- Power button
- Volume button

Cable Management

Support

Case Color

Black

Dimensions (WxDxH)[1]

Models	Dimensions
Models with full function monitor stand	614 x 329 x 554.25 mm (24.17 x 12.95 x 21.82 inches)
Models without stand	614 x 73.89 x 413.1 mm (24.17 x 2.91 x 16.26 inches)

Packaging Dimensions (WxDxH)

782 x 172 x 469 mm (30.79 x 77.00 x 18.46 inches)

Weight[2]

Models	Weight
Models without stand	Around 4.90 kg (10.82 lbs)
Models with full function monitor stand	Around 7.95 kg (17.53 lbs)

Packaging Weight

9.75 kg (21.5 lbs)

Mounting

Supports VESA mount 100mm

Stand

Full function monitor stand, supports -5° to +30° tilt, left & right 45° swivel, up to 110mm lift, -5° to +90° pivot

In the Box

- Power adapter (170W)
- Power cable[3]
- Detachable stand
- TIO (monitor)

Notes:

[1] The system dimensions may vary depending on configurations.

[2] The system weight is approximate and based on results in Lenovo® lab, which varies depending on the source of component, variance of the distribution of each component, and manufacturing process. It may not be the exact weight for each specific model.
[3] Model with the “WL” suffix is shipped without a power cable.

CONNECTIVITY

Ports[1]

Rear Ports

- 1x USB-B 3.1 Gen 1, USB upstream
- 1x HDMI® 1.4
- 1x DisplayPort™ 1.2
- 1x power connector

Left Ports[2]

- 2x USB 3.1 Gen 1 (on TIO)
  The availability and version depends on the Tiny installed or the PC connected via USB upstream port (USB-B 3.1 Gen 1)
- 1x headphone / microphone combo jack (on TIO)
- Side ports offered by installed Tiny (on Tiny)

Notes:

[1] The transfer speed of following ports will vary and, depending on many factors, such as the processing speed of the host device, file attributes and other factors related to system configuration and your operating environment, will be slower than theoretical speed.
USB 2.0: 480 Mbit/s;
USB 3.2 Gen 1 (SuperSpeed USB 5Gbps, formerly USB 3.0 / USB 3.1 Gen 1): 5 Gbit/s;
USB 3.2 Gen 2 (SuperSpeed USB 10Gbps, formerly USB 3.1 Gen 2): 10 Gbit/s;
USB4® 20Gbps / USB 3.2 Gen 2x2 (SuperSpeed USB 20Gbps): 20 Gbit/s;
USB4® 40Gbps (USB 40Gbps): 40 Gbit/s;
Thunderbolt™ 3/4: 40 Gbit/s.
Thunderbolt™ 5: 80 Gbit/s (bidirectional), up to 120 Gbit/s in bandwidth boost mode for video-intensive applications.
[2] The USB ports are enabled by installing a Tiny or connecting USB upstream port; the audio port is enabled by installing a Tiny or connecting USB upstream, DisplayPort™(in), or HDMI®(in) port.

SECURITY & PRIVACY

Security

Physical Locks

Kensington Security Slot™, 3 x 7 mm

SERVICE

Warranty

Base Warranty

3-year limited warranty

OPERATING REQUIREMENTS

Operating Environment

Temperature

Operating: 0°C to 40°C (32°F to 104°F)
Storage: -20°C to 60°C (-4°F to 140°F)

Relative Humidity

Operating: 8% to 80%
Storage: 5% to 95%

CERTIFICATIONS

Green Certifications[1]

Green Certifications

- ENERGY STAR® Certified
- EPEAT Silver Registered[2]
- RoHS compliant
- TCO Certified Edge 2.0
- ULE Gold
- WEEE

Notes:

[1] The items listed under the "Green Certifications" section may not only refer to certification but also registration or self-declaration. For ESG & regulatory compliance documents, please visit https://compliance.lenovo.com.
[2] EPEAT is registered where applicable, please visit epeat.net for registration status by country.

Other Certifications

Other Certifications

- TÜV Rheinland® Eye Comfort Certification
- TÜV Rheinland® Flicker Free
- TÜV Rheinland® Low Blue Light

- Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not responsible for photographic or typographical errors. LENOVO PROVIDES THIS PUBLICATION "AS IS", WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow disclaimer of express or implied warranties in certain transactions, therefore this disclaimer may not apply to you.
- The specifications on this page may not be available in all regions, and may be changed or updated without notice.











