

PERFORMANCE

Panel

Panel

In-Plane Switching (IPS)

Display Size

21.5 inches (546.1mm)

Max View Area

WxH: 476.1 x 267.8 mm (18.74 x 10.54 inches)

Native Resolution

1920x1080

Aspect Ratio

16:9

Pixel Pitch

0.24795 x 0.24795 mm

DPI

102.4 dpi

Brightness

250 nits

Contrast Ratio

1000:1

Pixel Response Time

4 ms (extreme mode) / 6 ms (typical mode) / 14 ms (off mode)

Color Gamut

72% NTSC

Viewing Angle

Horizontal: +/- 89°, vertical: +/- 89°

Anti-glare

Anti-glare

Multi-Media

Camera

720p, with dual microphone and LED indicator

Microphone

Dual array microphone

Speakers

Stereo speakers, 2W x2

Power Supply

Power Supply

Power	Type	Efficiency	Key Features
90W	Adapter	88%	-

Power Consumption

19 watts typical, 32 watts max

DESIGN

Menu

Presets and User Settings

- Presets: 25

ThinkCentre Tiny-In-One 22 Gen 3

- User settings: 25

On Screen Display

On screen display with digital user controls (8 languages)

Display

Touchscreen

(Optional)10-point multi-touch, supports Wake on Touch. ONLY for model 10R0PAT1 and 10R0PAR1.

Mechanical

Compatible Tiny

P330 / P320 / M920(x) / M720 / M910(x) / M710 / M900(x) / M700 / M630e / M625 / M600 / M75q / M715 / M93p / M83 / M73 / M53 / Chromebox Tiny

Bezel Width

- Top / side: 2mm
- Bottom: 22.1mm

Buttons

- Power button
- Exit button
- Menu button
- Mode-switching button
- Brightness button

Cables

Undetachable 3-in-1 cable (power connector, USB [supports USB 3.1 Gen 1 / USB 2.0], DisplayPort™)

Case Color

Black

Dimensions (WxDxH)

Models	Dimensions
Models without stand	489 x 72.5 x 339 mm (19.26 x 2.85 x 13.35 inches)
Models with full function monitor stand	489.3 x 273.3 x 370.7 mm (19.26 x 10.76 x 14.59 inches)

Weight

Models	Weight
Models without stand	3.19 kg (7.01 lbs)
Models with full function monitor stand	5.34 kg (11.77 lbs)

Mounting

Supports VESA mount 100mm

Stand

Full function monitor stand, supports -5° to +30° tilt, left & right 45° swivel, up to 150mm lift, -5° to +90° pivot

In the Box

- TIO (monitor)
- Detachable stand
- Driver CD
- Power adapter
- Power cord
- Quick start and safety poster
- User's guide

CONNECTIVITY

Ports

Rear Ports

- 1x USB upstream port
- 1x DisplayPort
- 1x power connector

Left Ports^[1]

- 1x USB 3.1 Gen 1 (on TIO)
- Side ports offered by installed Tiny (on Tiny)

Notes:

1. The availability and version depends on the Tiny installed or the PC connected via USB upstream port

SERVICE

Warranty

Base Warranty

3-year customer carry-in or mail-in via rapid replacement service

CERTIFICATIONS

Green Certifications

Green Certifications

- EPEAT™ Silver
- ENERGY STAR® 8.0
- TCO Certified 7.0
- TCO edge 2.0
- TUV
- ULE Gold
- RoHS compliant
- VOC
- WEEE

Other Certifications

Other Certifications

- FCC Class B
- ISO 9241-307
- TÜV Rheinland Eye Comfort Certification

