

PERFORMANCE

Panel

Panel

In-Plane Switching (IPS)

Display Size

23.8 inches (604.52mm)

Max View Area

WxH: 527 x 296.5 mm (20.75 x 11.67 inches)

Aspect Ratio

16:9

Pixel Pitch

0.2745 x 0.2745 mm

Brightness

250 nits

Contrast Ratio

1000:1

Pixel Response Time

4 ms (extreme mode) / 6 ms (typical mode) / 14 ms (off mode)

Color Gamut

72% NTSC

Viewing Angle

Horizontal: +/- 89°, vertical: +/- 89°

Anti-glare

Anti-glare

Multi-Media

Camera

- FHD 1080p, with dual microphone and Think Shutter
- IR & RGB camera, with dual microphone and ThinkShutter

Microphone

Dual array microphone

Speakers

Stereo speakers, 2W x2

Power Supply

Power Supply

Power	Type	Efficiency	Key Features
90W	Adapter	88%	-

Power Consumption

15 watts typical, 27 watts max

DESIGN

Menu

Presets and User Settings

- Presets: 25
- User settings: 25

On Screen Display

On screen display with digital user controls (8 languages)

Display

Touchscreen

(Optional) Advanced In-cell Touch (AIT), supports 10-point touch (for models 11GCPAT1 and 11GCPAR1 only)

Mechanical

Compatible Tiny

P340 / P330 / P320 / P350 / P360 / M90q / M80q / M70q / M75q / M920(x) / M720 / M910(x) / M710 / M715 / M900(x) / M700 / M630e / M625 / M600 Tiny / M90n / M75n Nano (with TIO kit)

Bezel Width

- Top / side: 2mm
- Bottom: 22.1mm

Buttons

- Power button
- Volume button
- Exit button
- Menu button
- Mode-switching button
- Brightness button

Cables

Undetachable 3-in-1 cable, embedded into TIO, connects to the I/Os of Tiny (Power connector, USB [supports USB 3.1 Gen 1 / USB 2.0], DisplayPort™™)

Case Color

Black

Dimensions (WxDxH)

Models	Dimensions
Models with full function monitor stand	539.8 x 230.4 x 596.9 mm (21.25 x 9.07 x 23.5 inches)
Models without stand	539.8 x 65.3 x 367.6 mm (21.25 x 2.57 x 14.47 inches)

Weight

Models	Weight
Models with full function monitor stand	Around 6.66 kg (14.68 lbs)
Models without stand	Around 3.61 kg (7.96 lbs)

Mounting

Supports VESA mount 100mm

Stand

Full function monitor stand, supports -5° to +30° tilt, left & right 45° swivel, up to 150mm lift, -5° to +90° pivot

In the Box

- TIO (monitor)
- Detachable stand
- Driver CD
- Information flyer
- Power adapter
- Power cord
- User's guide

CONNECTIVITY

Ports

Rear Ports

- 1x USB upstream port
- 1x DisplayPort
- 1x power connector

Left Ports^[1]

ThinkCentre Tiny-In-One 24 Gen 4

- 1x USB 3.1 Gen 1 (on TIO)
- Side ports offered by installed Tiny (on Tiny)

Notes:

1. The availability and version depends on the Tiny installed or the PC connected via USB upstream port

SERVICE

Warranty

Base Warranty^[1]

3-year courier or carry-in service

Notes:

1. More information of warranty policy, please access <https://pcsupport.lenovo.com/warranty>.

CERTIFICATIONS

Green Certifications

Green Certifications

- EPEAT™ Silver
- ENERGY STAR® 8.0
- ErP Lot 5
- GREENGUARD®
- TCO edge 2.0
- RoHS compliant
- WEEE

Other Certifications

Other Certifications

TÜV Rheinland® Eye Comfort Certification

- Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not responsible for photographic or typographical errors. LENOVO PROVIDES THIS PUBLICATION “AS IS,” WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow disclaimer of express or implied warranties in certain transactions, therefore this disclaimer may not apply to you.
- The specifications on this page may not be available in all regions, and may be changed or updated without notice.

