## ThinkPad A275 Platform Specifications

Processor	AMD PRO A-Se	eries A	PUs						Smart card reader Optional: Smart card reader		
	Processor	# of	_, # of	Base Frequency	Max Turbo Frequency	Cache	Memory Types	Processor	Media reader Ports	4-in-1 reader (MMC, SD, SDHC, SDXC) Two USB 3.1 Gen 1 (USB 3.0, one Always On), USB 3.1 Type-C Gen 1 (with the function of Power Delivery and DisplayPort),	
	Number	Cores	Threads					Graphics AMD			
	PRO A10-8730B			2.4 GHz	3.3 GHz			Radeon™		HDMI 1.4b, Ethernet (RJ-45)  * Depending on many factors, actual data transfer speed may be lower than theoretical speed	
	DDC 442 2222D	4	4	0.5.011	0.4.011	2MB	DDR4-1866	R5 Graphics	Monitor cable	HDMI to VGA: Lenovo HDMI to VGA Monitor Adapter	
	PRO A12-8830B PRO A10-9700B			2.5 GHz 2.5 GHz	3.4 GHz 3.4 GHz		22	AMD Radeon	(optional)	USB-C to VGA: Lenovo USB-C to VGA Adapter USB-C to DP: Lenovo USB-C to DisplayPort Adapter	
	PRO A12-9800B			2.7 GHz	3.4 GHz			R7 Graphics	Camera (ontional)	, , , , , , , , , , , , , , , , , , , ,	
	* Windows 7 is only supported by PRO A10-8730B and PRO A12-8830B Audio support HD Audio, Realtek ALC3268 codec / stereo speakers, 1.5W x 2								HD Audio, Realtek ALC3268 codec / stereo speakers, 1.5W x 2 /		
Graphics	AMD Radeon R5 or R7 Graphics in processor only;								]	dual array microphone, combo audio/microphone jack	
	supports external digital monitor via HDMI or USB Type-C; supports three independent displays; Max resolution: 4096x2160@60Hz (USB Type-C); 4096x2160@30Hz (HDMI)								Keyboard UltraNav™	6-row, spill-resistant, multimedia Fn keys, optional LED backlight TrackPoint® pointing device and buttonless Mylar surface multi-touch touchpad	
Chipset Memory									Security Security chip	Power-on password, hard disk password, supervisor password, security keyhole dTPM 1.2: discrete TPM 1.2, TCG Certified dTPM 2.0: discrete TPM 2.0. TCG Certified	
Display	Some: 12.5" (317.5mm) HD (1366x768), anti-glare, LED backlight, 220 nits, 16:9 aspect ratio, 500:1 contrast ratio  Some: 12.5" (317.5mm) FHD (1920x1080), anti-glare, LED backlight, IPS, 300 nits, 16:9 aspect ratio, 700:1 contrast ratio, 170° viewing angle  On-cell touch, supports 10-finger gesture (FHD only, US only)								Fingerprint reader		
									Internal battery External battery Max battery life	Optional: Integrated Li-ion or Li-Polymer 3-cell (23Wh) Li-ion 3-cell (23Wh) or 6-cell (48Wh)	
Multi-touch (opt)										Models No + 3-cell 3-cell + 3-cell 3-cell + 6-cell 48Wh	
Storage	System has one HDD slot or one M.2 slot exclusively for storage  Some: HDD / SATA 6.0Gb/s, 2.5" wide, 7mm high, Active Protection System™  Some: SSD / SATA 6.0Gb/s, 2.5" wide, 7mm high (e.g. xxxGB SSD)  Some: M.2 SSD / PCIe NVMe, PCIe 3.0 x 2, 16Gb/s							TM		Wax battery life 3.05 III 10.1 III 15.0 III	
								ystem™	AC adapter	* Battery life varies significantly with settings, usage, & other factors 45W slim tip AC adapter or 45W USB Type-C AC adapter	
Optical	None Op								Operating system One of the following, configurable by model:  • Windows® 7 Professional 64 preinstalled		
Ethernet	Realtek® RTL8111EPV Gigabit Ethernet connection									Windows 10 Home 64     Windows 10 Pro 64	
WLAN Bluetooth™	Realtek RTL8822BE, Wi-Fi 2x2 802.11ac + BT4.1, M.2 card Bluetooth 4.1 wireless, integrated in Wi-Fi + Bluetooth combo adapter										
WWAN (optional)										One of the following, configurable by model:	
	<ul> <li>Wireless WAN upgradable</li> <li>Integrated Mobile Broadband 4G LTE-A, Qualcomm® Snapdragon™ X7 LTE-A (Sierra Wireless EM7455)</li> </ul>									<ul> <li>1-year depot repair service</li> <li>3-year/1-yr battery depot repair service</li> <li>3-year/1-yr battery limited onsite service</li> </ul>	
	* For non-WWAN model, it means the model is NOT WWAN upgradable								Mil-Spec test	MIL-STD-810G military testing	
SIM card (opt)	Micro-SiM card slot, opt Verizon LTE (US) SIM card								•	EPEAT™ Gold (US only); ENERGY STAR® 6.1; RoHS-compliant	
Dimensions Weight	WxDxH:       12.03" x 8.21" x 0.80"; 305.5mm x 208.5mm x 20.3mm         Models       No + 3-cell       3-cell + 3-cell       3 + 6-cell         Weight       2.79 lb / 1.27 kg       2.98 lb / 1.36 kg       3.33 lb / 1.52 kg								LIMIOIIIIGIIL	El Exi adia (de diny), Elleria i dixi i di.1, Horio compilant	
Case color Case material	Black Glass-Fiber Reinforced Plastic										

Note: The specifications above may not be available in all regions.