# **OVERVIEW**

1. USB 3.2 Gen 1	5. USB-C 3.2 Gen 2
2. Ethernet (RJ-45)	6. USB 3.2 Gen 1 (Always On)
3. Kensington Nano Security Slot	7. HDMI
4. USB-C 3.2 Gen 1	8. Headphone / microphone combo jack (3.5mm)

# PERFORMANCE

# Processor

### **Processor Family**

AMD Ryzen<sup>™</sup> 3 / 5 / 7 Processor

### Processor\*\*

Processor Name	Cores	Threads	Base Frequency	Max Frequency	Cache	Processor Graphics
AMD Ryzen™ 3 7330U	4	8	2.3GHz	4.3GHz	2MB L2 / 8MB L3	AMD Radeon™ Graphics
AMD Ryzen™ 5 7430U	6	12	2.3GHz	4.3GHz	3MB L2 / 16MB L3	AMD Radeon™ Graphics
AMD Ryzen™ 5 7530U	6	12	2.0GHz	4.5GHz	3MB L2 / 16MB L3	AMD Radeon™ Graphics
AMD Ryzen™ 7 7730U	8	16	2.0GHz	4.5GHz	4MB L2 / 16MB L3	AMD Radeon™ Graphics

# **Operating System**

### **Operating System**\*\*

- Windows® 11 Pro
- Windows® 11 Home
- Windows® 11 Home Single Language
- Windows® 11 DG Windows® 10 Pro 64<sup>[1]</sup>
- No preload operating system

#### Notes:

[1] Windows® 11 DG Windows® 10 Pro 64 is for special bid only.

# Graphics

## Graphics

	Graphics	Туре	Memory	TGP	Key Features	
ſ	AMD Radeon™ Graphics	Integrated	Shared	Share CPU TDP	DirectX® 12	

# **Monitor Support**

### **Monitor Support**

Supports up to 4 independent displays (native display and 3 external monitors via HDMI® and USB-C®)

- HDMI<sup>®</sup> supports up to 4096x2160@30Hz
- USB-C<sup>®</sup> supports up to 5120x2160@60Hz

# Chipset

## Chipset

AMD SoC (System on Chip) platform

# Memory

### Max Memory<sup>[1]</sup>

Up to 40GB (8GB soldered + 32GB SO-DIMM) DDR4-3200

### Memory Slots

One memory soldered to systemboard, one DDR4 SO-DIMM slot, dual-channel capable

#### Memory Type

DDR4-3200

### Notes:

[1] The max memory is based on the test results with current Lenovo® memory offerings.

# Storage

### Storage Support<sup>[1]</sup>

Up to two drives, 2x M.2 SSD

- M.2 2242 SSD up to 512GB
- M.2 2280 SSD up to 1TB

### Storage Slot

- Two M.2 slots
- One M.2 2242 PCIe<sup>®</sup> 3.0 x4 slot
- One M.2 2280 PCIe® 3.0 x4 slot

### Storage Type\*\*\*[2]

Disk Type	Interface	Offering	Security
M.2 2242 SSD	PCIe® NVMe®, PCIe® 4.0 x4	256GB / 512GB	Opal 2.0
M.2 2280 SSD	PCIe <sup>®</sup> NVMe <sup>®</sup> , PCIe <sup>®</sup> 4.0 x4	1TB	Opal 2.0

Notes:

[1] The storage capacity supported is based on the test results with current Lenovo<sup>®</sup> storage offerings.

[2] The SSD with PCIe<sup>®</sup> 4.0x4 is downgraded to closer to PCIe<sup>®</sup> 3.0 x4 due to AMD platform limitations.

# Removable Storage

## Card Reader

No card reader

#### Multi-Media

#### Audio Chip

High Definition (HD) Audio, Synaptic® CX11880 codec

#### Speakers

Stereo speakers, 2W x2, Dolby Atmos®

#### Microphone

Dual-microphone array, Dolby Voice®

#### Camera\*\*

- FHD 1080p + IR hybrid, with privacy shutter, fixed focus
- FHD 1080p, with privacy shutter, fixed focus
- HD 720p, with privacy shutter, fixed focus

# Battery

#### Battery\*\*

- Integrated Li-Polymer 47Wh battery, supports Rapid Charge (charge up to 80% in 1hr)
- Integrated Li-Polymer 57Wh battery, supports Rapid Charge (charge up to 80% in 1hr)

#### Battery Life<sup>[1]</sup>

Configuration 1 (max battery life) MobileMark® 2018: up to 14.45 hr @200nits JEITA 2.0: up to 20.68 hr @150nits Local video playback: up to 19.13 hr @150nits

Alternate configuration 2 MobileMark® 2018: up to 12.03 hr @200nits JEITA 2.0: up to 16.71 hr @150nits Local video playback: up to 15.25 hr @150nits

Alternate configuration 3 MobileMark® 2018: up to 12.38 hr @200nits JEITA 2.0: up to 14.37 hr @150nits Local video playback: up to 15.2 hr @150nits

Notes:

[1] Configuration 1 (max battery life): WUXGA (non-touch), AMD Ryzen™ 7 7730U, 8GB DDR4, Win 11, 57Wh battery, best power efficiency power mode Alternate configuration 2: WUXGA (touch), AMD Ryzen™ 5 7530U, 16GB DDR4, Win 11, 57Wh battery, best power efficiency power mode

Alternate configuration 3: WUXGA (non-touch), AMD Ryzen™ 7 7730U, 8GB DDR4, Win 11, 47Wh battery, best power efficiency power mode

Lenovo

All battery life claims are approximate maximum and based on results using <u>MobileMark® 2018</u>, JEITA 2.0, continuous 1080p local video playback (using default Media Player in Fullscreen mode with 150nits brightness and default volume level), or Google Power Load Test (PLT) battery-life benchmark tests.

Actual battery life will vary depending on many factors such as product configuration, software, wireless functionality, power management settings, and screen brightness.

The maximum capacity of the battery will decrease with time, ambient temperature and use.

Refer to Microsoft® link for more information about the Windows® Performance power slider.

## **Power Adapter**

Power Adapter\*\*[1]

- 65W USB-C<sup>®</sup> (2-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz
- 65W USB-C<sup>®</sup> (3-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz

Notes:

[1] AC adapter offerings depend on the country.

# DESIGN

## Display

#### Display\*\*[1]

Size	Resolution	Touch	Туре	Brightness	Surface	Aspect Ratio	Contrast Ratio	Color Gamut	Refresh Rate	Viewing Angle (L/R/U/D)	Key Features
16″	WUXGA (1920x1200)	None	IPS	300nits	Anti- glare	16:10	800:1	45% NTSC	60Hz	85°/85°/85°/85°	TÜV Low Blue Light (Software)
16″	WUXGA (1920x1200)	None	IPS	300nits	Anti- glare	16:10	1200:1	100% sRGB	60Hz	85°/85°/85°/85°	Eyesafe® Certified 2.0
16″	WUXGA (1920x1200)	Multi- touch	IPS	300nits	Anti- glare	16:10	800:1	45% NTSC	60Hz	85°/85°/85°/85°	TÜV Low Blue Light (Software)
16″	WQXGA (2560x1600)	None	IPS	400nits	Anti- glare	16:10	1200:1	100% sRGB	60Hz	85°/85°/85°/85°	Eyesafe® Certified 2.0

#### Touchscreen

- On-cell multi-touch, supports 10-point touch
- Non-touch

Notes:

[1] IPS (in-plane switching) technology may refer to IPS, PLS, ADS, AHVA, AAS.

## Input Device

#### Keyboard

6-row, spill-resistant, multimedia Fn keys with Unified Communications controls, numeric keypad

#### Keyboard Backlight

- LED backlight
- Non-backlight

#### UltraNav™

TrackPoint® pointing device and Mylar® surface multi-touch touchpad, 68 x 115 mm (2.68 x 4.53 inches)

## **Mechanical**

#### Dimensions (WxDxH)<sup>[1]</sup>

356.1 x 247.7 x 19.85 mm (14.02 x 9.75 x 0.78 inches) **Weight**<sup>[2]</sup>

Lenovo

Models	Weight
Aluminium (top), PC-ABS (bottom) models	Starting at 1.77 kg (3.90 lbs)
Aluminium (top), aluminium (bottom) models	Starting at 1.81 kg (3.99 lbs)

#### Case Color

Graphite black

#### Case Material\*\*

- Aluminium (top), PC-ABS (bottom)
- Aluminium (top), aluminium (bottom)

#### Notes:

[1] The system dimensions may vary depending on configurations.

[2] The system weight is approximate and based on results in Lenovo<sup>®</sup> lab, which varies depending on the source of component, variance of the distribution of each component, and manufacturing process. It may not be the exact weight for each specific model.

# CONNECTIVITY

### Network

#### Ethernet

Gigabit Ethernet, Realtek® RTL8111H-CG, 1x RJ-45, supports Wake-on-LAN

#### WLAN + Bluetooth®\*\*

- Wi-Fi<sup>®</sup> 6, 802.11ax 2x2 Wi-Fi<sup>®</sup> + Bluetooth<sup>®</sup> 5.1, M.2 card<sup>[1]</sup>
- MediaTek Wi-Fi<sup>®</sup> 6 MT7921, 802.11ax 2x2 Wi-Fi<sup>®</sup> + Bluetooth<sup>®</sup> 5.1 (Bluetooth<sup>®</sup> 5.3 hardware ready), M.2 Card<sup>[2]</sup>
- Realtek<sup>®</sup> Wi-Fi<sup>®</sup> 6 RTL8852BE, 802.11ax Dual Band 2x2 Wi-Fi<sup>®</sup> + Bluetooth<sup>®</sup> 5.1 (Bluetooth<sup>®</sup> 5.3 hardware ready), M.2 card
   <sup>[3]</sup>
- Wi-Fi<sup>®</sup> 6E, 802.11ax 2x2 Wi-Fi<sup>®</sup> + Bluetooth<sup>®</sup> 5.1, M.2 card<sup>[4]</sup>
- Realtek<sup>®</sup> Wi-Fi<sup>®</sup> 6E RTL8852CE, 802.11ax Dual Band 2x2 Wi-Fi<sup>®</sup> + Bluetooth<sup>®</sup> 5.1 (Bluetooth<sup>®</sup> 5.3 hardware ready), M.2 card<sup>[5]</sup>
- AMD Wi-Fi<sup>®</sup> 6E RZ616, 802.11ax 2x2 Wi-Fi<sup>®</sup> + Bluetooth<sup>®</sup> 5.1 (Bluetooth<sup>®</sup> 5.3 hardware ready), M.2 Card<sup>[6]</sup>

#### WWAN

No support

#### SIM Card

No physical SIM card inbox

#### NFC

No support

#### Notes:

[1] Wi-Fi<sup>®</sup> 6 full features might be limited by country-level restrictions.

[2], [3] Wi-Fi<sup>®</sup> 6 full features might be limited by country-level restrictions.

Bluetooth<sup>®</sup> 5.3 is hardware ready but may run at a lower version due to OS limitations.

[4] Wi-Fi<sup>®</sup> 6E full features might be limited by country-level restrictions.

Wi-Fi<sup>®</sup> 6E is only enabled on Windows<sup>®</sup> 11 and operates as Wi-Fi<sup>®</sup> 6 with Windows<sup>®</sup> 10.

6GHz Wi-Fi<sup>®</sup> 6E operation is dependent on the support of the operating system, routers/APs/Gateways that support Wi-Fi<sup>®</sup> 6E, and the regional regulatory certifications & spectrum allocation.

[5], [6] Wi-Fi<sup>®</sup> 6E full features might be limited by country-level restrictions.

Wi-Fi<sup>®</sup> 6E is only enabled on Windows<sup>®</sup> 11 and operates as Wi-Fi<sup>®</sup> 6 with Windows<sup>®</sup> 10.

6GHz Wi-Fi® 6E operation is dependent on the support of the operating system, routers/APs/Gateways that support Wi-Fi® 6E, and the regional regulatory certifications & spectrum allocation.

Bluetooth® 5.3 is hardware ready but may run at a lower version due to OS limitations.

# Ports<sup>III</sup>

# Standard Ports

- 1x USB 3.2 Gen 1
- 1x USB 3.2 Gen 1 (Always On)
- 1x USB-C<sup>®</sup> 3.2 Gen 1 (support data transfer, Power Delivery 3.0 and DisplayPort<sup>™</sup> 1.4)
- 1x USB-C<sup>®</sup> 3.2 Gen 2 (support data transfer, Power Delivery 3.0 and DisplayPort<sup>™</sup> 1.4)

- 1x HDMI® 1.4b
- 1x Headphone / microphone combo jack (3.5mm)
- 1x Ethernet (RJ-45)

#### Notes:

[1] The transfer speed of following ports will vary and, depending on many factors, such as the processing speed of the host device, file attributes and other factors related to system configuration and your operating environment, will be slower than theoretical speed.

USB 2.0: 480 Mbit/s; USB 3.2 Gen 1 (SuperSpeed USB 5Gbps, formerly USB 3.0 / USB 3.1 Gen 1): 5 Gbit/s; USB 3.2 Gen 2 (SuperSpeed USB 10Gbps, formerly USB 3.1 Gen 2): 10 Gbit/s; USB4® 20Gbps / USB 3.2 Gen 2x2 (SuperSpeed USB 20Gbps): 20 Gbit/s; USB4® 40Gbps (USB 40Gbps): 40 Gbit/s; Thunderbolt<sup>™</sup> 3/4: 40 Gbit/s.

# Docking

### Docking

Various docking solutions supported via USB-C<sup>®</sup>. For more compatible docking solutions, please visit <u>Docking for ThinkPad<sup>®</sup> E16 Gen 1 (AMD)</u>

# **SECURITY & PRIVACY**

# Security

### Security Chip\*\*

- Firmware TPM 2.0 integrated in SoC
- Discrete TPM 2.0, TCG certified, FIPS 140-2 certified

#### Physical Locks

Kensington<sup>®</sup> Nano Security Slot™, 2.5 x 6 mm

#### Smart Card Reader

No smart card reader

#### Fingerprint Reader

- Touch style fingerprint reader integrated in power button
- No fingerprint reader

### **BIOS Security**

- Supervisor password
- Power-on password
- NVMe<sup>®</sup> password
- Self-healing BIOS

#### **Other Security**

- (Optional) IR camera for Windows<sup>®</sup> Hello (facial recognition)
- Camera privacy shutter

# MANAGEABILITY

## System Management

System Management

Non-DASH

# SERVICE

# Warranty

### Base Warranty\*\*

- 1-year mail-in service
- 1-year courier or carry-in service
- 1-year courier or carry-in with 2-year system board service (Korea only)
- 1-year limited onsite service

• No base warranty

# ACCESSORIES

# **Bundled Accessories**

Bundled Accessories<sup>[1]</sup>

None

Notes:

[1] For more compatible accessory solutions, please visit Accessories for ThinkPad® E16 Gen 1 (AMD).

# **OPERATING REQUIREMENTS**

# **Operating Environment**

#### Temperature<sup>[1]</sup>

- Operating: 5°C (41°F) to 35°C (95°F)
- Storage and transportation in original shipping package: -20°C (-4°F ) to 60°C (140°F)
- Storage without package: 5°C (41°F) to 43°C (109°F)

#### **Relative Humidity**

- Operating: 8% to 95% at wet-bulb temperature 23°C (73°F)
- Storage and transportation: 5% to 95% at wet-bulb temperature 27°C (81°F)

### Altitude

Maximum altitude (without pressurization): 3048 m (10,000 ft)

Notes:

[1] When you charge the battery, its temperature must be no lower than 10°C (50°F).

# ENVIRONMENTAL

## **Sustainability**

### Material

25% PCC recycled plastic used in the battery 30% PCC recycled plastic used in speaker enclosure 90% PCC recycled plastic used in standard 65W adapter Low-temperature solder

# CERTIFICATIONS

# **Green Certifications**<sup>III</sup>

### Green Certifications<sup>[2]</sup>

- ENERGY STAR® 8.0
- EPEAT<sup>™</sup> Gold Registered<sup>[3]</sup>
- ErP Lot 6
- ErP Lot 26
- RoHS compliant
- TCO Certified 9.0

#### Notes:

[1] The items listed under the "Green Certifications" section may not only refer to certification but also registration or self-declaration. For ESG & regulatory compliance documents, please visit <u>https://compliance.lenovo.com</u>.

[2] EPEAT<sup>™</sup> registration and ENERGY STAR<sup>®</sup> certification are dependent on system OS. Please visit <u>epeat.net</u> and <u>energystar.gov</u> for more information.

[3] EPEAT<sup>™</sup> is registered where applicable, please visit <u>epeat.net</u> for registration status by country.

# **Other Certifications**

## Mil-Spec Test

MIL-STD-810H military test passed

### Other Certifications

- (Optional) Eyesafe® Certified 2.0
- (Optional) TÜV Rheinland® Low Blue Light (Hardware Solution)
- (Optional) TÜV Rheinland® Low Blue Light (Software Solution)
- Feature with \*\* means that only one offering listed under the feature is configured on selected models.
- Feature with \*\*\* means that one or more offerings listed under the feature could be configured on selected models.
- Lenovo reserves the right to change specifications or other product information without
  notice. Lenovo is not responsible for photographic or typographical errors. LENOVO PROVIDES
  THIS PUBLICATION "AS IS," WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING
  THE IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some
  jurisdictions do not allow disclaimer of express or implied warranties in certain
  transactions, therefore this disclaimer may not apply to you.
- The specifications on this page may not be available in all regions, and may be changed or updated without notice.



AMD