

PERFORMANCE

Processor

Processor Family

AMD Ryzen™ 3 / 5 / 7 Processor

Processor

Processor Name	Cores	Threads	Base Frequency	Max Frequency	Cache	Memory Support	Processor Graphics
AMD Ryzen 3 3200U	2	4	2.6GHz	3.5GHz	1MB L2 / 4MB L3	DDR4-2400	AMD Radeon™ Vega 3 Graphics
AMD Ryzen 5 3500U	4	8	2.1GHz	3.7GHz	2MB L2 / 4MB L3	DDR4-2400	AMD Radeon Vega 8 Graphics
AMD Ryzen 7 3700U	4	8	2.3GHz	4.0GHz	2MB L2 / 4MB L3	DDR4-2400	AMD Radeon RX Vega 10 Graphics

Operating System

Operating System

- Windows® 10 Home 64
- Windows 10 Pro 64
- No operating system

Graphics

Graphics

Graphics	Type	Memory	Key Features
AMD Radeon Vega 3 Graphics	Integrated	Shared	DirectX® 12
AMD Radeon Vega 8 Graphics	Integrated	Shared	DirectX 12
AMD Radeon RX Vega 10 Graphics	Integrated	Shared	DirectX 12

Monitor Support

Monitor Support

Supports up to 2 independent displays via native display and 1 external monitor; supports external monitor via HDMI® (up to 3840x2160@30Hz) or USB-C (up to 3840x2160@60Hz)

Chipset

Chipset

AMD SoC (System on Chip) platform

Memory

Max Memory^[1]

Up to 32GB DDR4-2400

Memory Slots

Two DDR4 SO-DIMM slots, dual-channel capable

Memory Type^[2]

DDR4-2400

Notes:

1. The max memory is based on the test results with current Lenovo® memory offerings. The system may support more memory as the technology develops.
2. Installed memory is actually 2666MHz but run at 2400MHz due to processor limitation

Storage

Storage Support

Up to two drives, 1x 2.5" HDD + 1x M.2 2242/2280 SSD

- 2.5" HDD up to 2TB

- M.2 2280 SSD up to 512GB
- M.2 2242 SSD up to 512GB

Storage Type

Disk Type	Interface	RPM	Security
2.5" SATA HDD	SATA 6Gb/s	5.4K	APS (Active Protection System™)
2.5" SATA HDD	SATA 6Gb/s	7.2K	APS (Active Protection System)
M.2 2242 SSD	PCIe NVMe, PCIe 3.0 x2	-	-
M.2 2242 SSD	PCIe NVMe, PCIe 3.0 x4	-	-
M.2 2280 SSD	PCIe NVMe, PCIe 3.0 x4	-	-

Removable Storage**Optical**

None

Card Reader

MicroSD card reader

Multi-Media**Audio Chip**

High Definition (HD) Audio, Synaptic® CX11880 codec

Speakers

Stereo speakers, 1.5W x2, Dolby® Advanced Audio

Microphone

Dual array microphone

Camera

720p, fixed focus

Battery**Battery**

Integrated Li-Polymer 45Wh battery, supports Rapid Charge (charge up to 80% in 1hr) with 65W AC adapter

Max Battery Life^[1]

MobileMark® 2014: 11 hr

Notes:

1. All battery life claims are approximate maximum and based on results using the MobileMark 2014, MobileMark 2018, and/or JEITA 2.0 battery-life benchmark tests. Actual battery life will vary and depends on many factors such as product configuration and usage, software use, wireless functionality, power management settings, and screen brightness. The maximum capacity of the battery will decrease with time and use.

Power Adapter**Power Adapter**

- 45W USB-C AC adapter
- 65W USB-C AC adapter

DESIGN**Display****Display^[1]**

Size	Resolution	Touch	Type	Brightness	Surface	Aspect Ratio	Contrast Ratio	Color Gamut	Viewing Angle	Key Features
14.0"	HD (1366x768)	None	TN	220 nits	Anti-glare	16:9	400:1	-	90°	-
14.0"	FHD (1920x1080)	None	IPS	250 nits	Anti-glare	16:9	600:1	-	170°	-

Touchscreen

Non-touch

Notes:

- California Electronic Waste Recycling Fee
In California, per state law, Lenovo charges an electronic waste recycling fee on this covered device at the time of sale of the product.
For more information, go to <https://www.calrecycle.ca.gov/Electronics/Consumer>

Input Device**Keyboard**

6-row, spill-resistant, multimedia Fn keys

Keyboard Backlight

No support

UltraNav™

TrackPoint® pointing device and Mylar® surface multi-touch touchpad

Mechanical**Dimensions (WxDxH)**

Models	Dimensions
Aluminium (top), PC + ABS (bottom) models	329 x 242 x 19.9 mm (12.96 x 9.53 x 0.78 inches)
PC + ABS (top), PC + ABS (bottom) models	329 x 242 x 21.9 mm (12.96 x 9.53 x 0.83 inches)

Weight^[1]

1.75 kg (3.87 lbs)

Case Color

Black

Case Material

- Aluminium (top), PC + ABS (bottom)
- PC + ABS (top), PC + ABS (bottom)

Notes:

- The system weight varies depending on configurations

CONNECTIVITY**Network****Onboard Ethernet**

Gigabit Ethernet, Realtek® RTL8111GUS

WLAN + Bluetooth™^[1]

- Realtek RTL8822BE, 802.11ac Dual Band 2x2 Wi-Fi + Bluetooth 4.2, M.2 card
- Intel® Wireless-AC 9260, 802.11ac Dual Band 2x2 Wi-Fi + Bluetooth 5.1, M.2 card

WWAN

No support

SIM Card

No SIM card inbox

NFC

No support

Notes:

- BT5.1 is supported on Windows 10 version 2004 or above (limited to BT5.0 on earlier version)

Ports^[1]**Standard Ports^[2]**

- 1x USB 3.1 Gen 1

- 1x USB 3.1 Gen 1 (Always On)
- 1x USB-C 3.1 Gen 1 (support data transfer, Power Delivery and DisplayPort™)
- 1x USB 2.0
- 1x HDMI 1.4b
- 1x microSD card reader
- 1x Ethernet (RJ-45)
- 1x headphone / microphone combo jack (3.5mm)

Notes:

1. The transfer speed of following ports will vary and, depending on many factors, such as the processing speed of the host device, file attributes and other factors related to system configuration and your operating environment, will be slower than theoretical speed.
USB 2.0: 480 Mbit/s;
USB 3.2 Gen 1 (SuperSpeed USB 5Gbps, formerly USB 3.0 / USB 3.1 Gen 1): 5 Gbit/s;
USB 3.2 Gen 2 (SuperSpeed USB 10Gbps, formerly USB 3.1 Gen 2): 10 Gbit/s;
USB 3.2 Gen 2x2 (SuperSpeed USB 20Gbps): 20 Gbit/s;
Thunderbolt™ 3: 40 Gbit/s;
FireWire 400: 400 Mbit/s;
FireWire 800: 800 Mbit/s
2. Depending on many factors, actual data transfer speed may be lower than theoretical speed

SECURITY & PRIVACY

Security

Security Chip

- Discrete TPM 2.0, TCG certified
- Firmware TPM 2.0 integrated in chipset

Physical Locks

Kensington® Security Slot

Smart Card Reader

No smart card reader

Fingerprint Reader

No fingerprint reader

BIOS Security

- Power-on password
- Supervisor password
- Hard disk password

SERVICE

Warranty

Base Warranty

- 1-year mail-in service
- 1-year depot service
- 1-year limited onsite service

ENVIRONMENTAL

Operating Environment

Temperature^[1]

- Storage without package: 5°C (41°F) to 43°C (109°F)
- Storage and transportation in original shipping package: -20°C (-4°F) to 60°C (140°F)
- Operating: 5°C (41°F) to 35°C (95°F)

Humidity

- Operating: 8% to 95% at wet-bulb temperature 23°C (73°F)
- Storage and transportation: 5% to 95% at wet-bulb temperature 27°C (81°F)

Altitude

Maximum altitude (without pressurization): 3048 m (10,000 ft)

Notes:

1. When you charge the battery, its temperature must be no lower than 10°C (50°F)

CERTIFICATIONS

Green Certifications

Green Certifications

- EPEAT™ Gold
- ENERGY STAR® 8.0
- TCO
- RoHS compliant

Other Certifications

Mil-Spec Test

MIL-STD-810G military test passed

