

OVERVIEW



1. Nano-SIM card slot *	6. HDMI
2. Thunderbolt 4	7. USB 3.2 Gen 1 (Always On)
3. USB 3.2 Gen 1	8. USB-C 3.2 Gen 2
4. Headphone / microphone combo jack (3.5mm)	9. Kensington Nano Security Slot
5. Pen slot *	10. Smart card reader *

Notes:

• Items with * are only available on selected models



PERFORMANCE

Processor

Processor Family

13th Generation Intel® U Series Core™ i3 / i5 / i7 Processor

Processor**

Processor Name	Cores	Threads	Base Frequency	Max Frequency	Cache	Processor Graphics
Core™ i3- 1315U	6 (2 P-core + 4 E-core)	ore + 4 E- 8 P-core 1.2GHz / E-core P-core 4.5GHz / E-core 1.3.3GHz		10MB	Intel® UHD Graphics	
Core™ i5- 1335U	10 (2 P-core + 8 E-core)	12	P-core 1.3GHz / E-core 0.9GHz	P-core 4.6GHz / E-core 3.4GHz	12MB	Intel® Iris® Xe Graphics
Core™ i5- 1345U	10 (2 P-core + 8 E-core)	12	P-core 1.6GHz / E-core 1.2GHz	P-core 4.7GHz / E-core 3.5GHz	12MB	Intel® Iris® Xe Graphics
Core™ i7- 1355U	i7- 10 (2 P-core + 8 E-core) 12		P-core 1.7GHz / E-core 1.2GHz	P-core 5.0GHz / E-core 3.7GHz	12MB	Intel® Iris® Xe Graphics
Core [™] i7- 10 (2 P-core + 8 12 E-core) 12		P-core 1.8GHz / E-core 1.3GHz	P-core 5.2GHz / E-core 3.9GHz	12MB	Intel® Iris® Xe Graphics	

Operating System

Operating System**

- Windows® 11 Pro
- Windows® 11 Home
- Windows® 11 Home Single Language
- Windows® 11 DG Windows® 10 Pro 64^[1]
- Windows® 10 IoT Enterprise LTSC 2021
- Ubuntu Linux^[2]
- · No preload operating system

Notes:

[1] Windows® 11 DG Windows® 10 Pro 64 is for special bid only.

[2] Some features may not be supported on the system with Linux preload, including but not limited to Intel® RST RAID, MIPI computer vision camera, WWAN, Human Presence Detection, etc.

Graphics

Graphics**

Graphics	Туре	Memory	TGP	Key Features	
Intel® UHD Graphics	Integrated	Shared	Share CPU TDP	DirectX® 12.1	
Intel® Iris® Xe Graphics	Integrated	Shared	Share CPU TDP	DirectX® 12.1	

Monitor Support

Monitor Support

Supports up to 4 independent displays (native display and 3 external monitors via HDMI®, USB-C® and Thunderbolt™)

- \bullet HDMI $^{\! @}$ supports up to 3840x2160@60Hz
- USB-C® supports up to 5120x3200@60Hz
- Thunderbolt™ supports up to 5120x3200@60Hz

Chipset

Chipset

Intel® SoC (System on Chip) platform

Memory

Max Memory

- 8GB soldered memory, not upgradable
- 16GB soldered memory, not upgradable

ThinkPad L13 Yoga Gen 4 (Intel)



• 32GB soldered memory, not upgradable

Memory Slots

Memory soldered to systemboard, no slots, dual-channel

Memory Type[1]

LPDDR5-4800

Notes:

[1] Installed memory is actually 6400MHz but run at 4800MHz due to platform limitation.

Storage

Storage Support[1]

One drive, up to 1TB M.2 2242 SSD

Storage Slot

One M.2 2242 PCIe® 4.0 x4 slot

Storage Type

Disk Type	Interface	Offering	Security
M.2 2242 SSD	PCle® NVMe®, PCle® 4.0 x4	256GB / 512GB / 1TB	Opal 2.0

Notes:

[1] The storage capacity supported is based on the test results with current Lenovo® storage offerings.

Removable Storage

Card Reader

No card reader

Multi-Media

Audio Chip

High Definition (HD) Audio, Realtek® ALC3287 codec

Speakers

Stereo speakers, 2W x2, Dolby® Audio™ Premium

Microphone

Dual-microphone array, far-field, Dolby® Voice

Camera**

- Front FHD 1080p + IR hybrid, with privacy shutter, fixed focus
- Front FHD 1080p + IR hybrid, with privacy shutter, fixed focus; rear 5.0-megapixel, autofocus
- Front FHD 1080p, with privacy shutter, fixed focus
- Front FHD 1080p, with privacy shutter, fixed focus; rear 5.0-megapixel, autofocus
- Front HD 720p, with privacy shutter, fixed focus
- Front HD 720p, with privacy shutter, fixed focus; rear 5.0-megapixel, autofocus

Battery

Battery

Integrated Li-Polymer 46Wh battery, supports Rapid Charge (charge up to 80% in 1hr) with 65W AC adapter

Battery Life[1]

Configuration 1 (max battery life)

MobileMark® 25: up to 10.76 hr with 628 performance score @250nits

JEITA 2.0: up to 20.83 hr @150nits

Local video playback: up to 16.23 hr @150nits

Alternate configuration 2

MobileMark® 25: up to 10.25 hr with 569 performance score @250nits

JEITA 2.0: up to 15.33 hr @150nits

Local video playback: up to 13.3 hr @150nits

Alternate configuration 3

MobileMark® 25: up to 9.35 hr with 726 performance score @250nits

ThinkPad L13 Yoga Gen 4 (Intel)



JEITA 2.0: up to 13.28 hr @150nits Local video playback: up to 11.57 hr @150nits

Notes:

[1] Configuration 1 (max battery life): WUXGA (touch), Intel® i3-1315U, 8GB LPDDR5, Win 11, 46Wh battery, best power efficiency power mode

Alternate configuration 2: WUXGA (touch), Intel® i5-1345U, 16GB LPDDR5, Win 11, 46Wh battery, best power efficiency power mode

Alternate configuration 3: WUXGA (touch), Intel® i7-1365U, 32GB LPDDR5, Win 11, 46Wh battery, best power efficiency power mode

All battery life claims are approximate maximum and based on results using MobileMark® 25, JEITA 2.0, continuous 1080p local video playback (using default Media Player in Fullscreen mode with 150nits brightness and default volume level), or Google Power Load Test (PLT) battery-life benchmark tests.

Actual battery life will vary depending on many factors such as product configuration, software, wireless functionality, power management settings, and screen brightness.

The maximum capacity of the battery will decrease with time, ambient temperature and use.

Refer to Microsoft® link for more information about the Windows® Performance power slider.

Power Adapter

Power Adapter**[1]

- 45W USB-C® (2-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz
- 45W USB-C[®] (3-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz
- 65W USB-C[®] (2-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz
- 65W USB-C® (3-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz
- 65W USB-C® slim (2-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz
- 65W USB-C[®] slim (3-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz

Notes:

[1] AC adapter offerings depend on the country.

DESIGN

Display

Display**[1]

Size	Resolution	Touch	Туре	Brightness	Surface	Aspect Ratio	Contrast Ratio	Color Gamut	Refresh Rate	Viewing Angle (L/R/U/D)	Key Features
13.3"	WUXGA (1920x1200)	Multi- touch	IPS	300nits	Anti- reflection, anti- smudge	16:10	1000:1	100% sRGB	60Hz	85°/85°/85°/85°	-
13.3"	WUXGA (1920x1200)	Multi- touch	IPS	400nits	Anti-glare, anti- smudge	16:10	1500:1	100% sRGB	60Hz	89°/89°/89°/89°	Low power, TÜV Low Blue Light

Touchscreen

OGS (One Glass Solution) multi-touch, supports 10-point touch

Notes:

[1] IPS (in-plane switching) technology may refer to IPS, PLS, ADS, AHVA, AAS.

Multi-mode

Multi-mode

Laptop, tent, stand, and tablet modes supported by 360° hinge

Input Device

Pen

ThinkPad L13 Yoga Gen 4 (Intel)



- Lenovo® Integrated Pen, with built-in rechargeable battery, 4096 levels of pressure sensitivity, on-board garaged and rechargeable
- No pen^[1]

Keyboard

6-row, spill-resistant, multimedia Fn keys with Unified Communications controls

Keyboard Backlight

- · LED backlight
- · Non-backlight

UltraNav™

TrackPoint® pointing device and Mylar® surface multi-touch touchpad, 56 x 115 mm (2.24 x 4.53 inches)

Notes:

[1] Customer needs to purchase an external pen separately.

Mechanical

Dimensions (WxDxH)[1]

305 x 218 x 17.06 mm (12.0 x 8.58 x 0.67 inches)

Weight^[2]

Starting at 1.32 kg (2.92 lbs)

Case Color**

- Storm grey
- · Thunder black

Case Material

Aluminium (top), GFRP (bottom)

Notes:

[1] The system dimensions may vary depending on configurations.

[2] The system weight is approximate and based on results in Lenovo® lab, which varies depending on the source of component, variance of the distribution of each component, and manufacturing process. It may not be the exact weight for each specific model.

CONNECTIVITY

Network

Ethernet[1]

No onboard Ethernet

WLAN + Bluetooth®**

- Intel® Wi-Fi® 6 AX201, 802.11ax 2x2 Wi-Fi® + Bluetooth® 5.2[2]
- Intel® Wi-Fi® 6E AX211, 802.11ax 2x2 Wi-Fi® + Bluetooth® 5.3^[3]

WWAN**

- Wireless WAN upgradable to 4G (with antenna ready)
- · Quectel EM05-G, 4G LTE CAT4, M.2 card, with embedded eSIM functionality
- Fibocom L860-GL-16, 4G LTE CAT16, M.2 card, with embedded eSIM functionality
- No support

SIM Card

No physical SIM card inbox

NFC

- · Near Field Communication
- No support

Notes:

- [1] Ethernet support via optional Lenovo® USB-C® to Ethernet Adapter.
- [2] Wi-Fi® 6 full features might be limited by country-level restrictions.

Bluetooth® 5.2 is hardware ready but may run at a lower version due to OS limitations.



[3] Wi-Fi[®] 6E full features might be limited by country-level restrictions.

Wi-Fi® 6E is only enabled on Windows® 11 and operates as Wi-Fi® 6 with Windows® 10.

6GHz Wi-Fi® 6E operation is dependent on the support of the operating system, routers/APs/Gateways that support Wi-Fi® 6E, and the regional regulatory certifications & spectrum allocation.

Bluetooth® 5.3 operation requires Windows® 11. For more information please see <u>General Bluetooth® Support Information</u> on Microsoft®.

Ports^[1]

Standard Ports

- 1x USB 3.2 Gen 1
- 1x USB 3.2 Gen 1 (Always On)
- 1x USB-C® 3.2 Gen 2 (support data transfer, Power Delivery 3.0 and DisplayPort™ 1.4)
- 1x Thunderbolt™ 4 / USB4® 40Gbps (support data transfer, Power Delivery 3.0 and DisplayPort™ 1.4)
- 1x HDMI® 2.1, up to 4K/60Hz
- 1x Headphone / microphone combo jack (3.5mm)

Optional Ports

- 1x Smart card reader
- 1x Nano-SIM card slot (WWAN support models)

Notes:

[1] The transfer speed of following ports will vary and, depending on many factors, such as the processing speed of the host device, file attributes and other factors related to system configuration and your operating environment, will be slower than theoretical speed.

USB 2.0: 480 Mbit/s;

USB 3.2 Gen 1 (SuperSpeed USB 5Gbps, formerly USB 3.0 / USB 3.1 Gen 1): 5 Gbit/s;

USB 3.2 Gen 2 (SuperSpeed USB 10Gbps, formerly USB 3.1 Gen 2): 10 Gbit/s;

USB4® 20Gbps / USB 3.2 Gen 2x2 (SuperSpeed USB 20Gbps): 20 Gbit/s;

USB4® 40Gbps (USB 40Gbps): 40 Gbit/s;

Thunderbolt™ 3/4: 40 Gbit/s.

Docking

Docking

Various docking solutions supported via Thunderbolt™ or USB-C®.

For more compatible docking solutions, please visit Docking for ThinkPad® L13 Yoga® Gen 4 (Intel®)

SECURITY & PRIVACY

Security

Security Chip

Discrete TPM 2.0, TCG certified, FIPS 140-2 certified

Physical Locks

Kensington® Nano Security Slot™, 2.5 x 6 mm

Smart Card Reader

- · Smart card reader
- No smart card reader

Fingerprint Reader

- Touch style fingerprint reader integrated in power button, match-on-chip
- · No fingerprint reader

BIOS Security

- Power-on password
- Supervisor password
- NVMe® password
- · Self-healing BIOS

Other Security

- (Optional) IR camera for Windows® Hello (facial recognition)
- · Camera privacy shutter

MANAGEABILITY



System Management

System Management

- Intel® vPro® Enterprise[1]
- Non-vPro®

Notes:

[1] Intel® vPro® offers a superset of DASH's defined capabilities.

SERVICE

Warranty

Base Warranty**

- 1-year courier or carry-in service
- 1-year courier or carry-in with 2-year system board service (Korea only)
- 1-year limited onsite service
- 3-year (1-yr battery) courier or carry-in service
- 3-year (1-yr battery) limited onsite service

ENVIRONMENTAL

Sustainability

Material

30% PCC recycled plastic used in top cover frame material

50% PCC recycled plastic used in speaker enclosure

90% PCC recycled plastic used in the battery pack

90% PCC recycled plastic used in standard adapter

Low-temperature solder

90% recycled and/or sustainable packaging

Operating Environment

Temperature[1]

- Operating: 5°C (41°F) to 35°C (95°F)
- Storage and transportation in original shipping package: -20°C (-4°F) to 60°C (140°F)
- Storage without package: 5°C (41°F) to 43°C (109°F)

Relative Humidity

- Operating: 8% to 95% at wet-bulb temperature 23°C (73°F)
- Storage and transportation: 5% to 95% at wet-bulb temperature 27°C (81°F)

Altitude

Maximum altitude (without pressurization): 3048 m (10,000 ft)

[1] When you charge the battery, its temperature must be no lower than 10°C (50°F).

ACCESSORIES

Bundled Accessories

Bundled Accessories***[1]

- Lenovo® HDMI® to VGA Monitor Adapter
- Lenovo® USB-C® to DisplayPort™ Adapter
- Lenovo® USB-C® to Ethernet Adapter (1Gbps) Lenovo® USB-C® to USB-A Adapter
- Lenovo® USB-C® to USB-C® Cable 2m
- Lenovo® USB-C® to HDMI® Adapter



Notes:

[1] For more compatible accessory solutions, please visit Accessories for ThinkPad® L13 Yoga® Gen 4 (Intel®)

CERTIFICATIONS

Green Certifications[2]

- ENERGY STAR® 8.0
- EPEAT[™] Gold Registered^[3]
- ErP Lot 6
- ErP Lot 26
- RoHS compliant
- TCO Certified 9.0

Notes:

[1] The items listed under the "Green Certifications" section may not only refer to certification but also registration or self-declaration.

[2] EPEAT™ registration and ENERGY STAR® certification are dependent on system OS. Please visit epeat.net and energystar.gov for more information.

[3] EPEAT™ is registered where applicable, please see epeat.net for registration status by country.

Other Certifications

Mil-Spec Test

MIL-STD-810H military test passed

Other Certifications

(Optional) TÜV Rheinland® Low Blue Light (Hardware Solution)

- Feature with ** means that only one offering listed under the feature is configured on selected models.
- Feature with *** means that one or more offerings listed under the feature could be configured on selected models.
- Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not
 responsible for photographic or typographical errors. LENOVO PROVIDES THIS PUBLICATION "AS IS,"
 WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES
 OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow
 disclaimer of express or implied warranties in certain transactions, therefore this disclaimer may not apply to
 you.
- The specifications on this page may not be available in all regions, and may be changed or updated without notice.













