


OVERVIEW



| | |
|------------------------------|---|
| 1. USB-C 3.2 Gen 1 | 7. MicroSD card reader |
| 2. USB-C 3.2 Gen 2 | 8. Ethernet (RJ-45) |
| 3. Side docking connector | 9. Smart card reader * |
| 4. USB 3.2 Gen 1 (Always On) | 10. Headphone / microphone combo jack (3.5mm) |
| 5. HDMI 2.0 | 11. USB 3.2 Gen 1 |
| 6. Nano-SIM card slot * | 12. Kensington Security Slot |

Notes:

- Ports with * are only available on selected models
- The combination of 2 and 3 is side docking connector

PERFORMANCE

Processor

Processor Family

AMD Ryzen™ 3 / 5 / 7 Processor

Processor**

| Processor Name | Cores | Threads | Base Frequency | Max Frequency | Cache | Memory Support | Processor Graphics |
|-----------------------|-------|---------|----------------|---------------|------------------|----------------|----------------------|
| AMD Ryzen 3 5400U | 4 | 8 | 2.6GHz | 4.0GHz | 2MB L2 / 8MB L3 | DDR4-3200 | AMD Radeon™ Graphics |
| AMD Ryzen 3 PRO 5450U | 4 | 8 | 2.6GHz | 4.0GHz | 2MB L2 / 8MB L3 | DDR4-3200 | AMD Radeon Graphics |
| AMD Ryzen 5 5600U | 6 | 12 | 2.3GHz | 4.2GHz | 3MB L2 / 16MB L3 | DDR4-3200 | AMD Radeon Graphics |
| AMD Ryzen 5 PRO 5650U | 6 | 12 | 2.3GHz | 4.2GHz | 3MB L2 / 16MB L3 | DDR4-3200 | AMD Radeon Graphics |
| AMD Ryzen 7 PRO 5850U | 8 | 16 | 1.9GHz | 4.4GHz | 4MB L2 / 16MB L3 | DDR4-3200 | AMD Radeon Graphics |

Operating System

Operating System**

- Windows® 11 Pro 64
- Windows 11 Home 64
- Windows 11 DG Windows 10 Pro 64
- Windows 10 Pro 64
- Windows 10 Home 64
- No operating system

Graphics

Graphics

| Graphics | Type | Memory | Key Features |
|---------------------|------------|--------|--------------|
| AMD Radeon Graphics | Integrated | Shared | DirectX® 12 |

Monitor Support

Monitor Support

Supports up to 4 independent displays (native display and 3 external monitors via HDMI® and USB-C®)

- HDMI supports up to 4096x2160@60Hz
- USB-C supports up to 5120x3200@60Hz

Chipset

Chipset

AMD SoC (System on Chip) platform

Memory

Max Memory^[1]

Up to 64GB DDR4-3200

Memory Slots

Two DDR4 SO-DIMM slots, dual-channel capable

Memory Type

DDR4-3200

Notes:

1. The max memory is based on the test results with current Lenovo® memory offerings. The system may support more memory as the technology develops.

Storage

Storage Support^[1]

One drive, up to 512GB M.2 2242 SSD or 1TB M.2 2280 SSD

Storage Type^{**}

| Disk Type | Interface | RPM | Offering | Security |
|--------------|---|-----|----------|----------|
| M.2 2242 SSD | PCIe [®] NVMe [®] , PCIe 3.0 x4 | - | - | - |
| M.2 2280 SSD | PCIe NVMe, PCIe x4 | - | - | Opal2 |

Notes:

- The storage capacity supported is based on the test results with current Lenovo storage offerings. The system may support larger storage as the technology develops.

Removable Storage

Optical

None

Card Reader

MicroSD card reader

Multi-Media

Audio Chip

High Definition (HD) Audio, Realtek[®] ALC3287 codec

Speakers

Stereo speakers, 2W x2, Dolby[®] Audio[™]

Microphone

Dual array microphone

Camera^{**}

- HD 720p, with privacy shutter, fixed focus
- IR & HD 720p hybrid, with privacy shutter, fixed focus

Battery

Battery

Integrated Li-Polymer 45Wh battery, supports Rapid Charge (charge up to 80% in 1hr) with 65W AC adapter

Max Battery Life^[1]

MobileMark[®] 2018: 11.8 hr

JEITA 2.0: 15.3 hr

Notes:

- All battery life claims are approximate maximum and based on results using the MobileMark 2014, MobileMark 2018, JEITA 2.0, continuous 1080p video playback (with 150nits brightness and default volume level) or Google Power Load Test (PLT) battery-life benchmark tests. Actual battery life will vary and depends on many factors such as product configuration and usage, software use, wireless functionality, power management settings, and screen brightness. The maximum capacity of the battery will decrease with time and use.

Power Adapter

Power Adapter^{**}^{[1][2]}

- 45W USB-C (2-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz
- 45W USB-C (3-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz
- 65W USB-C (2-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz
- 65W USB-C slim (2-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz
- 65W USB-C slim (3-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz
- 65W USB-C (3-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz
- No power adapter

Notes:

- AC adapter offerings depend on the country.

ThinkPad L14 Gen 2 (AMD)

2. No power adapter is for special bid only
45W USB-C AC adapter and 65W USB-C slim AC adapter are NOT available in EMEA

DESIGN

Display

Display**^[1]

| Size | Resolution | Touch | Type | Brightness | Surface | Aspect Ratio | Contrast Ratio | Color Gamut | Viewing Angle | Key Features |
|-------|-----------------|-------------|------|------------|------------|--------------|----------------|-------------|---------------|--------------|
| 14.0" | HD (1366x768) | None | TN | 220 nits | Anti-glare | 16:9 | 400:1 | 45% NTSC | 90° | - |
| 14.0" | FHD (1920x1080) | None | IPS | 250 nits | Anti-glare | 16:9 | 700:1 | 45% NTSC | 170° | - |
| 14.0" | FHD (1920x1080) | None | IPS | 400 nits | Anti-glare | 16:9 | 800:1 | 72% NTSC | 170° | Low power |
| 14.0" | FHD (1920x1080) | Multi-touch | IPS | 300 nits | Anti-glare | 16:9 | 700:1 | 45% NTSC | 170° | - |

Touchscreen

- On-cell touch, supports 10-point touch
- Non-touch

Notes:

1. California Electronic Waste Recycling Fee
In California, per state law, Lenovo charges an electronic waste recycling fee on this covered device at the time of sale of the product.
For more information, go to <https://www.calrecycle.ca.gov/Electronics/Consumer>

Input Device

Keyboard

6-row, spill-resistant, multimedia Fn keys with Unified Communications controls

Keyboard Backlight

- LED backlight
- Non-backlight

UltraNav™

TrackPoint® pointing device and Mylar® surface multi-touch touchpad

Mechanical^[1]

Dimensions (WxDxH)

331 x 235 x 20.4 mm (13.03 x 9.25 x 0.80 inches)

Weight

Starting at 1.59 kg (3.49 lbs)

Case Color

Black

Case Material

PC + ABS (top), PC + ABS (bottom)

Notes:

1. The system dimensions and weight vary depending on configurations.

CONNECTIVITY

Network

Onboard Ethernet**

- Gigabit Ethernet, Realtek RTL8111HN (non-DASH models), 1x RJ-45, supports Wake-on-LAN

ThinkPad L14 Gen 2 (AMD)

- Gigabit Ethernet, Realtek RTL8111EPV (DASH models), 1x RJ-45, supports Wake-on-LAN

WLAN + Bluetooth[®]**^{[1][2]}

- Wi-Fi[®] 6, 802.11ax 2x2 Wi-Fi + Bluetooth 5.2, M.2 card
- Mediatek Wi-Fi 6 MT7921, 802.11ax 2x2 Wi-Fi + Bluetooth 5.2, M.2 Card
- Realtek Wi-Fi 6 RTL8852AE, 802.11ax Dual Band 2x2 Wi-Fi + Bluetooth 5.2, M.2 card
- Intel[®] Wi-Fi 6 AX200, 802.11ax 2x2 Wi-Fi + Bluetooth 5.2, M.2 card
- Qualcomm[®] QCNFA765, Wi-Fi 6E, 802.11ax Dual Band 2x2 Wi-Fi + Bluetooth 5.2, M.2 Card
- No WLAN and Bluetooth

WWAN**

- Wireless WAN upgradable to 4G (with antenna ready)
- Integrated Mobile Broadband 4G LTE, Quectel EM120R-GL, M.2 card
- Integrated Mobile Broadband 4G LTE, Quectel EM120R-GL, M.2 card, with embedded eSIM functionality
- No support

SIM Card

No SIM card inbox

NFC

No support

Notes:

1. Bluetooth 5.2 is hardware ready but may run at a lower version due to OS limitation
2. Wi-Fi 6 and Wi-Fi 6E full features might be limited by country level restrictions.
Wi-Fi 6E is only available on Windows 11.

Ports^[1]

Standard Ports

- 1x USB 3.2 Gen 1
- 1x USB 3.2 Gen 1 (Always On)
- 1x USB-C 3.2 Gen 1 (support data transfer, Power Delivery 2.0 and DisplayPort™ 1.4)
- 1x USB-C 3.2 Gen 2 (support data transfer, Power Delivery 2.0 and DisplayPort 1.4)
- 1x HDMI 2.0
- 1x microSD card reader
- 1x Ethernet (RJ-45)
- 1x Headphone / microphone combo jack (3.5mm)
- 1x Side docking connector

Optional Ports***

- 1x Smart card reader
- 1x Nano-SIM card slot (WWAN support models)

Notes:

1. The transfer speed of following ports will vary and, depending on many factors, such as the processing speed of the host device, file attributes and other factors related to system configuration and your operating environment, will be slower than theoretical speed.
USB 2.0: 480 Mbit/s;
USB 3.2 Gen 1 (SuperSpeed USB 5Gbps, formerly USB 3.0 / USB 3.1 Gen 1): 5 Gbit/s;
USB 3.2 Gen 2 (SuperSpeed USB 10Gbps, formerly USB 3.1 Gen 2): 10 Gbit/s;
USB 3.2 Gen 2x2 (SuperSpeed USB 20Gbps): 20 Gbit/s;
Thunderbolt™ 3/4: 40 Gbit/s

Docking

Docking

Various docking solutions supported via USB-C.

For more compatible docking solutions, please visit [Docking for ThinkPad® L14 Gen 2 \(AMD\)](#)

Monitor Cable

Monitor Cable***

- Lenovo HDMI to VGA Monitor Adapter
- Lenovo USB-C to DisplayPort Adapter
- Lenovo USB-C to VGA Adapter
- No monitor cable

SECURITY & PRIVACY

Security

Security Chip

Discrete TPM 2.0, TCG certified

Physical Locks

Kensington® Security Slot, 3 x 7 mm

Smart Card Reader

- Smart card reader
- No smart card reader

Fingerprint Reader

- Touch style fingerprint reader on palm rest, match-on-chip
- No fingerprint reader

BIOS Security

- Power-on password
- Supervisor password
- NVMe password
- Self-healing BIOS

Other Security

- Camera privacy shutter
- (Optional) IR camera for Windows Hello

MANAGEABILITY

System Management

System Management

- DASH
- Non-DASH

SERVICE

Warranty

Base Warranty**^[1]

- 1-year depot service
- 1-year depot with 2-year system board service (Korea only)
- 1-year limited onsite service
- 3-year (1-yr battery) depot service
- 3-year (1-yr battery) limited onsite service
- No base warranty

Notes:

1. More information of warranty policy, please access <https://pcsupport.lenovo.com/warranty>

ENVIRONMENTAL

Operating Environment

Temperature^[1]

- Operating: 5°C (41°F) to 35°C (95°F)
- Storage and transportation in original shipping package: -20°C (-4°F) to 60°C (140°F)
- Storage without package: 5°C (41°F) to 43°C (109°F)

Humidity

- Operating: 8% to 95% at wet-bulb temperature 23°C (73°F)
- Storage and transportation: 5% to 95% at wet-bulb temperature 27°C (81°F)

Altitude

Maximum altitude (without pressurization): 3048 m (10,000 ft)

Notes:

1. When you charge the battery, its temperature must be no lower than 10°C (50°F).

CERTIFICATIONS

Green Certifications

Green Certifications

- EPEAT™ Gold
- ENERGY STAR® 8.0
- TCO Certified
- RoHS compliant

Other Certifications


Mil-Spec Test

MIL-STD-810H military test passed

- Feature with ** means that only one offering listed under the feature is configured on selected models.
- Feature with *** means that one or more offerings listed under the feature could be configured on selected models.
- Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not responsible for photographic or typographical errors. LENOVO PROVIDES THIS PUBLICATION “AS IS,” WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow disclaimer of express or implied warranties in certain transactions, therefore this disclaimer may not apply to you.
- The specifications on this page may not be available in all regions, and may be changed or updated without notice.



AMD



AMD



AMD



AMD



AMD



AMD