# **OVERVIEW**



1. Headphone / microphone combo jack (3.5mm)	6. Kensington Security Slot
2. SD card reader	7. Power connector
3. HDMI	8. Thunderbolt 4
4. 2x USB 3.2 Gen 1	9. Smart card reader *
5. Ethernet (RJ-45)	

Notes:

- Items with \* are only available on selected models
- Nano-SIM card slot on the rear side (not shown on the sample product above)

## ThinkPad P15v Gen 3 (Intel)

## PERFORMANCE

## **Processor**

### **Processor Family**

12th Generation H series Intel® Core™ i5 / i7 / i9 processor, supports up to 14 cores, up to 5.0GHz

#### Processor\*\*

Processor Name	Cores	Threads	Base Frequency	Max Frequency	Cache	Processor Graphics
Core™ i5- 12500H	12 (4 P-core + 8 E-core)	16	P-core 2.5GHz / E-core 1.8GHz	P-core 4.5GHz / E-core 3.3GHz	18MB	Intel® Iris® Xe Graphics
Core™ i7- 12700H	14 (6 P-core + 8 E-core)	20	P-core 2.3GHz / E-core 1.7GHz	P-core 4.7GHz / E-core 3.5GHz	24MB	Intel® Iris® Xe Graphics
Core™ i7- 12800H	14 (6 P-core + 8 E-core)	20	P-core 2.4GHz / E-core 1.8GHz	P-core 4.8GHz / E-core 3.7GHz	24MB	Intel® Iris® Xe Graphics
Core™ i9- 12900H	14 (6 P-core + 8 E-core)	20	P-core 2.5GHz / E-core 1.8GHz	P-core 5.0GHz / E-core 3.8GHz	24MB	Intel® Iris® Xe Graphics

## **Operating System**

#### **Operating System**

- Windows<sup>®</sup> 11 Pro
- Windows® 11 Home
- Windows<sup>®</sup> 11 Home Single Language
- Windows® 11 DG Windows® 10 Pro 64
- Red Hat Enterprise Linux 8.6 (certified only, for detailed and latest information, please visit <u>Red Hat Certified Hardware</u>)
- Ubuntu Linux LTS
- No preload operating system

## Graphics

## Graphics

Graphics	Туре	Memory	TGP	Key Features
Intel <sup>®</sup> Iris <sup>®</sup> Xe Graphics <sup>[1]</sup>	Integrated	Shared	Share CPU TDP	DirectX® 12.1
NVIDIA® RTX A2000 Laptop GPU	Discrete	4GB GDDR6	35W	Dynamic Boost 2.0, DirectX® 12
NVIDIA® T1200 Laptop GPU	Discrete	4GB GDDR6	35W	DirectX® 12
NVIDIA® T600 Laptop GPU	Discrete	4GB GDDR6	35W	DirectX® 12

Notes:

[1] Intel<sup>®</sup> Iris<sup>®</sup> Xe Graphics capability requires system to be configured with dual-channel memory. On the system with single-channel memory, Intel<sup>®</sup> Iris<sup>®</sup> Xe Graphics will function as Intel<sup>®</sup> UHD Graphics.

## **Monitor Support**

#### **Monitor Support**

Supports up to 3 independent displays (native display and 2 external monitors via HDMI® and Thunderbolt™)

- HDMI® supports up to 3840x2160@60Hz
- Thunderbolt<sup>™</sup> supports up to 5120x3200@60Hz (Thunderbolt<sup>™</sup> or USB-C<sup>®</sup> to DP)

## Chipset

Chipset

Intel® SoC (System on Chip) platform

## Memory

Max Memory Up to 64GB DDR5-4800 Memory Slots

Lenovo

Two DDR5 SO-DIMM slots, dual-channel capable

#### **Memory Type**

DDR5-4800 non-ECC

## Storage

### Storage Support<sup>[1]</sup>

Up to two drives, 2x M.2 SSD • M.2 2280 SSD up to 4TB, 2TB each • RAID 0/1 support

## Storage Slot

Two M.2 2280 PCIe® 4.0 x4 slots

#### Storage Type

Disk Type	Interface	Offering	Security
M.2 2280 SSD	PCIe® NVMe®, PCIe® 4.0 x4	256GB / 512GB / 1TB	Opal 2.0
M.2 2280 SSD	PCIe® NVMe®, PCIe® 4.0 x4 Performance	512GB / 1TB / 2TB	Opal 2.0

#### RAID

RAID 0/1 support

Notes:

[1] The storage capacity supported is based on the test results with current Lenovo® storage offerings.

## **Removable Storage**

### Optical

None

#### **Card Reader**

SD card reader

## Multi-Media

#### **Audio Chip**

High Definition (HD) Audio, Realtek® ALC3287 codec

#### **Speakers**

Stereo speakers, 2W x2, Dolby<sup>®</sup> Audio<sup>™</sup> Premium

#### Microphone

- Dual-microphone array, far-field, Dolby<sup>®</sup> Voice<sup>®</sup>
- No microphone

#### Camera\*\*

- HD 720p + IR hybrid with privacy shutter, fixed focus
- HD 720p with privacy shutter, fixed focus
- No camera

## **Battery**

#### Battery

Integrated Li-Polymer 68Wh battery, supports Rapid Charge (charge up to 80% in 1hr)

## **Power Adapter**

#### Power Adapter<sup>[1]</sup>

- 135W slim tip (3-pin) AC adapter, 100-240V, 50-60Hz
- No power adapter •

## Notes:

[1] AC adapter offerings depend on the country.

# DESIGN

## Display

### Display\*\*[1]

Size	Resolution	Touch	Туре	Brightness	Surface	Aspect Ratio	Contrast Ratio	Color Gamut	Viewing Angle (L/R/U/D)	Key Features
15.6″	FHD (1920x1080)	None	IPS	300nits	Anti- glare	16:9	800:1	45% NTSC	85°/85°/-/-	DC dimming
15.6″	FHD (1920x1080)	None	IPS	300nits	Anti- glare	16:9	1200:1	100% sRGB	85°/85°/-/-	DC dimming
15.6″	FHD (1920x1080)	Multi- touch	IPS	300nits	Anti- glare	16:9	800:1	45% NTSC	85°/85°/-/-	DC dimming
15.6″	UHD (3840x2160)	None	IPS	600nits	Anti- glare	16:9	1400:1	100% Adobe® RGB	85°/85°/-/-	Dolby® Vision®, DisplayHDR™ 400, optional X-Rite® Factory Color Calibration, DC dimming

#### **Color Calibration**

- X-Rite<sup>®</sup> factory color calibration (UHD display)
- No color calibration

## Touchscreen

- On-cell multi-touch, supports 10-point touch (selected FHD display)
- Non-touch

### Notes:

[1] IPS (in-plane switching) technology may refer to IPS, PLS, ADS, AHVA, AAS.

## Input Device

## Keyboard

6-row, spill-resistant, multimedia Fn keys with Unified Communications controls, numeric keypad

- Keyboard Backlight
- LED backlight
- Non-backlight

## UltraNav™

3-button TrackPoint® pointing device and Mylar® surface multi-touch touchpad

## Mechanical

## Dimensions (WxDxH)[1]

366.5 x 250 x 22.7 mm (14.43 x 9.84 x 0.89 inches)

#### Weight<sup>[2]</sup>

Models	Weight
Models with integrated graphic	s Starting at 2.096 kg (4.62 lbs)
Models with discrete graphics	Starting at 2.226 kg (4.91 lbs)

## Case Color

Black

## Case Material

PC-ABS (top), PC-ABS (bottom)

Notes:

<sup>[1]</sup> The system dimensions may vary depending on configurations.

<sup>[2]</sup> The system weight is approximate and based on results in Lenovo<sup>®</sup> lab, which varies depending on the source of component, variance of the distribution of each component, and manufacturing process. It may not be the exact weight for each specific model.

# CONNECTIVITY

## Network

## Ethernet\*\*

- Gigabit Ethernet, Intel® Ethernet Connection I219-LM (vPro® models), 1x RJ-45, supports Wake-on-LAN
- Gigabit Ethernet, Intel® Ethernet Connection I219-V (non-vPro® models), 1x RJ-45, supports Wake-on-LAN

## WLAN + Bluetooth®[1]

Intel® Wi-Fi® 6E AX211, 802.11ax 2x2 Wi-Fi® + Bluetooth® 5.1 (Bluetooth® 5.3 hardware ready)

## WWAN\*\*

- Wireless WAN upgradable to 4G (with antenna ready)
- Fibocom L860-GL-16, 4G LTE CAT16, MIMO 4x4, M.2 card
- No support

### SIM Card

- Gemalto eSIM card (physical)
- No physical SIM card inbox

### NFC

No support

### Notes:

[1] Bluetooth<sup>®</sup> 5.3 is hardware ready but may run at a lower version due to OS limitations.

## Ports<sup>[1]</sup>

## Standard Ports<sup>[2]</sup>

- 2x USB 3.2 Gen 1 (one Always On)
- 1x Thunderbolt<sup>™</sup> 4 / USB4<sup>®</sup> 40Gbps (support data transfer, Power Delivery 3.0 and DisplayPort<sup>™</sup> 1.4)
- 1x HDMI $^{\circ}$  2.1, up to 4K/60Hz
- 1x Headphone / microphone combo jack (3.5mm)
- 1x Ethernet (RJ-45)
- 1x SD card reader
- 1x Power connector

## **Optional Ports**

- 1x Smart card reader
- 1x Nano-SIM card slot (WWAN support models)

#### Notes:

[1] The transfer speed of following ports will vary and, depending on many factors, such as the processing speed of the host device, file attributes and other factors related to system configuration and your operating environment, will be slower than theoretical speed.

USB 2.0: 480 Mbit/s;

USB 3.2 Gen 1 (SuperSpeed USB 5Gbps, formerly USB 3.0 / USB 3.1 Gen 1): 5 Gbit/s;

USB 3.2 Gen 2 (SuperSpeed USB 10Gbps, formerly USB 3.1 Gen 2): 10 Gbit/s;

 $\mathsf{USB4}^{\circledast}$  20Gbps / USB 3.2 Gen 2x2 (SuperSpeed USB 20Gbps): 20 Gbit/s;

USB4® 40Gbps (USB 40Gbps): 40 Gbit/s;

Thunderbolt™ 3/4: 40 Gbit/s.

[2] Power Delivery only supports power-out for charging peripherals.

## Docking

## Docking

Various docking solutions supported via Thunderbolt™, USB-C®, or USB-A. For more compatible docking solutions, please visit <u>Docking for ThinkPad® P15v Gen 3 (Intel®)</u>

## **Monitor Cable**

## Monitor Cable

- (Optional) Lenovo® USB-C® to DisplayPort<sup>™</sup> Adapter
- (Optional) Lenovo® HDMI® to VGA Monitor Adapter
- (Optional) Lenovo® USB-C® to VGA Adapter

# **SECURITY & PRIVACY**

## Security

## Security Chip

Discrete TPM 2.0, TCG certified, FIPS 140-2 certified

Physical Locks

Kensington<sup>®</sup> Security Slot<sup>™</sup>, 3 x 7 mm

### Smart Card Reader

- Smart card reader
- No smart card reader

#### **Fingerprint Reader**

Touch style fingerprint reader on palm rest, match-on-chip

### BIOS Security

- Power-on password
- Supervisor password
- NVMe<sup>®</sup> password
- Self-healing BIOS

### **Other Security**

- (Optional) IR camera for Windows® Hello (facial recognition)
- (Optional) Camera privacy shutter
- Bottom cover tamper detection

## MANAGEABILITY

## System Management

## System Management\*\*[]]

- Intel<sup>®</sup> vPro<sup>®</sup> Enterprise
- Intel<sup>®</sup> vPro<sup>®</sup> Essentials
- Non-vPro®

Notes:

[1] Intel® vPro® offers a superset of DASH's defined capabilities.

## SERVICE

## Warranty

## Base Warranty\*\*

- 1-year courier or carry-in service
- 1-year courier or carry-in with 2-year system board service (Korea only)
- 1-year limited onsite service
- 3-year (1-yr battery) courier or carry-in service
- 3-year (1-yr battery) limited onsite service

# ENVIRONMENTAL

## **Sustainability**

#### Material<sup>[1]</sup>

90% recycled and/or sustainable packaging

Notes:

[1] PCC: Post Consumer Content, recycled materials from customers. FSC: Forest Stewardship Council.

## **Operating Environment**

## Temperature<sup>[1]</sup>

• Operating: 5°C (41°F) to 35°C (95°F)

## ThinkPad P15v Gen 3 (Intel)

Lenovo

- Storage and transportation in original shipping packaging: -20°C (-4°F) to 60°C (140°F)
- Storage without package: 5°C (41°F) to 43°C (109°F)

#### **Relative Humidity**

- Operating: 8% to 95% at wet-bulb temperature 23°C (73°F)
- Storage and transportation: 5% to 95% at wet-bulb temperature 27°C (81°F)

#### Altitude

Maximum altitude (without pressurization): 3048 m (10,000 ft)

Notes:

[1] When you charge the battery, its temperature must be no lower than 10°C (50°F).

## CERTIFICATIONS

## **Green Certifications**<sup>III</sup>

### Green Certifications<sup>[2]</sup>

- ENERGY STAR® 8.0
- EPEAT<sup>™</sup> Gold Registered<sup>[3]</sup>
- RoHS compliant
- TCO Certified 9.0

Notes:

[1] The items listed under the "Green Certifications" section may not only refer to certification but also registration or selfdeclaration.

[2] EPEAT<sup>™</sup> registration and ENERGY STAR<sup>®</sup> certification are dependent on system OS. Please visit <u>epeat.net</u> and <u>energystar.gov</u> for more information.

[3] EPEAT<sup>™</sup> is registered where applicable, please see <u>epeat.net</u> for registration status by country.

## **Other Certifications**

Mil-Spec Test MIL-STD-810H military test passed

## **ISV Certifications**

ISV Certifications Please visit ISV certifications for Lenovo® Workstations

- Feature with \*\* means that only one offering listed under the feature is configured on selected models.
- Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not responsible for photographic or typographical errors. LENOVO PROVIDES THIS PUBLICATION "AS IS," WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow disclaimer of express or implied warranties in certain transactions, therefore this disclaimer may not apply to you.
- The specifications on this page may not be available in all regions, and may be changed or updated without notice.







