


## OVERVIEW



1. Ethernet (RJ-45)	6. Headphone / microphone combo jack (3.5mm)
2. USB4	7. Smart card reader *
3. USB-C 3.2 Gen 2	8. USB 3.2 Gen 1
4. HDMI	9. Security keyhole
5. USB 3.2 Gen 1 (Always On)	

Notes:

- Items with \* are only available on selected models

## PERFORMANCE

### Processor

#### Processor Family

AMD Ryzen™ 5 / 7 PRO 7040U Series Processor, supports up to 8 cores, up to 5.1GHz

#### Processor\*\*

Processor Name	Cores	Threads	Base Frequency	Max Frequency	Cache	Processor Graphics
AMD Ryzen™ 5 PRO 7540U	6	12	3.2GHz	4.9GHz	6MB L2 / 16MB L3	AMD Radeon™ 740M
AMD Ryzen™ 7 PRO 7840U	8	16	3.3GHz	5.1GHz	8MB L2 / 16MB L3	AMD Radeon™ 780M

### Operating System

#### Operating System\*\*

- Windows® 11 Pro
- Windows® 11 Home
- Windows® 11 Home Single Language
- Windows® 11 DG Windows® 10 Pro 64
- Fedora Linux
- Red Hat Enterprise Linux 9.1 (certified only, for detailed and latest information, please visit [Red Hat Certified Hardware](#))
- Ubuntu Linux LTS
- No preload operating system

### Graphics

#### Graphics\*\*

Graphics	Type	Memory	TGP	Key Features
AMD Radeon™ 740M	Integrated	Shared	Share CPU TDP	DirectX® 12
AMD Radeon™ 780M	Integrated	Shared	Share CPU TDP	DirectX® 12

### Monitor Support

#### Monitor Support

Supports up to 4 independent displays (native display and 3 external monitors via HDMI®, USB-C® 3.2 Gen 2 and USB4®)

- HDMI® supports up to 3840x2160@60Hz
- USB-C® 3.2 Gen 2 and USB4® support up to 5120x2880@60Hz (USB-C® to DP)

### Chipset

#### Chipset

AMD SoC (System on Chip) platform

### Memory

#### Max Memory

- Models with 16GB LPDDR5x: 16GB soldered memory, not upgradable
- Models with 32GB LPDDR5x: 32GB soldered memory, not upgradable
- Models with 64GB LPDDR5x: 64GB soldered memory, not upgradable

#### Memory Slots

Memory soldered to systemboard, no slots, dual-channel

#### Memory Type

LPDDR5x-7500 non-ECC<sup>[1]</sup>

Notes:

[1] System comes with LPDDR5x-7500 DIMMs and will run as LPDDR5x-6400 due to platform limitations.

### Storage

#### Storage Support<sup>[1]</sup>

One drive, up to 2TB M.2 2280 SSD

# ThinkPad P16s Gen 2 (AMD)

## Storage Slot

One M.2 2280 PCIe® 4.0 x4 slot

## Storage Type\*\*

Disk Type	Interface	Offering	Security
M.2 2280 SSD	PCIe® NVMe®, PCIe® 4.0 x4	256GB / 512GB / 1TB	Opal 2.0
M.2 2280 SSD	PCIe® NVMe®, PCIe® 4.0 x4 Performance	512GB / 1TB / 2TB	Opal 2.0

Notes:

[1] The storage capacity supported is based on the test results with current Lenovo® storage offerings.

## Removable Storage

### Card Reader

No card reader

## Multi-Media

### Audio Chip

High Definition (HD) Audio, Realtek® ALC3287 codec

### Speakers

Stereo speakers, 2W x2, Dolby® Audio™

### Microphone

Dual-microphone array, far-field, Dolby® Voice®

### Camera\*\*

- 5.0MP + IR with privacy shutter and Ultrasonic Human Presence Detection, fixed focus
- FHD 1080p + IR hybrid with privacy shutter and Ultrasonic Human Presence Detection, fixed focus
- HD 720p with privacy shutter, fixed focus

## Battery

### Battery\*\*

- Integrated Li-Polymer 52.5Wh battery, supports Rapid Charge (charge up to 80% in 1hr)
- Integrated Li-Polymer 86Wh battery

## Power Adapter

### Power Adapter\*\*[1]

- 65W USB-C® (2-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz
- 65W USB-C® (3-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz
- 65W USB-C® slim (2-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz
- 65W USB-C® slim (3-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz
- 100W USB-C® slim (3-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz

Notes:

[1] AC adapter offerings depend on the country.

## DESIGN

## Display

### Display\*\*

Size	Resolution	Touch	Type	Brightness	Surface	Aspect Ratio	Contrast Ratio	Color Gamut	Viewing Angle (L/R/U/D)	Key Features
16"	WUXGA (1920x1200)	None	IPS <sup>[1]</sup>	300nits	Anti-glare	16:10	800:1	45% NTSC	85°/85°/85°/85°	85.4% screen to body ratio, DC dimming
16"	WUXGA (1920x1200)	Multi-touch	IPS <sup>[2]</sup>	300nits	Anti-glare	16:10	800:1	45% NTSC	85°/85°/85°/85°	85.4% screen to body ratio, DC

# ThinkPad P16s Gen 2 (AMD)

										dimming
16"	WUXGA (1920x1200)	None	IPS <sup>[3]</sup>	400nits	Anti-glare	16:10	1000:1	100% sRGB	85°/85°/85°/85°	ICC Template color calibration, Low power, Low Blue Light, Eyesafe <sup>®</sup> Certified 2.0, 85.4% screen to body ratio, DC dimming
16"	WUXGA (1920x1200)	Multi-touch	IPS	500nits	Anti-glare	16:10	1000:1	100% sRGB	85°/85°/85°/85°	ThinkPad <sup>®</sup> Privacy Guard
16"	WQUXGA (3840x2400)	None	OLED	400nits	Anti-reflection, anti-smudge	16:10	100,000:1	100% DCI-P3	85°/85°/85°/85°	X-Rite <sup>®</sup> Factory Color Calibration, Low Blue Light, Eyesafe <sup>®</sup> Certified 2.0, DisplayHDR <sup>™</sup> 400, Dolby <sup>®</sup> Vision <sup>®</sup> , 85.4% screen to body ratio

### Color Calibration\*\*

- ICC Template color calibration (low power display)
- X-Rite<sup>®</sup> factory color calibration (OLED display)
- No color calibration

### Touchscreen

- On-cell multi-touch, supports 10-point touch (selected FHD display)
- Non-touch

### Notes:

[1], [2], [3] IPS (in-plane switching) technology may refer to IPS, PLS, ADS, AHVA, AAS.

## Input Device

### Keyboard

6-row, spill-resistant, multimedia Fn keys with Unified Communications controls, numeric keypad

### Keyboard Backlight

- LED backlight
- Non-backlight

### UltraNav™

3-button TrackPoint<sup>®</sup> pointing device and glass-like Mylar<sup>®</sup> surface multi-touch touchpad, 67 x 115 mm (2.64 x 4.53 inches)

## Mechanical

### Dimensions (WxDxH)<sup>[1]</sup>

361.98 x 255.5 x 20.5 mm (14.25 x 10.06 x 0.81 inches)

### Weight<sup>[2]</sup>

Models	Weight
Models with black cover	Starting at 1.70 kg (3.76 lbs)
Models with grey cover	Starting at 1.74 kg (3.85 lbs)

### Case Color\*\*

- Storm grey
- Villi black

### Case Material\*\*

- Models with black cover: PC 50% GF + PC 20% CF (top), PPS (bottom)
- Models with grey cover: aluminium (top), PPS (bottom)

# ThinkPad P16s Gen 2 (AMD)

## Notes:

[1] The system dimensions may vary depending on configurations.

[2] The system weight is approximate and based on results in Lenovo® lab, which varies depending on the source of component, variance of the distribution of each component, and manufacturing process. It may not be the exact weight for each specific model.

## CONNECTIVITY

### Network

#### Ethernet

Gigabit Ethernet, Realtek® RTL8111EPV, 1x RJ-45, supports Wake-on-LAN and AMD PRO Manageability

#### WLAN + Bluetooth®\*\*

- Qualcomm® Wi-Fi® 6E NFA725A, 802.11ax 2x2 Wi-Fi® + Bluetooth® 5.3<sup>[1]</sup>
- AMD Wi-Fi® 6E RZ616, 802.11ax 2x2 Wi-Fi® + Bluetooth® 5.3<sup>[2]</sup>

#### WWAN\*\*

- Wireless WAN upgradable to 4G (with antenna ready)
- Quectel EM05-G, 4G LTE CAT4, M.2 card, with embedded eSIM functionality
- Fibocom L860-GL-16, 4G LTE CAT16, M.2 card, with embedded eSIM functionality
- No support

#### SIM Card

No physical SIM card inbox

#### NFC

- Near Field Communication
- No support

## Notes:

[1], [2] Wi-Fi® 6E full features might be limited by country-level restrictions.

Wi-Fi® 6E is only enabled on Windows® 11 and operates as Wi-Fi® 6 with Windows® 10.

6GHz Wi-Fi® 6E operation is dependent on the support of the operating system, routers/APs/Gateways that support Wi-Fi® 6E, and the regional regulatory certifications & spectrum allocation.

Bluetooth® 5.3 operation requires Windows® 11. For more information please see [General Bluetooth® Support Information on Microsoft®](#).

### Ports<sup>[1]</sup>

#### Standard Ports

- 2x USB 3.2 Gen 1 (one Always On)
- 1x USB-C® 3.2 Gen 2 (support data transfer, Power Delivery 3.0 and DisplayPort™ 1.4)
- 1x USB4® 40Gbps (support data transfer, Power Delivery 3.0 and DisplayPort™ 1.4)
- 1x HDMI® 2.1, up to 4K/60Hz
- 1x Headphone / microphone combo jack (3.5mm)
- 1x Ethernet (RJ-45)
- 1x Security keyhole

#### Optional Ports\*\*\*

- 1x Smart card reader
- 1x Nano-SIM card slot (WWAN support models)

## Notes:

[1] The transfer speed of following ports will vary and, depending on many factors, such as the processing speed of the host device, file attributes and other factors related to system configuration and your operating environment, will be slower than theoretical speed.

USB 2.0: 480 Mbit/s;

USB 3.2 Gen 1 (SuperSpeed USB 5Gbps, formerly USB 3.0 / USB 3.1 Gen 1): 5 Gbit/s;

USB 3.2 Gen 2 (SuperSpeed USB 10Gbps, formerly USB 3.1 Gen 2): 10 Gbit/s;

USB4® 20Gbps / USB 3.2 Gen 2x2 (SuperSpeed USB 20Gbps): 20 Gbit/s;

USB4® 40Gbps (USB 40Gbps): 40 Gbit/s;

Thunderbolt™ 3/4: 40 Gbit/s.

### Docking

## Docking

Various docking solutions supported via Thunderbolt™ or USB-C®. For more compatible docking solutions, please visit [Docking for ThinkPad® P16s Gen 2 \(AMD\)](#)

## Monitor Cable

### Monitor Cable

- Lenovo® HDMI® to VGA Monitor Adapter
- Lenovo® USB-C® to VGA Adapter
- Lenovo® USB-C® to DisplayPort™ Adapter
- No monitor cable

# SECURITY & PRIVACY

## Security

### Security Chip

Discrete TPM 2.0 (TCG certified) and Microsoft® Pluton TPM 2.0, one enabled at one time<sup>[1]</sup>

### Physical Locks

Kensington® Nano Security Slot™, 2.5 x 6 mm

### Smart Card Reader

- Smart card reader
- No smart card reader

### Fingerprint Reader

- Touch style fingerprint reader integrated in power button, match-on-chip
- No fingerprint reader

### BIOS Security

- Power-on password
- Supervisor password
- NVMe® password
- Self-healing BIOS

### Other Security

- (Optional) IR camera for Windows® Hello (facial recognition)
- (Optional) Ultrasonic Human Presence Detection for IR camera
- (Optional) Camera privacy shutter
- Bottom cover tamper detection

Notes:

[1] Microsoft® Pluton TPM 2.0 is only applicable on Windows® 11.

# MANAGEABILITY

## System Management

### System Management

AMD PRO Manageability 2.0

# SERVICE

## Warranty

### Base Warranty\*\*

- 1-year courier or carry-in service
- 1-year courier or carry-in with 2-year system board service (Korea only)
- 1-year limited onsite service
- 3-year (1-yr battery) courier or carry-in service
- 3-year (1-yr battery) limited onsite service
- No base warranty

## ENVIRONMENTAL

### Sustainability

#### Material<sup>[1]</sup>

- 85% PCC recycled plastic used in key caps (backlight)
- 70% PCC recycled plastic used in key caps (non-backlight)
- 90% PCC recycled plastic used in speaker enclosure
- 90% PCC recycled plastic used in the battery
- 90% PCC recycled plastic used in 65W adapter
- 90% recycled and/or sustainable packaging

Notes:

- [1] PCC: Post Consumer Content, recycled materials from customers.
- FSC: Forest Stewardship Council.

### Operating Environment

#### Temperature<sup>[1]</sup>

- Operating: 5°C (41°F) to 35°C (95°F)
- Storage and transportation in original shipping package: -20°C (-4°F ) to 60°C (140°F)
- Storage without package: 5°C (41°F) to 43°C (109°F)

#### Relative Humidity

- Operating: 8% to 95% at wet-bulb temperature 23°C (73°F)
- Storage and transportation: 5% to 95% at wet-bulb temperature 27°C (81°F)

#### Altitude

Maximum altitude (without pressurization): 3048 m (10,000 ft)

Notes:

- [1] When you charge the battery, its temperature must be no lower than 10°C (50°F).

## ACCESSORIES

### Bundled Accessories

#### Bundled Accessories<sup>[1]</sup>

- Lenovo® USB-C® to Ethernet Adapter (1Gbps)
- None

Notes:

- [1] For more compatible accessory solutions, please visit [Accessories for ThinkPad® P16s Gen 2 \(AMD\)](#)

## CERTIFICATIONS

### Green Certifications<sup>[1]</sup>

#### Green Certifications<sup>[2]</sup>

- ENERGY STAR® 8.0
- EPEAT™ Gold Registered
- RoHS compliant
- TCO Certified 9.0

Notes:

- [1] The items listed under the "Green Certifications" section may not only refer to certification but also registration or self-declaration.

- [2] EPEAT™ registration and ENERGY STAR® certification are dependent on system OS. Please visit [epeat.net](http://epeat.net) and [energystar.gov](http://energystar.gov) for more information.

### Other Certifications

#### Mil-Spec Test

MIL-STD-810H military test passed

### Other Certifications

- (Optional) Eyesafe® Certified 2.0
- (Optional) TÜV Rheinland® Low Blue Light

## ISV Certifications

### ISV Certifications

Please visit [ISV certifications for Lenovo® Workstations](#)

- Feature with \*\* means that only one offering listed under the feature is configured on selected models.
- Feature with \*\*\* means that one or more offerings listed under the feature could be configured on selected models.
- Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not responsible for photographic or typographical errors. LENOVO PROVIDES THIS PUBLICATION “AS IS,” WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow disclaimer of express or implied warranties in certain transactions, therefore this disclaimer may not apply to you.
- The specifications on this page may not be available in all regions, and may be changed or updated without notice.



