OVERVIEW

1. Nano-SIM card slot *	5. HDMI
2. Thunderbolt 4	6. 2x Thunderbolt 4
3. USB-A (USB 5Gbps), Always On	7. Headphone / microphone combo jack (3.5mm)
4. Kensington Nano Security Slot	

Notes:

- Items with * are only available on selected models

PERFORMANCE

Processor

Processor Family

Intel® Core™ Ultra 5 / 7 / X7 Processor (Series 3)

Processor**[1]

Processor Name	Cores	Threads	Base Frequency	Max Frequency	Cache	Processor Graphics	NPU
Core Ultra 5 325	8 (4 P-core + 4 LP E-core)	8	P-core 2.1GHz / LP E-core 1.6GHz	P-core 4.5GHz / LP E-core 3.4GHz	12MB Intel® Smart Cache	Intel® Graphics, up to 40 TOPS	Up to 47 TOPS
Core Ultra 5 335	8 (4 P-core + 4 LP E-core)	8	P-core 2.2GHz / LP E-core 1.6GHz	P-core 4.6GHz / LP E-core 3.4GHz	12MB Intel® Smart Cache	Intel® Graphics, up to 40 TOPS	Up to 47 TOPS
Core Ultra 7 355	8 (4 P-core + 4 LP E-core)	8	P-core 2.3GHz / LP E-core 1.7GHz	P-core 4.7GHz / LP E-core 3.5GHz	12MB Intel® Smart Cache	Intel® Graphics, up to 40 TOPS	Up to 49 TOPS
Core Ultra 7 365	8 (4 P-core + 4 LP E-core)	8	P-core 2.4GHz / LP E-core 1.8GHz	P-core 4.8GHz / LP E-core 3.6GHz	12MB Intel® Smart Cache	Intel® Graphics, up to 40 TOPS	Up to 49 TOPS
Core Ultra 7 366H	16 (4 P-core + 8 E-core + 4 LP E-core)	16	P-core 2.0GHz / E-core 1.6GHz / LP E-core 1.6GHz	P-core 4.8GHz / E-core 3.6GHz / LP E-core 3.4GHz	18MB Intel® Smart Cache	Intel® Graphics, up to 40 TOPS	Up to 50 TOPS
Core Ultra X7 368H	16 (4 P-core + 8 E-core + 4 LP E-core)	16	P-core 2.0GHz / E-core 1.6GHz / LP E-core 1.6GHz	P-core 5.0GHz / E-core 3.8GHz / LP E-core 3.6GHz	18MB Intel® Smart Cache	Intel® Arc™ B390 GPU, up to 122 TOPS	Up to 50 TOPS

Notes:

[1] Processors with an “H” suffix are not available in NA.

AI (Artificial Intelligence)

AI PC Category

Copilot+ PC[1]

NPU

Up to 50 TOPS

Notes:

[1] Copilot+ PCs have at least 16GB RAM, 256GB storage, and a NPU that runs 40+ TOPs to run the latest AI tools build-in latest Windows® 11 to accelerate productivity and creativity.

Operating System

Operating System**

- Windows® 11 Pro
- Windows® 11 Home
- Ubuntu Linux[1]
- Linux[2]
- No preload operating system

Notes:

[1], [2] Some features may not be supported on the system with Linux preload, including but not limited to Intel® RST RAID, MIPI computer vision camera, WWAN, Human Presence Detection, etc.

Graphics

Graphics**

Graphics	Type	Memory	Key Features

Intel® Graphics	Integrated	Shared	DirectX® 12 Ultimate
Intel® Arc™ B390 GPU	Integrated	Shared	DirectX® 12 Ultimate

Monitor Support

Monitor Support[1]

Supports up to 4 independent displays (native display and 3 external monitors via HDMI® and Thunderbolt™)
• HDMI® supports up to 4K@60Hz
• Thunderbolt™ supports up to 8K@60Hz[2]

Notes:

[1] Refresh rates >60hz also supported, however max resolution will be limited.
[2] 8K resolution support needs 2 display pipes. That is, simultaneous display number will "-1" when 8K resolution displayed.

Chipset

Chipset

Intel® SoC (System on Chip) platform

Memory

Max Memory

- 16GB soldered memory, not upgradable
- 24GB soldered memory, not upgradable
- 32GB soldered memory, not upgradable
- 64GB soldered memory, not upgradable

Memory Slots

Memory soldered to systemboard, no slots, dual-channel

Memory Type**[1]

- LPDDR5X-7467
- LPDDR5X-8533
- LPDDR5X-9600

Notes:

[1] Installed memory is 16GB LPDDR5X-8533, 32GB LPDDR5X-8533 or 64GB LPDDR5X-9600 but may runs at lower frequency due to platform limitation.

Storage

Max Storage Support[1]

One drive, up to 2TB M.2 2280 SSD

Storage Slot[2]

One M.2 2280 PCIe® 5.0 x4 slot

Storage Type**

Disk Type	Interface	Offering	Security
M.2 2280 SSD	PCIe® NVMe®, PCIe® 4.0 x4	256GB / 512GB / 1TB	Opal 2.0
M.2 2280 SSD	PCIe® NVMe®, PCIe® 5.0 x4 Performance	512GB / 1TB / 2TB	Opal 2.0

Notes:

[1] The storage capacity supported is based on the test results with current Lenovo® storage offerings.
[2] The actual data transfer rate of the following PCIe® interface also depends on the capabilities of the connected PCIe® device. The listed values represent theoretical maximums.
PCIe® 3.0 (x2 / x4): 2 GB/s (16 Gbps) / 4 GB/s (32 Gbps);
PCIe® 4.0 (x2 / x4): 4 GB/s (32 Gbps) / 8 GB/s (64 Gbps);
PCIe® 5.0 (x2 / x4): 8 GB/s (64 Gbps) / 16 GB/s (128 Gbps).

Removable Storage

Card Reader

No card reader

Multi-Media

Audio Chip

SoundWire®, Cirrus Logic® CS42L45 codec

Speakers

Stereo speakers, 2W x2, Dolby Atmos®

Microphone

Dual-microphone array, 360° far-field

Camera**

- 5.0MP + IR discrete, with privacy shutter, fixed focus, vHDR, Computer Vision on Image Signal Processor (ISP), temporal noise reduction[1]
- UHD 10.0MP + IR discrete, with Privacy Shutter, MIPI, ToF sensor, fixed focus, ultrawide, temporal noise reduction

Notes:

[1] Computer Vision on ISP is only available on the models with preloaded OS.

Battery

Battery

58Wh Rechargeable Li-ion Battery, supports Rapid Charge (charge up to 80% in 1hr) with 65W AC adapter[1]

Battery Life[2]

Configuration 1
MobileMark® 30: up to 17.2 hr with 1064 performance score @250nits
JEITA-BAT 3.0 (Video/Idle): up to 19.1 hr / 33.4 hr @200nits
Local video playback: up to 30.9 hr @150nits

Alternate configuration 2
MobileMark® 30: up to 16.6 hr with 1220 performance score @250nits
JEITA-BAT 3.0 (Video/Idle): up to 17.5 hr / 31.8 hr @200nits
Local video playback: up to 30.0 hr @150nits

Alternate configuration 3
MobileMark® 30: up to 12.6 hr with 1294 performance score @250nits
JEITA-BAT 3.0 (Video/Idle): up to 12.1 hr / 16.5 hr @200nits
Local video playback: up to 19.8 hr @150nits

Notes:

[1] Rapid charge is only guaranteed when the computer is turned off or in standby mode or in hibernation mode. When the computer is powered on, the Charge Time will vary depending on system power consumption and AC adapter power.
[2] Configuration 1: WUXGA AGAS (touch), Intel® Core™ Ultra 5 335, 32GB LPDDR5X-7467, Win 11, 58Wh battery, best power efficiency power mode
Alternate configuration 2: WUXGA ARAS (touch), Intel® Core™ Ultra 7 366H, 32GB LPDDR5X-8533, Win 11, 58Wh battery, best power efficiency power mode
Alternate configuration 3: 2.8K (touch), Intel® Core™ Ultra X7 368H, 64GB LPDDR5X-9600, Win 11, 58Wh battery, best power efficiency power mode

All battery life claims are approximate maximum and based on results using MobileMark® 30, JEITA 3.0, continuous 1080p local video playback (using default Media Player in Fullscreen mode with 150nits brightness and default volume level), or Google Power Load Test (PLT) battery-life benchmark tests.
Actual battery life will vary depending on many factors such as product configuration, software, wireless functionality, power management settings, and screen brightness.
The maximum capacity of the battery will decrease with time, ambient temperature and use.
Refer to Microsoft® link for more information about the Windows® Performance power slider.

Power Adapter

Power Adapter**[1]

- 65W USB-C® (2-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz
- 65W USB-C® (3-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz
- 65W USB-C® nano GaN (2-pin, wall-mount) AC adapter, supports PD 3.0, 100-240V, 50-60Hz
- 65W USB-C® nano GaN (3-pin, wall-mount) AC adapter, supports PD 3.0, 100-240V, 50-60Hz

- 65W USB-C® slim GaN (2-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz
- 65W USB-C® slim GaN (3-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz
- No power adapter

Notes:

[1] AC adapter offerings depend on the country.

DESIGN

Display

Display**

Size	Resolution	Touch	Type	Brightness	Surface	Aspect Ratio	Contrast Ratio	Color Gamut	Refresh Rate	Viewing Angle (L/R/U/D)	Key Features
14″	WUXGA (1920x1200)	Multi-touch	IPS[1]	500nits	Anti-glare, anti-smudge	16:10	1000:1	100% sRGB	60Hz	85° / 85° / 85° / 85°	Low power, Eyesafe® Certified 2.0
14″	WUXGA (1920x1200)	Multi-touch	IPS[2]	500nits	Anti-reflection, anti-smudge	16:10	1000:1	100% sRGB	60Hz	85° / 85° / 85° / 85°	Low power, Eyesafe® Certified 2.0
14″	WUXGA (1920x1200)	Multi-touch	IPS[3]	500nits	Anti-glare, anti-smudge	16:10	1500:1	100% sRGB	60Hz	85° / 85° / 85° / 85°	ThinkPad® Privacy Guard, Eyesafe® Certified 2.0
14″	2.8K (2880x1800)	Multi-touch	OLED	500nits	Anti-reflection, anti-smudge	16:10	100,000:1	100% DCI-P3	120Hz VRR	85° / 85° / 85° / 85°	DisplayHDR™ True Black 500, Eyesafe® Certified 2.0

Touchscreen

OGS (One Glass Solution) multi-touch, supports 10-point touch

Screen-to-Body Ratio

86.46%

Notes:

[1], [2], [3] IPS (in-plane switching) technology may refer to IPS, PLS, ADS, AHVA, AAS.

Multi-mode

Multi-mode

Laptop, tent, stand, and tablet modes supported by 360° hinge

Input Device

Pen

- Lenovo® Slim Pen 2, supports magnetic attachment, tilt detection, on-board garaged with pogo pin charge
- No pen bundled (purchase separately)

Keyboard

6-row, spill-resistant, air intake design, multimedia Fn keys, key travel 1.5mm / 1.35mm (Fn row & G/H/B), Copilot key

Keyboard Backlight

LED backlight

UltraNav™**

- TrackPoint® pointing device, double-tap to open the TrackPoint® Quick Menu
  Glass-like Mylar® surface multi-touch 3-button Trackpad, 80 x 120 mm (3.15 x 4.72 inches)
- TrackPoint® pointing device, double-tap to open the TrackPoint® Quick Menu
  Glass surface multi-touch Haptic Touchpad, 80 x 130 mm (3.15 x 5.12 inches)

Mechanical

Dimensions (WxDxH)[1]

313.5 x 219.25 x 9.24/16.4 (front/rear), 17.9 (maximum) mm
12.34 x 8.63 x 0.36/0.65 (front/rear), 0.70 (maximum) inches

Weight[2]

Models	Weight
Models with Haptic Touchpad	Starting at 1.15 kg (2.54 lbs)
Models with Trackpad	Starting at 1.14 kg (2.52 lbs)

Case Color

Grey

Case Material

Aluminium (top), aluminium (bottom)

Notes:

[1] The system dimensions may vary depending on configurations.
[2] The system weight is approximate and based on results in Lenovo® lab, which varies depending on the source of component, variance of the distribution of each component, and manufacturing process. It may not be the exact weight for each specific model.

CONNECTIVITY

Network

WLAN + Bluetooth®**[1]

- Intel® Wi-Fi® 7 BE211, 802.11be 2x2 Wi-Fi® + Bluetooth® 5.4 (Bluetooth® 6.0 hardware ready)
- Intel® Wi-Fi® 7 BE211, 802.11be 2x2 Wi-Fi® + Bluetooth® 5.4 (Bluetooth® 6.0 hardware ready), Intel® vPro® technology support[2]

WWAN**

- Wireless WAN upgradable to 4G or 5G (with antenna ready)[3]
- Snapdragon® X12 LTE Modem, 4G LTE CAT6, M.2 card, with embedded eSIM functionality
- Snapdragon® X61 5G Modem-RF System, Sub-6 GHz, M.2 card, with embedded eSIM functionality
- No support

SIM Card**[4]

- KDDI eSIM Program 3-year (Japan)
- KDDI eSIM Program 3-year with international roaming (Japan)
- KDDI eSIM Program 4-year (Japan)
- KDDI eSIM Program 4-year with international roaming (Japan)
- KDDI eSIM Program 5-year (Japan)
- KDDI eSIM Program 5-year with international roaming (Japan)
- No physical SIM card included

Ethernet

No onboard Ethernet[5]

NFC

- Near Field Communication[6]
- No support

Notes:

[1] Wi-Fi® operation (including Wi-Fi® 6, Wi-Fi® 6E, Wi-Fi® 7, etc.) is subject to the regulatory requirements of each country. Bluetooth® may operate at a lower version than hardware design depending on the factors such as operating system, driver, etc.
[2] Intel® vPro® platform requires the hardware and software necessary to deliver the manageability use cases, security features, system performance, and stability that define the platform. For detailed vPro® support information, please refer to the System Management section.
[3] Wireless WAN upgradable to 4G is only available in EMEA.
[4] KDDI eSIM Program has no physical SIM card inbox and is for special bid only.
[5] Ethernet support via optional Lenovo® USB-C® to Ethernet Adapter.
[6] NFC is mutually exclusive with Haptic Touchpad.

Ports[1]

Standard Ports

- 1x USB-A (USB 5Gbps), Always On
- 3x Thunderbolt™ 4, with USB PD 15-65W and DisplayPort™ 2.1
- 1x HDMI® 2.1, up to 4K/60Hz
- 1x Headphone / microphone combo jack (3.5mm)

Optional Ports

1x Nano-SIM card slot (WWAN support models)

Notes:

[1] The transfer speed of the ports will vary and, depending on many factors, such as the processing speed of the host device, file attributes and other factors related to system configuration and your operating environment, will be slower than theoretical speed.

Docking

Docking

Various docking solutions supported via Thunderbolt™ / USB-C®.
For more compatible docking solutions, please visit Docking for ThinkPad® X1 2-in-1 Gen 11 Aura Edition

SECURITY & PRIVACY

Security

ThinkShield

ThinkShield is a comprehensive security solution that encompasses hardware, software, and supply chain components. For more details, visit here

Security Chip

Discrete TPM 2.0, TCG certified

Physical Locks

Kensington® Nano Security Slot™, 2.5 x 6 mm

Smart Card Reader

No smart card reader

Fingerprint Reader

Touch style fingerprint reader, integrated in power button on keyboard, match-on-chip

BIOS Security

- Certificate-based BIOS authentication
- FIDO (Fast Identity Online) authentication
- NVMe® password
- Power-on password
- Supervisor password
- System management password
- Self-healing BIOS
- More BIOS security features, please visit BIOS Simulator[1]

Other Security

- (Optional) ToF based Human Presence Detection
- (Optional) Computer Vision-based Human Presence Detection on Image Signal Processor (ISP)
- Camera privacy shutter
- IR camera for Windows® Hello (facial recognition)
- Privacy Guard with Privacy Alert (models with ThinkPad® Privacy Guard display)

Notes:

[1] The BIOS simulator is just for reference. Default settings and some options may vary depending on the hardware, operating system and BIOS version.

MANAGEABILITY

System Management

System Management[1]

- Intel® vPro® Enterprise[2]
- Non-vPro®

Notes:

[1] Intel® vPro® platform require an eligible Intel® processor, a supported operating system, Intel® LAN and/or WLAN silicon, firmware enhancements, and other hardware and software necessary to deliver the manageability use cases, security features, system performance, and stability that define the platform. See Intel® vPro® Platform for details.
[2] Intel® vPro® offers a superset of DASH's defined capabilities.

SERVICE

Warranty

Base Warranty**

- 1-year courier or carry-in service
- 1-year courier or carry-in with 2-year system board service (Korea only)
- 1-year limited onsite service
- 3-year (1-yr battery) courier or carry-in service
- 3-year (1-yr battery) limited onsite service
- No base warranty[1]

Notes:

[1] No base warranty is for special bid only.

ACCESSORIES

Bundled Accessories

Bundled Accessories***[1]

- Lenovo® HDMI® to VGA Monitor Adapter
- Lenovo® USB-C® to Ethernet Adapter (1Gbps)
- None

Notes:

[1] For more compatible accessory solutions, please visit Accessories for ThinkPad® X1 2-in-1 Gen 11 Aura Edition.

OPERATING REQUIREMENTS

Operating Environment

Temperature[1]

- Operating: 5°C (41°F) to 35°C (95°F)
- Storage and transportation in original shipping package: -20°C (-4°F) to 60°C (140°F)
- Storage without package: 5°C (41°F) to 43°C (109°F)

Relative Humidity

- Operating: 8% to 95% at wet-bulb temperature 23°C (73°F)
- Storage and transportation: 5% to 95% at wet-bulb temperature 27°C (81°F)

Altitude

Maximum altitude (without pressurization): 3048 m (10,000 ft)

Notes:

[1] When you charge the battery, its temperature must be no lower than 10°C (50°F).

ENVIRONMENTAL

Sustainability

Material[1]

Top cover: 75% recycled aluminum
Keyboard frame: 90% recycled magnesium
Bottom cover: 50% PIC + 5% PCC recycled aluminum
Keyboard (keycaps): 85% PCC recycled material (black keyboard)
Keyboard (base plate): 50% recycled PIR aluminum
Speaker enclosure: 98% PCC recycled material
TouchPad: 30% PCC recycled material (Haptic TouchPad magnet)
Battery: 100% recycled cobalt
Battery frame: 90% PCC recycled material
Adapter: 90% PCC recycled material
Cable/antenna holders: 30% PCC + 5% Lenovo® closed-loop PCC
Fan housing: 25% PCC recycled plastic, 90% recycled steel
Pen: 90% PIC aluminum (for pen body), 65% PCC recycled plastic (pen cap, end cap, upper holder)
Packaging: Plastic-free primary packaging with FSC-certified paper

Notes:

[1] PCC: Post Consumer Content, recycled materials from customers.

CERTIFICATIONS

Green Certifications[1]

Green Certifications[2]

- ENERGY STAR® 9.0
- EPEAT 2.0 Gold Registered[3]
- ErP Lot 6/26
- RoHS compliant
- TCO Certified, generation 10

Notes:

[1] The items listed under the "Green Certifications" section may not only refer to certification but also registration or self-declaration. For ESG & regulatory compliance documents, please visit https://compliance.lenovo.com.
[2] EPEAT registration and ENERGY STAR® certification are optional and only available on the models with preloaded OS. Please visit epeat.net and energystar.gov for more information.
[3] EPEAT is registered where applicable, please visit epeat.net for registration status by country.

Other Certifications

Mil-Spec Test

MIL-STD-810H military test passed

Other Certifications

- (Optional) Intel® Evo™ Platform
- Eyesafe® Certified 2.0
- SGS High Performance AI PC Certification 2.0
- TÜV Rheinland® Dynamic Privacy Filter (DPF) Certification (Privacy Guard models)

- Feature with ** means that only one option listed under the feature can be configured on selected models. Please refer to the model configuration for specific information.
- Feature with *** means that one or more options listed under the feature can be configured on selected models. Please refer to the model configuration for specific information.
- Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not responsible for photographic or typographical errors. LENOVO PROVIDES THIS PUBLICATION "AS IS", WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow disclaimer of express or implied warranties in certain transactions, therefore this disclaimer may not apply to you.
- The specifications on this page may not be available in all regions, and may be changed or updated without

notice.

Copilot+PC

intel.

Copilot+PC

intel.

Copilot+PC

intel.

Copilot+PC

intel.

Copilot+PC

intel.

Copilot+PC

intel.