


## OVERVIEW



1. Optical drive *	14. 3x USB-A (USB 5Gbps)
2. Front access storage bay or 2nd HDD bay *	15. USB-A (USB 5Gbps), with Smart Power On
3. Power button	16. Padlock loop
4. SD card reader *	17. PS/2 port (mouse) *
5. Microphone (3.5mm)	18. PS/2 port (keyboard) *
6. Headphone / microphone combo jack (3.5mm)	19. Ethernet (GbE RJ-45)
7. USB-C (USB 10Gbps), data transfer only	20. E-lock slot *
8. 2x USB-A (USB 5Gbps)	21. Serial (9-pin) *
9. 2x USB-A (USB 10Gbps)	22. Smart cable clip slots
10. Audio line-out (3.5mm)	23. Optional ports on expansion cards *
11. Flex IO *	24. Kensington Security Slot
12. HDMI	25. Power-in
13. 2x DisplayPort	

Notes:

- Items with \* are only available on selected models

## PERFORMANCE

### Processor

#### Processor Family

Up to one 125W Intel® Core™ i5 / i7 / i9 (12th Gen), Intel® Core™ i3 / i5 / i7 / i9 (13th Gen), or Intel® Core™ i5 / i7 / i9 (14th Gen) processor; supports up to 24 cores; up to 6GHz.

#### Processor\*\*[1]

Processor Name	Cores	Threads	Base Frequency	Max Frequency	Cache	Memory Support	Processor Graphics
Core i5-12500	6 (6 P-core + 0 E-core)	12	P-core 3.0GHz	P-core 4.6GHz	18MB	DDR5-4800	Intel® UHD Graphics 770
Core i7-12700	12 (8 P-core + 4 E-core)	20	P-core 2.1GHz / E-core 1.6GHz	Max Turbo up to 4.9GHz / P-core 4.8GHz / E-core 3.6GHz	25MB	DDR5-4800	Intel® UHD Graphics 770
Core i9-12900K	16 (8 P-core + 8 E-core)	24	P-core 3.2GHz / E-core 2.4GHz	Max Turbo up to 5.2GHz / P-core 5.1GHz / E-core 3.9GHz	30MB	DDR5-4800	Intel® UHD Graphics 770
Core i3-13100	4 (4 P-core + 0 E-core)	8	P-core 3.4GHz	P-core 4.5GHz	12MB	DDR5-4800	Intel® UHD Graphics 730
Core i5-13500	14 (6 P-core + 8 E-core)	20	P-core 2.5GHz / E-core 1.8GHz	P-core 4.8GHz / E-core 3.5GHz	24MB	DDR5-4800	Intel® UHD Graphics 770
Core i5-13600K	14 (6 P-core + 8 E-core)	20	P-core 3.5GHz / E-core 2.6GHz	P-core 5.1GHz / E-core 3.9GHz	24MB	DDR5-5600	Intel® UHD Graphics 770
Core i7-13700	16 (8 P-core + 8 E-core)	24	P-core 2.1GHz / E-core 1.5GHz	Max Turbo up to 5.2GHz / P-core 5.1GHz / E-core 4.1GHz	30MB	DDR5-5600	Intel® UHD Graphics 770
Core i7-13700K	16 (8 P-core + 8 E-core)	24	P-core 3.4GHz / E-core 2.5GHz	Max Turbo up to 5.4GHz / P-core 5.3GHz / E-core 4.2GHz	30MB	DDR5-5600	Intel® UHD Graphics 770
Core i9-13900	24 (8 P-core + 16 E-core)	32	P-core 2.0GHz / E-core 1.5GHz	Max Turbo up to 5.6GHz / P-core 5.2GHz / E-core 4.2GHz	36MB	DDR5-5600	Intel® UHD Graphics 770
Core i9-13900K	24 (8 P-core + 16 E-core)	32	P-core 3.0GHz / E-core 2.2GHz	Max Turbo up to 5.8GHz / P-core 5.4GHz / E-core 4.3GHz	36MB	DDR5-5600	Intel® UHD Graphics 770
Core i5-14500	14 (6 P-core + 8 E-core)	20	P-core 2.6GHz / E-core 1.9GHz	P-core 5.0GHz / E-core 3.7GHz	24MB	DDR5-4800	Intel® UHD Graphics 770
Core i7-14700	20 (8 P-core + 12 E-core)	28	P-core 2.1GHz / E-core 1.5GHz	Max Turbo up to 5.4GHz / P-core 5.3GHz / E-core 4.2GHz	33MB	DDR5-5600	Intel® UHD Graphics 770
Core i7-14700K	20 (8 P-core + 12 E-core)	28	P-core 3.4GHz / E-core 2.5GHz	Max Turbo up to 5.6GHz / P-core 5.5GHz / E-core 4.3GHz	33MB	DDR5-5600	Intel® UHD Graphics 770
Core i9-14900	24 (8 P-core + 16 E-core)	32	P-core 2.0GHz / E-core 1.5GHz	Max Turbo up to 5.8GHz / P-core 5.4GHz / E-core 4.3GHz	36MB	DDR5-5600	Intel® UHD Graphics 770
Core i9-14900K	24 (8 P-core + 16 E-core)	32	P-core 3.2GHz / E-core 2.4GHz	Max Turbo up to 6.0GHz / P-core 5.6GHz / E-core 4.4GHz	36MB	DDR5-5600	Intel® UHD Graphics 770

#### Processor Sockets

1x FCLGA1700

#### Notes:

[1] Intel® Max Turbo frequency will vary depending on application workload and the hardware and software configurations, see

<http://www.intel.com/technology/turboboost/> for more information.

## Operating System

### Operating System

- Windows® 11 Pro
- Windows® 11 Home
- Windows® 11 Home Single Language
- Ubuntu Linux LTS
- Red Hat Enterprise Linux 9.4 (certified only, for detailed and latest information, please visit [Red Hat Certified Hardware](#))<sup>[1]</sup>
- No preload operating system

Notes:

[1] Red Hat Enterprise Linux 9.3 certification will be available after May 2024.

## Graphics

### Integrated Graphics\*\*

- Intel® UHD Graphics 730
- Intel® UHD Graphics 770

### Discrete Graphics Support<sup>[1]</sup>

Supports up to two NVIDIA® RTX A2000 12GB

### Discrete Graphics Offering

Graphics	Memory	Power	Connector	Form Factor	SLI / NVLink
NVIDIA® T400 4GB	4GB GDDR6	40W	3x miniDP 1.4	Single slot	None
NVIDIA® T1000	4GB GDDR6	50W	4x miniDP 1.4	Single slot	None
NVIDIA® T1000 8GB	8GB GDDR6	50W	4x miniDP 1.4	Single slot	None
NVIDIA® RTX A2000 12GB	12GB GDDR6	70W	4x miniDP 1.4a	Dual slot	None
NVIDIA® RTX A400	4GB GDDR6	50W	4x miniDP 1.4a	Single slot	None
NVIDIA® RTX A1000	8GB GDDR6	50W	4x miniDP 1.4a	Single slot	None

Notes:

[1] Discrete graphics support may vary by configurations such as processor selection or power supply wattage.

## Monitor Support

### Monitor Support

Onboard graphics supports up to 4 independent displays via onboard two DP, one HDMI® and one optional USB-C®; the number of maximum monitors also depends on the discrete graphic card in use

## Chipset

### Chipset

Intel® W680 chipset

## Memory

### Max Memory<sup>[1]</sup>

Up to 128GB (4x 32GB DDR5 UDIMM)

### Memory Type\*\*<sup>[2]</sup>

- DDR5-4400 UDIMM ECC, maximum transfer speeds of up to 4400 MT/s
- DDR5-4400 UDIMM non-ECC, maximum transfer speeds of up to 4400 MT/s

### Memory Slots

Four DDR5 UDIMM slots, dual-channel capable

### Memory Protection

ECC on models with ECC DIMMs and ECC capable processor

Notes:

[1] The max memory is based on the test results with current Lenovo® memory offerings.

[2] 4400MT/s is the maximum operating speed, memory operating speed varies depending on memory configuration:  
 1x 8GB / 2x 8GB / 1x 16GB / 2x 16GB / 2x 32GB configurations run at 4400 MT/s;  
 4x 8GB / 4x 16GB configurations run at 4000 MT/s;  
 4x 32GB configuration runs at 3600 MT/s.

## Storage

### Storage Support<sup>[1]</sup>

Up to 2x 3.5" SATA HDD; also supports up to 3x M.2 SSD (two by onboard, one by M.2 to PCIe<sup>®</sup> adapter)

- 3.5" HDD up to 4TB each
- Onboard M.2 SSD up to 4TB each
- M.2 SSD by M.2 to PCIe<sup>®</sup> adapter up to 2TB

### Storage Type

Disk Type	Interface	RPM	Offering	Security
3.5" SATA HDD	SATA 6Gb/s	7.2K	1TB / 2TB / 4TB	-
M.2 2280 SSD for Onboard M.2 slots	PCIe <sup>®</sup> NVMe <sup>®</sup> , PCIe <sup>®</sup> 4.0 x4	-	256GB / 512GB / 1TB	Opal 2.0
M.2 2280 SSD for Onboard M.2 slots	PCIe <sup>®</sup> NVMe <sup>®</sup> , PCIe <sup>®</sup> 4.0 x4 Performance	-	512GB / 1TB / 2TB / 4TB	Opal 2.0
M.2 2280 SSD for single M.2 to PCIe <sup>®</sup> adapter	PCIe <sup>®</sup> NVMe <sup>®</sup> , PCIe <sup>®</sup> 4.0 x4 <sup>[2]</sup>	-	256GB / 512GB / 1TB / 2TB	Opal 2.0

### Storage Controllers<sup>\*\*\*</sup>

Storage Controller	Type	Interface	RAID	Cache
Integrated SATA controller	Standard	SATA 6.0Gb/s	0/1	None
Integrated NVMe <sup>®</sup> controller	Standard	PCIe <sup>®</sup> NVMe <sup>®</sup>	0/1	None

Notes:

[1] The storage capacity supported is based on the test results with current Lenovo<sup>®</sup> storage offerings.

[2] M.2 2280 SSD is PCIe<sup>®</sup> 4.0 x4, and the M.2 slot on single M.2 to PCIe<sup>®</sup> adapter are PCIe<sup>®</sup> 3.0 x4. See M.2 Slots section for more information.

## Removable Storage

### Optical Support

Optional one 9.0mm optical drive, DVD-ROM, DVD±RW, and Blu-ray

### Card Reader

- SD card reader
- No card reader

## Multi-Media

### Audio Chip

High Definition (HD) Audio, Realtek<sup>®</sup> ALC897Q-CG codec

### Speakers

Single speaker, 2W x1

## Power Supply

### Power Supply<sup>\*\*</sup>

Power	Type	Efficiency	Key Features
500W	Fixed	92%	Autosensing, 80 PLUS Platinum qualified
750W	Fixed	92%	Autosensing, 80 PLUS Platinum qualified

## DESIGN

### Mechanical

**Form Factor**

Tower (17L)

**Dimensions (WxDxH)<sup>[1]</sup>**

170 x 315.35 x 376 mm (6.7 x 12.4 x 14.8 inches, with feet)

**Weight<sup>[2]</sup>**

9.67 kg (21.32 lbs, maximum configuration)

**Bays**

Three internal disk bays, up to two 3.5" bays plus one 2.5" bay:

- Bay 1 supports one 3.5" HDD, standard; or one 2.5" HDD / SSD, optional
- Bay 2 supports one 3.5" HDD or 2.5" HDD / SSD, optional
- Bay 3 supports one 2.5" HDD / SSD, optional
- Front Access HDD Bay supports one 3.5" HDD or 2.5" HDD / SSD, optional, occupies Bay 2 location<sup>[3]</sup>

**Expansion Slots**Supports four PCIe<sup>®</sup> slots with two PCIe<sup>®</sup> 4.0 x16 and two PCIe<sup>®</sup> 3.0 x1.

- Slot 1: PCIe<sup>®</sup> 4.0 x16, full height, full length, 75W, double-width
- Slot 2: PCIe<sup>®</sup> 3.0 x1, full height, half length, 25W
- Slot 3: PCIe<sup>®</sup> 4.0 x16 (x4 lanes), full height, half length, 25W
- Slot 4: PCIe<sup>®</sup> 3.0 x1, full height, half length, 25W

**Notes:**

[1] The system dimensions may vary depending on configurations.

[2] The system weight is approximate and based on results in Lenovo<sup>®</sup> lab, which varies depending on the source of component, variance of the distribution of each component, and manufacturing process. It may not be the exact weight for each specific model.

[3] 3.5" bay and Front Access HDD Bay need optional 3.5" to 2.5" HDD bracket kit. 2.5" drive is for customer-own configuration. None of configurable 2.5" drive options are provided.

## CONNECTIVITY

### Network

**Onboard Ethernet**Gigabit Ethernet, Intel<sup>®</sup> Ethernet Connection I219-LM, 1x RJ-45, supports Wake-on-LAN**Optional Ethernet**Up to two additional PCIe<sup>®</sup> x1 Ethernet adapters; or one PCIe<sup>®</sup> x4 plus one PCIe<sup>®</sup> x1 Ethernet adapter, up to five additional GbE ports

- Gigabit Ethernet, Intel<sup>®</sup> I210-T1, 1x RJ-45, PCIe<sup>®</sup> x1
- Gigabit Ethernet, Intel<sup>®</sup> I350-T2, 2x RJ-45, PCIe<sup>®</sup> x4
- Gigabit Ethernet, Intel<sup>®</sup> I350-T4, 4x RJ-45, PCIe<sup>®</sup> x4
- Gigabit Ethernet, Realtek<sup>®</sup> RTL8168H, 1x RJ-45, PCIe<sup>®</sup> x1

**WLAN + Bluetooth<sup>®</sup>**

- Intel<sup>®</sup> Wi-Fi<sup>®</sup> 6E AX211, 802.11ax 2x2 Wi-Fi<sup>®</sup> + Bluetooth<sup>®</sup> 5.3, Intel<sup>®</sup> vPro<sup>®</sup> technology support
- No WLAN and Bluetooth<sup>®</sup>

### Ports<sup>[1]</sup>

**Front Ports**

- 1x USB-C<sup>®</sup> (USB 10Gbps / USB 3.2 Gen 2), data transfer only
- 2x USB-A (USB 5Gbps / USB 3.2 Gen 1)
- 2x USB-A (USB 10Gbps / USB 3.2 Gen 2)
- 1x headphone / microphone combo jack (3.5mm)
- 1x microphone (3.5mm)

**Rear Ports<sup>[2]</sup>**

- 4x USB-A (USB 5Gbps / USB 3.2 Gen 1), one supports Smart Power On
- 1x HDMI<sup>®</sup> 2.1 TMDS
- 2x DisplayPort<sup>™</sup> 1.4
- 1x Ethernet (RJ-45)
- 1x line-out (3.5mm)

**Optional Rear Ports**

- 1x USB-C® (USB 5Gbps / USB 3.2 Gen 1), with DisplayPort™ 2.1 (Flex IO)
- 1x HDMI® 2.1 TMDS (Flex IO)
- 1x DP 1.2 (Flex IO)
- 1x VGA (Flex IO)
- 1x parallel (via cable and PCIe® bracket)
- 1x USB-C® (USB 20Gbps / USB 3.2 Gen 2x2), support data transfer, via USB-C® PCIe® x4 card
- 2x USB-A (Hi-Speed USB / USB 2.0), via cable and PCIe® bracket
- 2x USB-A (USB 5Gbps / USB 3.2 Gen 1), via additional PCIe® adapter
- 1x serial (via cable)
- 4x serial (via 4-port serial expansion card, PCIe® x1)
- 2x PS/2 (via cable)

---

**Notes:**

[1] The transfer speed of the ports will vary and, depending on many factors, such as the processing speed of the host device, file attributes, and other factors related to system configuration and your operating environment, will be slower than the theoretical speed.

[2] For video ports on discrete graphics, please see graphics section.

## SECURITY & PRIVACY

### Security

#### Security Chip

Discrete TPM 2.0, TCG certified, FIPS 140-2 certified

#### Physical Locks

- (Optional) E-lock
- Kensington® Security Slot™, 3 x 7 mm
- Padlock Loop

#### Chassis Intrusion Switch

- Chassis intrusion switch
- No chassis intrusion switch

#### BIOS Security

- Administrator password
- Power-on password
- Self-healing BIOS

## MANAGEABILITY

### System Management

#### System Management<sup>[1]</sup>

- Intel® vPro® Enterprise with Intel® AMT 16
- Non-vPro®

---

**Notes:**

[1] Intel® vPro® offers a superset of DASH's defined capabilities.

## SERVICE

### Warranty<sup>[1]</sup>

#### Base Warranty\*\*

- 1-year limited onsite service
- 2-year limited onsite service
- 3-year limited onsite service
- No base warranty

---

**Notes:**

[1] The warranty upgrades may be bundled with some models, please check the "Included upgrade" column in the specific

model's configurations. For more service extensions, please go to <https://smartfind.lenovo.com/>. To learn more details of warranty policy, please access <https://support.lenovo.com/warrantylookup/warrantypolicy>.

## OPERATING REQUIREMENTS

### Operating Environment

#### Temperature

- Operating: 10°C (50°F) to 35°C (95°F)
- Storage: -40°C (-40°F) to 60°C (140°F)

#### Altitude

- Operating: 0 m (0 ft) to 3048 m (10,000 ft)
- Storage: 0 m (0 ft) to 12192 m (40,000 ft)

#### Relative Humidity

- Operating: 20% to 80%
- Storage: 10% to 90%

## ENVIRONMENTAL

### Sustainability

#### Material<sup>[1]</sup>

- 85% PCC ABS bezel
- 95% PCC ABS wired USB keyboard/mouse top/bottom cover
- 90% PIC recycled plastic EPE cushion
- 30% OBP used in bag
- FSC certified paper in packaging

Notes:

- [1] PCC: Post Consumer Content, recycled materials from customers.  
PIC: Post Industry Content, recycled materials from internal factories.  
EPE: Expanded Polyethylene.  
OBP: Ocean Bound Plastic, reducing plastic spill into the sea.  
FSC: Forest Stewardship Council.

## CERTIFICATIONS

### Green Certifications<sup>[1]</sup>

#### Green Certifications

- (Optional) ENERGY STAR® 8.0
- (Optional) EPEAT™ Gold Registered
- ErP Lot 3
- RoHS compliant
- TCO Certified 9.0

Notes:

- [1] The items listed under the "Green Certifications" section may not only refer to certification but also registration or self-declaration. For ESG & regulatory compliance documents, please visit <https://compliance.lenovo.com>.

### ISV Certifications

#### ISV Certifications

Please visit [ISV certifications for Lenovo® Workstations](#)

- Feature with \*\* means that only one offering listed under the feature is configured on selected models.
- Feature with \*\*\* means that one or more offerings listed under the feature could be configured on selected models.
- Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not responsible for photographic or typographical errors. LENOVO PROVIDES THIS PUBLICATION "AS IS,"

WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow disclaimer of express or implied warranties in certain transactions, therefore this disclaimer may not apply to you.

- The specifications on this page may not be available in all regions, and may be changed or updated without notice.



