


OVERVIEW



1. Power button	8. Line-out (3.5mm)
2. Card reader	9. Serial *
3. 4x USB 3.2 Gen 1	10. 2x PS/2 ports (keyboard / mouse)
4. Headphone / microphone combo jack (3.5mm)	11. 2x USB 2.0
5. 2x Flex bay	12. 4x USB 3.2 Gen 1
6. Microphone (3.5mm)	13. 2x Ethernet (RJ-45)
7. Line-in (3.5mm)	

Notes:

- Items with * are only available on selected models

PERFORMANCE

Processor

Processor Family

Up to two 165W Gen 1 or Gen 2 Intel® Xeon® Scalable family processors, Bronze, Silver, Gold, or Platinum

Processor**^[1]

Processor Name	Cores	Threads	Base Frequency	Max Frequency	Cache	Memory Support
Xeon W-3223	8	16	3.5GHz	4.0GHz	16.5MB	DDR4-2666
Xeon W-3225	8	16	3.7GHz	4.3GHz	16.5MB	DDR4-2666
Xeon Bronze 3104	6	6	1.7GHz	-	8.25MB	DDR4-2133
Xeon Bronze 3106	8	8	1.7GHz	-	11MB	DDR4-2133
Xeon Bronze 3204	6	6	1.9GHz	1.9GHz	8.25MB	DDR4-2133
Xeon Bronze 3206R	8	8	1.9GHz	1.9GHz	11MB	DDR4-2133
Xeon Silver 4108	8	16	1.8GHz	3.0GHz	11MB	DDR4-2400
Xeon Silver 4109T	8	16	2.0GHz	3.0GHz	11MB	DDR4-2400
Xeon Silver 4110	8	16	2.1GHz	3.0GHz	11MB	DDR4-2400
Xeon Silver 4112	4	8	2.6GHz	3.0GHz	8.25MB	DDR4-2400
Xeon Silver 4114	10	20	2.2GHz	3.0GHz	13.75MB	DDR4-2400
Xeon Silver 4114T	10	20	2.2GHz	3.0GHz	13.75MB	DDR4-2400
Xeon Silver 4116	12	24	2.1GHz	3.0GHz	16.5MB	DDR4-2400
Xeon Silver 4208	8	16	2.1GHz	3.2GHz	11MB	DDR4-2400
Xeon Silver 4209T	8	16	2.2GHz	3.2GHz	11MB	DDR4-2400
Xeon Silver 4210	10	20	2.2GHz	3.2GHz	13.75MB	DDR4-2400
Xeon Silver 4210R	10	20	2.4GHz	3.2GHz	13.75MB	DDR4-2400
Xeon Silver 4214	12	24	2.2GHz	3.2GHz	16.5MB	DDR4-2400
Xeon Silver 4214R	12	24	2.4GHz	3.5GHz	16.5MB	DDR4-2400
Xeon Silver 4215	8	16	2.5GHz	3.5GHz	11MB	DDR4-2400
Xeon Silver 4215R	8	16	3.2GHz	4.0GHz	11MB	DDR4-2400
Xeon Silver 4216	16	32	2.1GHz	3.2GHz	22MB	DDR4-2400
Xeon Gold 5115	10	20	2.4GHz	3.2GHz	13.75MB	DDR4-2400
Xeon Gold 5118	12	24	2.3GHz	3.2GHz	16.5MB	DDR4-2400
Xeon Gold 5120	14	28	2.2GHz	3.2GHz	19.25MB	DDR4-2400
Xeon Gold 5120T	14	28	2.2GHz	3.2GHz	19.25MB	DDR4-2400
Xeon Gold 5122	4	8	3.6GHz	3.7GHz	16.5MB	DDR4-2666
Xeon Gold 5215	10	20	2.5GHz	3.4GHz	13.75MB	DDR4-2666
Xeon Gold 5217	8	16	3.0GHz	3.7GHz	11MB	DDR4-2666
Xeon Gold 5218	16	32	2.3GHz	3.9GHz	22MB	DDR4-2666
Xeon Gold 5220	18	36	2.2GHz	3.9GHz	24.75MB	DDR4-2666
Xeon Gold 5222	4	8	3.8GHz	3.9GHz	16.5MB	DDR4-2933
Xeon Gold 6128	6	12	3.4GHz	3.7GHz	19.25MB	DDR4-2666
Xeon Gold 6130	16	32	2.1GHz	3.7GHz	22MB	DDR4-2666
Xeon Gold 6134	8	16	3.2GHz	3.7GHz	24.75MB	DDR4-2666
Xeon Gold 6136	12	24	3.0GHz	3.7GHz	24.75MB	DDR4-2666
Xeon Gold 6138	20	40	2.0GHz	3.7GHz	27.5MB	DDR4-2666
Xeon Gold 6142	16	32	2.6GHz	3.7GHz	22MB	DDR4-2666

Xeon Gold 6146	12	24	3.2GHz	4.2GHz	24.75MB	DDR4-2666
Xeon Gold 6148	20	40	2.4GHz	3.7GHz	27.5MB	DDR4-2666
Xeon Gold 6226	12	24	2.7GHz	3.7GHz	19.25MB	DDR4-2933
Xeon Gold 6226R	16	32	2.9GHz	3.9GHz	22MB	DDR4-2933
Xeon Gold 6230	20	40	2.1GHz	3.9GHz	27.5MB	DDR4-2933
Xeon Gold 6234	8	16	3.3GHz	4.0GHz	24.75MB	DDR4-2933
Xeon Gold 6238T	22	44	1.9GHz	3.7GHz	30.25MB	DDR4-2933
Xeon Gold 6240R	24	48	2.4GHz	4.0GHz	35.75MB	DDR4-2933
Xeon Gold 6242	16	32	2.8GHz	3.9GHz	22MB	DDR4-2933
Xeon Gold 6244	8	16	3.6GHz	4.4GHz	24.75MB	DDR4-2933
Xeon Gold 6246	12	24	3.3GHz	4.2GHz	24.75MB	DDR4-2933
Xeon Gold 6248	20	40	2.5GHz	3.9GHz	27.5MB	DDR4-2933
Xeon Platinum 8160T	24	48	2.1GHz	3.7GHz	33MB	DDR4-2666

Processor Sockets

2x FCLGA3647

Notes:

[1] Intel® Max Turbo frequency will vary depending on application workload and the hardware and software configurations, see

<http://www.intel.com/technology/turboboost/> for more information.

Operating System

Operating System**

- Windows® 11 Pro for Workstations
- Windows® 11 DG Windows® 10 Pro 64 for Workstations
- Windows® 10 Pro 64 for Workstations
- Red Hat Enterprise Linux 8.5 (certified only, for detailed and latest information, please visit [Red Hat Certified Hardware](#))
- Ubuntu Linux LTS
- No preload operating system

Graphics

Discrete Graphics Support^[1]

Supports up to two NVIDIA® Quadro® RTX 8000 with NVLink

Discrete Graphics Offering***

Graphics	Memory	Power	Connector	Form Factor	SLI / NVLink
NVIDIA® T400	2GB GDDR6	40W	3x miniDP 1.4	Single slot	None
NVIDIA® T400 4GB	4GB GDDR6	40W	3x miniDP 1.4	Single slot	None
NVIDIA® T600	4GB GDDR6	40W	4x miniDP 1.4	Single slot	None
NVIDIA® T1000	4GB GDDR6	50W	4x miniDP 1.4	Single slot	None
NVIDIA® T1000 8GB	8GB GDDR6	50W	4x miniDP 1.4	Single slot	None
NVIDIA® RTX A2000	6GB GDDR6	70W	4x miniDP 1.4a	Dual slot	None
NVIDIA® RTX A2000 12GB	12GB GDDR6	70W	4x miniDP 1.4a	Dual slot	None
NVIDIA® RTX A4000	16GB GDDR6 with ECC	140W	4x DP 1.4a	Single slot	None
NVIDIA® RTX A4500	20GB GDDR6 with ECC	200W	4x DP 1.4	Dual slot	NVLink
NVIDIA® RTX A5000	24GB GDDR6 with ECC	230W	4x DP 1.4a	Dual slot	NVLink
NVIDIA® RTX A5500	24GB GDDR6 with ECC	230W	4x DP 1.4a	Dual slot	NVLink
Quadro® GP100	16GB HBM2	235W	1x DVI-D DL, 4x DP	Dual slot	NVLink
Quadro® GV100	32GB HBM2	250W	4x DP 1.4	Dual slot	NVLink

Quadro® P1000	4GB GDDR5	50W	4x miniDP 1.4	Single slot	None
Quadro® P2000	5GB GDDR5	75W	4x DP	Single slot	None
Quadro® P2200	5GB GDDR5	75W	4x DP 1.4	Single slot	None
Quadro® P400	2GB GDDR5	30W	3x miniDP 1.4	Single slot	None
Quadro® P4000	8GB GDDR5	120W	4x DP 1.4	Single slot	None
Quadro® P5000	16GB GDDR5X	180W	1x DVI-D DL, 4x DP 1.4	Dual slot	SLI
Quadro® P600	2GB GDDR5	45W	4x miniDP	Single slot	None
Quadro® P6000	24GB GDDR5X	250W	1x DVI-D DL, 4x DP 1.4	Dual slot	SLI
Quadro® P620	2GB GDDR5	40W	4x miniDP 1.4	Single slot	None
Quadro® RTX 4000	8GB GDDR6	160W	3x DP 1.4, 1x VirtualLink	Single slot	None
Quadro® RTX 5000	16GB GDDR6	265W	4x DP 1.4, 1x VirtualLink	Dual slot	NVLink
Quadro® RTX 6000	24GB GDDR6	295W	4x DP 1.4, 1x VirtualLink	Dual slot	NVLink
Quadro® RTX 8000	48GB GDDR6	295W	4x DP 1.4, 1x VirtualLink	Dual slot	NVLink

Notes:

[1] Discrete graphics support may vary by configurations such as processor selection or power supply wattage.

Monitor Support

Monitor Support

Supports multiple displays via discrete graphics, the number of maximum monitors supported depends on the graphic card in use

Chipset

Chipset

Intel® C621 chipset

Memory

Max Memory^[1]

Up to 768GB (12x 64GB RDIMM)

Memory Type**

- DDR4-2666 RDIMM ECC
- DDR4-2933 RDIMM ECC

Memory Slots

12 DDR4 DIMM slots, 12 channels capable (6 DIMM slots with 6 channels per processor)

Memory Protection

ECC

Notes:

[1] The max memory is based on the test results with current Lenovo® memory offerings.

Storage

Storage Support^{[1][2]}

Up to 6x 3.5" SATA HDD / 10x 2.5" SATA HDD / 8x 2.5" SAS HDD / 10x 2.5" SATA SSD / 4x 2.5" PCIe® SSD + 9x M.2 PCIe® SSD + 2x PCIe® AIC SSD

- 3.5" HDD up to 6TB each
- 2.5" SATA HDD up to 500GB each
- 2.5" SAS HDD up to 600GB each
- 2.5" SATA SSD up to 2TB each
- M.2 SSD up to 2TB each
- 2.5" PCIe® SSD up to 1.5TB each
- PCIe® AIC SSD up to 480GB each

Storage Type***

Disk Type	Interface	RPM	Offering
2.5" SATA HDD	SATA 6Gb/s	7.2K	500GB / 500GB FIPS
3.5" SATA HDD	SATA 6Gb/s	7.2K	1TB / 2TB / 4TB / 6TB
2.5" PCIe® SSD	PCIe® NVMe®	-	1.5TB
2.5" SAS HDD	SAS 12Gb/s	10K	300GB / 600GB
2.5" SATA SSD	SATA 6Gb/s	-	256GB / 512GB / 1TB / 2TB
M.2 PCIe® SSD	PCIe® NVMe®	-	256GB / 512GB / 1TB / 2TB
PCIe® AIC SSD	PCIe® NVMe®	-	480GB

Storage Controllers

Storage Controller	Type	Interface	RAID	Cache
Onboard Intel® RSTe SATA RAID	Standard	SATA 6.0Gb/s	0/1/10/5	None
9440-8i PCIe®	Optional	SAS 12.0Gb/s, SATA 6.0Gb/s	0/1/10/5	None
9460-16i PCIe®	Optional	SAS 12.0Gb/s, SATA 6.0Gb/s	0/1/10/5/6	4GB DDR4, SuperCap
NVMe® Basic	Optional	PCIe® NVMe®	0/1/10	None
NVMe® Premium	Optional	PCIe® NVMe®	0/1/10/5	None
NVMe® for Intel® SSD	Optional	PCIe® NVMe®	0/1/10/5	None

Notes:

[1] The storage capacity supported is based on the test results with current Lenovo® storage offerings.

[2] For detailed storage bays information and how to upgrade optional drives for ThinkStation® products, please visit [ThinkStation® Storage Upgrade Guide](#)

Removable Storage

Optical Support

Up to two HH or 9.0mm optical drive, DVD-ROM, DVD±RW, and Blu-ray

Card Reader

- 15-in-1 card reader
- SD card reader
- No card reader

Multi-Media

Audio Chip

High Definition (HD) Audio, Realtek® ALC662 codec

Speakers

Single speaker

Power Supply

Power Supply**

Power	Type	Efficiency	Key Features
690W	Fixed	92%	Autosensing, 80 PLUS Platinum qualified
900W	Fixed	92%	Autosensing, 80 PLUS Platinum qualified
1000W	Fixed	92%	Autosensing, 80 PLUS Platinum qualified

DESIGN

Mechanical

Form Factor

Tower (36L)

Dimensions (WxDxH)^[1]

175 x 485 x 446 mm (6.89 x 19.1 x 17.6 inches, with feet)

Weight^[2]

25.7 kg (56.7 lbs, maximum configuration)

Bays^[3]

- 2x 3.5" disk bay (standard)
- 4x 3.5" disk bay (optional):
2 bays come with 3rd disk or Storage Bay Upgrade Kit
2 bays via flex bay

Flex Bays

2x flex bays, supports the following:

- 2x half-height optical drives
- 2x 5.25" 9.0mm optical drives
- 1x 5.25" 9.0mm optical drive + 2x 3.5"/2.5" SATA SSD/HDD
- 1x 3.5"/2.5" SATA SSD/HDD with Front Access Storage Enclosure
- 1x flex module for the following options:

Tray 1: 9.0mm optical

Tray 2: 15-in-1 USB 3.1 Gen 1 reader, 2x Thunderbolt™, or 4-digit diagnostic display

Port 1 and 2: Front USB 3.1 Gen 1 Type-C or eSATA

M.2 Slots

Up to 9x M.2 SSD:

- 2 via onboard slots
- 4 via Quad M.2 to PCIe® adapter
- 3 via Single M.2 to PCIe® adapter

Expansion Slots

Supports 5 PCIe® slots plus one PCI slot.

- Slot 1: PCIe® 3.0 x16, full height, full length, 75W, by CPU 2
- Slot 2: PCIe® 3.0 x16, full height, full length, 75W, double-width, by CPU 1
- Slot 3: PCIe® 3.0 x8, full height, full length, 25W, by CPU 1
- Slot 4: PCIe® 3.0 x16, full height, full length, 75W, double-width, by CPU 1
- Slot 5: PCI, full height, full length, 25W
- Slot 6: PCIe® 3.0 x4, full height, half length, 25W, by PCH

Notes:

[1] The system dimensions may vary depending on configurations.

[2] The system weight is approximate and based on results in Lenovo® lab, which varies depending on the source of component, variance of the distribution of each component, and manufacturing process. It may not be the exact weight for each specific model.

[3] 4x 3.5" bay can also support up to 8x 2.5" SSD / HDD with 2 disks per bay. Additional 9440-8i or 9460-16i PCIe® adapter and other parts are needed.

CONNECTIVITY

Network

Onboard Ethernet

Two Gigabit Ethernet, Intel® Ethernet Connection I219-LM and I210-AT, 2x RJ-45, supports Wake-on-LAN

Optional Ethernet

Two additional Ethernet adapters support, up to four additional 10 GbE ports

- Gigabit Ethernet, Intel® I210-T1, 1x RJ-45, PCIe® x1
- Gigabit Ethernet, Intel® I350-T2, 2x RJ-45, PCIe® x4
- Gigabit Ethernet, Intel® I350-T4, 4x RJ-45, PCIe® x4
- Gigabit Ethernet, Bitland BN8E88, 1x RJ-45, PCIe® x1
- Gigabit Ethernet, Broadcom BCM5719, 4x RJ-45, PCIe® x4
- Gigabit Ethernet, Broadcom BCM5720, 2x RJ-45, PCIe® x1
- 5 Gigabit Ethernet, Marvell AQtion AQN-108, 1x RJ-45, PCIe® x1
- 10 Gigabit Ethernet, Intel® X540-T2, 2x RJ-45, PCIe® x8
- 10 Gigabit Ethernet, Intel® X550-T2, 2x RJ-45, PCIe® x4
- 10 Gigabit Ethernet, Intel® X710-DA2, 2x SFP+, PCIe® x8
- 10 Gigabit Ethernet, Marvell AQtion AQN-107, 1x RJ-45, PCIe® x4

WLAN + Bluetooth®

- Intel® Dual-Band Wireless-AC 8265, 802.11ac Dual-Band 2x2 Wi-Fi® + Bluetooth® 4.2
- Intel® Wi-Fi® 6E AX210, 802.11ax 2x2 Wi-Fi® + Bluetooth® 5.1 (Bluetooth® 5.3 hardware ready), Intel® vPro® technology support
- No WLAN and Bluetooth®

Ports^[1]**Front Ports**

- 1x USB 3.2 Gen 1 (Always On and fast charge)
- 3x USB 3.2 Gen 1
- 1x headphone / microphone combo jack (3.5mm)

Optional Front Ports^{*}**

- 2x Thunderbolt™ 3 (with flex module, USB-C® form, one supports video-out)
- 1x USB-C® 3.2 Gen 1 (support data transfer, with flex module)
- 1x eSATA (with flex module)

Rear Ports^[2]

- 2x USB 2.0
- 4x USB 3.2 Gen 1
- 1x line-in (3.5mm)
- 1x line-out (3.5mm)
- 1x microphone (3.5mm)
- 2x Ethernet (RJ-45)
- 2x PS/2 ports (keyboard / mouse)

Optional Rear Ports^{*}**

- 1x Thunderbolt™ 3
- 2x USB-C® 3.2 Gen 2 (support data transfer, via 2-port USB-C® expansion card)
- 1x serial

Notes:

[1] The transfer speed of following ports will vary and, depending on many factors, such as the processing speed of the host device, file attributes and other factors related to system configuration and your operating environment, will be slower than theoretical speed.

USB 2.0: 480 Mbit/s;

USB 3.2 Gen 1 (SuperSpeed USB 5Gbps, formerly USB 3.0 / USB 3.1 Gen 1): 5 Gbit/s;

USB 3.2 Gen 2 (SuperSpeed USB 10Gbps, formerly USB 3.1 Gen 2): 10 Gbit/s;

USB4® 20Gbps / USB 3.2 Gen 2x2 (SuperSpeed USB 20Gbps): 20 Gbit/s;

USB4® 40Gbps (USB 40Gbps): 40 Gbit/s;

Thunderbolt™ 3/4: 40 Gbit/s.

[2] For video ports on discrete graphics, please see graphics section.

SECURITY & PRIVACY**Security****Security Chip**

Discrete TPM 2.0, TCG certified, FIPS 140-2 certified

Physical Locks

- (Optional) Access panel lock kit with common key
- (Optional) Access panel lock kit with unique key
- Kensington® Security Slot™, 3 x 7 mm

Chassis Intrusion Switch

Chassis intrusion switch

BIOS Security

- Administrator password
- Power-on password

MANAGEABILITY

System Management

System Management^[1]

Intel® vPro® with Intel® AMT 11

Notes:

[1] Intel® vPro® offers a superset of DASH's defined capabilities.

Diagnostic

Diagnostic

- ThinkStation® Diagnostics
- Photo-audio transfer with Lenovo® PC Diagnostics for Android™ and iOS
- Front 4-digit diagnostic
- Lenovo® UEFI Bootable Diagnostics
- None

SERVICE

Warranty^[1]

Base Warranty**

- 1-year limited onsite service
- 3-year limited onsite service

Notes:

[1] The warranty upgrades may be bundled with some models, please check the "Included upgrade" column in the specific model's configurations. For more service extensions, please go to <https://smartfind.lenovo.com/>. To learn more details of warranty policy, please access <https://pcsupport.lenovo.com/warranty>.

ENVIRONMENTAL

Operating Environment

Temperature

- Operating: 10°C (50°F) to 35°C (95°F)
- Storage: -40°C (-40°F) to 60°C (140°F)

Altitude

- Operating: 0 m (0 ft) to 3048 m (10,000 ft)
- Storage: 0 m (0 ft) to 12192 m (40,000 ft)

Relative Humidity

- Operating: 20% to 80%
- Storage: 10% to 90%

CERTIFICATIONS

Green Certifications^[1]

Green Certifications

- (Optional) ENERGY STAR® 8.0
- ENERGY STAR® 8.0 (on model 30BA00EQUS)
- EPEAT™ Silver Registered
- GREENGUARD®
- RoHS compliant

Notes:

[1] The items listed under the "Green Certifications" section may not only refer to certification but also registration or self-declaration.

ISV Certifications

ISV Certifications

Please visit www.thinkworkstations.com/isv-certifications/

- Feature with ** means that only one offering listed under the feature is configured on selected models.
- Feature with *** means that one or more offerings listed under the feature could be configured on selected models.
- Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not responsible for photographic or typographical errors. LENOVO PROVIDES THIS PUBLICATION “AS IS,” WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow disclaimer of express or implied warranties in certain transactions, therefore this disclaimer may not apply to you.
- The specifications on this page may not be available in all regions, and may be changed or updated without notice.

