Lenovo ThinkVision LT1713p Specifications

Product Specifications Reference (PSREF)

Name	**LT1713p Square Flat Panel Monitor**
Case color	**Business black**
Type-model	**60B3HAR2US**
Panel	TFT-LCD, twisted nematic (TN), LED backlight
Viewable image size	**17.0"** (**432mm**) diagonal
Max view area (W x H)	13.3" x 10.6" (337.9mm x 270.3mm)
Optimum resolution	**1280x1024**
Aspect ratio	5:4
Pixel pitch (mm)	0.264mm
Dot/Pixel per Inch	96 dpi
Brightness	250 nits or cd/m^2 (typical)
Contrast ratio	1000:1 (typical)
Pixel response time	5ms (typical)
Color gamut	72%
Viewing angle at 10:1 CR	170° (+/- 85°) horizontal, 160° (+/- 80°) vertical
Stand	Tilt height adjustable stand
Bezel width	*Sides:* 0.60" (15.3mm); *top:* 0.73" (18.4mm); *bottom:* 1.10" (28.1mm)
Dimensions (HxWxD, including stand)	16.0" H x 14.6" W x 6.5" D; 405.7mm H x 370.0mm W x 165.2mm D
Power supply	13.0 watts typical, 16.0 watts maximum, <0.5 watts standby/suspend, universal, integrated (no external brick-like power supply)
Weight	7.90 lb; 3.60kg
Limited warranty[4]	**3 year** (includes backlight)
Available date	January 2014

VESA-compliant[2]	VESA DDC2B/CI, VESA DPMS-compliant
Power management	ENERGY STAR® 6.0
Ergonomics	ISO 9241-307
Emission standards	FCC Class B
Environmental	TCO Displays 6.0, TCO Certified Edge 1.2, WEEE, RoHS, **EPEAT™ Gold rating**
Preset resolutions	VGA: 640x350, 640x480, 640x500, 720x400 SVGA: 800x600 XGA: 1024x768, 1152x864, SXGA: 1280x1024
Presets / user settings	Standard presets: 17; user settings: 22

Features

- 17-inch Square LCD monitor
- Supports SXGA 1280x1024 resolution
- Includes dual input connection for attachment to two systems concurrently (analog and digital)
- Arsenic free glass
- Supports Lenovo Tiny PC and 3rd party thin client via optional Lenovo bracket
- Microsoft® Windows® 7 certified
- Microsoft Windows 8 certified
- Microsoft Windows 8.1 certified



ThinkVision LT1713p Monitor

Viewing adjustments	*Tilt:* 22° back, -3° forward; *lift:* 4.3" (110mm)
Rotating screen	None
On screen display	On screen display with digital user controls (8 languages)
Control features	Direct access (buttons on front) for automatic image setup
Multiple input	Dual input (two different PCs attach to two different connectors; one PC shows image; select via button)
Monitor connectors	(1) VGA 15-pin D-shell, analog, blue (2) Digital Visual Interface (DVI-D), digital, white, **HDCP-compliant**
Signal cables	(1) detachable, VGA 15-pin D-shell at each end, analog, 1.8 meter (2) detachable, DVI-D at each end, digital, 1.8 meter
Mounting features	Wall or desk mounting using the Extend Arm or third-party accessories meeting the VESA FPMPMI® (100mm mount)
Security	Security keyhole for attachment of optional cable lock (Kensington® lock-compatible)
Ship group	Monitor and stand, Setup poster, Safety and Warranty Information, 1.8 meter analog signal cable, 1.8 meter digital signal cable, 1.8 meter black power cord

Limited Warranty

See details at **http://support.lenovo.com/en_US/guides-and-manuals/detail.page?DocID=UM008281**

Accessories

Kensington MicroSaver Cable Lock	73P2582
Kensington Twin Head Cable Lock	45K1620
Lenovo Easy Reach Monitor Stand	55Y9258

See details at **www.lenovo.com/support/monitoraccessories**

See all monitors at **www.lenovo.com/thinkvision**

See footnotes for important warranty information

US model announced December 17, 2013

© Lenovo