Lenovo ThinkVision LT2013s Specifications

Product Specifications Reference (PSREF)

Name	**LT2013s Wide Flat Panel Monitor**
Case color	**Business black**
Type-model	**60ABAAR1US**
Panel	TFT-LCD, twisted nematic (TN), White LED backlight
Viewable image size	**19.5"** (**494mm**) diagonal
Max view area (W x H)	17.08" x 9.30" / 433.9mm x 236.3mm
Optimum resolution	**1600x900**
Aspect ratio	16:9
Pixel pitch (mm)	.27 (H) x .26 (V) mm
Dot/Pixel per Inch	281/94 dpi
Brightness	200 nits or cd/m^2 (typical)
Contrast ratio	600:1 (typical)
Pixel response time	5ms (typical)
Color gamut	72%
Viewing angle at 10:1 CR	90° (+/- 45°) horizontal, 50° (+ 15/- 35°) vertical
Stand	Tilt stand
Bezel width	*Sides:* 0.62" (15.85mm); *top:* 0.73" (18.55mm); *bottom:* 0.73" (18.55mm)
Dimensions (HxWxD, excluding stand)	10.83" H x 18.41" W x 2.09" D; 274.8mm H x 467.0mm W x 53.0mm D
Dimensions (HxWxD, including stand)	13.50" H x 18.41" W x 6.33" D; 342.4mm H x 467.0mm W x 160.7mm D
Power supply	17 watts typical, 19 watts maximum, <0.5 watts sleep/off; <0.5 watts switch off integrated (no external brick-like power supply)
Weight	5.50 lb; 2.50kg (excluding stand)
Limited warranty[4]	**3 year** (includes backlight)
Available date	July 2013

VESA-compliant[2]	VESA DDC2B/CI, EDID 1.3
Power management	ENERGY STAR® 6.0
Ergonomics	ISO 9241-307
Emission standards	FCC Class B
Environmental	RoHS, **EPEAT™ Silver rating**

Preset resolutions	VGA: 640x350, 640x480, 720x400 SVGA: 800x600, 832x624 XGA: 1024x768, 1152x864 SXGA: 1280x1024 WXGA: 1366x768 WXGA+: 1440x900 WSXGA+: 1600x900
Presets / user settings	Presets: 24; user settings: 24

Features

- Widescreen 19.5-inch monitor
- Compliance with ENERGY STAR 6.0
- Support Lenovo Tiny PC and 3rd party thin client via optional Lenovo bracket
- EPEAT Silver certified
- Microsoft® Windows® 7 certified
- Microsoft Windows 8 certified



ThinkVision LT2013s Wide Monitor

Viewing adjustments	*Tilt:* 22° back, -5° forward
Rotating screen	**None**
On screen display	On screen display with digital user controls (8 languages)
Control features	Direct access (buttons on front) for automatic image setup, input switch, and brightness
USB hub	None
Multiple input	VGA input
Monitor connectors	(1) VGA 15-pin D-shell, analog, blue
Signal cables	(1) detachable, VGA 15-pin D-shell at each end, analog, 1.8 meter
Mounting features	Wall or desk mounting using the Extend Arm or third-party asccessories meeting the VESA FPMPMI® (100mm mount)
Security	Security keyhole for attachment of optional cable lock (Kensington® lock-compatible)
Ship group	Monitor, stand and base, Quick start and safety poster, analog signal cable, 1.8 meter black power cord

Limited Warranty

See details at **http://support.lenovo.com/en_US/guides-and-manuals/detail.page?DocID=UM008281**

Accessories

Kensington MicroSaver Cable Lock	73P2582
Kensington Twin Head Cable Lock	45K1620
Lenovo Security Cable Lock	57Y4303
Lenovo Easy Reach Monitor Stand	55Y9258
ThinkCentre Extend Arm	57Y4352

See details at **www.lenovo.com/support/monitoraccessories**

See all monitors at **www.lenovo.com/thinkvision**

See footnotes for important warranty information
US model announced July 10, 2013

© Lenovo
(LT2013S) July 2013