

ThinkVision P24h-10 MONITOR



SPECIFICATIONS

DISPLAY		DIMENSIONS (W x D x H)	
Panel Size	23.8" Wide	Size Packed (mm)	635 x 188 x 422
Panel Type	IPS	Size Packed (inches)	25" x 7.4" x 16.61"
Backlight	WLED	Size Unpacked with Stand (mm)	540.2 x 261.75 x 373.4
Resolution	2560 x 1440	Size Unpacked with Stand (inches)	21.26" x 10.3" x 14.7"
Aspect Ratio	16:9	Size Unpacked without Stand (Monitor Head Only) (mm)	540.2 x 46.45 x 325.98
Anti-Glare	Yes	Size Unpacked without Stand (Monitor Head Only) (inches)	21.26" x 1.82" x 12.83"
Borderless Screen	Yes	Stand Base Footprint Area (mm / inches)	250 x 250 / 9.84" x 9.84"
Screen Dimensions (W x H) (mm)	526.848 (H) x 296.352 (V)	Weight Packed	Starting at 19.73 lbs (8.95 kg)
Maximum Brightness (Typical)	300 cd/m ²	Weight Unpacked	Starting at 12.54 lbs (5.69 kg)
Viewing Angle (H/V at CR 10:1)	178°/178°	Weight Monitor Head Only	Starting at 8.42 lbs (3.82 kg)
Contrast Ratio (Typical)	1000:1		
Dynamic Contrast Ratio	3M:1	POWER CONSUMPTION	
Pixel Pitch (mm)	0.2058	Typical	24 W
Color Gamut (CIE 1931)	99% sRGB	Maximum	120 W
Display Colors (Typical)	16.7 Million	Sleep-Mode	<0.5 W
Response Time	4/6/14 ms (G-to-G)	Off-Mode	<0.5 W
SIGNAL INPUT		Power Supply	Internal
Video Input Signals	2 x HDMI 1.4 + USB-C + DisplayPort 1.2 + DisplayPort-Out	Power Voltage	90 VAC – 264 VAC
Video Cables Supplied (Length)	USB-C – USB-C Cable (1.8 m)	COMPLIANCE	
SIGNAL INTERFACE / PERFORMANCE		Arsenic-Free Glass	Yes
Audio	Audio-Out	PVC-Free	Yes
OSD Languages	English, French, Italian, German, Spanish, Japanese, Chinese, Russian	Mercury-Free	Yes
MECHANICAL		EPEAT	Silver
Tilt Angle (Front / Back)	-5° / 30°	ENERGY STAR Rating	8.0
Cable Management	Yes	ULE	Gold
Kensington Lock	Yes	TCO	7.0
VESA Mounting	Yes (100 mm)	TCO Edge	2.0
Bezel Color	Raven Black	TÜV Eye Comfort Certification	Yes
Bezel Width		RoHS (EU 2002/95/EC)	Yes
Top (mm / inches)	2 / 0.08"	China Energy Efficiency Standard	Tier 2
Bottom (mm / inches)	22 / 0.87"	Windows Certification	Windows 7 / Windows 10
Sides (mm / inches)	2 / 0.08"		

¹ Depending on many factors such as the processing capability of peripheral devices, file attributes, and other factors related to system configuration and operating environments, the actual transfer rate using the various USB connectors on this device will vary and is typically slower than the data rates as defined by the respective USB specifications: - 5 Gbit/s for USB 3.1 Gen 1; 10 Gbit/s for USB 3.1 Gen 2 & 20 Gbit/s for USB 3.2.



WWW.LENOVO.COM