Lenovo ThinkVision T2364t Wide Touch

Product Specifications Reference (PSREF)

Name	**T2364t Wide Flat Panel Monitor**
Bezel color	**Black**
Type-model	**60E9MAR1US / 60E9MAT1EU**
Panel	TFT-LCD, In-Plane Switching (IPS), White LED backlight
Viewable image size	**23.0"** (**584mm**) diagonal
Max view area (W x H)	20.05" x 11.28" (509.2mm x 286.4mm)
Native resolution	**1920x1080**
Touch	Supports 10-point touch
Aspect ratio	16:9
Pixel pitch (mm)	0.2652 x 0.2652 mm
Dot/Pixel per Inch	95 dpi
Brightness	250 nits or cd/m^2 (typical)
Contrast ratio	1000:1 (typical)
Pixel response time	7ms (typical)
Color gamut	72%
Viewing angle at 10:1 CR	178° (+/- 89°) horizontal, 178° (+/- 89°) vertical
Stand	Tilt adjustable stand
Bezel width	*Sides:* 0.079" (2.0mm)
Dimensions (HxWxD)	12.53" H x 20.56" W x 2.86" D; 318.2mm H x 522.2mm W x 72.7mm D
Power supply	22 watts typical, 45 watts maximum, <0.5 watts standby/suspend, universal, integrated (no external brick-like power supply)
Weight	9.24 lb; 4.32 kg
Limited warranty	**3 year** (includes backlight)
Available date	June 2015

VESA-compliant	VESA DDC2B/CI
Power management	ENERGY STAR® qualified
Ergonomics	ISO 9241-307
Emission standards	FCC Class B
Environmental	TCO Displays 7.0, TCO Certified Edge 2.0, WEEE, RoHS, **EPEAT™ Gold rating**

Preset resolutions	VGA:	640x350, 640x480, 720x400, 700x570
	SVGA:	800x600, 832x624
	XGA:	1024x768, 1152x864
	SXGA:	1280x1024
	WXGA:	1366x768
	WXGA+:	1440x900, 1600x900
	WSXGA+:	1680x1050
	Full HD:	1920x1080
Presets / user settings	User settings: 20	

Features

- Widescreen 23.0-inch monitor
- Supports 1920x1080 resolution
- Includes dual input connection for attachment to two systems concurrently
- EPEAT Gold certified
- 10-point touch screen
- Microsoft® Windows® 7 certified
- Microsoft Windows 10 certified



ThinkVision T2364t

Viewing adjustments	*Tilt:* 10° - 70° degrees; detachable stand
Rotating screen	None
On screen display	On screen display with digital user controls (8 languages)
Control features	Direct access (buttons on front) for automatic image setup, dual input and brightness
USB hub	USB 3.0 Hub: 1 port into PC (USB 3.0); 3 ports for accessories (3 USB 3.0)
Multiple input	Dual input (two different PCs attach to two different connectors; one PC shows image; select via button)
Monitor connectors	(1) VGA 15-pin D-shell, analog, blue (2) HDMI (1.4), digital, HDCP-compliant (3) DisplayPort, digital, black, HDCP-compliant
Signal cables	(1) detachable, VGA 15-pin D-shell at each end, analog, 1.8 meter (2) detachable, HDMI at each end, digital, 1.8 meter (3) detachable, DisplayPort at each end, digital, 1.8 meter
Mounting features	Wall or desk mounting using the Extend Arm or third-party accessories, 100mm x 100mm mount
Security	Security keyhole for attachment of optional cable lock (Kensington® lock-compatible)

Ship group	Monitor with stand, Safety and Warranty Information, 1.8 meter analog signal cable, 1.8 meter HDMI cable, 1.8 meter DisplayPort cable, 1.8 meter USB signal cable, 1.8 meter black power cord

Limited Warranty

See details at **http://support.lenovo.com/en_US/guides-and-manuals/detail.page?DocID=UM008281**

Accessories

Kensington MicroSaver Cable Lock	73P2582
Kensington Twin Head Cable Lock	45K1620

See details at **www.lenovo.com/support/monitoraccessories**

See all monitors at **www.lenovo.com/thinkvision**