

Name	T2424p Wide Flat Panel Monitor	Features • Widescreen 23.8-inch monitor • Supports 1920x1080 resolution • Supports ThinkCentre Tiny Clamp Bracket • Supports optional soundbar • Includes dual input connection for attachment to two systems concurrently (analog and digital) • EPEAT Gold certified • Microsoft® Windows® 7 certified • Microsoft Windows 8 / Windows 8.1 certified • Microsoft Windows 10 certified				
Bezel color	Raven black					
Type-model	60F7MAR1US / 60F7MAT1US / 60C8MAT1EU					
Panel	TFT-LCD, In-Plane Switching (IPS), White LED backlight					
Viewable image size	23.8" (604.7mm) diagonal					
Max view area (W x H)	20.75" x 11.67" (527.0mm x 296.5mm)					
Native resolution	1920x1080					
Aspect ratio	16:9					
Pixel pitch (mm)	0.2745 x 0.2745 mm					
Dot/Pixel per Inch	93 dpi					
Brightness	250 nits or cd/m² (typical)					
Contrast ratio	1000:1 (typical)					
Pixel response time	7ms (typical)					
Color gamut	72%					
Viewing angle at 10:1 CR	178° (+/- 89°) horizontal, 178° (+/- 89°) vertical					
Stand	Tilt, swivel, pivot, and height adjustable stand					
Bezel width	Sides: 0.69" (17.5mm)					
Dimensions (HxWxD)	14.67" H x 22.19" W x 10.39" D; 372.5mm H x 563.6mm W x 264.2mm D					
Power supply	22 watts typical, 26 watts maximum (without USB 3.0 hub), 54 watts maximum (with USB 3.0 hub), <0.5 watts standby/suspend, universal, integrated (no external brick-like power supply)					
Weight	12.90 lb; 5.85 kg					
Limited warranty	3 year (includes backlight)					
Available date	March 2015					
VESA-compliant	VESA DDC2B/CI					
Power management	ENERGY STAR® qualified					
Ergonomics	ISO 9241-307					
Emission standards	FCC Class B					
Environmental	TCO Displays 7.0, TCO Certified Edge 2.0, WEEE, RoHS, EPEAT™ Gold rating					
Preset resolutions	VGA: 640x350, 640x480, 720x400 SVGA: 800x600 XGA: 1024x768, 1152x864 SXGA: 1280x1024 WXGA: 1366x768 WXGA+: 1440x900, 1600x900 WSXGA+: 1680x1050 Full HD: 1920x1080					
Presets / user settings	Standard presets: 22; user settings: 22					
Viewing adjustments	Tilt: 30° back, -5° forward; lift: 4.3" (110mm); swivel: +/-45°; detachable stand					
Rotating screen	Screen pivots 90 degrees from landscape to portrait					
On screen display	On screen display with digital user controls (8 languages)					
Control features	Direct access (buttons on front) for automatic image setup, dual input and brightness					
USB hub	USB 3.0 Hub: 1 port into PC (USB 3.0); 4 ports for accessories (4 USB 3.0)					
Multiple input	Dual input (two different PCs attach to two different connectors; one PC shows image; select via button)					
Monitor connectors	(1) VGA 15-pin D-shell, analog, blue (2) HDMI (1.4), digital, HDCP-compliant (3) DisplayPort, digital, black, HDCP-compliant					
Signal cables	(1) detachable, VGA 15-pin D-shell at each end, analog, 1.8 meter (2) detachable, DisplayPort at each end, digital, 1.8 meter					
Mounting features	Wall or desk mounting using the Extend Arm or third-party accessories, 100mm x 100mm mount					
Security	Security keyhole for attachment of optional cable lock (Kensington® lock-compatible)					
Ship group	Monitor with stand, Safety and Warranty Information, 1.8 meter analog signal cable, 1.8 meter DP signal cable, 1.8 meter USB signal cable, 1.8 meter black power cord					
Limited Warranty See details at http://support.lenovo.com/en_US/guides-and-manuals/detail.page?DocID=UM008281		Accessories <table><tr><td>Kensington MicroSaver Cable Lock</td><td>73P2582</td></tr><tr><td>Kensington Twin Head Cable Lock</td><td>45K1620</td></tr></table> See details at www.lenovo.com/support/monitoraccessories See all monitors at www.lenovo.com/thinkvision	Kensington MicroSaver Cable Lock	73P2582	Kensington Twin Head Cable Lock	45K1620
Kensington MicroSaver Cable Lock	73P2582					
Kensington Twin Head Cable Lock	45K1620					