## ThinkVision T24d-10 MONITOR

## SPECIFICATIONS

DISPLAY		DIMENSIONS (W x D x H)	
Panel Size Panel Type Resolution Backlight Aspect Ratio Pixel Pitch (W x H) (mm) Dot/Pixel Per Inch (DPI/PPI) Anti-Glare Screen Dimensions (W x H) (mm) (inches) Maximum Brightness (Typical) Viewing Angle (H/V at CR 10:1) Contrast Ratio (Typical) Dynamic Contrast Ratio Color Gamut (CIE 1931) Display Colors (Typical) Response Time Extreme Typical Off	24" In-Plane Switching 1920 x 1200 WLED 16:10 0.27 x 0.27 94 PPI Yes 518.4 x 324 20.41" x 12.75" 300 cd/m <sup>2</sup> 178°/178° 1000:1 3M:1 99% sRGB 16.7 Million 4 ms 7 ms 15 ms	Size Packed (mm) (inches) Size Unpacked with Stand (mm) (inches) Size Monitor Head Only (mm) (inches) Distance from Table to Panel Lowest Pixel at Bottom of Screen (mm / inches) Highest Pixel at Top of Screen (mm / inches) Stand Base Footprint Area (mm) (inches) Weight Packed Unpacked Monitor Head Only	160 x 655 x 422 6.3" x 25.79" x 16.61" 533.2 x 260.4 x 497.4 20.99" x 10.25" x 19.58" 533.2 x 42.3 x 355.1 20.99" x 1.67" x 13.98" 56 / 2.2" 490 / 19.29" 250 x 250 9.84" x 9.84" Starting at 19.18 lbs (8.7 kg) Starting at 12.41 lbs (5.63 kg) Starting at 8.77 lbs (3.98 kg)
SIGNAL INPUT		POWER CONSUMPTION	
Video Input Signals Video Cables Supplied Video Cable Length USB Hub USB Cable Supplied Audio-Out SIGNAL INTERFACE / PERFO Horizontal Frequency	VGA + DisplayPort 1.2 + HDMI 1.4 VGA + DisplayPort + HDMI 1.8 m USB 3.0 <sup>1</sup> Yes Yes (3.5 mm) <b>DRMANCE</b> 30 kHz - 83 KHz	Typical Maximum Sleep-Mode Switch Off-Mode Power Supply Power Voltage Voltage Dynamic Frequency ENVIRONMENTAL Temperature	22 W 64 W <0.3 W <0.3 W Internal 100 VAC - 240 VAC 50 Hz - 60 Hz
Vertical Frequency Native Resolution Maximum Pixel Clock Speed/ Bandwidth VGA HDMI <sup>™</sup> DisplayPort <sup>™</sup> Default Color Temperature Preset Display Modes OSD Buttons OSD Languages	205 MHz 1920 x 1200 205 MHz 165 MHz 165 MHz 6500 K 20 5 English, French, German, Spanish, Italian, Japanese, Simplified Chinese, Russian	Operating Non-Operating Humidity Operating Non-Operating Altitude Operating Non-Operating Arsenic-Free Glass PVC-Free Mercury-Free PCC % of Plastic Resins	0°C - 40°C -20°C - 60°C 10% - 80% 5% - 95% 0 m - 5000 m 0 ft - 40,000 ft Yes Yes Yes Yes >85%
MECHANICAL		COMPLIANCE	
Tilt Angle (Front / Back) Swivel Angle (Left / Right) Lift (mm) Pivot VESA® Mount (mm x mm) Cable Management Kensington® Lock Bezel Color Bezel Width Top (mm / inches) Bottom (mm / inches) Sides (mm / inches)	-5°/30° +/-45° 110 +/-90° 100 x 100 Yes Yes Business Black 2 / 0.08" 22.7 / 0.89" 2 / 0.08"	EPEAT ENERGY STAR Rating ULE TCO RoHS (EU 2002/95/EC) China Energy Efficiency Standard Windows Certification WARRANTY AND AVAILABI Warranty Geography Availability	Silver 8.0 Gold TCO Display 7.0 / TCO Edge 2.0 Yes Tier 2 Windows 7 / Windows 10 ILITY 3 Years WW

\* NA only.

Depending on many factors such as the processing capability of peripheral devices, file attributes, and other factors related to system configuration and operating environments, the actual transfer rate using the various USB connectors on this device will vary and is typically slower than the data rates as defined by the respective USB specifications: - 5 Gbit/s for USB 3.1 Gen 1, 10 Gbit/s for USB 3.1 Gen 2 & 20 Gbit/s for USB 3.2.



Lenovo reserves the right to alter product offerings and specifications at any time, without notice. Lenovo makes every effort to ensure accuracy of all information but is not liable or responsible for any editorial, photographic errors. All images are for illustration purposes only. For full Lenovo product, service and warranty specifications visit www.lenovo.com. Lenovo makes no representations or warranties regarding third party products or services. **Trademarks**: The following are trademarks or registered trademarks of Lenovo: Lenovo, the Lenovo logo, Rescue and Recovery, Think/Bactine, Think/Station, Think/St