

ThinkVision T24i-10 MONITOR



SPECIFICATIONS

DISPLAY		DIMENSIONS (W x D x H)	
Panel Size	23.8" Wide	Size Packed (mm)	422 x 622 x 190
Panel Type	In-Plane Switchng	Size Packed (inches)	16.61" x 24.48" x 7.48"
Backlight	WLED	Size Unpacked with Stand Lowest Position (mm)	540.2 x 261.75 x 373.4
Resolution (H x V)	1920 x 1080	Size Unpacked with Stand Highest Position (mm)	540.2 x 261.75 x 483.4
Aspect Ratio	16:9	Size Unpacked without Stand (Monitor Head Only) (mm)	540.2 x 46.45 x 325.98
Anti-Glare	Yes	Size Unpacked without Stand (Monitor Head Only) (inches)	21.26" x 1.82" x 12.83"
Near Edgeless Screen	Yes	Stand Base Footprint Area (mm)	250 x 250
Screen Dimensions (W x H) (mm)	527.04 x 296.46	Stand Base Footprint Area (inches)	9.84" x 9.84"
Screen Dimensions (W x H) (inches)	20.75" x 11.67"	Weight Packed	Starting at 16.39 lbs (7.45 kg)
Maximum Brightness (Typical)	250 cd/m ²	Weight Unpacked	Starting at 11.33 lbs (5.15 kg)
Viewing Angle (H/V at CR 10:1)	178°/178°	Weight Monitor Head Only	Starting at 7.26 lbs (3.3 kg)
Contrast Ratio (Typical)	1000:1	Full Container Load (40' STD / 20' STD)	1140 / 540 Units
Dynamic Contrast Ratio	3M:1		
Pixel Pitch (mm)	0.2745 x 0.2745	CONNECTIVITY	
Color Gamut (CIE 1931)	72% NTSC	Video Input Signals	VGA + HDMI 1.4 + DisplayPort 1.2
Color Support (Typical)	16.7 Million	Video Cables Supplied (Length)	1.8 m
Response Time (gray to gray)	4 ms (Extreme mode) 6 ms (Normal mode)	USB Hub	1 x USB 3.0 ¹ (Upstream) 4 x USB 3.0 ¹ (Downstream, Incl. 1 BC)
OSD Controls Buttons	5	Audio Out	Yes (3.5 mm)
OSD Controls Languages	English, French, German, Spanish, Italian, Japanese, Simplified Chinese, Russian	POWER CONSUMPTION	
		Typical	16.5 W
		Maximum	55 W
		Sleep-Mode	<0.5 W
		Switch Off-Mode	<0.3 W
		Power Supply	Internal
		Power Voltage	90 VAC – 264 VAC
MECHANICAL		WHAT'S IN THE BOX	
Tilt Angle (Front / Back)	-5° / 30°	Monitor with Stand	
Swivel Angle (Left / Right)	+/-45°	1 x Power Cable	
Lift Range (mm)	110	1 x VGA Cable	
Pivot	+/-90°	1 x DisplayPort - DisplayPort Cable	
Cable Management	Yes	1 x HDMI Cable (NA Only)	
Kensington Lock	Yes	Quick Setup Guide	
VESA Mount (mm x mm)	Yes (100 X 100)	CERTIFICATIONS	
Bezel Color	Raven Black	EPEAT	Silver
Bezel Width Top (mm / inches)	2 / 0.08"	ENERGY STAR Rating	8.0
Bezel Width Sides (mm / inches)	2 / 0.08"	TCO	7.0
		TCO Edge	2.0
		ULE	Gold
		RoHS (EU 2002/95/EC)	Yes
		China Energy Efficiency Standard	Tier 2
		Windows Certification	Windows 7 / Windows 10
		TüV Eye Comfort Certification	Yes

¹ Depending on many factors such as the processing capability of peripheral devices, file attributes, and other factors related to system configuration and operating environments, the actual transfer rate using the various USB connectors on this device will vary and is typically slower than the data rates as defined by the respective USB specifications: - 5 Gbit/s for USB 3.1 Gen 1; 10 Gbit/s for USB 3.1 Gen 2 & 20 Gbit/s for USB 3.2.



WWW.LENOVO.COM