# **OVERVIEW**



1. Power connector	6. USB 3.2 Gen 1
2. HDMI 1.4	7. Audio line-out (3.5mm)
3. DP 1.2	8. USB 3.2 Gen 1
4. 1x USB-C 3.2 Gen 1 (DP 1.2 Alt Mode)	9. USB 3.2 Gen 1 (BC 1.2)
5. USB 3.2 Gen 1	

## PERFORMANCE

## Panel

#### Panel

3-side NearEdgeless, In-Plane Switching

Backlight

WLED

#### **Display Size**

23.8 inches

#### Max View Area

WxH: 527.04 x 296.46 mm

## Resolution

1920 x 1080

#### 1520 × 1000

Aspect Ratio

## 16:9

**Pixel Pitch** 

#### 0.2745 x 0.2745 mm

Dot / Pixel Per Inch

93 dpi

## Brightness

300 cd/m<sup>2</sup>

#### **Contrast Ratio**

- Contrast Ratio: 1000:1
- Dynamic Contrast Ratio: 3M<sup>™</sup>:1

#### View Angle (H / V)

Horizontal: 178°, Vertical: 178°

#### **Response Time**

- Extreme Mode: 4 ms
- Normal Mode: 6 ms

#### **Refresh Rate**

60Hz

**Color Gamut** 

99% sRGB

**Color Support** 

16.7 Million

Screen Surface Treatment

Anti-glare

## **Operating System**

Operating System

- Windows® 7 Support
- Windows<sup>®</sup> 10 Support

## **Power Supply**

#### **Power Consumption**

- Typical / Max: 25W / 150W
- Sleep / Off mode: <0.5W
- Switch-off Mode: <0.3W
- Energy Star Power On: 17W
- Energy Star TEC: 56kWh
- Internal Power Supply

## Voltage Required

AC 100 to 240 V (50-60Hz)

## **Special Features**

#### **Special Features**

- Lenovo® ThinkColour (Lenovo® Accessories and Display Manager) Support
- Lenovo® ThinkColour supports Windows® 10 & 11, Mac OS, and Windows® On Arm (functions vary across systems). Lenovo® Accessories and Display Manager is formerly Lenovo® Display Control Center.
- Smart Power

The Smart Power function intelligently detects overall power consumption and dynamically manages the power delivery to each device

## DESIGN

## **Display**

#### Touchscreen

Supports 10-point touch

## **Mechanical**

### **Bezel Width**

- Side: 2mm
- Top / Bottom: 2mm / 22.2mm

#### **Cable Management**

#### Support

#### **Case Color**

Raven black

#### Dimensions (WxDxH)<sup>[1]</sup>

Models	Dimensions
Lowest Position	539.8 x 244.1 x 340.5 mm (21.25 x 9.61 x 13.41 inches)
Highest Position	539.8 x 244.1 x 430.5 mm (21.25 x 9.61 x 16.95 inches)
Head Only	539.8 x 44.1 x 326.5 mm (21.25 x 1.74 x 12.85 inches)

#### Packaging Dimensions (WxDxH)

#### 421 x 622 x 172 mm (16.57 x 24.49 x 6.77 inches)

Weight<sup>[2]</sup>

Models	Weight
Monitor With Stand	5.85 kg (12.90 lbs)
Monitor Head Only	3.79 kg (8.36 lbs)

#### **Packaging Weight**

8.31 kg (18.32 lbs)

#### Mounting

Supports VESA mount 100mm

# Stand

Supports -5° to +70° tilt, up to 90mm lift

### In the Box

- Monitor with Stand
- 1x DP Cable (1.8m) (for US, Canada only)
- \* 1x USB-C $^{\circ}$  to USB-A Cable (1.8m) (for US, Canada only)
- 1x USB-C $^{\circ}$  to USB-C $^{\circ}$  Cable
- 1x Power cable (1.8m)
- Quick Setup Guide

#### Notes:

[1] The system dimensions may vary depending on configurations.

[2] The system weight is approximate and based on results in Lenovo<sup>®</sup> lab, which varies depending on the source of component, variance of the distribution of each component, and manufacturing process. It may not be the exact weight

for each specific model.

# CONNECTIVITY

#### **Ports**<sup>II</sup>

#### Rear Ports<sup>[2]</sup>

- 1x USB-C<sup>®</sup> 3.2 Gen 1 (DP 1.2 Alt Mode and to 90W PD), USB upstream
- 4x USB 3.2 Gen 1 (1x BC 1.2), USB downstream
- 1x HDMI® 1.4[3]
- 1x DisplayPort<sup>™</sup> 1.2
- 1x Power Connector
- 1x audio-out (3.5mm)

#### Notes:

[1] The transfer speed of following ports will vary and, depending on many factors, such as the processing speed of the host device, file attributes and other factors related to system configuration and your operating environment, will be slower than theoretical speed.

USB 2.0: 480 Mbit/s;

USB 3.2 Gen 1 (SuperSpeed USB 5Gbps, formerly USB 3.0 / USB 3.1 Gen 1): 5 Gbit/s;

USB 3.2 Gen 2 (SuperSpeed USB 10Gbps, formerly USB 3.1 Gen 2): 10 Gbit/s;

USB4® 20Gbps / USB 3.2 Gen 2x2 (SuperSpeed USB 20Gbps): 20 Gbit/s;

USB4<sup>®</sup> 40Gbps (USB 40Gbps): 40 Gbit/s;

Thunderbolt<sup>™</sup> 3/4: 40 Gbit/s.

[2] Up to 90W power delivery to compatible devices by USB-C<sup>®</sup>. Listed as maximum capacity of power delivery. Actual capacity of power delivery may vary depending upon devices connected or monitor configuration, and may decline with downstream USB ports connected or higher brightness setting.

[3] Supports 1920x1080@75Hz as specified in HDMI® 1.4

# **SECURITY & PRIVACY**

## Security

Physical Locks Kensington® Security Slot™

## SERVICE

#### Warranty

**Base Warranty** 3-year limited warranty

## **CERTIFICATIONS**

## **Green Certifications**<sup>III</sup>

- **Green Certifications**
- ENERGY STAR<sup>®</sup> Certified
- EPEAT<sup>™</sup> Gold Registered<sup>[2]</sup>
- RoHS compliant
- TCO Certified 8.0
- TCO edge 2.0

Notes:

[1] The items listed under the "Green Certifications" section may not only refer to certification but also registration or self-declaration. For ESG & regulatory compliance documents, please visit <u>https://compliance.lenovo.com</u>.
[2] EPEAT™ is registered where applicable, please visit <u>epeat.net</u> for registration status by country.

## **Other Certifications**

#### **Other Certifications**

PSREF

Reference

Product Specifications

Lenovo

- Eyesafe® Certified
- TÜV Rheinland<sup>®</sup> Eye Comfort Certification
- TÜV Rheinland® Low Blue Light (Hardware Solution)
- Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not responsible for photographic or typographical errors. LENOVO PROVIDES THIS PUBLICATION "AS IS," WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow disclaimer of express or implied warranties in certain transactions, therefore this disclaimer may not apply to you.
- The specifications on this page may not be available in all regions, and may be changed or updated without notice.

PSREF Lenovo Product Specifications Reference













