

OVERVIEW



1. Joystick	7. USB-B 3.2 Gen 1
2. Source Key	8. USB 3.2 Gen 1
3. Power connector	9. Audio-out (3.5mm)
4. HDMI 2.1 TMDS	10. USB 3.2 Gen 1
5. DP 1.2	11. USB 3.2 Gen 1
6. VGA	12. USB 3.2 Gen 1

## PERFORMANCE

### Panel

**Panel**

3-side NearEdgeless, In-Plane Switching

**Backlight**

WLED

**Display Size**

27 inches

**Max View Area**

WxH: 597.9 x 336.3 mm

**Resolution**

1920 x 1080

**Aspect Ratio**

16:9

**Pixel Pitch**

0.3114 x 0.3114 mm

**Dot / Pixel Per Inch**

82 dpi

**Brightness**

300 cd/m<sup>2</sup>

**Contrast Ratio**

- Contrast Ratio: 1000:1
- Dynamic Contrast Ratio: 3M™:1

**View Angle (H / V)**

Horizontal: 178°, Vertical: 178°

**Response Time**

- Extreme Mode: 4 ms
- Normal Mode: 6 ms
- Off Mode: 14 ms

**Refresh Rate**

60Hz

**Color Gamut**

99% sRGB

**Color Support**

16.7 Million

**Color Depth**

8-bit (6-bit+FRC)

**Screen Surface Treatment**

Anti-glare

### Operating System

**Operating System**

- Windows® 11 Support
- Windows® 10 Support

### Multi-Media

**Camera**

- No bundled webcam (Support ThinkVision® MC 60 Monitor Webcam, sold separately)
- ThinkVision® MC 60 monitor webcam (Some models only)

**Speakers**

Optional Modular Soundbar support (MS30 Monitor Soundbar)

Power Supply

Power Consumption

- Typical / Max: 24W / 65W
- Sleep / Off mode: <0.5W
- Switch-off Mode: <0.3W
- Energy Star Power On: 15W
- Energy Star TEC: 50kWh
- Internal Power Supply

Voltage Required

AC 100 to 240 V (50-60Hz)

Special Features

Special Features

- Natural Low Blue Light
- Lenovo® ThinkColour (Lenovo® Display Accessories and Display Manager) Support  
Lenovo® ThinkColour supports Windows® 10 & 11, Mac OS, and Windows® On Arm (functions vary across systems).  
Lenovo® Display Accessories and Display Manager is formerly Lenovo® Display Control Center.

DESIGN

Mechanical

ThinkCentre® M Series Support

ThinkCentre® M Series Tiny Support  
For supporting Tiny devices, additional Tiny Clamp Bracket Mounting Kit III (PN: 4XF1K72399) are needed (sold separately).

Bezel Width

- Side: 2mm
- Top / Bottom: 2mm / 17.6mm

Cable Management

Support

Case Color

Raven black

Dimensions (WxDxH)<sup>[1]</sup>

Models	Dimensions
Lowest Position	611.9 x 204.5 x 389.3 mm (24.09 x 8.05 x 15.33 inches)
Highest Position	611.9 x 204.5 x 544.3 mm (24.09 x 8.05 x 21.43 inches)
Head Only	611.9 x 50.0 x 362.5 mm (24.08 x 1.97 x 14.27 inches)

Packaging Dimensions (WxDxH)

690 x 148 x 525 mm (21.17 x 5.83 x 20.67 inches)

Weight<sup>[2]</sup>

Models	Weight
Monitor With Stand	6.9 kg (15.2 lbs)
Monitor Head Only	4.9 kg (10.8 lbs)

Packaging Weight

10.1 kg (22.27 lbs)

Mounting

Supports VESA mount 100mm

Stand

Supports -5° to +23.5° tilt, left & right 45 swivel, 90° pivot, up to 155mm lift

In the Box

- Monitor with Stand

- 1x DP Cable (1.8m) (No for Brazil)
- 1x HDMI® Cable (1.8m) (Brazil only)
- 1x USB-A to USB-B Cable (1.8m)
- 1x Power cable (1.8m)
- Quick Setup Guide

---

**Notes:**

[1] The system dimensions may vary depending on configurations.

[2] The system weight is approximate and based on results in Lenovo® lab, which varies depending on the source of component, variance of the distribution of each component, and manufacturing process. It may not be the exact weight for each specific model.

## CONNECTIVITY

### Ports<sup>[1]</sup>

#### Rear Ports

- 1x USB-B 3.2 Gen 1, USB upstream
- 4x USB 3.2 Gen 1 (1x BC 1.2), USB downstream
- 1x HDMI® 2.1 TMDS<sup>[2]</sup>
- 1x DisplayPort™ 1.2
- 1x VGA
- 1x Power Connector
- 1x audio-out (3.5mm)

---

**Notes:**

[1] The transfer speed of following ports will vary and, depending on many factors, such as the processing speed of the host device, file attributes and other factors related to system configuration and your operating environment, will be slower than theoretical speed.

USB 2.0: 480 Mbit/s;

USB 3.2 Gen 1 (SuperSpeed USB 5Gbps, formerly USB 3.0 / USB 3.1 Gen 1): 5 Gbit/s;

USB 3.2 Gen 2 (SuperSpeed USB 10Gbps, formerly USB 3.1 Gen 2): 10 Gbit/s;

USB4® 20Gbps / USB 3.2 Gen 2x2 (SuperSpeed USB 20Gbps): 20 Gbit/s;

USB4® 40Gbps (USB 40Gbps): 40 Gbit/s;

Thunderbolt™ 3/4: 40 Gbit/s.

[2] Supports 1920x1080@60Hz as specified in HDMI® 2.1

## SECURITY & PRIVACY

### Security

#### Physical Locks

Kensington® Security Slot™

## SERVICE

### Warranty

#### Base Warranty

3-year limited warranty

## CERTIFICATIONS

### Green Certifications<sup>[1]</sup>

#### Green Certifications

- ENERGY STAR® Certified
- EPEAT™ Gold Registered<sup>[2]</sup>
- RoHS compliant
- TCO Certified 9.0
- TCO edge

**Notes:**

[1] The items listed under the "Green Certifications" section may not only refer to certification but also registration or self-declaration.

[2] EPEAT™ is registered where applicable, please see [epeat.net](https://epeat.net) for registration status by country.

**Other Certifications****Other Certifications**

- Eyesafe® Certified
- TÜV Rheinland® Eye Comfort Certification
- TÜV Rheinland® Low Blue Light (Hardware Solution)

- Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not responsible for photographic or typographical errors. LENOVO PROVIDES THIS PUBLICATION "AS IS," WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow disclaimer of express or implied warranties in certain transactions, therefore this disclaimer may not apply to you.
- The specifications on this page may not be available in all regions, and may be changed or updated without notice.

