

OVERVIEW



1. E-shutter switch	5. HDMI
2. Power button	6. USB-C (USB 10Gbps), with USB PD 3.0 & DP 1.4
3. Headphone / microphone combo jack (3.5mm)	7. USB-C (USB4 40Gbps), with USB PD 3.0 & DP 1.4
4. USB-A (USB 5Gbps), Always On	

PERFORMANCE

Processor

Processor Family

AMD Ryzen™ 5 / 7 8000 Series Processor

Processor

Processor Name	Cores	Threads	Base Frequency	Max Frequency	Cache	Processor Graphics	NPU	Overall TOPS
AMD Ryzen™ 7 8845HS	8	16	3.8GHz	5.1GHz	8MB L2 / 16MB L3	AMD Radeon™ 780M	AMD Ryzen™ AI, up to 16 TOPS	Up to 38 TOPS

AI (Artificial Intelligence)

AI PC Category

AI PC^[1]

NPU

Integrated AMD Ryzen™ AI, up to 16 TOPS

Notes:

[1] AI PCs have a NPU capable of 10+ TOPs to run the Copilot assistant by pressing the optional Microsoft® Copilot key or using Win + C.

Operating System

Operating System**

- Windows® 11 Pro
- Windows® 11 Home
- Windows® 11 Home Single Language
- No preload operating system

Graphics

Graphics**

Graphics	Type	Memory	Boost Clock	TGP	Key Features
AMD Radeon™ 780M	Integrated	Shared	-	Share CPU TDP	DirectX® 12
NVIDIA® GeForce RTX™ 3050 Laptop GPU	Discrete	6GB GDDR6	1777 MHz	63W	Dynamic Boost 2.0, DirectX® 12 Ultimate

Monitor Support

Monitor Support

Supports up to 4 independent displays (native display and 3 external monitors via HDMI® and USB-C®)

- HDMI® supports up to 4K@60Hz
- USB-C® supports up to 5K@60Hz

Chipset

Chipset

AMD SoC (System on Chip) platform

Memory

Max Memory

16GB soldered memory, not upgradable

Memory Slots

Memory soldered to systemboard, no slots, dual-channel

Memory Type

LPDDR5x-6400

Storage

Max Storage Support^[1]

One drive, up to 1TB M.2 2242 SSD or 1TB M.2 2280 SSD

Storage Slot^[2]

One M.2 2280 PCIe® 4.0 x4 slot

Storage Type**

Disk Type	Interface	Offering
M.2 2242 SSD	PCIe® NVMe®, PCIe® 4.0 x4	1TB
M.2 2280 SSD	PCIe® NVMe®, PCIe® 4.0 x4	512GB / 1TB

Notes:

[1] The storage capacity supported is based on the test results with current Lenovo® storage offerings.

[2] The actual data transfer rate of the following PCIe® interface also depends on the capabilities of the connected PCIe® device. The listed values represent theoretical maximums.

PCIe® 3.0 (x2 / x4): 2 GB/s (16 Gbps) / 4 GB/s (32 Gbps);

PCIe® 4.0 (x2 / x4): 4 GB/s (32 Gbps) / 8 GB/s (64 Gbps);

PCIe® 5.0 (x2 / x4): 8 GB/s (64 Gbps) / 16 GB/s (128 Gbps).

Removable Storage

Card Reader

No card reader

Multi-Media

Audio Chip

High Definition (HD) Audio, Realtek® ALC3306 codec

Speakers

4 stereo speakers, 2W x2 (woofers), 2W x2 (tweeters), optimized with Dolby Atmos®, Amplifier (AMP)

Microphone

Quad-microphone array

Camera

FHD 1080p + IR, with E-shutter, fixed focus

Sensor

Sensors

- Hall sensor
- ToF sensor

Battery

Battery^[1]

73Wh Rechargeable Li-ion Battery, supports Rapid Charge Express (get 3 hours of runtime with a 15-minute charge)

Max Battery Life^[2]

MobileMark® 25@250nits: 10.52 hr

Local video (1080p) playback@150nits: 17.23 hr

Notes:

[1] Rapid Charge Express is only effective in hibernates or fully shutting down the computer.

[2] All battery life claims are approximate maximum and based on results using the MobileMark® 2014, MobileMark® 2018, MobileMark® 25, MobileMark® 30, JEITA 2.0, JEITA 3.0, continuous 1080p video playback (with 150nits brightness and default volume level) or Google Power Load Test (PLT) battery-life benchmark tests. Actual battery life will vary depending on many factors such as product configuration and usage, software use, wireless functionality, power management settings, and screen brightness. The maximum capacity of the battery will decrease with time and use.

Power Adapter

Power Adapter**^[1]

- 100W USB-C® slim (3-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz
- 140W USB-C® slim (3-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz

Notes:

[1] AC adapter offerings depend on the country.

DESIGN

Display

Display**[1]

Size	Resolution	Touch	Type	Brightness	Surface	Aspect Ratio	Contrast Ratio	Color Gamut	Refresh Rate	Viewing Angle (L/R/U/D)	Key Features
14.5"	2.5K WQXGA (2560x1600)	Non-touch	IPS	350nits	Anti-glare	16:10	1,500:1	100% sRGB	90Hz (Max)	85° / 85° / 85° / 85°	Eyesafe® Certified 2.0, Dolby Vision®
14.5"	2.5K WQXGA (2560x1600)	OGS touch	IPS	350nits	Glossy, anti-fingerprint	16:10	1,500:1	100% sRGB	90Hz (Max)	85° / 85° / 85° / 85°	Eyesafe® Certified 2.0, Dolby Vision®, Glass
14.5"	3K (3072x1920)	Non-touch	IPS	400nits	Anti-glare	16:10	1,500:1	100% P3, 100% sRGB	120Hz (Max)	85° / 85° / 85° / 85°	Eyesafe® Certified 2.0, Dolby Vision®, TCON

Touchscreen

- OGS (One Glass Solution) multi-touch, supports 10-point touch
- Non-touch

Screen-to-Body Ratio

91.4% AAR (active area ratio)

Color Calibration

- TCON (Timing Controller) color calibration
- No color calibration

Notes:

[1] IPS (in-plane switching) technology may refer to IPS, PLS, ADS, AHVA, AAS.

Input Device

Pen

No support

Keyboard

6-row, multimedia Fn keys, key travel 1.5mm, Copilot key

Keyboard Backlight

LED backlight

Touchpad

Buttonless glass surface multi-touch touchpad, supports Precision TouchPad (PTP), 80 x 135 mm (3.15 x 5.31 inches)

Mechanical

Dimensions (WxDxH)^[1]

325.5 x 226.49 x 16.6 mm (12.81 x 8.92 x 0.65 inches)

Weight^[2]

Models	Weight
--------	--------

Models with integrated graphics	Starting at 1.49 kg (3.28 lbs)
Models with discrete graphics	Starting at 1.64 kg (3.62 lbs)

Case Color**

- Luna grey
- Tidal teal

Case Material

Aluminium (top), aluminium (bottom)

Surface Treatment

Aluminium stamping (anodized with sandblasting)

Notes:

[1] The system dimensions may vary depending on configurations.

[2] The system weight is approximate and based on results in Lenovo® lab, which varies depending on the source of component, variance of the distribution of each component, and manufacturing process. It may not be the exact weight for each specific model.

CONNECTIVITY

Network

WLAN + Bluetooth®

Wi-Fi® 6E, 802.11ax 2x2 Wi-Fi® + Bluetooth® 5.3, M.2 card^[1]

WWAN

No support

Ethernet

No onboard Ethernet

Notes:

[1] Wi-Fi® 6E operation is subject to the regulation rules in each country.

Ports^[1]

Standard Ports

- 1x USB-A (USB 5Gbps / USB 3.2 Gen 1), Always On
- 1x USB-C® (USB 10Gbps / USB 3.2 Gen 2), with USB PD 3.0 and DisplayPort™ 1.4
- 1x USB-C® (USB4® 40Gbps), with USB PD 3.0 and DisplayPort™ 1.4
- 1x HDMI® 2.1, up to 4K/60Hz
- 1x Headphone / microphone combo jack (3.5mm)

Notes:

[1] The transfer speed of the ports will vary and, depending on many factors, such as the processing speed of the host device, file attributes and other factors related to system configuration and your operating environment, will be slower than theoretical speed.

Docking

Docking

Various docking solutions are supported via USB-C®.

For more compatible docking solutions, please visit [Docking for Yoga® Pro 7 14AHP9](#)

SECURITY & PRIVACY

Security

Security Chip

Microsoft® Pluton TPM 2.0 Enabled

Fingerprint Reader

No fingerprint reader

BIOS Security

- Administrator password
- Master hard disk password
- User hard disk password
- User password
- Self-healing BIOS
- More BIOS security features, please visit [BIOS Simulator](#)^[1]

Other Security

- E-shutter
- IR camera for Windows® Hello (facial recognition)

Notes:

[1] The BIOS simulator is just for reference. Default settings and some options may vary depending on the hardware, operating system and BIOS version.

SERVICE

Warranty

Base Warranty**

- 1-year courier or carry-in service
- 1-year courier or carry-in with 2-year system board service (Korea only)
- 2-year (1-yr battery) courier or carry-in service
- 3-year (1-yr battery) courier or carry-in service

ACCESSORIES

Bundled Accessories

Bundled Accessories^[1]

- Yoga® Pro Mouse
- None

Notes:

[1] For more compatible accessory solutions, please visit [Accessories for Yoga® Pro 7 14AHP9](#).

OPERATING REQUIREMENTS

Operating Environment

Temperature^[1]

- At altitudes up to 2438 m (8,000 ft)
 - Operating: 5°C to 35°C (41°F to 95°F)
 - Storage: 5°C to 43°C (41°F to 109°F)
- At altitudes above 2438 m (8,000 ft)
 - Maximum temperature when operating under the unpressurized condition: 31.3°C (88°F)

Relative Humidity

- Operating: 8% to 95% at wet-bulb temperature 23°C (73°F)
- Storage and transportation: 5% to 95% at wet-bulb temperature 27°C (81°F)

Altitude

Maximum altitude (without pressurization): 3048 m (10,000 ft)

Notes:

[1] When you charge the battery, its temperature must be no lower than 10°C (50°F).

CERTIFICATIONS

Green Certifications^[1]

Green Certifications^[2]

- ENERGY STAR® 8.0
- EPEAT™ Gold Registered^[3]
- ErP Lot 6/26
- RoHS compliant

Notes:

[1] The items listed under the "Green Certifications" section may not only refer to certification but also registration or self-declaration. For ESG & regulatory compliance documents, please visit <https://compliance.lenovo.com>.

[2] EPEAT™ registration and ENERGY STAR® certification are optional and only available on the models with preloaded OS. Please visit epeat.net and energystar.gov for more information.

[3] EPEAT™ is registered where applicable, please visit epeat.net for registration status by country.

Other Certifications**Mil-Spec Test**

MIL-STD-810H military test passed (21 test items)

Other Certifications

- Eyesafe® Certified 2.0
- TÜV Rheinland® Low Blue Light (Hardware Solution)

- Feature with ** means that only one option listed under the feature can be configured on selected models. Please refer to the model configuration for specific information.
- Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not responsible for photographic or typographical errors. LENOVO PROVIDES THIS PUBLICATION "AS IS," WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow disclaimer of express or implied warranties in certain transactions, therefore this disclaimer may not apply to you.
- The specifications on this page may not be available in all regions, and may be changed or updated without notice.



AMD



AMD



AMD



AMD



AMD



AMD