

COLORFUL CLARITY.
PRECISE ACCURACY.



Lenovo

A VERSATILE 23.8" DISPLAY FOR TOTAL PRODUCTIVITY.

Vivid color with precise clarity defines the productivity-enhancing Lenovo ThinkVision P24q-10 monitor. The stunning 23.8" QHD resolution (2560 x 1440) screen displays a rich, consistent color palette. Factory-calibrated accuracy ensures exquisite viewing with maximum detail on the stunning Near-Edgeless IPS-type screen. It's perfect for multi-screen settings, and connects easily to virtually any device, thanks to 5 digital video and 4 USB 3.0¹ ports.

WHY YOU SHOULD BUY THE THINKVISION P24q-10 MONITOR



Precise, Detailed Viewing

QHD (2560 x 1440) resolution means the sharpest detail across the 23.8" Near-Edgeless IPS-type screen (1.77x more pixels than FHD). It's perfect for multi-screen settings.



Superb Color

ThinkVision P24q-10 delivers more colors, and more accurate colors. With over 99% sRGB color gamut and factory-calibrated accuracy, it's ideal for the most detailed applications.



Extreme Versatility

Connect easily to virtually any device with 5 digital video ports including Mini DisplayPort for laptops, plus 4 USB 3.0¹ ports and audio-out. All mounted on a versatile multi-function stand.

THE THINKVISION P24q-10 MONITOR IS BEST SUITED FOR

1

Engineers, designers and other creative professionals who demand the most accurate and consistent color for their highly-detailed work.

2

Power users who employ high-performance devices and advanced software, demanding a display that supports total productivity.

3

Young, technology-focused professionals who value the versatility of a monitor that delivers consistent performance for a variety of devices.



WWW.LENOVO.COM



ThinkVision P24q-10 MONITOR

SPECIFICATIONS

DISPLAY		MECHANICAL	
Panel Size	23.8"	Tilt Angle (Front / Back)	-5° / 30°
Panel Type	In-Plane Switching	Swivel Angle (Left / Right)	+/-45°
Backlight	WLED	Lift (mm)	110
Resolution	2560 x 1440, QHD	Pivot	CW/CCW 90°
Aspect Ratio	16:9	VESA Mount	Yes (100 mm)
Screen Dimensions (W x H) (mm)	526.848 (H) x 296.352 (V)	Kensington Lock Slot	Yes
Maximum Brightness (Typical)	300 cd/m ²	Pivot Auto Rotation	No
Minimum Brightness (Typical)	240 cd/m ²	Cable Management	Yes
Viewable Area (Diagonal) (mm / inches)	604.5 / 23.8"	Bezel Color	Raven Black
Viewing Angle (H/V at CR 10:1)	178°/178°	Bezel Width	
Viewing Angle (H/V at CR 5:1)	178°/178°	Sides (mm / inches)	2 / 0.08"
Contrast Ratio (Typical)	1000:1	Top (mm / inches)	2 / 0.08"
Dynamic Contrast Ratio (Typical)	3M:1	Bottom (mm / inches)	22 / 0.87"
Pixel Pitch (mm)	0.2058		
Dot/Pixel Per Inch (DP/PPI)	123.6	SPECIAL FEATURES	
Color Gamut (CIE 1931)	99% sRGB	Anti-Glare	Yes
Color Support (Typical)	16.7 Million	Thin Client Support (Tiny)	Yes
Response Time (Typical)	4/6/14 ms (G to G)	Others	Daisy Chain
Processor LUT	8-bit (6-bit + 2-bit FRC)		
DIMENSIONS (W x D x H)		ENVIRONMENTAL	
Size Packed		Temperature	
(mm)	635 x 188 x 422	Operating	0 °C - 40 °C
(inches)	25" x 7.4" x 16.61"	Non-operating	-20 °C - 60 °C
Size Unpacked with Stand		Humidity	
(mm)	540.2 x 261.75 x 373.4	Operating	10% - 80%
(inches)	21.26" x 10.3" x 14.7"	Non-operating	5% - 95%
Size Unpacked without Stand		Altitude	
(Monitor Head Only)		Operating	0 m - 5000 m
(mm)	540.2 x 42 x 325.98	Non-operating	0 ft - 40,000 ft
(inches)	21.26" x 1.65" x 12.83"	Ambient Operating Temperature	0 °C - 40 °C
Distance from Table to Panel		Heat Dissipation	
(mm / inches)		Typical	75.02 Btu/h
Lowest Pixel at Bottom of Screen	70.64 / 2.78"	Maximum	228.47 Btu/h
Highest Pixel at Top of Screen	366.99 / 14.45"	Arsenic-Free Glass	Yes
Stand Base Footprint Area		PVC-Free	Yes (Without Cable)
(mm / inches)	250 x 250 / 9.84" x 9.84"	Mercury-Free	Yes
Weight		PCC % of Plastic Resins	>85%
Packed	Starting at 19.69 lbs (8.93 kg)		
Unpacked	Starting at 12.35 lbs (5.6 kg)		
Monitor Head Only	Starting at 8.22 lbs (3.73 kg)		
Full Container Load (40' STD / 20' STD)	1050 Units / 500 Units		
SIGNAL INPUT		SIGNAL INTERFACE / PERFORMANCE	
Video Input Signals	2 x HDMI 1.4 DisplayPort 1.2 Mini DisplayPort DisplayPort-Out	Horizontal Frequency	50 Hz - 76 Hz
Video Cables Supplied	Mini DisplayPort - DisplayPort Cable	Vertical Frequency	30 kHz - 99 KHz
Video Cable Length	1.8 m	Native Resolution	2560 x 1440
Daisy Chain Support	Yes	Maximum Pixel Clock Speed / Bandwidth	
USB Hub	USB 3.0 ¹ (1 x Up, 4 x Down (1 x BC 1.2)	HDMI	300 MHz
USB Cable Supplied	Yes	DisplayPort	5.4 GHz
USB Cable Length	1.8 m	Default Color Temperature	6500K
Audio-Out	Yes (3.5 mm)	Preset/User Modes	20/24
		On Screen Display (OSD) Controls	
		Buttons	5 Buttons
		Languages	English, French, German, Spanish, Italian, Japanese, Simplified Chinese, Russian
POWER CONSUMPTION		CERTIFICATIONS	
Typical	24 W	TCO	TCO 7.0 / TCO Edge 2.0
Maximum	67 W	GREENGUARD	VOC
Sleep-Mode	<0.5 W	RoHS (EU 2002/95/EC)	Yes
Off-Mode	<0.5 W	Windows Certification	Windows 7 / Windows 10
Power Supply	Internal	Image Quality Capability	ISO 9241-307
Power Voltage	90 VAC - 264 VAC	Reduction of Hazardous Substances	Arsenic-Free / Mercury-Free
Voltage Dynamic Frequency	47 Hz - 63 Hz	China Energy Efficiency Standard	Tier 2
WARRANTY AND AVAILABILITY			
Geography Availability	Worldwide		
ThinkVision Logo	Yes		
Global Model	Yes		
Warranty	3 Years		



¹ Depending on many factors such as the processing capability of peripheral devices, file attributes, and other factors related to system configuration and operating environments, the actual transfer rate using the various USB connectors on this device will vary and is typically slower than the data rates as defined by the respective USB specifications: - 5 Gbit/s for USB 3.1 Gen 1; 10 Gbit/s for USB 3.1 Gen 2 & 20 Gbit/s for USB 3.2.