

ThinkVision T24v-10 MONITOR

BEST-IN-CLASS VoIP MONITOR.



Lenovo™

EASY CONFERENCING. EASY MANAGEMENT. EASY CHOICE.

When it's vital to collaborate with partners and colleagues, this best-in-class VoIP monitor makes conferencing easy. The near-edgeless Lenovo™ ThinkVision® T24v Monitor integrates a webcam, microphone and speakers making it truly easy to setup and manage. Equipped with Windows Hello, you'll get enterprise-grade security with just a look when sign-in to your Windows devices. The outstanding 23.8" professional monitor features a full range of connectivity options and full-function stand to suit any environment.

WHY YOU SHOULD BUY THE LENOVO THINKVISION T24v-10 MONITOR




Easy conferencing

Conference calls are a breeze with integrated webcam with privacy lock, speakers and microphone.



Easy sign-in

With Windows Hello supported devices such as smartwatches, smart bracelets or smartphones, you'll get enhanced security without having to type in a password.



Easy on the eyes

The near-edgeless 23.8" In-Plane Switching screen provides exceptional visuals across wide-viewing angles.

THE LENOVO THINKVISION T24v-10 MONITOR IS BEST SUITED FOR

1

Constant collaborators who want a large-screen monitor designed for easy yet full-function conferencing.

2

Teaching professionals who utilize distance education or frequently collaborate with students outside the classroom.

3

IT professionals who live on the web and frequently provide remote support to computer users.



WWW.LENOVO.COM



ThinkVision T24v-10 MONITOR

SPECIFICATIONS

DISPLAY		ENVIRONMENTAL	
Panel Size	23.8"	Temperature	
Panel Type	In-Plane Switching	Operating	0°C – 40°C
Backlight	WLED	Non-Operating	-20°C – 60°C
Resolution	1920 x 1080	Humidity	
Aspect Ratio	16:9	Operating	10% – 80%
Anti-Glare	Yes	Non-Operating	5% – 95%
Screen Dimensions (W x H) (mm)	527.04 x 296.46	Altitude	
Maximum Brightness (Typical)	250 cd/m ²	Operating	0 m – 8000 m
Viewing Angle (H/V at CR 10:1)	178°/178°	Non-Operating	0 ft – 40,000 ft
Contrast Ratio (Typical)	1000:1	Arsenic-Free Glass	Yes
Dynamic Contrast Ratio	3M:1	PVC-Free	Yes
Pixel Pitch (W x H) (mm)	0.25 x 0.25	Mercury-Free	Yes
Dot/Pixel Per Inch (DP/PPI)	102	PCC % of Plastic Resins	>85%
Color Gamut (CIE 1931)	72% sRGB		
Response Time (Extreme/Typical/Off)	4/6/14 ms (G-to-G)		
POWER CONSUMPTION		DIMENSIONS (W x D x H)	
Typical	20 W	Size Packed	
Maximum	45 W	(mm)	608 x 395 x 187
Sleep-Mode	<0.5 W	(inches)	23.94" x 15.55" x 7.36"
Switch Off-Mode	<0.3 W	Size Unpacked with Stand	
Power Supply	Internal	Lowest Position	
Power Voltage	90 VAC – 264 VAC	(mm)	540.2 x 261.9 x 390.5
Voltage Dynamic Frequency	47 Hz – 63 Hz	(inches)	21.28" x 10.32" x 15.39"
		Highest Position	
		(mm)	540.2 x 261.9 x 500.5
		(inches)	21.28" x 10.32" x 19.72"
		Size Unpacked without Stand	
		(Monitor Head Only)	
		(mm)	540.2 x 43.8 x 343.7
		(inches)	21.27" x 1.72" x 13.53"
		Distance from Table to Panel	
		Lowest Pixel at Bottom of Screen	
		(mm / inches)	69.6 / 2.74"
		Highest Pixel at Top of Screen	
		(mm / inches)	69.6 / 2.74"
		Stand Base Footprint Area	
		(mm / inches)	242.5 x 212.8 / 9.55" x 8.38"
		Weight	
		Packed	Starting at 15.78 lbs (7.16 kg)
		Unpacked	Starting at 11.18 lbs (5.07 kg)
		Monitor Head Only	Starting at 7.3 lbs (3.31 kg)
SIGNAL INPUT		COMPLIANCE	
Video Input Signals	HDMI™ 1.4 + DisplayPort™ 1.2 + VGA	EPEAT™	Silver
Video Cables Supplied	HDMI™ (ROW) + DisplayPort™ + VGA + USB 3.0 ¹	ENERGY STAR® Rating	7.0
Video Cable Length	1.8 m	ULE	Gold
USB Hub	Yes	TCO®	TCO Display 7.0 / TCO Edge 2.0
USB Cable Supplied	Yes	RoHS (EU 2002/95/EC)	Yes
Audio-Out	Yes (3.5 mm)	Windows Certification	Windows 7 / Windows 10
		China Energy Efficiency Standard	Grade 2
		TÜV Eye Comfort	Yes
SIGNAL INTERFACE / PERFORMANCE		WARRANTY AND AVAILABILITY	
Horizontal Frequency	30 kHz – 81 kHz	Warranty	
Vertical Frequency	50 Hz – 75 Hz	ROW	3 Years
Native Resolution	1920 x 1080	PRC	18 Months
Maximum Pixel Clock Speed/ Bandwidth	VGA : 205 MHz HDMI™ : 165 MHz DisplayPort™ : 165 MHz	Geography Availability	WW
Default Color Temperature	6500K		
Preset/User Modes	27/21		
OSD Buttons	5+2 Buttons		
OSD Languages	English, French, German, Spanish, Italian, Japanese, Simplified Chinese, Russian		
MECHANICAL			
Tilt Angle (Front / Back)	-5° / 30°		
Swivel Angle (Left / Right)	+/-45°		
Lift (mm)	Yes (110)		
Pivot	+/-90°		
VESA® Mount (mm)	Yes (100 x 100)		
Kensington® Lock Slot	Yes		
Cable Management	Yes		
Bezel Color	Raven Black		
Bezel Width			
Top (mm / inches)	2 / 0.08"		
Bottom (mm / inches)	22 / 0.87"		
Sides (mm / inches)	2 / 0.08"		



WWW.LENOVO.COM

¹ Depending on many factors such as the processing capability of peripheral devices, file attributes, and other factors related to system configuration and operating environments, the actual transfer rate using the various USB connectors on this device will vary and is typically slower than the data rates as defined by the respective USB specifications: - 5 Gbit/s for USB 3.1 Gen 1; 10 Gbit/s for USB 3.1 Gen 2 & 20 Gbit/s for USB 3.2.