


OVERVIEW



1. F	Power button	7. VGA
2. H	Headphone / microphone combo jack (3.5mm)	8. HDMI 2.1 TMDS
3. L	JSB-C (USB 5Gbps), with 15W charging	9. 4x USB-A (Hi-Speed USB)
4. L	JSB-A (USB 5Gbps)	10. Ethernet (RJ-45)
5. L	JSB-A (USB 10Gbps)	11. Power connector
6. A	Audio-out (3.5mm)	



PERFORMANCE

Processor

Processor Family

Intel® U Series Core Ultra 5 / 7 Processor (Series 2)

Processor**

Processor Name	Cores	Threads	Base Frequency	Max Frequency	Cache	Processor Graphics	NPU
Core Ultra 5 225	10 (6 P-core + 4 E-core)	10	P-core 3.3GHz / E- core 2.7GHz	P-core 4.9GHz / E- core 4.4GHz	20MB	Intel® Graphics	Intel® AI Boost
Core Ultra 5 225F	10 (6 P-core + 4 E-core)	10	P-core 3.3GHz / E- core 2.7GHz	P-core 4.9GHz / E- core 4.4GHz	22MB	-	Intel® AI Boost
Core Ultra 7 265	20 (8 P-core + 12 E-core)	20	P-core 2.4GHz / E- core 1.8GHz	P-core 5.2GHz / E- core 4.6GHz	36MB	Intel® Graphics	Intel® AI Boost
Core Ultra 7 265F	20 (8 P-core + 12 E-core)	20	P-core 2.4GHz / E- core 1.8GHz	P-core 5.2GHz / E- core 4.6GHz	36MB	-	Intel® AI Boost

Al (Artificial Intelligence)

AI PC Category

- Lenovo® AI PC
- Non-AI PC

Al Performance

Up to 33 overall TOPS

NPU

Integrated Intel® Al Boost, up to 13 TOPS

Operating System

Operating System**

- Windows® 11 Pro
- Windows® 11 Home
- Windows® 11 Home Single Language
- No preload operating system

Graphics

Graphics**[1]

Graphics	Туре	Memory	AI TOPS (Peak)	Max Resolution	Connector	Key Features
Intel® Graphics	Integrated	Shared	-	2048*1536@50HZ(VGA) 1920*1080@60HZ(VGA) 3840*2160@60Hz(HDMI®)	1x HDMI® 1.4 1x VGA	DirectX® 12.1
NVIDIA® GeForce RTX™ 3050	Discrete	6GB GDDR6	108	7680x4320@60Hz(HDMI®), 7680x4320@60Hz(DP)	1x HDMI® 2.1 FRL, 1x DP 1.4	DirectX® 12
NVIDIA® GeForce RTX™ 4060	Discrete	8G GDDR6	-	7680x4320@60Hz(HDMI®), 7680x4320@60Hz(DP)	1x HDMI® 2.1a FRL, 3x DP 1.4a (HBR3, DSC)	DirectX® 12, OpenGL 4.6

Notes:

[1] The information of integrated graphics are not applicable for the models with processor which has no integrated graphics inside (for the details, please refer to processor section).

Monitor Support

Monitor Support

Supports up to 2 independent displays via onboard ports (VGA and HDMI®), more displays support via discrete graphics



Chipset

Chipset

Intel® B860 chipset

Memory

Max Memory[1]

Up to 32GB DDR5-5600

Memory Slots

Two DDR5 UDIMM slots, dual-channel capable

Memory Type**

- DDR5-4800
- DDR5-5600

Memory Protection

Non-ECC

Notes:

[1] The max memory is based on the test results with current Lenovo® memory offerings.

Storage

Storage Support[1]

Up to three drives, 1x 3.5" HDD + 2x M.2 SSD

- 3.5" HDD up to 2TB
- M.2 SSD up to 2TB each

Storage Type**

Disk Type	Interface	RPM
3.5" SATA HDD	SATA 6Gb/s	7.2K
M.2 2280 SSD	PCle® NVMe®, PCle® 4.0 x4	-

Notes:

[1] The max capacity of each disk type is based on the test results with current Lenovo® storage offerings.

Removable Storage

Optical

None

Card Reader

No card reader

Multi-Media

Audio Chip

High Definition (HD) Audio, Realtek® ALC623-CG codec

Speakers

No speakers

Power Supply

Power Supply**

Power	Туре	Efficiency	Key Features
260W	Fixed	90%	100-240V, 50-60Hz
310W	Fixed	92%	100-240V, 50-60Hz
500W	Fixed	92%	100-240V, 50-60Hz
400W	Fixed	92%	100-240V, 50-60Hz

DESIGN



Input Device

Keyboard**

- Lenovo® Calliope Keyboard (USB connector), cloud grey
- Lenovo® Calliope Keyboard (USB connector), luna grey
- No keyboard

Mouse**

- No mouse
- Lenovo® Calliope Mouse (USB connector), Cloud Grey
- Lenovo® Calliope Mouse (USB connector), Luna Grey

Mechanical

Form Factor

Tower (17L)

Dimensions (WxDxH)[1]

170 x 279 x 376 mm (6.7 x 10.98 x 14.8 inches)

Packaging Dimensions (WxDxH)

270 x 525 x 395 mm (10.62 x 20.66 x 15.55 inches)

Weight^[2]

Around 7.2 kg (15.87 lbs)

Packaging Weight

All models: Around 10.3 kg (22.7 lbs)

Case Color**

- · Cloud grey
- · Luna grey

Expansion Slots

- One PCIe® 4.0 x16, full height
- One PCIe® 3.0 x1, full height
- Three M.2 slots (one for WLAN, two for SSD)

Cooling System (Fan & Cooler)

- 1x front system fan, 1x rear system fan
- · 1x rear system fan
- None

Notes:

[1] The system dimensions may vary depending on configurations.

[2] The system weight is approximate and based on results in Lenovo® lab, which varies depending on the source of component, variance of the distribution of each component, and manufacturing process. It may not be the exact weight for each specific model.

CONNECTIVITY

Network

Onboard Ethernet

Gigabit Ethernet, 1x RJ-45

WLAN + Bluetooth®**

- Wi-Fi[®] 6, 802.11ax 2x2 Wi-Fi[®] + Bluetooth[®] 5.2, M.2 card
- Wi-Fi® 6E, 802.11ax 2x2 Wi-Fi® + Bluetooth® 5.2, M.2 card
- Wi-Fi® 7, 802.11be 2x2 Wi-Fi® + Bluetooth® 5.4, M.2 card
- No WLAN and Bluetooth®

Ports^[1]

Front Ports

- 1x USB-A (USB 5Gbps / USB 3.2 Gen 1)
- 1x USB-A (USB 10Gbps / USB 3.2 Gen 2)

IdeaCentre Tower 17IAS10



- 1x headphone / microphone combo jack (3.5mm)
- 1x USB-C[®] (USB 5Gbps / USB 3.2 Gen 1)

Rear Ports[2]

- 4x USB-A (Hi-Speed USB / USB 2.0)
- 1x HDMI® 2.1 TMDS
- 1x VGA
- 1x Ethernet (RJ-45)
- 1x audio-out (3.5mm)
- 1x power connector

Notes:

[1] The transfer speed of following ports will vary and, depending on many factors, such as the processing speed of the host device, file attributes and other factors related to system configuration and your operating environment, will be slower than theoretical speed.

USB 2.0: 480 Mbit/s;

USB 3.2 Gen 1 (SuperSpeed USB 5Gbps, formerly USB 3.0 / USB 3.1 Gen 1): 5 Gbit/s;

USB 3.2 Gen 2 (SuperSpeed USB 10Gbps, formerly USB 3.1 Gen 2): 10 Gbit/s;

USB4® 20Gbps / USB 3.2 Gen 2x2 (SuperSpeed USB 20Gbps): 20 Gbit/s;

USB4® 40Gbps (USB 40Gbps): 40 Gbit/s;

Thunderbolt™ 3/4: 40 Gbit/s.

[2] For video ports on discrete graphics, please see graphics section.

SECURITY & PRIVACY

Security

Security Chip

Firmware TPM 2.0 integrated in chipset

BIOS Security

- · Administrator password
- Hard disk password

SERVICE

Warranty^[1]

Base Warranty**

- 1-year mail-in service
- 1-year courier or carry-in service
- 1-year onsite service
- · 2-year courier or carry-in service
- · 3-year courier or carry-in service

Notes:

[1] The warranty upgrades may be bundled with some models, please check the "Included upgrade" column in the specific model's configurations. For more service extensions, please go to https://smartfind.lenovo.com/. To learn more details of warranty policy, please access https://support.lenovo.com/warrantylookup/warrantypolicy.

OPERATING REQUIREMENTS

Operating Environment

Temperature

- Operating: 10°C (50°F) to 35°C (95°F)
- Storage: -40°C (-40°F) to 60°C (140°F)

Relative Humidity

- Operating: 20% to 80%
- Storage: 20% to 90%

Altitude

• Operating: -15.2 m (-50 ft) to 3048 m (10,000 ft)



• Storage: -15.2 m (-50 ft) to 10668 m (35,000 ft)

CERTIFICATIONS

Green Certifications

- (Optional) ENERGY STAR® 8.0
- ErP Lot 3
- RoHS compliant

Notes:

[1] The items listed under the "Green Certifications" section may not only refer to certification but also registration or self-declaration. For ESG & regulatory compliance documents, please visit https://compliance.lenovo.com.

- Feature with ** means that only one option listed under the feature can be configured on selected models.

 Please refer to the model configuration for specific information.
- Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not
 responsible for photographic or typographical errors. LENOVO PROVIDES THIS PUBLICATION "AS IS,"
 WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES
 OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow
 disclaimer of express or implied warranties in certain transactions, therefore this disclaimer may not apply to
 you.
- The specifications on this page may not be available in all regions, and may be changed or updated without notice.













