

OVERVIEW



| 1 | . Kensington Nano Security Slot | 4. Headphone / microphone combo jack (3.5mm) | | | |
|---|---------------------------------|--|--|--|--|
| 2 | 2. USB-C 3.2 Gen 1 | 5. microSD card reader | | | |
| 3 | 3. USB 3.2 Gen 1 | | | | |



PERFORMANCE

Processor

Processor Family

MediaTek Processor

Processor

| Processor Name | Cores | Threads | Max Frequency | Processor Graphics |
|-----------------------|----------------------------|---------|--------------------------|----------------------|
| MediaTek Kompanio 520 | Octa-core: 2x A76 + 6x A55 | 8 | A76@2.05GHz / A55@2.0GHz | Arm Mali-G52 2EE MC2 |

Operating System

Operating System

ChromeOS

Graphics

Graphics

| Graphics | Туре | Memory |
|--------------------------|------------|--------|
| Arm Mali-G52 2EE MC2 GPU | Integrated | Shared |

Monitor Support

Monitor Support

Supports up to 2 independent displays (native display and 1 external monitor via USB-C®)

• USB-C® supports up to 1920x1080@60Hz

Chipset

Chipset

MediaTek SoC (System on Chip) platform

Memory

Max Memory

- 4GB soldered memory, not upgradable
- 8GB soldered memory, not upgradable

Memory Slots

Memory soldered to systemboard, no slots, dual-channel

Memory Type**

- LPDDR4x-3600
- LPDDR4x-3733

Storage

Storage Support

- · 64GB eMMC 5.1 on systemboard
- 128GB eMMC 5.1 on systemboard

Storage Slot

eMMC on systemboard, no slots

Storage Type

| Disk Type | Interface | Offering | | |
|--------------|-----------|--------------|--|--|
| Flash Memory | eMMC 5.1 | 64GB / 128GB | | |

Removable Storage

Card Reader

microSD card reader

Multi-Media

Audio Chip

IP Slim 3 Chrome 14M868



High Definition (HD) Audio

Speakers

Stereo speakers, 2W x2, optimized with Waves MaxxAudio®

Microphone

Dual-microphone array

Camera**

- FHD 1080p, with privacy shutter, fixed focus
- HD 720p, with privacy shutter, fixed focus

Battery

Battery

47Wh Rechargeable Li-ion Battery

Max Battery Life[1]

Google power load test: 13.5 hr

Notes:

[1] All battery life claims are approximate maximum and based on results using the MobileMark® 2014, MobileMark® 2018, MobileMark® 25, MobileMark® 30, JEITA 2.0, JEITA 3.0, continuous 1080p video playback (with 150nits brightness and default volume level) or Google Power Load Test (PLT) battery-life benchmark tests. Actual battery life will vary depending on many factors such as product configuration and usage, software use, wireless functionality, power management settings, and screen brightness. The maximum capacity of the battery will decrease with time and use.

Power Adapter

Power Adapter

45W USB-C® (3-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz

DESIGN

Display

Display**

| Size | Resolution | Touch | Туре | Brightness | Surface | Aspect Ratio | Contrast Ratio | Color Gamut | Viewing Angle (L/R/U/D) |
|------|--------------------|-----------------|--------------------|------------|----------------|-----------------|-------------------|----------------|----------------------------|
| 14" | HD (1366x768) | None | TN | 250nits | Anti- glare | 16:9 | 400:1 | 45% NTSC | 45° / 45° / 15° / 35° |
| 14" | FHD (1920x1080) | None | TN | 250nits | Anti- glare | 16:9 | 400:1 | 45% NTSC | 45° / 45° / 15° / 35° |
| 14" | FHD (1920x1080) | Multi- touch | IPS ^[1] | 300nits | Anti- glare | 16:9 | 1000:1 | 100% sRGB | 89° / 89° / 89° / 89° |

Touchscreen

- On-cell multi-touch, supports 10-point touch
- Non-touch

Notes:

[1] IPS (in-plane switching) technology may refer to IPS, PLS, ADS, AHVA, AAS.

Input Device

Pen

No support

Keyboard

Chrome keyboard, 6-row, spill-resistant

Keyboard Backlight

Non-backlight

Touchpad



Buttonless Mylar® surface multi-touch touchpad, 69 x 104 mm (2.72 x 4.09 inches)

Mechanical

Dimensions (WxDxH)[1]

325.9 x 221.8 x 18.6 mm (12.83 x 8.73 x 0.73 inches)

Weight^[2]

Around 1.3 kg (2.87 lbs)

Case Color**

- · Abyss blue
- Cloud grey

Surface Treatment

Texture painting

Case Material

PC-ABS + 15% Talc (top), PC-ABS + 15% Talc (bottom)

Notes:

[1] The system dimensions may vary depending on configurations.

[2] The system weight is approximate and based on results in Lenovo® lab, which varies depending on the source of component, variance of the distribution of each component, and manufacturing process. It may not be the exact weight for each specific model.

CONNECTIVITY

Network

Ethernet

No onboard Ethernet

WLAN + Bluetooth®

Wi-Fi® 6, 802.11ax 2x2 Wi-Fi® + Bluetooth® 5.3, M.2 card[1]

WWAN

No support

Notes:

[1] Wi-Fi® 6 full features might be limited by country-level restrictions.

Ports^[1]

Standard Ports

- 1x USB 3.2 Gen 1
- 1x USB-C® 3.2 Gen 1 (support data transfer, Power Delivery 3.0 and DisplayPort™ 1.1a)
- 1x Headphone / microphone combo jack (3.5mm)
- 1x microSD card reader

Notes:

[1] The transfer speed of following ports will vary and, depending on many factors, such as the processing speed of the host device, file attributes and other factors related to system configuration and your operating environment, will be slower than theoretical speed.

USB 2.0: 480 Mbit/s;

USB 3.2 Gen 1 (SuperSpeed USB 5Gbps, formerly USB 3.0 / USB 3.1 Gen 1): 5 Gbit/s;

USB 3.2 Gen 2 (SuperSpeed USB 10Gbps, formerly USB 3.1 Gen 2): 10 Gbit/s;

USB4® 20Gbps / USB 3.2 Gen 2x2 (SuperSpeed USB 20Gbps): 20 Gbit/s;

USB4® 40Gbps (USB 40Gbps): 40 Gbit/s;

Thunderbolt™ 3/4: 40 Gbit/s.

SECURITY & PRIVACY

Security



Security Chip

Google Security Chip H1

Physical Locks

Kensington® Nano Security Slot™, 2.5 x 6 mm

Fingerprint Reader

No fingerprint reader

BIOS Security

No support

Other Security

Camera privacy shutter

SERVICE

Warranty

Base Warranty**

- 1-year courier or carry-in service
- 1-year courier or carry-in with 2-year system board service (Korea only)
- · 2-year (1-yr battery) courier or carry-in service
- 3-year (1-yr battery) courier or carry-in service

OPERATING REQUIREMENTS

Operating Environment

Temperature[1]

- Operating: 5°C (41°F) to 35°C (95°F)
- Storage: 5°C (41°F) to 43°C (109°F)

Relative Humidity

- Operating: 8% to 95% at wet-bulb temperature 23°C (73°F)
- Storage: 5% to 95% at wet-bulb temperature 27°C (81°F)

Altitude

Maximum altitude (without pressurization): 3048 m (10,000 ft)

Notes:

[1] When you charge the battery, its temperature must be no lower than 10°C (50°F).

CERTIFICATIONS

Green Certifications

- ENERGY STAR® 8.0
- EPEAT™ Gold Registered^[2]
- ErP Lot 6/26
- · RoHS compliant

Notes:

[1] The items listed under the "Green Certifications" section may not only refer to certification but also registration or self-declaration. For ESG & regulatory compliance documents, please visit https://compliance.lenovo.com.

[2] EPEAT™ is registered where applicable, please visit <u>epeat.net</u> for registration status by country.

- Feature with ** means that only one option listed under the feature can be configured on selected models. Please refer to the model configuration for specific information.
- Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not responsible for photographic or typographical errors. LENOVO PROVIDES THIS PUBLICATION "AS IS,"
 WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES

IP Slim 3 Chrome 14M868



OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow disclaimer of express or implied warranties in certain transactions, therefore this disclaimer may not apply to you.

• The specifications on this page may not be available in all regions, and may be changed or updated without notice.







MediaTek Kompanio



MediaTek Kompanio



MediaTek Kompanio



MediaTek Kompanio



MediaTek Kompanio