

OVERVIEW



1. USB-C (USB 10Gbps), with PD 140W & DP 1.4	5. HDMI
2. Combo audio jack	6. Ethernet (RJ-45)
3. USB-A (USB 5Gbps)	7. USB-A (USB 5Gbps)
4. USB-A (USB 5Gbps)	8. Power connector

Notes:

• Port 1: PD 140W is the input power and requires the use of Lenovo unique adapter, otherwise it may support lower than 140W.



PERFORMANCE

Processor

Processor Family

13th Generation Intel® Core™ i5 / i7 or 14th Generation Intel® Core™ i7 Processor

Processor**

Processor Name	Cores	Threads	Base Frequency Max Frequency		Cache	Processor Graphics
Core i5- 13450HX	10 (6 P-core + 4 E-core)	16	P-core 2.4GHz / E-core 1.8GHz	P-core 4.6GHz / E-core 3.4GHz	20MB	Intel® UHD Graphics
Core i7- 13650HX	14 (6 P-core + 8 E-core)	20	P-core 2.6GHz / E-core 1.9GHz	P-core 4.9GHz / E-core 3.6GHz	24MB	Intel® UHD Graphics
Core i7- 14700HX	(28		P-core 2.1GHz / E-core 1.5GHz	P-core 5.5GHz / E-core 3.9GHz	33MB	Intel® UHD Graphics

Operating System

Operating System**

- Windows® 11 Pro
- Windows® 11 Home
- Windows® 11 Home Single Language
- · No preload operating system

Graphics

Graphics**

Graphics	Туре	Memory	Boost Clock	TGP	AI TOPS (Peak)	Key Features
NVIDIA® GeForce RTX™ 3050 Laptop GPU	Discrete	6GB GDDR6	1732 MHz	95W	142 TOPS	Advanced Optimus, DLSS 2, Dynamic Boost 2.0, DirectX® 12 Ultimate
NVIDIA® GeForce RTX™ 3050A Laptop GPU	Discrete	4GB GDDR6	2205 MHz	65W	-	DLSS, Dynamic Boost 2.0, VR ready, DirectX® 12 Ultimate
NVIDIA® GeForce RTX™ 4050 Laptop GPU	Discrete	6GB GDDR6	2370 MHz	105W	194	Advanced Optimus, DLSS 3.5, Dynamic Boost 2.0, DirectX® 12 Ultimate
NVIDIA® GeForce RTX™ 4060 Laptop GPU	Discrete 8GB 2370 MHz		115W	233 TOPS	Advanced Optimus, DLSS 3.5, Dynamic Boost 2.0, VR ready, DirectX® 12 Ultimate	

Notes:

[1] The actual TGP may depend on system configuration. System configured with 170W power adapter, TGP will be 105W. System configured with 230W power adapter, TGP will be 115W.

Monitor Support

Monitor Support

Supports up to 3 independent displays (native display and 2 external monitors via HDMI®, USB-C®)

- HDMI® supports up to 4K@60Hz
- USB-C® supports up to 4K@60Hz

Chipset

Chipset

Intel® HM770 chipset

Memory

Max Memory[1]

- Up to 32GB DDR5-4800
- Up to 32GB DDR5-5600

Memory Slots



Two DDR5 SO-DIMM slots, dual-channel capable

Memory Type**

- DDR5-4800
- DDR5-5600

Notes:

[1] Maximum memory is only to test technical readiness of notebook. Available memory to sell would vary.

Storage

Storage Support[1]

Up to two drives, 2x M.2 SSD

• M.2 2242 SSD up to 1TB each

Storage Slot

Two M.2 2280 PCle® 4.0 x4 slots

Storage Type

Disk Type	Interface	Offering	
M.2 2242 SSD	PCIe® NVMe®, PCIe® 4.0 x4	512GB / 1TB	

Notes:

[1] The storage capacity supported is based on the test results with current Lenovo® storage offerings.

Removable Storage

Card Reader

No card reader

Multi-Media

Audio Chip

High Definition (HD) Audio, Realtek® ALC3287 codec

Speakers

Stereo speakers, 2W x2, optimized with Nahimic Audio

Microphone

Dual-microphone array

Camera**

- FHD 1080p, with E-shutter, fixed focus
- HD 720p, with E-shutter, fixed focus

Battery

Battery

Integrated Li-Polymer 60Wh battery, supports Rapid Charge Pro (charge up to 50% in 30min)

Max Battery Life[1]

MobileMark® 25: 4.1 hr

Local video (1080p) playback@150nits: 5.6 hr

Notes:

[1] All battery life claims are approximate maximum and based on results using the MobileMark® 2014, MobileMark® 2018, MobileMark® 25, MobileMark® 30, JEITA 2.0, JEITA 3.0, continuous 1080p video playback (with 150nits brightness and default volume level) or Google Power Load Test (PLT) battery-life benchmark tests. Actual battery life will vary depending on many factors such as product configuration and usage, software use, wireless functionality, power management settings, and screen brightness. The maximum capacity of the battery will decrease with time and use.

Power Adapter

Power Adapter**[1]

- 170W slim tip (3-pin) AC adapter, 100-240V, 50-60Hz
- 230W slim tip (3-pin) AC adapter, 100-240V, 50-60Hz



Notes:

[1] AC adapter offerings depend on the country.

Special Features

Special Features

Al Chip: LA1

DESIGN

Display

Display**[1]

Size	Resolution	Touch	Туре	Brightness	Surface	Aspect Ratio	Contrast Ratio	Color Gamut	Refresh Rate	Viewing Angle (L/R/U/D)	Key Features
15.6"	FHD (1920x1080)	None	IPS	300nits	Anti- glare	16:9	1000:1	100% sRGB	144Hz	85° / 85° / 85° / 85°	Advanced Optimus, NVIDIA® G- SYNC®, TÜV Low Blue Light (Software)
15.6"	WQHD (2560x1440)	None	IPS	350nits	Anti- glare	16:9	1000:1	100% sRGB	165Hz	85° / 85° / 85° / 85°	Advanced Optimus, NVIDIA® G- SYNC®, TÜV Low Blue Light (Software)

Touchscreen

Non-touch

Notes:

[1] IPS (in-plane switching) technology may refer to IPS, PLS, ADS, AHVA, AAS.

Input Device

Pen

No support

Keyboard

6-row, multimedia Fn keys, numeric keypad

Keyboard Backlight**

- 4-Zone RGB backlight
- · White backlight

Touchpad

Buttonless Mylar® surface multi-touch touchpad, supports Precision TouchPad (PTP), 75 x 120 mm (2.95 x 4.72 inches)

Mechanical

Dimensions (WxDxH)[1]

359.86 x 258.7 x 21.9-23.9 mm (14.17 x 10.19 x 0.86-0.94 inches)

Weight^[2]

Starting at 2.38 kg (5.25 lbs)

Case Color

Luna grey

Surface Treatment

Painting

Case Material

PC-ABS (top), PC-ABS (bottom)



Notes:

[1] The system dimensions may vary depending on configurations.

[2] The system weight is approximate and based on results in Lenovo® lab, which varies depending on the source of component, variance of the distribution of each component, and manufacturing process. It may not be the exact weight for each specific model.

CONNECTIVITY

Network

Ethernet[1]

Gigabit Ethernet, 1x RJ-45, supports Wake-on-LAN

WLAN + Bluetooth®[2]

Wi-Fi® 6, 802.11ax 2x2 Wi-Fi® + Bluetooth® 5.2, M.2 card[3]

WWAN

No support

Notes:

[1] Wake-on-LAN needs the power adapter plugged in.

[2] Bluetooth® may operate at a lower version than hardware design depending on the factors such as operating system, driver, etc.

[3] Intel® Wi-Fi® 6 full features might be limited by country-level restrictions.

Ports^[1]

Standard Ports

- 3x USB-A (USB 5Gbps / USB 3.2 Gen 1)
- 1x USB-C[®] (USB 10Gbps / USB 3.2 Gen 2), with Lenovo[®] PD 140W and DisplayPort[™] 1.4^[2]
- 1x HDMI® 2.1, up to 8K/60Hz
- 1x Headphone / microphone combo jack (3.5mm)
- 1x Ethernet (RJ-45)
- 1x Power connector

Notes:

[1] The transfer speed of the ports will vary and, depending on many factors, such as the processing speed of the host device, file attributes and other factors related to system configuration and your operating environment, will be slower than theoretical speed.

[2] PD 140W is the input power and requires the use of Lenovo® unique adapter, otherwise it may support lower than 140W.

Docking

Docking

Various docking solutions supported via USB-C®.

For more compatible docking solutions, please visit <u>Docking for LOQ™ 15IRX9</u>

SECURITY & PRIVACY

Security

Security Chip

Firmware TPM 2.0 integrated in chipset

Fingerprint Reader

No fingerprint reader

BIOS Security

- Administrator password
- Master hard disk password
- Power-on password
- User hard disk password

LOQ 15IRX9



- · User password
- Self-healing BIOS
- More BIOS security features, please visit <u>BIOS Simulator</u>[1]

Other Security

E-shutter

Notes:

[1] The BIOS simulator is just for reference. Default settings and some options may vary depending on the hardware, operating system and BIOS version.

SERVICE

Warranty

Base Warranty**

- 1-year courier or carry-in service
- 1-year courier or carry-in with 2-year system board service (Korea only)
- 2-year (1-yr battery) courier or carry-in service
- 3-year (1-yr battery) courier or carry-in service
- No base warranty

ACCESSORIES

Bundled Accessories

Bundled Accessories[1]

- Lenovo® LOQ™ M100 RGB Mouse (USB connector)
- None

Notes:

[1] For more compatible accessory solutions, please visit Accessories for LOQ™ 15IRX9

OPERATING REQUIREMENTS

Operating Environment

Temperature^[1]

- At altitudes up to 2438 m (8,000 ft)
 - Operating: 5°C to 35°C (41°F to 95°F)
 - Storage: 5°C to 43°C (41°F to 109°F)
- At altitudes above 2438 m (8,000 ft)
 - Maximum temperature when operating under the unpressurized condition: 31.3°C (88°F)

Relative Humidity

- Operating: 8% to 95% at wet-bulb temperature 23°C (73°F)
- Storage: 5% to 95% at wet-bulb temperature 27°C (81°F)

Altitude

Maximum altitude (without pressurization): 3048 m (10,000 ft)

Notes:

[1] When you charge the battery, its temperature must be no lower than 10°C (50°F).

CERTIFICATIONS

Green Certifications

Green Certifications

- ErP Lot 3
- RoHS compliant

LOQ 15IRX9



Notes:

[1] The items listed under the "Green Certifications" section may not only refer to certification but also registration or self-declaration. For ESG & regulatory compliance documents, please visit https://compliance.lenovo.com.

Other Certifications

Mil-Spec Test

MIL-STD-810H military test passed

Other Certifications

TÜV Rheinland® Low Blue Light (Software Solution)

- Feature with ** means that only one option listed under the feature can be configured on selected models.

 Please refer to the model configuration for specific information.
- Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not
 responsible for photographic or typographical errors. LENOVO PROVIDES THIS PUBLICATION "AS IS,"
 WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES
 OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow
 disclaimer of express or implied warranties in certain transactions, therefore this disclaimer may not apply to
 you.
- The specifications on this page may not be available in all regions, and may be changed or updated without notice.













