

OVERVIEW



1. Volume button	6. USB-C 3.1 Gen 1
2. Power button	7. USB 3.1 Gen 1
3. USB 3.1 Gen 1	8. microSD card reader *
4. USB-C 3.1 Gen 1	9. Headphone / microphone combo jack (3.5mm)
5. Kensington Security Slot	10. Pen slot

Notes:

- Items with * are only available on selected models

PERFORMANCE

Processor

Processor Family

Intel® Celeron® Processor

Processor**

Processor Name	Cores	Threads	Base Frequency	Max Frequency	Cache	Processor Graphics
Celeron N4100	4	4	1.1GHz	2.4GHz	4MB	Intel UHD Graphics 600
Celeron N4120	4	4	1.1GHz	2.6GHz	4MB	Intel UHD Graphics 600

Operating System

Operating System^[1]

ChromeOS

Notes:

[1] Some features may not be supported on the system with Linux preload, including but not limited to Intel RST RAID, MIPI computer vision camera, WWAN, Human Presence Detection, etc.

Graphics

Graphics

Graphics	Type	Memory	Key Features
Intel UHD Graphics 600	Integrated	Shared	DirectX® 12

Monitor Support

Monitor Support

Supports up to 2 independent displays (native display and 1 external monitor via USB-C®)

- USB-C supports up to 4096x2160@60Hz

Chipset

Chipset

Intel SoC (System on Chip) platform

Memory

Max Memory

- 4GB soldered memory, not upgradable
- 8GB soldered memory, not upgradable

Memory Slots

Memory soldered to systemboard, no slots

Memory Type

LPDDR4-2400

Storage

Storage Support^[1]

- 32GB eMMC 5.1 on systemboard
- 64GB eMMC 5.1 on systemboard

Storage Type

Disk Type	Interface	Offering
Flash Memory	eMMC 5.1	32GB / 64GB

Notes:

[1] The storage capacity supported is based on the test results with current Lenovo® storage offerings. The system may support larger storage as the technology develops.

Removable Storage

Optical

None

Card Reader

- microSD card reader
- No card reader

Multi-Media

Audio Chip

High Definition (HD) Audio, Maxim MAX98357A Dialog DA7219 codec

Speakers

Stereo speakers, 2W x2

Microphone

Single microphone

Camera

Front HD 720p, fixed focus; rear 5.0-megapixel, autofocus

Battery

Battery

Integrated Li-Polymer 42Wh battery

Max Battery Life^[1]

Google power load test: 10 hr

Notes:

[1] All battery life claims are approximate maximum and based on results using the MobileMark® 2014, MobileMark 2018, MobileMark 25, JEITA 2.0, continuous 1080p video playback (with 150nits brightness and default volume level) or Google Power Load Test (PLT) battery-life benchmark tests. Actual battery life will vary depending on many factors such as product configuration and usage, software use, wireless functionality, power management settings, and screen brightness. The maximum capacity of the battery will decrease with time and use.

Power Adapter

Power Adapter**^[1]

- 45W USB-C (2-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz
- 45W USB-C (3-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz

Notes:

[1] AC adapter offerings depend on the country.

DESIGN

Display

Display^[1]

Size	Resolution	Touch	Type	Brightness	Surface	Aspect Ratio
11.6"	HD (1366x768)	Multi-touch	IPS	250 nits	Glossy, anti-fingerprint	16:9

Touchscreen

Capacitive-type multi-touch, supports 10-point touch

Notes:

[1] California Electronic Waste Recycling Fee

In California USA, per state law, Lenovo charges an electronic waste recycling fee on this covered device at the time of sale of the product. For more information, please go to <https://www.calrecycle.ca.gov/Electronics/Consumer>

Multi-mode

Multi-mode

Laptop, tent, stand, and tablet modes supported by 360° hinge

Input Device

Pen

Lenovo 500e Chrome Pen, garaged, on-board rechargeable. For more information, please read [Lenovo 500e Chrome Pen Overview](#)

Keyboard

6-row, spill-resistant, Anti-pry keycaps

Keyboard Backlight

Non-backlight

Touchpad

One-piece multi-touch touchpad

Mechanical

Dimensions (WxDxH)^[1]

290 x 204 x 20.35 mm (11.42 x 8.03 x 0.8 inches)

Weight^[2]

Starting at 1.31 kg (2.89 lbs)

Case Color

Black

Surface Treatment

Texture

Case Material

PC-ABS (top), PC-ABS (bottom)

Notes:

[1] The system dimensions may vary depending on configurations.

[2] The system weight is approximate and based on results in Lenovo lab, which varies depending on the source of component, variance of the distribution of each component, and manufacturing process. It may not be the exact weight for each specific model.

CONNECTIVITY

Network

Ethernet

No onboard Ethernet

WLAN + Bluetooth®

Intel Wireless-AC 9560, 802.11ac Dual Band 2x2 Wi-Fi® + Bluetooth 5.1, M.2 card

Ports^[1]

Standard Ports

- 2x USB 3.1 Gen 1
- 2x USB-C 3.1 Gen 1 (support data transfer, Power Delivery and DisplayPort™)
- 1x Headphone / microphone combo jack (3.5mm)

Optional Ports

1x microSD card reader

Notes:

[1] The transfer speed of following ports will vary and, depending on many factors, such as the processing speed of the host device, file attributes and other factors related to system configuration and your operating environment, will be slower than theoretical speed.

USB 2.0: 480 Mbit/s;

USB 3.2 Gen 1 (SuperSpeed USB 5Gbps, formerly USB 3.0 / USB 3.1 Gen 1): 5 Gbit/s;

USB 3.2 Gen 2 (SuperSpeed USB 10Gbps, formerly USB 3.1 Gen 2): 10 Gbit/s;
USB4® 20Gbps / USB 3.2 Gen 2x2 (SuperSpeed USB 20Gbps): 20 Gbit/s;
USB4 40Gbps (USB 40Gbps): 40 Gbit/s;
Thunderbolt™ 3/4: 40 Gbit/s

SECURITY & PRIVACY

Security

Security Chip

Google Security Chip H1

Physical Locks

Kensington® Security Slot™, 3 x 7 mm

Fingerprint Reader

No fingerprint reader

BIOS Security

No support

SERVICE

Warranty^[1]

Base Warranty**

- 1-year courier or carry-in service
- 1-year mail-in service
- 1-year courier or carry-in with 2-year system board service (Korea only)
- 2-year (1-yr battery) courier or carry-in service

Notes:

[1] The warranty upgrades may be bundled with some models, please check the "Included upgrade" column in the specific model's configurations. For more service extensions, please go to <https://smartfind.lenovo.com/>. To learn more details of warranty policy, please access <https://pcsupport.lenovo.com/warranty>.

ENVIRONMENTAL

Operating Environment

Temperature^[1]

- Operating: 5°C (41°F) to 35°C (95°F)
- Storage: 5°C (41°F) to 43°C (109°F)

Humidity

- Operating: 8% to 95% at wet-bulb temperature 23°C (73°F)
- Storage: 5% to 95% at wet-bulb temperature 27°C (81°F)

Altitude

Maximum altitude (without pressurization): 3048 m (10,000 ft)

Notes:

[1] When you charge the battery, its temperature must be no lower than 0°C (32°F)

CERTIFICATIONS

Green Certifications^[1]

Green Certifications^[2]

- EPEAT™ Silver Registered
- TCO Certified
- RoHS compliant

Notes:

[1] The items listed under the "Green Certifications" section may not only refer to certification but also registration or self-declaration.

[2] EPEAT is registered where applicable, please see <https://www.epeat.net> for registration status by country.

Other Certifications

Mil-Spec Test

MIL-STD-810G military test passed

- Feature with ** means that only one offering listed under the feature is configured on selected models.
- Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not responsible for photographic or typographical errors. LENOVO PROVIDES THIS PUBLICATION "AS IS," WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow disclaimer of express or implied warranties in certain transactions, therefore this disclaimer may not apply to you.
- The specifications on this page may not be available in all regions, and may be changed or updated without notice.

