

# **OVERVIEW**





1. SD card reader	6. USB-A (USB 5Gbps), Always On
2. USB-A (USB 5Gbps)	7. HDMI
3. Ethernet (RJ-45)	8. USB-C (USB4 40Gbps), with USB PD 3.0 & DP 1.4
4. Kensington Nano Security Slot	9. Headphone / microphone combo jack (3.5mm)
5. USB-C (USB 10Gbps), with USB PD 3.0 & DP 1.4	



## **PERFORMANCE**

#### **Processor**

#### **Processor Family**

AMD Ryzen™ 3 / 5 / 7 Processor

#### Processor\*\*

Processor Name	Cores	Threads	Base Frequency	Max Frequency	Cache	Processor Graphics
AMD Ryzen™ 3 7335U	4	8	3.0GHz	4.3GHz	2MB L2 / 8MB L3	AMD Radeon™ 660M
AMD Ryzen™ 5 7533HS	6	12	3.3GHz	4.45GHz	3MB L2 / 16MB L3	AMD Radeon™ 660M
AMD Ryzen™ 5 7535HS	6	12	3.3GHz	4.55GHz	3MB L2 / 16MB L3	AMD Radeon™ 660M
AMD Ryzen™ 7 7735HS	8	16	3.2GHz	4.75GHz	4MB L2 / 16MB L3	AMD Radeon™ 680M

## **Operating System**

## Operating System\*\*[1]

- Windows® 11 Pro
- Windows® 11 Home
- Windows® 11 Home Single Language
- · No preload operating system

## Notes:

[1] Windows® 11 Pro Education license can be requested for EMEA Education Customers only with limited specs. Any request please contact Lenovo® Sales Representative for more information.

## **Graphics**

## Graphics\*\*

Graphics	Туре	Memory	TGP	Key Features
AMD Radeon™ 660M	Integrated	Shared	Share CPU TDP	DirectX® 12
AMD Radeon™ 680M	Integrated	Shared	Share CPU TDP	DirectX® 12

## **Monitor Support**

### **Monitor Support**

Supports up to 4 independent displays (native display and 3 external monitors via HDMI®, USB-C® and USB4®). More external displays can be supported via docking or daisy chain.

- HDMI® supports up to 4K@60Hz
- USB-C® supports up to 5K@60Hz
- USB4® supports up to 5K@60Hz

### Chipset

## Chipset

AMD SoC (System on Chip) platform

## **Memory**

Max Memory[1]

Up to 64GB DDR5-4800

## **Memory Slots**

Two DDR5 SO-DIMM slots, dual-channel capable

#### **Memory Type**

DDR5-4800

### Notes:

[1] Maximum memory is only to test technical readiness of notebook. Available memory to sell would vary.

## **Storage**



#### Storage Support[1]

Up to two drives, 2x M.2 SSD • M.2 2280 SSD up to 2TB each

#### **Storage Slot**

Two M.2 2280 PCIe® 4.0 x4 slots

#### Storage Type<sup>[2]</sup>

Disk Type	Interface	Offering		
M.2 2242 SSD	PCIe® NVMe®, PCIe® 4.0 x4	128GB / 256GB / 512GB / 1TB		

#### Notes:

[1] The system supports dual SSD via two M.2 slots, but Lenovo® offers only one SSD configuration with a second slot for user self-expansion.

The max storage capacity is only technical readiness and may be different from current Lenovo® storage offerings.

[2] 128GB SSD is qualified for Belgium, Netherlands, and Luxembourg only.

## **Removable Storage**

#### **Card Reader**

SD card reader

### Multi-Media

#### **Audio Chip**

High Definition (HD) Audio, Realtek® ALC3287 codec

#### **Speakers**

Stereo speakers, 2W x2, Dolby Audio™

### Microphone

Dual-microphone array with smart noise-cancelling

#### Camera\*\*

- FHD 1080p + IR hybrid, with privacy shutter, fixed focus
- FHD 1080p, with privacy shutter, fixed focus
- · HD 720p, with privacy shutter, fixed focus

### **Battery**

#### Battery\*\*

- 45Wh Rechargeable Li-ion Battery, supports Rapid Charge Pro (charge up to 50% in 30min)
- 60Wh Rechargeable Li-ion Battery, supports Rapid Charge (charge up to 80% in 1hr)

#### Max Battery Life[1]

• Models with 45Wh battery:

MobileMark® 25: 7.46 hr

Local video (1080p) playback@150nits: 14.85 hr

Models with 60Wh battery:

MobileMark® 25: 11.0 hr

Local video (1080p) playback@150nits: 17.75 hr

#### Notes:

[1] All battery life claims are approximate maximum and based on results using the MobileMark® 2014, MobileMark® 2018, MobileMark® 25, MobileMark® 30, JEITA 2.0, JEITA 3.0, continuous 1080p video playback (with 150nits brightness and default volume level) or Google Power Load Test (PLT) battery-life benchmark tests. Actual battery life will vary depending on many factors such as product configuration and usage, software use, wireless functionality, power management settings, and screen brightness. The maximum capacity of the battery will decrease with time and use.

## **Power Adapter**

#### Power Adapter\*\*[1]

- 65W USB-C® (3-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz
- 65W USB-C® slim (wall-mount) AC adapter, supports PD 3.0, 100-240V, 50-60Hz

Notes:



[1] AC adapter offerings depend on the country.

## **Special Features**

### **Special Features**

Modern Standby

## **DESIGN**

## **Display**

## Display\*\*

Size	Resolution	Touch	Туре	Brightness	Surface	Aspect Ratio	Contrast Ratio	Color Gamut	Refresh Rate	Viewing Angle (L/R/U/D)	Key Features
14"	WUXGA (1920x1200)	None	IPS <sup>[1]</sup>	300nits	Anti- glare	16:10	1000:1	45% NTSC	60Hz	89° / 89° / 89° / 89°	TÜV Low Blue Light (Software)
14"	WUXGA (1920x1200)	Multi- touch	IPS <sup>[2]</sup>	300nits	Anti- glare	16:10	1000:1	45% NTSC	60Hz	89° / 89° / 89° / 89°	TÜV Low Blue Light (Software)
14"	WUXGA (1920x1200)	None	IPS <sup>[3]</sup>	300nits	Anti- glare	16:10	1000:1	100% sRGB	60Hz	89° / 89° /	Eyesafe® Certified 2.0

#### **Touchscreen**

- Add-on Film Touch, supports 10-point touch
- Non-touch

#### Notes:

[1], [2], [3] IPS (in-plane switching) technology may refer to IPS, PLS, ADS, AHVA, AAS.

## **Input Device**

## Pen

No support

#### Keyboard

6-row, spill-resistant, multimedia Fn keys, Copilot key

## **Keyboard Backlight**

- · LED backlight
- · Non-backlight

### Touchpad

Buttonless Mylar® surface multi-touch touchpad, supports Precision TouchPad (PTP), 75 x 120 mm (2.95 x 4.72 inches)

### Mechanical

### Dimensions (WxDxH)[1]

Models	Dimensions
Models with aluminium (top) and PC-ABS (bottom)	313.5 x 224 x 17.6 mm (12.34 x 8.82 x 0.69 inches)
Models with aluminium (top) and aluminium (bottom)	313.5 x 224 x 16.9 mm (12.34 x 8.82 x 0.67 inches)

#### Weight<sup>[2]</sup>

Models	Weight
Models with aluminium (top) and PC-ABS (bottom)	Starting at 1.36 kg (2.99 lbs)
Models with aluminium (top) and aluminium (bottom)	Starting at 1.38 kg (3.04 lbs)

### **Case Color**

- Arctic grey, dual-tone design
- · Cosmic blue, dual-tone design

### **Surface Treatment**



Anodizing sandblasting

#### Case Material\*\*

- Aluminium (top), PC-ABS (bottom)
- Aluminium (top), aluminium (bottom)

#### Notes:

[1] The system dimensions may vary depending on configurations.

[2] The system weight is approximate and based on results in Lenovo® lab, which varies depending on the source of component, variance of the distribution of each component, and manufacturing process. It may not be the exact weight for each specific model.

## CONNECTIVITY

#### **Network**

#### Ethernet[1]

Gigabit Ethernet, 1x RJ-45, supports Wake-on-LAN

#### WLAN + Bluetooth®\*\*

- Wi-Fi<sup>®</sup> 6, 802.11ax 2x2 Wi-Fi<sup>®</sup> + Bluetooth<sup>®</sup> 5.3, M.2 card<sup>[2]</sup>
- Wi-Fi® 6E, 802.11ax 2x2 Wi-Fi® + Bluetooth® 5.3, M.2 card[3]

#### **WWAN**

No support

#### Notes:

- [1] Wake-on-LAN needs the power adapter plugged in.
- [2] Wi-Fi® 6 full features might be limited by country-level restrictions.
- [3] Wi-Fi® 6E full features might be limited by country-level restrictions.

6GHz Wi-Fi® 6E operation is dependent on the support of the operating system, routers/APs/Gateways that support Wi-Fi® 6E, and the regional regulatory certifications & spectrum allocation.

### Ports<sup>[1]</sup>

#### Standard Ports

- 1x USB-A (USB 5Gbps / USB 3.2 Gen 1)
- 1x USB-A (USB 5Gbps / USB 3.2 Gen 1), Always On
- 1x USB-C® (USB 10Gbps / USB 3.2 Gen 2), with USB PD 3.0 and DisplayPort™ 1.4
- 1x USB-C® (USB4® 40Gbps), with USB PD 3.0 and DisplayPort™ 1.4
- 1x HDMI® 2.1, up to 4K/60Hz
- 1x Headphone / microphone combo jack (3.5mm)
- 1x Ethernet (RJ-45)
- 1x SD card reader

#### Notes:

[1] The transfer speed of the ports will vary and, depending on many factors, such as the processing speed of the host device, file attributes and other factors related to system configuration and your operating environment, will be slower than theoretical speed.

## **Docking**

### **Docking**

Various docking solutions supported via USB-C®.

For more compatible docking solutions, please visit Docking for ThinkBook® 14 G7 ARP

## **SECURITY & PRIVACY**

## **Security**

Security Chip[1]

Firmware TPM 2.0 integrated in SoC

**Physical Locks** 



Kensington® Nano Security Slot™, 2.5 x 6 mm

#### **Fingerprint Reader**

Touch style fingerprint reader integrated in power button, match-on-chip

#### **BIOS Security**

- Hard disk password
- Power-on password
- · Supervisor password
- User password
- Self-healing BIOS
- More BIOS security features, please visit BIOS Simulator[2]

#### **Other Security**

- Camera privacy shutter
- (Optional) IR camera for Windows® Hello (facial recognition)

#### Notes:

[1] The Discrete TPM 2.0 is technical readiness.

[2] The BIOS simulator is just for reference. Default settings and some options may vary depending on the hardware, operating system and BIOS version.

### **SERVICE**

### Warranty

#### Base Warranty\*\*

- 1-year courier or carry-in service
- 2-year (1-yr battery) courier or carry-in service

### **ACCESSORIES**

#### **Bundled Accessories**

Bundled Accessories[1]

None

Notes:

[1] For more compatible accessory solutions, please visit Accessories for ThinkBook® 14 G7 ARP.

## **OPERATING REQUIREMENTS**

## **Operating Environment**

## Temperature[1]

- At altitudes up to 2438 m (8,000 ft)
  - Operating: 5°C to 35°C (41°F to 95°F)
  - Storage: 5°C to 43°C (41°F to 109°F)
- At altitudes above 2438 m (8,000 ft)
  - Maximum temperature when operating under the unpressurized condition: 31.3°C (88°F)

### **Relative Humidity**

- Operating: 8% to 95% at wet-bulb temperature 23°C (73°F)
- Storage: 5% to 95% at wet-bulb temperature 27°C (81°F)

#### Altitude

Maximum altitude (without pressurization): 3048 m (10,000 ft)

Notes:

[1] When you charge the battery, its temperature must be no lower than 10°C (50°F).

### **ENVIRONMENTAL**



## Sustainability

#### Material<sup>[1]</sup>

25% PCC recycled plastic used in the battery pack enclosure 50% PCC recycled plastic used in key caps 30% PCC recycled plastic used in speaker 90% PCC recycled plastic used in standard 65W adapter

97% recycled content in PIC cushion

90% recycled content in OBP bag FSC certified content in carton box

Notes:

[1] PCC: Post Consumer Content, recycled materials from customers.

## **CERTIFICATIONS**

### Green Certifications<sup>11</sup>

#### Green Certifications[2]

- ENERGY STAR® 8.0
- EPEAT™ Gold Registered[3]
- ErP Lot 6/26
- · RoHS compliant
- TCO Certified 9.0

#### Notes:

[1] The items listed under the "Green Certifications" section may not only refer to certification but also registration or self-declaration. For ESG & regulatory compliance documents, please visit <a href="https://compliance.lenovo.com">https://compliance.lenovo.com</a>.

[2] EPEAT™ registration and ENERGY STAR® certification are optional and only available on the models with preloaded OS. Please visit <u>epeat.net</u> and <u>energystar.gov</u> for more information.

[3] EPEAT™ is registered where applicable, please visit epeat.net for registration status by country.

## **Other Certifications**

#### Mil-Spec Test

MIL-STD-810H military test passed

## Other Certifications

- (Optional) Eyesafe® Certified 2.0
- (Optional) TÜV Rheinland® Low Blue Light (Hardware Solution)
- (Optional) TÜV Rheinland® Low Blue Light (Software Solution)
- Feature with \*\* means that only one option listed under the feature can be configured on selected models. Please refer to the model configuration for specific information.
- Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not
  responsible for photographic or typographical errors. LENOVO PROVIDES THIS PUBLICATION "AS IS,"
  WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES
  OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow
  disclaimer of express or implied warranties in certain transactions, therefore this disclaimer may not apply to
  you.
- The specifications on this page may not be available in all regions, and may be changed or updated without notice.













