

OVERVIEW





1. Optical drive *	10. Flex IO *
2. Power button	11. HDMI 2.1 TMDS
3. Microphone jack (3.5mm)	12. 2x DisplayPort 1.4
4. Card reader *	13. 4x USB 2.0
5. Headphone / microphone combo jack (3.5mm)	14. 2x PS/2 ports (keyboard / mouse) *
6. USB-C 3.2 Gen 1	15. Ethernet (RJ-45)
7. 2x USB 3.2 Gen 1	16. Optional ports on expansion cards *
8. 2x USB 3.2 Gen 2	17. Power connector
9. Line-out (3.5mm)	

Notes:

- Items with * are only available on selected models
- More ports are available through the optional expansion cards (not shown on the sample product above)

ThinkCentre M70s Gen 3

PERFORMANCE

Processor

Processor Family

Intel® Pentium® or 12th Generation Intel® Core™ i3 / i5 / i7 / i9 Processor

Processor**

Processor Name	Cores	Threads	Base Frequency	Max Frequency	Cache	Processor Graphics
Pentium® Gold G7400	2	4	3.7GHz	-	6MB	Intel® UHD Graphics 710
Core i3-12100	4 (4 P-core + O E-core)	8	P-core 3.3GHz	P-core 4.3GHz ^[1]	12MB	Intel® UHD Graphics 730
Core i3-12300	4 (4 P-core + 0 E-core)	8	P-core 3.5GHz	P-core 4.4GHz ^[2]	12MB	Intel® UHD Graphics 730
Core i5-12400	6 (6 P-core + 0 E-core)	12	P-core 2.5GHz	P-core 4.4GHz ^[3]	18MB	Intel® UHD Graphics 730
Core i5-12400F	6 (6 P-core + 0 E-core)	12	P-core 2.5GHz	P-core 4.4GHz ^[4]	18MB	-
Core i5-12500	6 (6 P-core + 0 E-core)	12	P-core 3.0GHz	P-core 4.6GHz ^[5]	18MB	Intel® UHD Graphics 770
Core i5-12600	6 (6 P-core + 0 E-core)	12	P-core 3.3GHz	P-core 4.8GHz ^[6]	18MB	Intel® UHD Graphics 770
Core i7-12700	12 (8 P-core + 4 E-core)	20	P-core 2.1GHz / E- core 1.6GHz	Max Turbo up to 4.9GHz / P-core 4.8GHz / E-core 3.6GHz ^[7]	25MB	Intel® UHD Graphics 770
Core i7-12700F	12 (8 P-core + 4 E-core)	20	P-core 2.1GHz / E- core 1.6GHz	Max Turbo up to 4.9GHz / P-core 4.8GHz / E-core 3.6GHz ^[8]	25MB	-
Core i9-12900	16 (8 P-core + 8 E-core)	24	P-core 2.4GHz / E- core 1.8GHz	Max Turbo up to 5.1GHz / P-core 5.0GHz / E-core 3.8GHz ^[9]	30MB	Intel® UHD Graphics 770
Core i9-12900F	16 (8 P-core + 8 E-core)	24	P-core 2.4GHz / E- core 1.8GHz	Max Turbo up to 5.1GHz / P-core 5.0GHz / E-core 3.8GHz ^[10]	30MB	-

Notes:

[1], [2], [3], [4], [5], [6], [7], [8], [9], [10] Intel[®] Max Turbo frequency will vary depending on application workload and the hardware and software configurations, see

http://www.intel.com/technology/turboboost/ for more information.

Operating System

Operating System**

- Windows® 11 Pro
- Windows® 11 Home
- Windows® 11 Home Single Language
- Windows[®] 11 DG Windows[®] 10 Pro 64
- Windows[®] 10 IoT Enterprise LTSC 2021
- Ubuntu Linux^[1]
- No preload operating system

Notes:

[1] Some features may not be supported on the system with Linux preload, including but not limited to Intel® RST RAID, Human Presence Detection, etc.

Graphics

Graphics***[1]

(Graphics	Туре	Memory	Max Resolution	Connector	Key Features	
---	----------	------	--------	----------------	-----------	-----------------	--

ThinkCentre M70s Gen 3

Lenovo

Intel® UHD graphics 710	Integrated	Shared	4096x2304@60Hz(DP), 4096x2160@60Hz[HDMI® / Flex IO(HDMI®) / Flex IO(DP)], 3840x2160@60Hz[Flex IO(USB- C®)], 2048x1536@50Hz[Flex IO(VGA)]	2x DP 1.4 HBR2, 1x HDMI® 2.1 TMDS, 1x Flex IO (VGA / DP 1.2 / HDMI® 2.1 TMDS / USB- C®)	DirectX® 12
Intel® UHD graphics 730	Integrated	Shared	4096x2304@60Hz(DP), 4096x2160@60Hz[HDMI [®] / Flex IO(HD MI) / Flex IO(DP)], 3840x2160@60Hz[Flex IO(USB- C [®])], 2048x1536@50Hz[Flex IO(VGA)]	2x DP 1.4 HBR2, 1x HDMI® 2.1 TMDS, 1x Flex IO (VGA / DP 1.2 / HDMI® 2.1 TMDS / USB- C®)	DirectX® 12
Intel® UHD graphics 770	Integrated	Shared	4096x2304@60Hz(DP), 4096x2160@60Hz[HDMI® / Flex IO(HD MI) / Flex IO(DP)], 3840x2160@60Hz[Flex IO(USB- C®)], 2048x1536@50Hz[Flex IO(VGA)]	2x DP 1.4 HBR2, 1x HDMI® 2.1 TMDS, 1x Flex IO (VGA / DP 1.2 / HDMI® 2.1 TMDS / USB- C®)	DirectX® 12
Intel® Iris® Xe MAX 100	Discrete	2GB LPDDR4X	3840x2160@60Hz(DP)	2x DP 1.4	DirectX® 12, OpenGL 4.6

Notes:

[1] The information of integrated graphics are not applicable for the models with processor which has no integrated graphics inside (for the details, please refer to processor section).

Monitor Support

Monitor Support^[1]

Supports up to 4 independent displays via onboard ports (2x DP, 1x HDMI®, and 1x optional Flex IO), more displays support via discrete graphics

Notes:

[1] Onboard video ports are only available for the models with integrated graphics.

Chipset

Chipset

Intel[®] Q670 chipset

Memory

Max Memory^[1]

Up to 128GB DDR4-3200

Memory Slots

Four DDR4 DIMM slots, dual-channel capable

Memory Type

DDR4-3200

Notes:

[1] The max memory is based on the test results with current Lenovo[®] memory offerings.

Storage

Storage Support^{[1][2]}

Up to three drives, 1x 2.5"/3.5" HDD + 1x 2.5" HDD + 1x M.2 SSD

• 2.5" HDD up to 1TB each

• 3.5" HDD up to 2TB

• M.2 SSD up to 2TB

Storage Type***

Disk Type	Interface	RPM	Security
2.5" SATA HDD	SATA 6Gb/s		-
3.5" SATA HDD	SATA 6Gb/s	7.2K	-

ThinkCentre M70s Gen 3

Lenovo

M.2 2242 SSD	PCIe® NVMe®, PCIe® 3.0 x4	-	-
M.2 2280 SSD	PCIe® NVMe®, PCIe® 3.0 x4	-	Opal
M.2 2280 SSD	PCIe® NVMe®, PCIe® 4.0 x4 Performance	-	Opal 2.0
M.2 2280 SSD	PCIe® NVMe®, PCIe® 4.0 x4 Value	-	Opal 2.0

RAID

RAID 0/1 support for HDDs (RAID preset only available via special bid models)

Notes:

[1] The max capacity of each disk type is based on the test results with current Lenovo[®] storage offerings.
[2] The max capacity of SSD/HDD is based on the test results with current Lenovo[®] SSD/HDD offerings.

Removable Storage

Optical**

- DVD-ROM, SATA connector, slim (9.0mm)
- DVD burner (DVD±RW), SATA connector, slim (9.0mm)
- None

Card Reader

- 3-in-1 card reader (SD, SDHC, SDXC)
- No card reader

Multi-Media

Audio Chip

High Definition (HD) Audio, Realtek® ALC897Q-CG codec

Speakers

Single speaker, 1W x1

Power Supply

Power Supply**

Power	Туре	Efficiency	Key Features
180W	Fixed	85%	100-240V, 50-60Hz
260W	Fixed	90%	100-240V, 50-60Hz
310W	Fixed	92%	100-240V, 50-60Hz
380W	Fixed	92%	100-240V, 50-60Hz

DESIGN

Input Device

Keyboard**

- Lenovo® Calliope Keyboard (USB connector), black
- Lenovo® Calliope Wireless Keyboard (2.4GHz via USB receiver), black
- Lenovo® Traditional Keyboard (USB connector), black
- No keyboard

Mouse**

- Lenovo[®] Calliope Mouse (USB connector), black
- Lenovo[®] Calliope Wireless Mouse (2.4GHz via USB receiver), black
- Lenovo® Mouse (PS/2 connector), black (only available via special bid)
- Lenovo[®] Fingerprint Mouse (USB connector), Windows[®] Hello support, black (EOL on Jan, 2023)
- No mouse

Mechanical

Form Factor

SFF (8.2L)

Dimensions (WxDxH)^[1]

92.5 x 297.7 x 339.5 mm (3.6 x 11.7 x 13.4 inches)

Weight^[2]

Around 5.3 kg (11.7 lbs)

Case Color

Black

Bays^[3]

- 1x 2.5" disk bay
- 1x 3.5" disk bay
- 1x slim ODD bay

Expansion Slots

- One PCIe[®] 4.0 x16, low-profile, length \leq 155mm, height \leq 70mm
- Two PCIe[®] 3.0 x1, low-profile, length ≤ 155mm, height ≤ 70mm
- Two M.2 slots (one for WLAN, one for SSD)

EOU

Toolless cover, disk, optical, extension card assembly / removal

Stand

- Vertical stand
- No stand

Others

- (Optional) Dust filter
- Supports Smart Power On

Notes:

[1] The system dimensions may vary depending on configurations.

[2] The system weight is approximate and based on results in Lenovo[®] lab, which varies depending on the source of component, variance of the distribution of each component, and manufacturing process. It may not be the exact weight for each specific model.

[3] 2.5" HDD tray is optional, or comes with 2.5 HDD. 3.5" bay supports 2.5" / 3.5" HDD, 3.5" to 2.5 converter comes with 2nd 2.5" HDD.

CONNECTIVITY

Network

Onboard Ethernet

Gigabit Ethernet, Intel® Ethernet Connection I219-LM, 1x RJ-45, supports Wake-on-LAN

Optional Ethernet***

• Gigabit Ethernet, Bitland BN8E88, 1x RJ-45, PCIe[®] x1

- Gigabit Ethernet, Bitland RTL8168H, 1x RJ-45, PCIe® x1
- 2.5 Gigabit Ethernet, Realtek® RTL8125BGS, 1x RJ-45, PCIe® x1
- No optional Ethernet

WLAN + Bluetooth®**

- Realtek[®] RTL8822CE, Wi-Fi[®] 5, 802.11ac Dual Band 2x2 Wi-Fi[®] + Bluetooth[®] 5.0, M.2 card
- Intel® Wireless-AC 9560, Wi-Fi® 5, 802.11ac Dual Band 2x2 Wi-Fi® + Bluetooth® 5.1, M.2 card
- Realtek[®] Wi-Fi[®] 6 RTL8852BE, 802.11ax Dual Band 2x2 Wi-Fi[®] + Bluetooth[®] 5.3, M.2 card^[1]
- Intel[®] Wi-Fi[®] 6 AX201, 802.11ax 2x2 Wi-Fi[®] + Bluetooth[®] 5.2, M.2 Card^[2]
- Intel® Wi-Fi® 6E AX211, 802.11ax 2x2 Wi-Fi® + Bluetooth® 5.3, Intel® vPro® technology support, M.2 Card^[3]
- No WLAN and Bluetooth[®]

Notes:

- [1], [3] Bluetooth[®] 5.3 requires Windows[®] 11.
- [2] Bluetooth[®] 5.2 requires Windows[®] 11.

Ports^[1]

Front Ports

- 1x USB-C[®] 3.2 Gen 1 (15W charging)
- 2x USB 3.2 Gen 1

- 2x USB 3.2 Gen 2
- 1x headphone / microphone combo jack (3.5mm)
- 1x microphone (3.5mm)

Optional Front Ports

1x card reader

Rear Ports^[2]

- 4x USB 2.0
- 1x HDMI[®] 2.1 TMDS
- 2x DisplayPort[™] 1.4a (HBR2, DSC)
- 1x Ethernet (RJ-45)
- 1x line-out (3.5mm)

Optional Rear Ports***

- 1x USB-C[®] 3.2 Gen 1 with DisplayPort[™] function and 5V@3A charging (Flex IO)
- 1x HDMI[®] 2.1 TMDS (Flex IO)
- 1x DP 1.2 (Flex IO)
- 1x VGA (Flex IO)
- 2x USB 3.2 Gen 1 (via 2-port USB expansion card, PCIe[®] x1)
- 1x parallel
- 1x serial
- 1x 2nd serial
- 4x serial (via 4-port serial expansion card, PCIe® x1)
- 2x PS/2

Notes:

[1] The transfer speed of following ports will vary and, depending on many factors, such as the processing speed of the host device, file attributes and other factors related to system configuration and your operating environment, will be slower than theoretical speed.

USB 2.0: 480 Mbit/s;

USB 3.2 Gen 1 (SuperSpeed USB 5Gbps, formerly USB 3.0 / USB 3.1 Gen 1): 5 Gbit/s;

USB 3.2 Gen 2 (SuperSpeed USB 10Gbps, formerly USB 3.1 Gen 2): 10 Gbit/s;

USB4® 20Gbps / USB 3.2 Gen 2x2 (SuperSpeed USB 20Gbps): 20 Gbit/s;

USB4® 40Gbps (USB 40Gbps): 40 Gbit/s;

Thunderbolt[™] 3/4: 40 Gbit/s.

[2] For video ports on discrete graphics, please see graphics section.

SECURITY & PRIVACY

Security

Security Chip

Discrete TPM 2.0, TCG certified

Physical Locks

- (Optional) E-lock
- (Optional) Smart Cable Clip
- Kensington[®] Security Slot[™], 3 x 7 mm
- Padlock Loop

Chassis Intrusion Switch

- Chassis intrusion switch
- No chassis intrusion switch

Fingerprint Reader

- Touch style fingerprint reader on mouse (EOL on Jan, 2023)
- No fingerprint reader

BIOS Security

- Administrator password
- Hard disk password
- Power-on password
- Boot sequence control
- Boot without keyboard and mouse
- Individual USB port disablement
- Self-healing BIOS (Level 2)

Lenovo

- Smart USB protection (allows keyboard / mouse only, blocks all storage devices)
- More BIOS security features, please visit <u>BIOS Simulator</u>^[1]

Notes:

[1] The BIOS simulator is just for reference. Default settings and some options may vary depending on the hardware, operating system and BIOS version.

MANAGEABILITY

System Management

System Management**

- Intel[®] vPro[®] Enterprise^[1]
- Intel[®] vPro[®] Essentials^[2]
- Non-vPro®

Notes:

[1], [2] Intel[®] vPro[®] offers a superset of DASH's defined capabilities.

SERVICE

Warranty^[1]

Base Warranty**

- 1-year courier or carry-in service
- 1-year limited onsite service
- 3-year limited onsite service
- No base warranty

Notes:

[1] The warranty upgrades may be bundled with some models, please check the "Included upgrade" column in the specific model's configurations. For more service extensions, please go to <u>https://smartfind.lenovo.com/</u>. To learn more details of warranty policy, please access <u>https://support.lenovo.com/warrantylookup/warrantypolicy</u>.

ACCESSORIES

Bundled Accessories

- **Bundled Accessories*****
- DP to DVI dongle
- DP to Dual DP dongle
- DP to HDMI® dongle
- DP to VGA dongle
- HDMI® to HDMI® cable (1.5m)
- HDMI[®] to VGA dongle
- Smart Cable (USB-A to USB-C®)
- None

OPERATING REQUIREMENTS

Operating Environment

Temperature

- Operating: 5°C (41°F) to 35°C (95°F)
- Storage: -40°C (-40°F) to 60°C (140°F)

Relative Humidity

- Operating: 20% to 80%
- Storage: 10% to 90%

Altitude

Lenovo

- Operating: 0 m (0 ft) to 3048 m (10,000 ft)
- Storage: 0 m (0 ft) to 12192 m (40,000 ft)

CERTIFICATIONS

Green Certifications^{III}

Green Certifications

- (Optional) ENERGY STAR[®] 8.0
- (Optional) EPEAT[™] Silver Registered^[2]
- (Optional) EPEAT[™] Gold Registered^[3]
- ErP Lot 3
- RoHS compliant
- TCO Certified 9.0

Notes:

[1] The items listed under the "Green Certifications" section may not only refer to certification but also registration or self-declaration. For ESG & regulatory compliance documents, please visit <u>https://compliance.lenovo.com</u>.
 [2], [3] EPEAT[™] is registered where applicable, please visit <u>epeat.net</u> for registration status by country.

Other Certifications

Other Certifications

- (Optional) TÜV Rheinland[®] Low Noise
- (Optional) TÜV Rheinland® Ultra Low Noise

Mil-Spec Test

MIL-STD-810H military test passed (Low Pressure [Altitude], High Temperature, Low Temperature, Temperature Shock, Humidity, Sand and Dust, Vibration, Shock, Fungus, Solar Radiation, Contamination by Fluids, Salt Fog)

- Feature with ** means that only one option listed under the feature can be configured on selected models. Please refer to the model configuration for specific information.
- Feature with *** means that one or more options listed under the feature can be configured on selected models. Please refer to the model configuration for specific information.
- Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not responsible for photographic or typographical errors. LENOVO PROVIDES THIS PUBLICATION "AS IS," WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow disclaimer of express or implied warranties in certain transactions, therefore this disclaimer may not apply to you.
- The specifications on this page may not be available in all regions, and may be changed or updated without notice.









PSREF Product Specifications Reference



intel













intel



intel