


OVERVIEW



1. Card reader *	11. Optional ports on expansion cards *
2. Microphone jack (3.5mm)	12. Audio line-out (3.5mm)
3. Headphone / microphone combo jack (3.5mm)	13. Padlock loop
4. USB-C 3.2 Gen 1	14. Serial (9-pin)
5. 2x USB 3.2 Gen 1	15. E-lock slot *
6. 2x USB 3.2 Gen 2	16. Ethernet (RJ-45)
7. Optical drive *	17. Serial (9-pin) *
8. Flex bay *	18. Smart cable clip slots
9. Video ports (2x DP, 1x HDMI) *	19. Kensington Security Slot
10. 4x USB 2.0 (with Smart Power On)	20. Power connector

Notes:

• Items with * are only available on selected models



PERFORMANCE

Processor

Processor Family

Up to one 65W AMD Ryzen™ 9 PRO 5000 Series Processor

Processor**

Processor Name	Cores	Threads	Base Frequency	Max Frequency	Cache	Memory Support	Processor Graphics
AMD Ryzen™ 3 PRO 4350G	4	8	3.8GHz	4.0GHz	2MB L2 / 4MB L3	DDR4-3200	AMD Radeon™ Graphics
AMD Ryzen™ 5 PRO 4650G	6	12	3.7GHz	4.2GHz	3MB L2 / 8MB L3	DDR4-3200	AMD Radeon™ Graphics
AMD Ryzen™ 5 PRO 5645	6	12	3.7GHz	4.6GHz	3MB L2 / 32MB L3	DDR4-3200	None
AMD Ryzen™ 7 PRO 4750G	8	16	3.6GHz	4.4GHz	4MB L2 / 8MB L3	DDR4-3200	AMD Radeon™ Graphics
AMD Ryzen™ 7 PRO 5845	8	16	3.4GHz	4.6GHz	4MB L2 / 32MB L3	DDR4-3200	None
AMD Ryzen™ 9 PRO 5945	12	24	3.0GHz	4.7GHz	6MB L2 / 64MB L3	DDR4-3200	None

Processor Sockets

Socket AM4

Operating System

Operating System**[1]

- Windows® 11 Pro
- Windows® 11 Home
- Windows® 11 Home Single Language
- Windows® 11 DG Windows® 10 Pro 64
- Ubuntu Linux LTS
- Red Hat Enterprise Linux 8.6 (certified only, for detailed and latest information, please visit <u>Red Hat Certified Hardware</u>)
- No preload operating system

Notes:

[1] Due to hardware limitations, Windows® Autopilot is temporarily not supported

Graphics

Integrated Graphics

- None
- Integrated AMD Radeon[™] Graphics

Discrete Graphics Support[1]

Supports up to one NVIDIA® GeForce RTX™ 3080 or NVIDIA® RTX A2000

Discrete Graphics Offering

Graphics	Memory	Power	Connector	Form Factor	SLI / NVLink
NVIDIA® T400 4GB	4GB GDDR6	40W	3x miniDP 1.4	Single slot	None
NVIDIA® T1000	4GB GDDR6	50W	4x miniDP 1.4	Single slot	None
NVIDIA® T1000 8GB	8GB GDDR6	50W	4x miniDP 1.4	Single slot	None
NVIDIA® RTX A2000 12GB	12GB GDDR6	70W	4x miniDP 1.4a	Dual slot	None
NVIDIA® GeForce RTX™ 3060	12GB GDDR6	170W	3x DP 1.4a, 1x HDMI® 2.1 FRL	Dual slot	None
NVIDIA® GeForce RTX™ 3070 Ti	8GB GDDR6	290W	3x DP 1.4a, 1x HDMI® 2.1 FRL	Triple slot	None
NVIDIA® GeForce RTX™ 3080	10GB GDDR6	320W	3x DP 1.4a, 1x HDMI® 2.1 FRL	Triple slot	None



Notes:

[1] Discrete graphics support may vary by configurations such as processor selection or power supply wattage.

Monitor Support

Monitor Support

- Models with Ryzen™ 3 Pro 4350G, 4650G, and 4750G: multiple displays via onboard and discrete graphics. Onboard graphics supports up to 3 independent displays via onboard two DP, one HDMI®:
 - DP supports up to 4096x2160@60Hz
 - HDMI® supports up to 3840x2160@30Hz

The maximum number of monitors supported by discrete graphics is related to the discrete graphics card used.

- Models with Ryzen[™] Pro 5000 processor: onboard video ports cannot work. Independent displays support depends on the discrete graphic card in use. Discrete graphics ports support:
 - miniDP supports up to 5120x2880@60Hz
 - HDMI® supports up to 7680x4320@60Hz

Chipset

Chipset

AMD PRO 565 chipset

Memory

Max Memory[1]

Up to 128GB (4x 32GB DDR4 UDIMM)

Memory Type**

- DDR4-3200 UDIMM ECC, maximum transfer speeds of up to 3200 MT/s
- DDR4-3200 UDIMM non-ECC, maximum transfer speeds of up to 3200 MT/s

Memory Slots

Four DDR4 UDIMM slots, dual-channel capable

Memory Protection

ECC on models with ECC DIMMs and ECC capable processor

Notes:

[1] The max memory is based on the test results with current Lenovo® memory offerings.

Storage

Storage Support[1]

Up to 2x 3.5" SATA HDD + 1x 2.5" SATA HDD / SSD + 1x M.2 SSD

- 3.5" HDD up to 4TB each
- M.2 SSD up to 2TB
- No pre-configured 2.5" HDD / SSD options

Storage Type^[2]

Disk Type	Interface		Offering	Security
3.5" SATA HDD	SATA 6Gb/s	7.2K	1TB / 2TB / 4TB	-
M.2 2280 SSD	PCIe® NVMe®, PCIe® 4.0 x4	-	256GB	Opal 2.0
M.2 2280 SSD	PCIe® NVMe®, PCIe® 4.0 x4 Performance	-	512GB / 1TB / 2TB	Opal 2.0

Storage Controllers***[3]

Storage Controller		Туре	Interface	RAID	Cache
	Integrated SATA controller	Standard	SATA 6.0Gb/s	0/1	None
	Integrated NVMe® controller	Standard	PCIe® NVMe®	-	None

Notes:

- [1] The storage capacity supported is based on the test results with current Lenovo® storage offerings.
- [2] System comes with one M.2 PCle® Gen 3 slot for M.2 SSD.
- [3] RAID requires that BIOS version is equal or newer than SOHKT12A.



RAID is only available on models with AMD Ryzen™ 3 Pro 4350G. Pre-configuration with RAID cannot be suppoted.

Removable Storage

Optical Support

Optional one 9.0mm DVD-ROM

Card Reader

- SD card reader
- · No card reader

Multi-Media

Audio Chip

High Definition (HD) Audio, Realtek® ALC623-CG codec

Speakers

Single speaker, 2W x1

Power Supply

Power Supply**

Power	Туре	Efficiency	Key Features
300W	Fixed	90%	Autosensing, 80 PLUS Gold qualified
500W	Fixed	92%	Autosensing, 80 PLUS Platinum qualified
750W	Fixed	92%	Autosensing, 80 PLUS Platinum qualified

DESIGN

Mechanical

Form Factor

Tower (17L)

Dimensions (WxDxH)[1]

170 x 315.4 x 376 mm (6.7 x 12.4 x 14.8 inches)

Weight^[2]

9.8 kg (21.6 lbs, maximum configuration)

Bays

- 1x 3.5" disk bay (standard)
- 1x 3.5" disk bay (optional)
- 1x 2.5" disk bay (optional)
- 1x slim ODD bay (optional)

Expansion Slots

Supports two PCIe® slots with one PCIe® 3.0 x16 and one PCIe® 3.0 x1.

- Slot 1: PCIe® 3.0 x16, full height, full length, 75W, double-width
- Slot 2: PCIe® 3.0 x1, full height, half length, 25W

Notes:

[1] The system dimensions may vary depending on configurations.

[2] The system weight is approximate and based on results in Lenovo® lab, which varies depending on the source of component, variance of the distribution of each component, and manufacturing process. It may not be the exact weight for each specific model.

CONNECTIVITY

Network

Onboard Ethernet

Gigabit Ethernet, Realtek® RTL8111EPV, 1x GbE RJ-45, supports Wake-on-LAN



Optional Ethernet

One additional Ethernet adapter support, up to one additional GbE port

- Gigabit Ethernet, Intel® I210-T1, 1x RJ-45, PCIe® x1
- Gigabit Ethernet, Realtek® RTL8168H, 1x RJ-45, PCIe® x1

WLAN + Bluetooth®

- MediaTek Wi-Fi® 6 MT7921, 802.11ax 2x2 Wi-Fi® + Bluetooth® 5.1
- No WLAN and Bluetooth®

Ports^[1]

Front Ports

- 1x USB-C® 3.2 Gen 1 (support data transfer)
- 2x USB 3.2 Gen 1
- 2x USB 3.2 Gen 2
- 1x headphone / microphone combo jack (3.5mm)
- 1x microphone (3.5mm)

Rear Ports[2]

- 4x USB 2.0 (one supports Smart Power On)
- 1x Ethernet (RJ-45)
- 1x line-out (3.5mm)
- 1x serial (9-pin)

Optional Rear Ports

- 2x USB 3.2 Gen 1 (via 2-port USB expansion card, PCIe® x1)
- 2x USB 2.0
- 1x HDMI® 2.1 TMDS (onboard, for AMD Ryzen™ 3 Pro 4350G models)
- 2x DisplayPort[™] 1.4 (onboard, for AMD Ryzen[™] 3 Pro 4350G models)
- 1x parallel
- 1x serial
- 4x serial (via 4-port serial expansion card, PCle® x1)

Notes:

[1] The transfer speed of following ports will vary and, depending on many factors, such as the processing speed of the host device, file attributes and other factors related to system configuration and your operating environment, will be slower than theoretical speed.

USB 2.0: 480 Mbit/s;

USB 3.2 Gen 1 (SuperSpeed USB 5Gbps, formerly USB 3.0 / USB 3.1 Gen 1): 5 Gbit/s;

USB 3.2 Gen 2 (SuperSpeed USB 10Gbps, formerly USB 3.1 Gen 2): 10 Gbit/s;

USB4® 20Gbps / USB 3.2 Gen 2x2 (SuperSpeed USB 20Gbps): 20 Gbit/s;

USB4® 40Gbps (USB 40Gbps): 40 Gbit/s;

Thunderbolt™ 3/4: 40 Gbit/s.

[2] For video ports on discrete graphics, please see graphics section.

SECURITY & PRIVACY

Security

Security Chip

Firmware TPM 2.0 integrated in processor

Physical Locks

- (Optional) E-lock
- (Optional) Smart Cable Clip
- Kensington® Security Slot™, 3 x 7 mm
- Padlock Loop

Chassis Intrusion Switch

- · Chassis intrusion switch
- · No chassis intrusion switch

BIOS Security

- · Administrator password
- Power-on password
- Self-healing BIOS



· UEFI Secure Boot

MANAGEABILITY

System Management

System Management

AMD PRO Manageability

SERVICE

Warranty^[1]

Base Warranty**

- 1-year limited onsite service
- 2-year limited onsite service
- 3-year limited onsite service
- · No base warranty

Notes:

[1] The warranty upgrades may be bundled with some models, please check the "Included upgrade" column in the specific model's configurations. For more service extensions, please go to https://smartfind.lenovo.com/. To learn more details of warranty policy, please access https://support.lenovo.com/warrantylookup/warrantypolicy.

OPERATING REQUIREMENTS

Operating Environment

Temperature

- Operating: 10°C (50°F) to 35°C (95°F)
- Storage: -40°C (-40°F) to 60°C (140°F)

Altitude

- Operating: 0 m (0 ft) to 3048 m (10,000 ft)
- Storage: 0 m (0 ft) to 12192 m (40,000 ft)

Relative Humidity

- Operating: 20% to 80%
- Storage: 10% to 90%

CERTIFICATIONS

Green Certifications¹¹

Green Certifications

- (Optional) ENERGY STAR® 8.0
- (Optional) EPEAT™ Gold Registered^[2]
- ErP Lot 3
- RoHS compliant
- TCO Certified 9.0

Notes:

[1] The items listed under the "Green Certifications" section may not only refer to certification but also registration or self-declaration. For ESG & regulatory compliance documents, please visit https://compliance.lenovo.com.

[2] EPEAT™ is registered where applicable, please visit epeat.net for registration status by country.

ISV Certifications

ISV Certifications

Please visit ISV certifications for Lenovo® Workstations

• Feature with ** means that only one option listed under the feature can be configured on selected models.

Please refer to the model configuration for specific information.

ThinkStation P358 Tower



- Feature with *** means that one or more options listed under the feature can be configured on selected models. Please refer to the model configuration for specific information.
- Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not
 responsible for photographic or typographical errors. LENOVO PROVIDES THIS PUBLICATION "AS IS,"
 WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES
 OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow
 disclaimer of express or implied warranties in certain transactions, therefore this disclaimer may not apply to
 you.
- The specifications on this page may not be available in all regions, and may be changed or updated without notice.













