ThinkCentre M78 Small and Tower

ThinkCentre_®



Lenovo ThinkCentre M78 Small and Tower



Lenovo ThinkCentre M78 Tower with Lenovo ThinkVision Monitor





Lenovo ThinkCentre M78 Small



Lenovo ThinkCentre M78 Small with Lenovo ThinkVision Monitor





Lenovo ThinkCentre M78 Tower



Lenovo ThinkCentre M78 Tower

Slot Type-model ba		Processor	Memory	SATA disk r ⁸ GB rpm		Media reader	Graphics	Chassis Intrusion switch			ENERGY STAR 5.2			Ann date (mm/dd/yy)
2114-A1G 4x	3	A6-5400B	4GBx1	500G 7200	DVD±RW	None	Radeon HD 7540D	None	None	Stand	ES52	GΡ	Pro 64	08/28/12

Positioning Processor	Mainstream enterprise stability and manageability AMD Accelerated Processor A6-5400B (dual-core, 3.6GHz, 1MB L2 cache), Turbo Core technology (up to 3.8GHz), integrated AMD Radeon HD 7540D Graphics, integrated DDR3 memory controller (up to 1866MHz) Processor in Socket FM2	Preloaded operating system Genuine Windows® 7 Professional 64 Ready to install applications (only some
Memory	32GB max, UDIMM, PC3-12800 1600MHz DDR3, four 240-pin DIMM sockets	listed)
Graphics	AMD Radeon HD Graphics, integrated in processor, uses main memory, DirectX [®] 11, one VGA, one DisplayPort™, supports dual independent display; works along with discrete graphics to support up to four independent monitors; <i>Maximum resolution:</i> 1920x1200 (VGA)@60Hz; 2560x2048 (DisplayPort)@60Hz	 Rescue and Recovery™ Password Manager Business-in-a-Box Preloaded applications (only some listed)
DP dongle	None	ThinkVantage® Product Recovery ThinkVantage® Product Recovery
Disk Optical SATA controller Onboard SATA eSATA port Media reader	SATA 6.0Gb/s 7200 rpm Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive Serial ATA, SATA 6.0Gb/s, integrated in chipset, RAID 0/1 Two SATA cables (each 1-drop to device), four SATA 6.0Gb/s connectors on planar None None	ThinkVantage System Update ThinkVantage Communication Utility ThinkVantage Power Manager View Management Utility Lenovo Solution Center Lenovo Message Center Plus Lenovo SimpleTap
Chipset	AMD A75 Chipset	Norton™ Internet Security (30 days of virus definitions)
Front ports Rear ports Rear audio ports Internal connector Audio Speaker IEEE 1394 Ethernet Modem Security chip Keyboard Mouse Floor Stand Power supply Machine	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm) Four USB 3.0, two USB 2.0, serial (9-pin), ethernet (RJ-45), VGA DB-15, DisplayPort, optional keyboard (PS/2), optional mouse (PS/2) Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone (stereo, 3.5mm) Two USB 2.0 planar conn (1 used; one open for additional USB device) High Definition (HD) Audio, Realtek® ALC662 codec Internal speaker for business audio None One gigabit ethernet port, Realtek RTL8111E, Wake on LAN® None Trusted Platform Module (TPM 1.2-compliant) Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo Enhanced Optical USB Mouse, black, Lenovo logo System floor stand for vertical orientation 240 watts, autosensing, 85% PSU Business black color; metal case 13.3" W X 15.0" D X 3.9" H 339mm W X 381mm D X 100mm H 16.5 lb (7.5 kg) in maximum configuration Toolless cover flips up and tilts backward on rear hinges Toolless disk and optical drive removal Toolless adapter retention Bay 1: 5.25", 1.6" high, access, std optical	Adobe® Reader® Google Chrome Google Toolbar Skype™ for Windows Evernote® RapidBoot HDD Accelerator Symantec™ VIP Windows Live™ Essentials Microsoft® Office preloaded; purchase a product key to activate Corel® Burn.Now™ (DVD±RW) Corel DVD MovieFactory® (DVD±RW)
•	Bay 2: 3.5", 1" high, no access, std disk Bay 3: 3.5", .5" high, access, opt reader	
Slot	Slot 1: Low Profile, PCI Express 2.0 x16 (40w max) Slot 2: Low Profile, PCIe 2.0 x1 Slot 3: Low Profile, 32-bit PCI 2.3 Slot 4: Low Profile, 32-bit PCI 2.3	Security Security Security chip (see information on left) Security slot (in rear for attachment of optional Kensington® MicroSaver® cable) Cable lock Power-on password Administrator password Hard disk password Boot sequence control Boot without keyboard and mouse Individual USB port disablement Chassis intrusion switch on selected model(s) EPEAT™ Gold rating ENERGY STAR® 5.2-compliant
Limited Warranty	3-years , limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding public and national holidays. Calls received after 3 pm will require an additional next business day for service dispatch / service upgrades available	ULE Gold RoHS-compliant Supports ThinkVantage Technologies

Slot x Type-model bay	Processor	Memory	SATA disk GB rpm	SATA optical	Media reader	Graphics		Floor ENERGY stand STAR 5.2		
		-				Radeon HD 7540E			_	Win8 Pro64 10/23/12 Win7 Pro64 10/30/12

Positioning	Mainstream enterprise stability and manageability	Preloaded operating system				
Processor	AMD Accelerated Processor A6-5400B (dual-core, 3.6GHz, 1MB L2 cache), Turbo Core technology (up to 3.8GHz), integrated AMD Radeon HD 7540D Graphics, integrated DDR3 memory controller (up to 1866MHz)	Some: Windows® 7 Professional 64 preinstalled through downgrade				
Implementation	Processor in Socket FM2	rights in Windows 8 Pro 64-bit Some: Windows 8 Pro 64-bit				
Memory	32GB max, UDIMM, PC3-12800 1600MHz DDR3, four 240-pin DIMM sockets	Preloaded applications (only some listed)				
Graphics	AMD Radeon HD Graphics, integrated in processor, uses main memory, DirectX [®] 11, one VGA, one DisplayPort™, supports dual independent display; works along with discrete graphics to support up to four independent monitors; <i>Maximum resolution:</i> 1920x1200 (VGA) @ 60Hz; 2560x2048 (DisplayPort) @ 60Hz	- Windows 7 models ThinkVantage® Product Recovery ThinkVantage Communication Utility ThinkVantage Power Manager				
DP dongle	None	Lenovo® Message Center Plus				
Disk Optical SATA controller Onboard SATA eSATA port Media reader	SATA 6.0Gb/s 7200 rpm Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive Serial ATA, SATA 6.0Gb/s, integrated in chipset, RAID 0/1 Two SATA cables (each 1-drop to device), four SATA 6.0Gb/s connectors on planar None None	Lenovo SimpleTap Adobe® Reader® Google Chrome Google Toolbar RapidBoot HDD Accelerator Symantec™ VIP Windows Live™ Essentials				
Chipset	AMD A75 Chipset	Corel® Burn.Now™ (DVD±RW)				
Front ports Rear ports Rear audio ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm) Four USB 3.0, two USB 2.0, serial (9-pin), ethernet (RJ-45), VGA DB-15, DisplayPort, optional keyboard (PS/2), optional mouse (PS/2) Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone (stereo, 3.5mm)	Corel DVD MovieFactory® (DVD±RW) Windows 8 models Lenovo Support				
Internal connector Audio Speaker	Two USB 2.0 planar conn (1 used; one open for additional USB device) High Definition (HD) Audio, Realtek® ALC662 codec Internal speaker for business audio	Lenovo Companion Lenovo Cloud Storage Lenovo QuickLaunch Norton™ Studio Intel AppUp®				
IEEE 1394 Ethernet Modem	None One gigabit ethernet port, Realtek RTL8111E, Wake on LAN® None	AccuWeather PC Device Stage Cyberlink Power2Go (DVD±RW)				
Security chip	Trusted Platform Module (TPM 1.2-compliant)	Cyberlink PowerProducer (DVD±RW)				
Keyboard Mouse Floor Stand	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo Enhanced Optical USB Mouse, black, Lenovo logo System floor stand for vertical orientation	All models ThinkVantage® System Update				
Power supply	240 watts, autosensing, 85% PSU	View Management UtilityLenovo Solution Center				
Machine Bay	Business black color; metal case 13.3" W X 15.0" D X 3.9" H 339mm W X 381mm D X 100mm H 16.5 lb (7.5 kg) in maximum configuration Toolless cover flips up and tilts backward on rear hinges Toolless disk and optical drive removal Toolless adapter retention Bay 1: 5.25", 1.6" high, access, std optical	 Norton Internet Security (30 days of virus definitions) Evernote[®] Microsoft[®] Office preloaded; purchase a product key to activate Skype[™] 				
,	Bay 2: 3.5", 1" high, no access, std disk Bay 3: 3.5", .5" high, access, opt reader					
Slot	Slot 1: Low Profile, PCI Express 2.0 x16 (40w max) Slot 2: Low Profile, PCIe 2.0 x1 Slot 3: Low Profile, 32-bit PCI 2.3 Slot 4: Low Profile, 32-bit PCI 2.3	Security Security chip (see information on left) Security slot (in rear for attachment of optional Kensington® MicroSaver® cable) Cable lock Power-on password				
	disk optical	Administrator password Hard disk password Boot sequence control Boot without keyboard and mouse Individual USB port disablement Chassis intrusion switch on selected model(s)				
Limited Warranty	3-years, limited onsite service, 8 am-5 pm, Mon - Fri coverage excluding public and	EPEAT™ Gold rating ENERGY STAR® 5.2-compliant ULE Gold				
	national holidays. Calls received after 3 pm will require an additional next business day for service dispatch / service upgrades available	RoHS-compliant Supports ThinkVantage Technologies				

Slot x Type-model bay	Processor	Memory ⁸	SATA disk 2 GB rpm		Media reader	Graphics	Chassis PS/2 intr switch port	Global	Preload	Ann date (mm/dd/yy)
						Radeon HD 7480D Radeon HD 7480D				

- Small and medium business (SMB) model(s), part of the Western Europe TopSeller Program 3-year limited warranty

Positioning	Mainstream enterprise stability and manageability	Preloaded operating system
Processor	AMD Accelerated Processor A4-5300 (dual-core, 3.4GHz, 1MB L2 cache), Turbo Core technology (up to 3.6GHz), integrated AMD Radeon™ HD 7480D Graphics,	Some: Windows® 7 Professional 64 preinstalled through downgrade
Implementation	integrated DDR3 memory controller (up to 1600MHz) Processor in Socket FM2	rights in Windows 8 Pro 64-bit Some: Windows 8 Pro 64-bit
Memory	32GB max, UDIMM, PC3-12800 1600MHz DDR3, four 240-pin DIMM sockets	Preloaded applications (only some listed)
Graphics	AMD Radeon HD Graphics, integrated in processor, uses main memory, DirectX [®] 11, one VGA, one DisplayPort™, supports dual independent display; works along with discrete graphics to support up to four independent monitors; Maximum resolution: 1920x1200 (VGA)@60Hz; 2560x2048 (DisplayPort)@60Hz	- Windows 7 models ThinkVantage® Product Recovery ThinkVantage Communication Utility ThinkVantage Power Manager
DP dongle	None	Lenovo® Message Center Plus
Disk Optical SATA controller Onboard SATA eSATA port Media reader Chipset	SATA 6.0Gb/s 7200 rpm Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive Serial ATA, SATA 6.0Gb/s, integrated in chipset, RAID 0/1 Two SATA cables (each 1-drop to device), four SATA 6.0Gb/s connectors on planar None None AMD A75 Chipset	Lenovo SimpleTap Adobe® Reader® Google Chrome Google Toolbar RapidBoot HDD Accelerator Symantec™ VIP Windows Live™ Essentials Corel® Burn.Now™ (DVD±RW)
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)	Corel DVD MovieFactory® (DVD±RW)
Rear ports	Four USB 3.0, two USB 2.0, serial (9-pin), ethernet (RJ-45), VGA DB-15, DisplayPort, optional keyboard (PS/2), optional mouse (PS/2)	- Windows 8 models • Lenovo Support
	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone (stereo, 3.5mm) Two USB 2.0 planar conn (1 used; one open for additional USB device) High Definition (HD) Audio, Realtek® ALC662 codec Internal speaker for business audio None One gigabit ethernet port, Realtek RTL8111E, Wake on LAN® None	Lenovo Companion Lenovo Cloud Storage Lenovo QuickLaunch Norton™ Studio Intel AppUp® AccuWeather PC Device Stage
Security chip	Trusted Platform Module (TPM 1.2-compliant)	Cyberlink Power2Go (DVD±RW) Cyberlink PowerProducer (DVD±RW)
Keyboard Mouse Power supply	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo Enhanced Optical USB Mouse, black, Lenovo logo 280 watts with variable speed fan, manual switch	- All models ThinkVantage® System Update View Management Utility
Machine Bay	Business black color; metal case 6.9" W X 17.4" D X 16.3" H 175mm W X 442mm D X 414mm H 27.5 lb (12.5 kg) in maximum configuration Toolless cover removal, toolless adapter retention Toolless disk, optical drive removal Bay 1: 5.25", 1.6" high, access, std optical Bay 2: 5.25", 1.6" high, access, open Bay 3: 3.5", 1" high, access, opt reader Bay 4: 3.5", 1" high, no access, std disk	Lenovo Solution Center Norton Internet Security (30 days of virus definitions) Evernote® Microsoft® Office preloaded; purchase a product key to activate Skype™
Slot	Bay 5: 3.5", 1" high, no access, opt disk Slot 1: half-length, full-height, PCI Express 2.0 x16 (60w max) Slot 2: half-length, full-height, PCIe 2.0 x1 Slot 3: half-length, full-height, 32-bit PCI 2.3 Slot 4: half-length, full-height, 32-bit PCI 2.3	Security
	② ③ disk □••□	Security chip (see information on left) One lock to secure both cover and entire system to fixed object: -Padlock loop (in rear for opt padlock) -Security slot (in rear for optional Kensington® MicroSaver® cable) Cable lock Power-on password Administrator password Hard disk password Boot sequence control Boot without keyboard and mouse Individual USB port disablement Chassis intrusion switch on selected model(s)
Limited Warranty	3-years , limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding public and national holidays. Calls received after 3 pm will require an additional next business day for service dispatch / service upgrades available	RoHS-compliant Supports ThinkVantage Technologies

Type-model	Slot x bay	Processor	Memory ⁸	SATA disk 2 GB rpm		SATA optical	Media reader	Graphics						Ann date (mm/dd/yy)
1565-A1G	4x5	A6-5400B	4GBx1	500G 7200	Bay	DVD±RW	None	Radeon HD 7540	D None	None	ES52	GP	Pro 64	08/28/12

Positioning Processor Implementation Memory Graphics DP dongle	Mainstream enterprise stability and manageability AMD Accelerated Processor A6-5400B (dual-core, 3.6GHz, 1MB L2 cache), Turbo Core technology (up to 3.8GHz), integrated AMD Radeon HD 7540D Graphics, integrated DDR3 memory controller (up to 1866MHz) Processor in Socket FM2 32GB max, UDIMM, PC3-12800 1600MHz DDR3, four 240-pin DIMM sockets AMD Radeon HD Graphics, integrated in processor, uses main memory, DirectX [®] 11, one VGA, one DisplayPort™, supports dual independent display; works along with discrete graphics to support up to four independent monitors; Maximum resolution: 1920x1200 (VGA) @ 60Hz; 2560x2048 (DisplayPort) @ 60Hz None	Preloaded operating system Genuine Windows® 7 Professional 64 Ready to install applications (only some listed) ■ Rescue and Recovery™ ■ Password Manager ■ Business-in-a-Box Preloaded applications (only some listed) ■ ThinkVantage® Product Recovery ■ ThinkVantage® Product Recovery					
Disk Optical SATA controller Onboard SATA eSATA port Media reader Chipset	SATA 6.0Gb/s 7200 rpm Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive Serial ATA, SATA 6.0Gb/s, integrated in chipset, RAID 0/1 Two SATA cables (each 1-drop to device), four SATA 6.0Gb/s connectors on planar None None AMD A75 Chipset	ThinkVantage System Update ThinkVantage Communication Utility ThinkVantage Power Manager View Management Utility Lenovo Solution Center Lenovo Message Center Plus Lenovo Simple Tap					
	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm) Four USB 3.0, two USB 2.0, serial (9-pin), ethernet (RJ-45), VGA DB-15, DisplayPort, optional keyboard (PS/2), optional mouse (PS/2) Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone (stereo, 3.5mm) Two USB 2.0 planar conn (1 used; one open for additional USB device) High Definition (HD) Audio, Realtek® ALC662 codec Internal speaker for business audio None One gigabit ethernet port, Realtek RTL8111E, Wake on LAN® None Trusted Platform Module (TPM 1.2-compliant)	(30 days of virus definitions) • Adobe® Reader® • Google Chrome • Google Toolbar • Skype™ for Windows • Evernote® • RapidBoot HDD Accelerator • Symantec™ VIP • Windows Live™ Essentials • Microsoft® Office preloaded; purchase a product key to activate • Corel® Burn.Now™ (DVD±RW) • Corel DVD MovieFactory® (DVD±RW)					
Keyboard Mouse Power supply Machine	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo Enhanced Optical USB Mouse, black, Lenovo logo 280 watts, autosensing, 85% PSU • Business black color; metal case • 6.9" W X 17.4" D X 16.3" H • 175mm W X 442mm D X 414mm H • 27.5 lb (12.5 kg) in maximum configuration • Toolless cover removal, toolless adapter retention • Toolless disk, optical drive removal Bay 1: 5.25", 1.6" high, access, std optical Bay 2: 5.25", 1.6" high, access, open Bay 3: 3.5", 1" high, access, opt reader Bay 4: 3.5", 1" high, no access, std disk Bay 5: 3.5", 1" high, no access, opt disk						
Slot	Slot 1: half-length, full-height, PCI Express 2.0 x16 (60w max) Slot 2: half-length, full-height, PCIe 2.0 x1 Slot 3: half-length, full-height, 32-bit PCI 2.3 Slot 4: half-length, full-height, 32-bit PCI 2.3 optical g iiiiiiiiiiiiiiiiiiiiiiiiiiiiiiiii	Security Security Security chip (see information on left) One lock to secure both cover and entire system to fixed object: -Padlock loop (in rear for opt padlock) -Security slot (in rear for optional Kensington® MicroSaver® cable) Cable lock Power-on password Administrator password Hard disk password Boot sequence control Boot without keyboard and mouse Individual USB port disablement Chassis intrusion switch on selected model(s) EPEAT™ Gold rating ENERGY STAR 5.2-compliant					
Limited Warranty	3-years , limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding public and national holidays. Calls received after 3 pm will require an additional next business day for service dispatch / service upgrades available	ULE Gold RoHS-compliant Supports ThinkVantage Technologies					

Slot x Type-model bay	Processor	Memory ⁸	SATA disk 2 GB rpm					ENERGY STAR 5.2		Ann date (mm/dd/yy)
				,		Radeon HD 7540D Radeon HD 7540D				

Positioning Processor	Mainstream enterprise stability and manageability AMD Accelerated Processor A6-5400B (dual-core, 3.6GHz, 1MB L2 cache),	Preloaded operating system
F100e5501	Turbo Core technology (up to 3.8GHz), integrated AMD Radeon HD 7540D Graphics,	Some: Windows® 7 Professional 64 preinstalled through downgrade
	integrated DDR3 memory controller (up to 1866MHz)	rights in Windows 8 Pro 64-bit
Implementation	Processor in Socket FM2	Some: Windows 8 Pro 64-bit
Memory	32GB max, UDIMM, PC3-12800 1600MHz DDR3, four 240-pin DIMM sockets	Preloaded applications (only some listed)
Graphics	AMD Radeon HD Graphics, integrated in processor, uses main memory, DirectX [®] 11, one VGA, one DisplayPort™, supports dual independent display; works along with discrete graphics to support up to four independent monitors; <i>Maximum resolution:</i> 1920x1200 (VGA)@60Hz; 2560x2048 (DisplayPort)@60Hz	 Windows 7 models ThinkVantage® Product Recovery ThinkVantage Communication Utility ThinkVantage Power Manager
DP dongle	None	Lenovo® Message Center Plus
Disk	SATA 6.0Gb/s 7200 rpm	Lenovo SimpleTap Adobe® Reader®
Optical SATA controller	Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive Serial ATA, SATA 6.0Gb/s, integrated in chipset, RAID 0/1	Google Chrome
Onboard SATA	Two SATA cables (each 1-drop to device), four SATA 6.0Gb/s connectors on planar	Google Toolbar
eSATA port	None	RapidBoot HDD Accelerator
Media reader	None	Symantec™ VIP Windows Live™ Essentials
Chipset	AMD A75 Chipset	Corel® Burn.Now™ (DVD±RW)
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)	 Corel DVD MovieFactory® (DVD±RW)
Rear ports	Four USB 3.0, two USB 2.0, serial (9-pin), ethernet (RJ-45), VGA DB-15, DisplayPort, optional keyboard (PS/2), optional mouse (PS/2)	- Windows 8 models • Lenovo Support
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone (stereo, 3.5mm)	 Lenovo Companion
	Two USB 2.0 planar conn (1 used; one open for additional USB device)	Lenovo Cloud Storage
Audio Speaker	High Definition (HD) Audio, Realtek® ALC662 codec Internal speaker for business audio	Lenovo QuickLaunch Norton™ Studio
IEEE 1394	None	Intel AppUp®
Ethernet	One gigabit ethernet port, Realtek RTL8111E, Wake on LAN®	AccuWeather
Modem	None	PC Device Stage Cyberlink Power2Go (DVD±RW)
Security chip	Trusted Platform Module (TPM 1.2-compliant)	Cyberlink PowerProducer (DVD±RW)
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo	- All models
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo	ThinkVantage® System Update
Power supply	280 watts, autosensing, 85% PSU	View Management Utility
Machine	 Business black color; metal case 6.9" W X 17.4" D X 16.3" H 	Lenovo Solution Center
	● 175mm W X 442mm D X 414mm H	Norton Internet Security (30 days of virus definitions)
	• 27.5 lb (12.5 kg) in maximum configuration	Evernote®
	Toolless cover removal, toolless adapter retention	 Microsoft® Office preloaded;
Ray	Toolless disk, optical drive removal Bay 1: 5.25", 1.6" high, access, std optical	purchase a product key to activate
Bay	Bay 2: 5.25", 1.6" high, access, std optical	Skype [™]
	Bay 3: 3.5", 1" high, access, opt reader	
	Bay 4: 3.5", 1" high, no access, std disk	
Slot	Bay 5: 3.5", 1" high, no access, opt disk Slot 1: half-length, full-height, PCI Express 2.0 x16 (60w max)	Security
Siot	Slot 2: half-length, full-height, PCIe 2.0 x1	Security chip (see information on left)
	Slot 3: half-length, full-height, 32-bit PCI 2.3	One lock to secure both cover and
	Slot 4: half-length, full-height, 32-bit PCI 2.3 optical	entire system to fixed object: -Padlock loop (in rear for opt padlock)
	2	-Security slot (in rear for optional
		Kensington® MicroSaver® cable)
	(3) disk	Cable lock Daylor on pageword
		Power-on password Administrator password
		Hard disk password
		Boot sequence control
	<u> </u>	Boot without keyboard and mouse Individual USB part disablement
		Individual USB port disablement Chassis intrusion switch on selected
		model(s)
		EPEAT™ Gold rating
		ENERGY STAR 5.2-compliant
Limited Warranty	3-years, limited onsite service, 8 am-5 pm, Mon - Fri coverage excluding public and	ULE Gold RoHS-compliant
	national holidays. Calls received after 3 pm will require an additional next business day for service dispatch / service upgrades available	·
	ior service dispatcit/ service apgrades available	Supports ThinkVantage Technologies