

Name Bezel color Type-model Panel Viewable image size Max view area (W x H) Native resolution Aspect ratio Pixel pitch (mm) Dot/Pixel per Inch Brightness Contrast ratio Pixel response time Color gamut Viewing angle at 10:1 CR Stand Bezel width Dimensions (HxWxD) Power supply Weight Limited warranty Available date	LI2054 Flat Panel Monitor Black 65BAACC1US TFT-LCD, In-Plane Switching (IPS), White LED backlight 19.45" (494mm) diagonal 16.48" x 10.33" (418.61mm x 262.35mm) 1440x900 16:10 0.0969 x 0.2915 mm 87.14 dpi 250 nits or cd/m² (typical) 1000:1 (typical) 7ms with OD 72% (typical) CIE 1931 R / L 178° (typical), U / D 178° (typical) Tilt adjustable stand <i>Sides:</i> 0.7" (17.9mm) 14.65" H x 17.95" W x 7.28" D; 372mm H x 456mm W x 184.8mm D 16 watts typical, 20 watts maximum, <0.5 watts standby/suspend, universal, integrated (no external brick-like power supply) 6.17 lb; 2.8 kg 1 year (includes backlight) August 2017				
VESA-compliant Power management Ergonomics Emission standards Environmental	Features • 19.45-inch monitor • Supports 1440x900 resolution • Arsenic-free glass • Mercury-free • PVC-free • Microsoft® Windows® 7 certified • Microsoft Windows 8 certified • Microsoft Windows 8.1 certified • Microsoft Windows 10 certified  LI2054 Monitor				
Preset resolutions Presets display modes	VGA: 640x480 SVGA: 800x600 XGA: 1024x768 SXGA: 1280x1024 WXGA: 1366x768 WXGA+: 1440x900 None				
Viewing adjustments Rotating screen On screen display Control features USB hub Multiple input Monitor connectors Signal cables Mounting features Security	<i>Tilt:</i> 22° back, -5° forward None On screen display with digital user controls (8 languages) Direct access (buttons on front) for power, Novo vision None None (1) VGA 15-pin D-shell, analog, blue (1) detachable, VGA 15-pin D-shell at each end, analog, 1.8 meter Wall or desk mounting using the Extend Arm or third-party accessories, 100mm x 100mm mount Security keyhole for attachment of optional cable lock (Kensington® lock-compatible)				
Ship group	Monitor with stand, Safety and Warranty Information, 1.8 meter analog signal cable, 1.8 meter black power cord				
Limited Warranty See details at http://support.lenovo.com/en_US/guides-and-manuals/detail.page?DocID=UM008281	Accessories <table> <tr> <td>Kensington MicroSaver Cable Lock</td> <td>73P2582</td> </tr> <tr> <td>Kensington Twin Head Cable Lock</td> <td>45K1620</td> </tr> </table> See details at www.lenovo.com/support/monitoraccessories See all monitors at www.lenovo.com/thinkvision	Kensington MicroSaver Cable Lock	73P2582	Kensington Twin Head Cable Lock	45K1620
Kensington MicroSaver Cable Lock	73P2582				
Kensington Twin Head Cable Lock	45K1620				