


OVERVIEW



1. Cable lock slot	3. 1x USB-C 3.1 Gen 1
2. 1x USB-C 3.1 Gen 1	



PERFORMANCE

Panel

Panel

In-Plane Switching (IPS)

Backlight

WLED

Display Size

15.6 inches

Max View Area

• Active Area: 344.2 x 193.6 mm

• Screen Dimension: 360.0 x 234.0 mm

Resolution

1920 x 1080

Aspect Ratio

16:9

Pixel Pitch

0.179 x 0.179 mm

Dot / Pixel Per Inch

141 dpi

Brightness

250 cd/m²

Contrast Ratio

• Contrast Ratio: 1000:1

• Dynamic Contrast Ratio (Typical): 3000000:1

View Angle (H / V)

Horizontal: 178°, Vertical: 178°

Response Time

Extreme Mode: 6 msNormal Mode: 14 ms

Refresh Rate

60Hz

Color Gamut

45% NTSC

Color Support

16.7 Million

Screen Surface Treatment

Anti-glare

Operating System

Operating System

- Windows® 10 Support
- Windows® 7 Support

Power Supply

Power Consumption

- Typical / Max: 8W / 9.5W
- Sleep / Off mode: <0.3W
- Switch-off Mode: <0.3W
- Energy Star Power On: 5W
- Energy Star TEC: 19kWh

External Power Supply (no adapter bundle)

Voltage Required



DC 5 / 9 / 15 / 20 V

Special Features

Special Features

Lenovo® ThinkColour (Lenovo® Accessories and Display Manager) Support

Lenovo® ThinkColour supports Windows® 10 & 11, Mac OS, and Windows® On Arm (functions vary across systems).

Lenovo® Accessories and Display Manager is formerly Lenovo® Display Control Center.

DESIGN

Mechanical

Bezel Width

• Side: 7.3mm

Top / Bottom: 7.3mm / 31.9mm

Cable Management

Support

Case Color

Raven black

Dimensions (WxDxH)[1]

Models	Dimensions
Lowest Position	108.4 x 235.5 x 360.0mm (4.27 x 9.27 x 14.17 inches)
Highest Position	108.4 x 245.5 x 360.0 mm (4.27 x 9.67 x 14.17 inches)

Packaging Dimensions (WxDxH)

279.9 x 407.9 x 75.9 mm (11.02 x 16.06 x 2.99 inches)

Weight^[2]

Models	Weight
Monitor With Stand	0.9 kg (1.9 lbs)

Packaging Weight

1.7 kg (3.75 lbs)

Mounting

Supports VESA mount 100mm, 2 screw holes

Stand

Supports 0° to +90° tilt, up to 10mm lift

In the Box

- M15 Monitor
- 1x USB-C® to USB-C® cable (1m)
- 1x Pair of clips
- 1x Sleeve
- Quick setup guide

Notes:

[1] The system dimensions may vary depending on configurations.

[2] The system weight is approximate and based on results in Lenovo® lab, which varies depending on the source of component, variance of the distribution of each component, and manufacturing process. It may not be the exact weight for each specific model.

CONNECTIVITY

Ports^[1]

Rear Ports[2]

2x USB-C® 3.2 Gen 1 (DP 1.2 Alt Mode, one USB upstream, one USB downstream and USB 2.0 data transfer)



Notes:

[1] The transfer speed of following ports will vary and, depending on many factors, such as the processing speed of the host device, file attributes and other factors related to system configuration and your operating environment, will be slower than theoretical speed.

USB 2.0: 480 Mbit/s:

USB 3.2 Gen 1 (SuperSpeed USB 5Gbps, formerly USB 3.0 / USB 3.1 Gen 1): 5 Gbit/s;

USB 3.2 Gen 2 (SuperSpeed USB 10Gbps, formerly USB 3.1 Gen 2): 10 Gbit/s;

USB4® 20Gbps / USB 3.2 Gen 2x2 (SuperSpeed USB 20Gbps): 20 Gbit/s;

USB4® 40Gbps (USB 40Gbps): 40 Gbit/s;

Thunderbolt[™] 3/4: 40 Gbit/s.

Thunderbolt[™] 5: 80 Gbit/s (bidirectional), up to 120 Gbit/s in bandwidth boost mode for video-intensive applications.

[2] Listed as maximum capacity of power delivery. Actual capacity of power delivery may vary depending upon devices connected or monitor configuration, and may decline with downstream USB ports connected or higher brightness setting.

SECURITY & PRIVACY

Security

Physical Locks

Kensington® Security Slot™

SERVICE

Warranty

Base Warranty

3-year limited warranty

OPERATING REQUIREMENTS

Operating Environment

Temperature

Operating: 0°C to 40°C (32°F to 104°F) Storage: -20°C to 60°C (-4°F to 140°F)

Relative Humidity

Operating: 10% to 80% Storage: 5% to 95%

CERTIFICATIONS

Green Certifications

- ENERGY STAR® Certified
- EPEAT™ Silver Registered[2]
- RoHS compliant

Notes:

[1] The items listed under the "Green Certifications" section may not only refer to certification but also registration or selfdeclaration. For ESG & regulatory compliance documents, please visit https://compliance.lenovo.com.

[2] EPEAT™ is registered where applicable, please visit epeat.net for registration status by country.

Other Certifications

Other Certifications

- TÜV Rheinland® Flicker Free
- TÜV Rheinland® Low Blue Light
- · Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not responsible for photographic or typographical errors. LENOVO PROVIDES THIS PUBLICATION "AS IS,"

WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES

ThinkVision M15



OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow disclaimer of express or implied warranties in certain transactions, therefore this disclaimer may not apply to you.

• The specifications on this page may not be available in all regions, and may be changed or updated without notice













